

# ATTACHMENT A

## APPENDIX A – URBAN DESIGN STUDY PREPARED BY BATES SMART

# ATTACHMENT A

**PROJECT NUMBER**

S11776

# PLANNING PROPOSAL DESIGN REPORT

12-40 ROSEBERY AVENUE  
ROSEBERY  
S11776

**BATESSMART™**

**ARCHITECTURE  
INTERIOR DESIGN  
URBAN DESIGN  
STRATEGY**

**MELBOURNE**

1 Nicholson Street  
Melbourne Victoria  
3000 Australia  
T +61 3 8664 6200  
F +61 3 8664 6300

**SYDNEY**

43 Brisbane Street  
Surry Hills New South Wales  
2010 Australia  
T +61 2 8354 5100  
F +61 2 8354 5199

**WWW.BATESSMART.COM**

**NOMINATED NSW REGISTERED ARCHITECTS**

Philip Vivian Reg. No. 6696 / Simon Swaney Reg. No. 7305 / Guy Lake Reg. No. 7119

**DISCLAIMER**

The Scheme (drawings documents information and materials) contained within this brochure have been prepared by Bates Smart Architects Pty Ltd solely for the purpose of providing information about potential schemes.

The materials should not be considered to be error free or to include all relevant information.

Nothing in this brochure in any way constitutes advice or a representation by Bates Smart nor does the transmission or sending of these materials create any contractual relationship.

Neither Bates Smart nor any of its officers, employees, agents or contractors, will be liable for any direct or indirect loss or damage you may suffer or incur arising directly or indirectly from the use of any materials from this brochure.


Bates Smart retains copyright and all present and future moral rights in all intellectual property in all the materials authored by it and in any works executed from these drawings and documents.

Note: All area calculations are advisory only and all figures should be checked and verified by a licensed surveyor.

# LOCATION

## 12-40 ROSEBERY AVENUE, ROSEBERY

The site in Rosebery is 4km South of Sydney CBD, and is part an area undergoing rapid transformation from industrial to residential. Alexandria is to the West, Zetland to the North and Green Square Station 1.5km North-West. The site is also conveniently located near Southern Cross Drive (M1) and the Australian Golf Club.



ATTACHMENT A


# SITE & CONTEXT ANALYSIS



Site boundary



City of Sydney proposed landscaped Open space



## SITE & DCP MASTERPLAN CONTEXT

The site occupies a large area of 15,215sqm with a width of 91.5m and a length of approximately 165m. It currently features several large 1 to 2 storey industrial/warehouse/office buildings.

The surrounding massing depicts the future context of the site according to the Sydney Development Control Plan 2012, indicating a transformation of the area from industrial to predominately multi-residential apartments.

The topography features a gentle fall of 2m across the site from North to South




Permissible massing



Design Excellence floorspace

Note: Building storeys indicated on diagram




## DCP PROPOSED MASSING

The permissible building heights on site, when compared with that of the surrounding context are low.

Within the site the DCP allows 5 storey buildings along Dalmerney Ave. The surrounding building forms on Dalmerney Ave feature:  
/ 8 storey buildings across the road to the East  
/ 6 to 7 storey buildings to the North and South of the site.


The DCP allows 6 and 7 storey buildings (with Design Excellence bonus) along Rosebery Ave. The context of surrounding building forms on Rosebery Ave feature:

/ 9-10 storey buildings across the road to the West  
/ 6 and 7 storey buildings to the West  
/ 5 and 6 storey buildings to the North and South



**ENVIRONMENTAL CONDITIONS**

The site provides excellent opportunities for solar access across the entire site with only minor late afternoon overshadowing from future apartment buildings to the West. The generous width of the site (91.5m) will also provide excellent building separation and solar access to landscaped communal courtyards.



**ACCESS & PEDESTRIAN CONNECTIONS**

According to the COS DCP the site will become further integrated into a future road/pedestrian/park system, which will create permeable residential scale blocks and improve connectivity across Rosebery and to public parks. There will be good access to the site with the extension of Rosebery and Dalmayn Avenues towards a new East-West arterial road North of the site.

The site currently makes no contribution to East-West connections across the site between Rosebery Ave and Dalmayn Ave. East-West permeability would provide opportunities to create neighbourhood connectivity and connect green park spaces.

# URBAN DESIGN STRATEGY

# ATTACHMENT A

↔ Pedestrian access (COS DCP 2012)




## EXISTING BLOCK SCALE

The immediate block in which the site sits currently is very large and demonstrates no permeability nor articulation of scale suitable for residential use.

COS has described future pedestrian access across the site to articulate the scale of the block.



↔ Shared Zone







## RESIDENTIAL BLOCK SCALE

Shared zones further articulate the scale of the block by providing pedestrian / bicycle / vehicle access across the development parcels. They can further provide access to development parcels off the major roadways Dairyway Ave and Rosebery Ave.

-  Pedestrian access / visual permeability
-  Landscaped vehicle access
-  City of Sydney future new roads
-  City of Sydney future pedestrian streets
-  City of Sydney future pedestrian & bike green link

-  Communal Landscape
-  Public Green Space

-  Pedestrian access
-  Shared Zone



**GREEN SPACE**

Green spaces in the form of landscaped pedestrian paths/shared zones and courtyards will provide increased public and residential amenity and broader connectivity to surroundings.

**PERMEABILITY**

A combination of pathways will create a sense of scale whilst providing regular East-West permeability and connectivity through the site and to the wider neighbourhood.



# SITE MASSING 2:1 SCHEME

**SITE AREA:** 15215 SQM

**BLOCK PLAN MASSING**


TOTAL GEA: 40350 SQM  
TOTAL GFA: 30260 SQM (75% EFFICIENCY)

**FSR** 2.0:1




BLOCK MASSING DIAGRAM

# SITE MASSING 2:1 SCHEME






VIEW FROM NORTH-WEST



VIEW FROM SOUTH-EAST

# INSOLATION DIAGRAMS



**VIEW FROM THE SUN DIAGRAMMS - MID WINTER 21 JUNE**  
The proposal demonstrates excellent solar access to the apartments, and communal open space, whilst minimising overshadowing to neighbouring buildings.

## SOLAR DIAGRAMMS

The following diagrams demonstrate insolation and overshadowing based on the shadows cast by the block massing diagrams.


- 3 out of 73 Apartments on a Typical floor receive no direct sunlight (4%) between 9am & 3pm on 21st June (Winter Solstice)



9am







- Apartments which do not receive direct sunlight between 9am and 3pm
- Apartments which receive a minimum of 2 hours direct sunlight



10am



11am



3pm



2pm





1pm



12pm

# SHADOW DIAGRAMS

## SHADOW IMPACT ANALYSIS - MID WINTER 21 JUNE




Note: Any other shadows are casted by neighbouring permissible form as specified by the COS DCP height and setbacks.

Shadow cast by 2.0:1 Scheme


Additional shadow cast by 2.16:1 Design Excellence bonus scheme




# ATTACHMENT A



3pm



2pm



1pm



12pm

## PUBLIC DOMAIN AND USES

### BUILT FORM

Public domain combined area is approximately 2200sqm as notated in the adjacent diagram, which equates to roughly 14% of the total site area of 15,215sqm.

There is an allocated non-residential area at the south corner of the north-western block adjacent to the main road, and allows for drop-off on the side of the through-site link if required.

All ground level apartments will have east and west orientation, and can be accessed from their individual private courtyards as well as the shared lift lobbies.



# BASEMENT CARPARK

## SUMMARY

Vehicle access along Dalmeny Ave provides two convenient entries for resident parking and garbage collection to the southern entry.

An efficient car park is provided with enough car spaces, storage and deepsoil planting over one basement level.

Terraces will each have lockup carparking with private storage and direct private access to units.

# ATTACHMENT A





# ATTACHMENT A

## **APPENDIX B – TRAFFIC AND PARKING ASSESSMENT PREPARED BY PARKING AND TRAFFIC CONSULTANTS**

# ATTACHMENT A



**PARKING & TRAFFIC**  
CONSULTANTS

*Driving success through valuable advice*

**12-40 Rosebery Avenue, Rosebery**

**For Filetron Pty Ltd**

Planning Proposal

For the attention of: Tim Bainbridge

7 April 2015



## Document Control

Our Reference: T2-1276, 12-40 Rosebery Avenue, Rosebery, Planning Proposal

| ISSUE | DATE        | ISSUE DETAILS            | AUTHOR | REVIEWED   |
|-------|-------------|--------------------------|--------|------------|
| 1     | 11 Mar 2015 | Draft Review for Client  | M. Yee | S. Wellman |
| 2     | 13 Mar 2015 | Draft Final for Client   | M. Yee | S. Wellman |
| 3     | 31 Mar 2015 | Final                    | M. Yee | C. Lynn    |
| 4     | 07 Apr 2015 | Final with minor changes | M. Yee | S. Wellman |

## Contact

Monica Yee  
02-89200800  
0411 490 813  
[Monica.yee@parkingconsultants.com](mailto:Monica.yee@parkingconsultants.com)

COMMERCIAL IN CONFIDENCE

The information contained in this document, including any intellectual property rights arising from designs developed and documents created, is confidential and proprietary to Parking & Traffic Consultants (PTC).

This document may only be used by the person/organisation to whom it is addressed for the stated purpose for which it is provided and must not be imparted to or reproduced, in whole or in part, by any third person without the prior written approval of a PTC authorised representative. PTC reserves all legal rights and remedies in relation to any infringement of its rights in respect of its intellectual property and/or confidential information.

© 2015

PARKING & TRAFFIC CONSULTANTS  
Suite 102, 506 Miller Street  
Camberay NSW 2062

Ph. +61 2 8920 0800  
Fax +61 2 8076 8665

Level 2, 710 Collins Street  
Docklands VIC 3008

Ph. +61 3 9097 1770

## Contents

|          |   |           |
|----------|---|-----------|
| <b>1</b> | <b>Introduction.....</b>  | <b>5</b>  |
| 1.1      | Project Summary .....   | 5         |
| 1.2      | Purpose of this Report .....  | 6         |
| <b>2</b> | <b>Proposal.....</b>  | <b>7</b>  |
| 2.1      | Development Site.....   | 7         |
| 2.2      | Planning Proposal .....   | 8         |
| <b>3</b> | <b>Existing Transport Facilities.....</b>   | <b>10</b> |
| 3.1      | Road Hierarchy.....   | 10        |
| 3.2      | Public Transport.....   | 11        |
| 3.2.1    | Railway Station.....  | 11        |
| 3.3      | Buses .....   | 12        |
| 3.4      | Bike Plan.....  | 14        |
| 3.5      | Car Share.....  | 15        |
| 3.6      | Existing Traffic Generation.....  | 16        |
| 3.7      | Existing Traffic Volumes .....  | 17        |
| 3.8      | Intersection Capacity Assessment (Existing Situation).....  | 18        |
| <b>4</b> | <b>Development Traffic Assessment .....</b>   | <b>20</b> |
| 4.1      | Traffic Generation.....   | 20        |
| 4.1.1    | Traffic Generation based on a FSR of 1.5:1 (residential development) .....                              | 20        |
| 4.1.2    | Traffic Generation based on a FSR of 2.0:1 (residential development).....                               | 21        |
| 4.1.3    | Summary of Traffic Generation Scenarios.....  | 22        |
| 4.2      | Traffic Distribution .....  | 22        |
| 4.3      | Intersection Capacity Assessment (Baseline FSR of 1.5:1) .....  | 23        |
| 4.4      | Intersection Capacity Assessment (Proposal FSR of 2.0:1) .....  | 24        |
| 4.5      | Assessment of Traffic Generation impacts by increasing the FSR by 0.5:1 .....                           | 25        |
| <b>5</b> | <b>Parking Assessment.....</b>  | <b>27</b> |
| <b>6</b> | <b>Summary .....</b>  | <b>31</b> |
|          | <b>Attachment 1 – Architectural Plans.....</b>  | <b>32</b> |
|          | <b>Attachment 2 – SIDRA OUTPUTS (Existing Situation).....</b>   | <b>33</b> |
|          | <b>Attachment 3 – SIDRA OUTPUTS (BASELINE FSR 1.5:1).....</b>   | <b>38</b> |
|          | <b>Attachment 4 – SIDRA OUTPUTS (PROPOSAL FSR 2.0:1) .....</b>  | <b>43</b> |
|          | Figure 1 – Site Location (Source: BateSMART, 2015).....   | 5         |
|          | Figure 2 – Site Location.....   | 7         |
|          | Figure 3 – Land Use surrounding the site (Source: 2012 Sydney LEP, Accessed 2 Mar 2015).....            | 8         |
|          | Figure 4 - RMS Road Hierarchy network surrounding the site.....   | 10        |
|          | Figure 5 – Proximity of site from Green Square Railway Station .....                                    | 12        |
|          | Figure 6 – Location of bus routes adjacent to development. ....   | 14        |
|          | Figure 7 – Cycle pathways within approximate to site development (Source: SydneyCycleways, 2014).....   | 15        |
|          | Figure 8 – Car Share facilities within direct access from the site (Source: City of Sydney, 2015) ..... | 16        |

# ATTACHMENT A

|   |    |
|---|----|
| Figure 9 – Existing AM Peak Hour traffic counts .....   | 18 |
| Figure 10 – Existing PM Peak Hour traffic counts .....  | 18 |
| Figure 11 - Future AM Peak Traffic Distribution (FSR 1.5:1) .....   | 24 |
| Figure 12 – Future PM Peak Traffic Distribution (FSR 1.5:1) .....   | 24 |
| Figure 13 - Future AM Peak Traffic Distribution .....   | 25 |
| Figure 14 – Future PM Peak Traffic Distribution.....  | 25 |
| Table 1 – Existing Traffic Generation from Site.....  | 17 |
| Table 2 SIDRA Intersection Performance Bands.....   | 19 |
| Table 3 – SIDRA Intersection Modelling Results (Existing Situation).....                                  | 19 |
| Table 4 - Calculated Permissible Traffic Generation based on a FSR of 1.5:1 Residential Development ..... | 21 |
| Table 5 - Calculated Existing Traffic Generation based on a FSR of 2.0:1 Residential Development .....    | 21 |
| Table 6 – Summary of traffic generation scenarios permissible at the development site .....               | 22 |
| Table 7 - Calculated split in/out trips associated with the Planning Proposal (FSR 2.0:1).....            | 23 |
| Table 8 – SIDRA Intersection Modelling Results (Baseline FSR of 1.5:1) .....                              | 24 |
| Table 9 – Summary of SIDRA Intersection Modelling Results (2.0:1 FSR).....                                | 25 |
| Table 10 – Summary of Level of Service Results.....   | 26 |
| Table 11 – Summary of Average Delay (Secs) Results .....  | 26 |
| Table 12 – Summary of Degree of Saturation Results .....  | 26 |
| Table 13 – Summary of Back of Queue Distance (m) Results .....  | 26 |
| Table 14 – Parking Provision (Baseline FSR of 1.5:1) .....  | 28 |
| Table 15 – Parking Provision (Proposal FSR of 2.0:1) .....  | 28 |

## 1 Introduction

### 1.1 Project Summary

Parking and Traffic Consultants (PTC) have been engaged by Filetron Pty Ltd to prepare a Traffic and Parking Assessment to accompany a Planning Proposal application to City of Sydney Council (Council). The Planning Proposal seeks to increase the overall floor space ratio (FSR) allowable on site from 1.5:1 to 2.0:1 at 12-40 Rosebery Avenue, Rosebery as shown in Figure 1. Following approval of the Planning Proposal a Development Application (DA) will be prepared for a potential 5 to 7 storey residential development, 2.5 storey terraces and one level of basement car parking.



Figure 1 – Site Location (Source: BateSMART, 2015)

## 1.2 Purpose of this Report

This report presents the following considerations in relation to this planning proposal:

- Section 2 - A description of the project,
- Section 3 - A description of the road network serving the development property,
- Section 4 - Determination of the traffic activity associated with the planning proposal,
- Section 5 - Assessment of the proposed access arrangements, and
- Section 6 - Conclusion

## 2 Proposal

### 2.1 Development Site

The subject site occupies an area of approximately 15,215 sqm<sup>i</sup> which accommodates several large 1 to 2 storey industrial warehouse/office buildings that has an approximate Gross Floor Area (GFA) of 9,800 sqm. The site is approximately 91.5m in width and approximately 165m in length as shown in Figure 2.




Figure 2 – Site Location

As shown in Figure 3 below, the land is zoned B4 Mixed Use under the City of Sydney Local Environmental Plan 2012 (the LEP) which enables a *“suitable business, office, residential, retail and other development in accessible locations so as to maximise public transport patronage and encourage walking and cycling”*. The area surrounding the site is presently transforming from predominantly industrial to multi-storey residential apartments.

<sup>i</sup> Sourced from BateSmart






Figure 3 – Land Use surrounding the site (Source: 2012 Sydney LEP, Accessed 2 Mar 2015)

Within the City of Sydney DCP, Council have defined a number of future roads, pedestrian and bike green links surrounding the site to create permeable residential scale blocks. This would supplement an improvement in connectivity across Rosebery to public parks by way of creating an east-west connector route between Rosebery Avenue and Dalmeny Ave which currently does not exist.

## 2.2 Planning Proposal

The site presently has a base FSR of 1:1 with an allowable additional 0.5:1 available under clause 6.14 of the Sydney LEP 2012. The Planning Proposal seeks to retain the base FSR of 1:1, however seeks to alter the additional FSR under clause 6.14 from 0.5:1 to 1:1. As such the Proposal seeks a total FSR of 2:1, and envisages approximately 365 units and 18 terrace dwellings.

This Planning Proposal also considers the introduction of three new east-west links between Rosebery Avenue and Dalmeny Avenue (two public roadways and one public pedestrian pathway) which support the design intent outlined within the DCP. Therefore this proposal would facilitate the re-activation of the street scape by way of improving safety and pedestrian amenity. It also considers removing all existing driveway access points to the existing industrial site from Rosebery Avenue by way of providing two (2) separate driveways accessed

# ATTACHMENT A



off Dalmeny and Rosebery Avenue. This would result in an increase of on-street parking along Rosebery Avenue.

Details of the proposal are presented on the architectural drawings prepared by BateSMART which are included as **Attachment 1**.

## 3 Existing Transport Facilities

### 3.1 Road Hierarchy

The subject development site is located in the suburb of Rosebery and is primarily serviced by Dalmeny Avenue and Rosebery Avenue, which are classified as Local Roads. The road network servicing the area comprises a number of State Roads, making the site easily accessible from different regions of the metropolitan area. The road network in this area also comprises local streets providing direct access to the surrounding retail, commercial and residential land-uses as presented in Figure 4.




Figure 4 - RMS Road Hierarchy network surrounding the site

The road network serving the site includes:

**The Eastern Distributor** is a toll road which connects from the Sydney Harbour Tunnel to areas north of Sydney, and from Southern Cross Drive in the south to areas between Rosebery, Kensington and Port Botany including Sydney Airport and the region to the west of the Airport. The Highway is aligned north-south and forms the eastern border of Rosebery and operates as a State Road, and an alternative route to Anzac Parade. For much of its length, the Highway carries 3 lanes in each direction, and provides connectivity to the local road network via a Link Road to Epsom Road.

**Rosebery Avenue** is classified as a Local Road within the vicinity of the development site. The road is sign posted 40km/hr in both directions. The carriageway generally carries one lane of travel in each direction, with an unrestricted parking provision on both sides of the road.

**Dalmeny Avenue** is classified as a Local Road within the vicinity of the development site. The road is sign posted as 40kph in both directions. The carriageway generally carries one lane of travel in each direction with unrestricted parking provision on both sides of the road.

**Epsom Road** is a regional road that provides east-west movement on the adjacent road network. The road is sign posted as a 50km/hr road providing one lane of travel in each direction. Restricted on-street parking is provided on both sides of the road, between 8:30am to 6:00pm Monday to Friday.

## 3.2 Public Transport

The site is within a highly accessible location with access to Green Square Railway Station and several local bus stops. The NSW Planning Guidelines for Walking and Cycling (2004), suggests a distance of 400m is a walkable catchment for accessibility to off-site parking provisions and local amenities. Furthermore the guide also recommends that an 800m catchment is an acceptable, walkable distance if the development is within an area with public transport links. The following subsection assesses the development's accessibility to existing public transport surrounding the site.

### 3.2.1 Railway Station

Green Square Railway Station is located a distance of 1.4km from the site as shown in Figure 5. Green Square Railway Station is operated by Sydney Trains and operates services on the Airport line (T2). The T2 railway line operates between Macarthur and the City (via the airport) approximately every 10 minutes between 5.00am and midnight. Since the railway station is more than 800m away being the deemed acceptable walking distance to public transport links, the site is not readily accessible by Train.





Figure 5 – Proximity of site from Green Square Railway Station

### 3.3 Buses

The site is serviced by buses that operate from two bus stops adjacent to the site on Rosebery Avenue, providing in/outbound movement every 30 minutes between the City and Mascot identified as bus route 301. An additional bus stop is located on Epsom Road which services bus routes 370 and 345 which provide bus access to Green Square Station every 15 minutes. It is noted that 301 also operates from this bus stop.



As mentioned previously, a distance of 400m is a walkable catchment to access local amenities. It is also suggested that an 800m catchment is an acceptable, walkable distance if the development is within an area with public transport links. Therefore, it has been assessed that the site is highly accessible by public transport given a bus stops are within 800m to the existing site.

Figure 6 below presents the bus routes servicing the site development.




Figure 6 – Location of bus routes adjacent to development.

### 3.4 Bike Plan

The City of Sydney has prepared a bike plan to encourage cycling as a preferred transport choice for residents, workers and visitors. The plan identifies a number of on and off-road cycle paths and establishes a practical program for cycling infrastructure. Figure 7 shows available cycle facilities adjacent to the site.




Figure 7 – Cycle pathways within approximate to site development (Source: SydneyCycleways, 2014)

As shown in Figure 7 above, the site is service by on-street cycle routes on Dalmeny Avenue and Epsom Road, which link directly to the site providing access to the greater Sydney cycle network.

The NSW Planning Guidelines for Walking and Cycling (2004) suggests a distance of 1500m is a suitable catchment for cycling for accessibility to public transport facilities and local amenities. As the development site is located within 1400m from Green Square Railway Station, it is considered to be highly accessible by public transport via cycling and walking.

### 3.5 Car Share

A car share space may be located within an existing development or on-street. It provides a more efficient use of parking space – a single car share vehicle can replace up to 12 private vehicles that would otherwise compete for local parking<sup>ii</sup>. Car share users are charged by time and distance, at a rate set by each operator. Costs associated with fuel, vehicle maintenance and insurance are usually included in the operator's hire fees.

Within proximity to the development, there are a number of existing on-street and off-street car share spaces available. As shown in Figure 8, within approximately 400m walking distance to the development, there are three Car Share locations, which are readily available to the general public.

<sup>ii</sup> Source: City Of Sydney Council, 2015



Car Share facilities provide;

- A more convenient solution than car rental; and
- A cheaper solution than owning a car, if usage is required infrequently.




Figure 8 – Car Share facilities within direct access from the site (Source: City of Sydney, 2015)

### 3.6 Existing Traffic Generation

The development proposes to amalgamate three individual lots currently allocated to industrial facilities. The traffic generation of the existing site use has been established with reference to RMS Guide to Traffic Generating Developments (the RMS Guide). Section 5.11 defines the existing usage as 'Industry' which can be divided into factories and manufacturing. Section 3.10 provides the trip generation rates for such a site.

Based on a site inspection, it was observed the existing uses are predominantly warehouses associated with various manufacturing and goods storage.

The RMS Guide indicates that factories and manufacturing tend to have different peak access periods to the general network commuter access periods travelling to and from work. Traffic associated with industrial use tends to depend on working patterns of employees which can result in less people travelling in the peak hour. As such, the calculations of the existing trip generation related to the site presented in Table 1 adopt the following assumptions:

- 1) Daily vehicular trips for warehouses is 4 per 100 sqm Gross Floor Area (GFA),

In calculating the AM Peak hour and PM Peak hour vehicle trips associated with these developments, these have been calculated as representing 10% of the daily vehicle trips generated for the site during each peak hour. Based on extensive survey of traffic professionals throughout Australia in 1996<sup>iii</sup> the peak hour traffic

<sup>iii</sup> DW Bennett, Traffic Engineering Practice (4<sup>th</sup> Edition), 1996

volume over a 24hour period is typically taken as 10%, for congested urban arterial road conditions. The remaining 80% of vehicular trips are spread through the remaining 22 hours in the day.

Table 1 – Existing Traffic Generation from Site

| Usage                 | Weekday Peak | Assessment                 | Area GFA (sqm) | Daily Trips | Total Peak Trips (10% Daily Traffic) |
|-----------------------|--------------|----------------------------|----------------|-------------|--------------------------------------|
| Warehouse Development | AM Peak      | 4 vehicles per 100 sqm GFA | 9,800          | 392         | 39.2                                 |
| <b>AM Peak Trips</b>  |              |                            |                |             | <b>39</b>                            |
| Warehouse Development | PM Peak      | 4 vehicles per 100 sqm GFA | 9,800          | 392         | 39.2                                 |
| <b>PM Peak Trips</b>  |              |                            |                |             | <b>39</b>                            |

The application of the RMS rates to the current use of the site has the potential to produce **39 vehicle trips** during the AM Peak and PM peak accessing from various access points on Rosebery Avenue and Dalmeny Avenue.

### 3.7 Existing Traffic Volumes

In order to assess the current traffic conditions in the vicinity of the development site, traffic surveys have been undertaken at the following intersections:

- Dalmeny Avenue and Epsom Road;
- Rosebery Avenue and Epsom Road; and
- Rosebery Avenue and Crewe Place.

These intersections were surveyed as it was assessed that these sites would experience the greatest impact from the proposed development.

The surveys were conducted on Wednesday 11 February 2015 between 7:30am and 9:30am and between 4:00pm and 6:00pm. These periods were selected as they reflect the typical peak access times across the road network within the area.

Figure 9 and Figure 10 provide a summary of the AM and PM Peak hour results.




Figure 9 – Existing AM Peak Hour traffic counts




Figure 10 – Existing PM Peak Hour traffic counts

The results of the surveys indicate that generally the peak hour traffic occurs at the following times:

- AM Peak (08:00 to 09:00) and
- PM Peak (17:00 to 18:00).

### 3.8 Intersection Capacity Assessment (Existing Situation)

In order to confirm the current operation of the intersections servicing the site, an assessment has been undertaken using SIDRA Intersection modelling software for individual intersections analysed in isolation. The program presents a range of performance indicators (Level of Service, Average Delay, etc.).

Typically there are four performance indicators used to summarise the performance of an intersection, being:

- Degree of Saturation – The total usage of the intersection expressed as a factor of 1 representing 100% use/saturation. (e.g. 0.8=80% saturation)
- Average Delay - The average delay encountered by all vehicles passing through the intersection. It is often important to review the average delay of each approach as a side road could have a long delay time, while the large free flowing major traffic will provide an overall low average delay.
- Back of Queue lengths (Q95) - is defined to be the queue length in metres that has only a 5-percent probability of being exceeded during the analysis time period. It transforms the average delay into measureable distance units.
- Level of Service - This is a categorisation of average delay, intended for simple reference. The RMS adopts the following bands:

Table 2 - SIDRA Intersection Performance Bands

| Level of Service | Average Delay (secs/vehicle) | Traffic Signals, Roundabout   | Give Way & Stop Signs                     |
|------------------|------------------------------|---|---|
| A                | <14                          | Good operation  |   |
| B                | 15 to 28                     | Good with acceptable delays & spare capacity  | Acceptable delays & spare capacity        |
| C                | 29 to 42                     | Satisfactory  | Satisfactory, but accident study required |
| D                | 43 to 56                     | Operating near capacity   | Near capacity & accident study required   |
| E                | 57 to 70                     | At capacity. At signals, incidents would cause excessive delays. Roundabouts require other control mode | At capacity, requires other control mode  |
| F                | >70                          | Extra capacity required   | Extreme delay, major treatment required   |

A summary of the SIDRA results is presented in the following table, whilst SIDRA outputs are provided in **Attachment 2**.

Table 3 – SIDRA Intersection Modelling Results (Existing Situation)

| Period         | Intersection            | Level of Service | Avg Delay | Deg. Of Sat. | Back of Queue (m) |
|----------------|-------------------------|------------------|-----------|--------------|-------------------|
| <b>AM Peak</b> | Rosebery Ave – Crewe Pl | A*               | 4.5       | 0.056        | 0.2               |
|                | Rosebery Ave – Epsom Rd | A*               | 21.3      | 0.530        | 16.5              |
|                | Dalmeny Ave – Epsom Rd  | B                | 22.6      | 0.638        | 108.6             |
| <b>PM Peak</b> | Rosebery Ave – Crewe Pl | A*               | 4.3       | 0.066        | 1.7               |
|                | Rosebery Ave – Epsom Rd | A*               | 11.5      | 0.344        | 12.5              |
|                | Dalmeny Ave – Epsom Rd  | B                | 22.4      | 0.777        | 126.3             |

\*The results presented are based on the worse approach with the greatest average delay.

The SIDRA models were calibrated using vehicle queue data observed on each approach arm to reflect actual traffic conditions on site. The findings of the analysis indicate all intersections are operating well within the capacities and provide an acceptable level of service during the typical weekday peak periods.

## 4 Development Traffic Assessment

---

### 4.1 Traffic Generation

As discussed in Section 2.2, the site presently has a base FSR of 1.0:1 with the potential for an additional 0.5:1 should the site provide community based infrastructure which is being proposed. As such without this planning proposal the site has the potential to provide a development with a FSR of 1.5:1 under current planning controls.

This planning proposal proposes an amendment to the current development controls associated with this site to increase the developable FSR by 0.5:1 to 2.0:1. With an FSR of 2.0:1, the site has the potential to accommodate 387 residential units. It is acknowledged that the site is presently underdeveloped as an Industrial land use.

To understand the potential traffic impact of increasing the FSR by 0.5:1, the following section assesses the traffic generated from the site by reviewing the following:

- Current Planning Controls (Baseline) adopting an FSR of 1.5:1
- Proposed Planning Controls (Future) adopting an FSR of 2.0:1

#### 4.1.1 Traffic Generation based on a FSR of 1.5:1 (residential development)

Under the current LEP, the site is permitted for redevelopment with an FSR of up to 1.5:1 which consists of the current 1:1 FSR an additional bonus 0.5:1 FSR. When comparing this to the development potential of the site at an FSR of 2.0:1, it results in the construction of only 75% of total apartments. Therefore the potential unit yield for this site is:

- 387 Units x 75% = 287 units.

In the context of the traffic generation rates, and given this proposal relates to more than 20 apartments, the RMS guide indicates the development is considered as a high density residential flat dwelling. Therefore, per Technical Direction 13/04, the following weekday trip generation rates have been provided:

- Weekday average morning peak hour trips - 0.19 per Unit
- Weekday average evening peak hour trips - 0.15 per Unit

Based on the above rates, Table 4 below illustrates the estimated total peak trips that could be generated from site should it be developed with an FSR of 1.5:1.

Table 4 - Calculated Permissible Traffic Generation based on a FSR of 1.5:1 Residential Development

| Usage                           | Weekday Peak | Measurement | Weekday Peak hour rates <sup>iv</sup> | Assessment | Total Peak Trips |
|---------------------------------|--------------|-------------|---------------------------------------|------------|------------------|
| Residential Development (Units) | AM Peak      | Per unit    | 0.19 (RMS Guide)                      | 287 Units  | 54.9 (55)        |
| <b>Total AM Peak Trips</b>      |              |             |                                       |            | <b>55</b>        |
| Residential Development (Units) | PM Peak      | Per unit    | 0.15 (RMS Guide)                      | 287 Units  | 43.1 (43)        |
| <b>Total PM Peak</b>            |              |             |                                       |            | <b>43</b>        |

Table 4 shows up to 55 and 43 trips in the AM Peak and PM Peak hour respectively may be generated from a site with a FSR of 1.5:1 currently permitted under the LEP. Comparing this to the existing situation, it results in an increase of 16 and 10 vehicular trips during the AM Peak and PM Peak respectively.

#### 4.1.2 Traffic Generation based on a FSR of 2.0:1 (residential development)

This planning proposal considers the development of 12-40 Rosebery Avenue, Rosebery for primarily residential use by seeking an amendment to the LEP to permit a FSR of 2.0:1 from the permitted FSR of 1.5:1.

Based on the existing site area of 15,215 sqm, and by way of applying the increased FSR it would result in a residential development with a total GFA of 30,779 sqm, allowing for approximately 365 apartments and 18 terraces to be built. This assumes the existing site usages would be completely removed from site. In the context of the traffic generation rates, and given this proposal relates to more than 20 apartments, the RMS guide indicates the development is considered as a high density residential flat dwelling. Therefore, per Technical Direction 13/04, the following weekday trip generation rates for have been provided:

- Weekday average morning peak hour trips - 0.19 per Unit
- Weekday average evening peak hour trips – 0.15 per Unit

In the context of the RMS traffic generation rates, the Planning Proposal is identified as primarily providing for high density residential dwellings. Based on this, Table 5 illustrates the estimated total peak trips that would be generated assuming a FSR of 2.0:1.

Table 5 - Calculated Existing Traffic Generation based on a FSR of 2.0:1 Residential Development

| Usage   | Weekday Peak | Measurement       | Weekday Peak hour rates <sup>v</sup> | Assessment | Total Peak Trips |
|---|--------------|-------------------|--------------------------------------|------------|------------------|
| Residential Development (365 units + 18 Terraces) | AM Peak      | Per unit/ Terrace | 0.19 (RMS Guide)                     | 383 Units  | 72.7 (73)        |
| <b>Total AM Peak Trips</b>                        |              |                   |                                      |            | <b>73</b>        |

| Usage   | Weekday Peak | Measurement       | Weekday Peak hour rates <sup>v</sup> | Assessment | Total Peak Trips |
|---|--------------|-------------------|--------------------------------------|------------|------------------|
| Residential Development (365 units + 18 Terraces) | PM Peak      | Per unit/ Terrace | 0.15 (RMS Guide)                     | 383 Units  | 57.45 (57)       |
| <b>Total PM Peak</b>                              |              |                   |                                      |            | <b>57</b>        |

Table 5 shows that the proposed planned use for the site would result in up to 73 and 57 trips in the AM Peak and PM Peak hour respectively. This is an increase of 34 trips in the AM Peak and 18 trips in the PM Peak compared to the current existing use as calculated in Section 3.6 above.

### 4.1.3 Summary of Traffic Generation Scenarios

The calculated total peak trips for each of the tested scenarios are summarised in Table 6. In reviewing the findings against the existing situation, the site presently has the potential to generate an additional:

- 16 and 10 vehicular trips during the AM Peak and PM Peak periods respectively under the current planning controls with an FSR of 1.5:1; and
- 34 and 18 vehicular trips during the AM Peak and PM Peak periods respectively under the proposed amended planning control with an FSR of 2.0:1.

In assessing the impact of increasing the developable FSR by 0.5:1, this will result in an additional 18 and 8 vehicular trips during the AM Peak and PM Peak respectively. The impact of the increase in vehicular traffic is reviewed in Section 4.2 below.

Table 6 – Summary of traffic generation scenarios permissible at the development site

| Usage  | Assessment  | AM Peak Trips | PM Peak Trips |
|--|---|---------------|---------------|
| <b>Existing Situation – Industrial Development [RTA Rates]</b> | 9,800 sqm GFA                                       | 39            | 39            |
| <b>Residential Use Development (FSR 1.5:1) [Baseline]</b>      | 287 Residential Units                               | 55            | 49            |
| <b>Residential Use Development (FSR 2.0:1) [Proposed]</b>      | 365 Residential Units and 18 three bedroom terraces | 73            | 57            |

## 4.2 Traffic Distribution

In reviewing the Planning Proposal, it is acknowledged that in conjunction with a Development Application, the traffic and parking impacts of the development would result in the closure of the existing driveway accesses from Dalmeny Avenue and Rosebery Avenue by way of a new vehicular access provided only from Dalmeny Avenue. In assessing the impacts of increasing traffic on Dalmeny Avenue, we have incorporated the following traffic distribution assumptions:

- For the residential development, 20% (In)/80% (Out) has been adopted in the AM peak and vice versa in the PM Peak. These movements generally occur during the road network peak due to residents leaving their

premises to travel to work, also allowing for some inbound movements for residents undertaking a round trip.

- To provide a robust assessment, we have assumed all vehicular trips associated with the existing developments with accesses on either Rosebery Avenue or Dalmeny Avenue have not been removed from the traffic volumes. To assess the impact of the additional traffic generated from the development we have removed 39 trips from the Proposed AM Peak and PM Peaks.
- To distribute the traffic onto the adjacent road network, we have assumed the existing traffic turning percentages currently utilising Epsom Road and Dalmeny Avenue to travel elsewhere in the network. They are:
  - AM Peak - Traffic turning out from Dalmeny Ave to Epsom Road 66% turn left 34% turn right;
  - AM Peak – Traffic turning in from Epsom Road to Dalmeny Ave 64% arrive from the eastbound approach; 36% arrive from the westbound approach
  - PM Peak - Traffic turning out from Dalmeny Ave to Epsom Road 72% turn left 28% turn right;
  - PM Peak – Traffic turning in from Epsom Road to Dalmeny Ave 65% arrive from the westbound approach; 35% arrive from the westbound approach

The calculated split of in/out trips during the AM and PM peak hours is presented in Table 7.

Table 7 - Calculated split in/out trips associated with the Planning Proposal (FSR 2.0:1)


|  | AM Peak |           |       | PM Peak   |         |       |
|--|---------|-----------|-------|-----------|---------|-------|
|  | In      | Out       | Total | In        | Out     | Total |
| Existing Situation                       |         |           | 39    |           |         | 39    |
| FSR 1.5:1 Residential [Baseline]         |         |           | 55    |           |         | 49    |
| FSR 1.5:1 Total Additional Trips (20:80) | 3.2 (3) | 12.8 (13) | 16    | 8         | 2       | 10    |
| FSR 2.1:1 Residential [Proposal]         |         |           | 73    |           |         | 57    |
| FSR 2.0:1 Total Additional Trips (20:80) | 6.8(7)  | 27.2 (27) | 34    | 14.4 (14) | 3.6 (4) | 18    |

### 4.3 Intersection Capacity Assessment (Baseline FSR of 1.5:1)

The post development traffic generation associated with a developable FSR 1.5:1 presented in Table 7 distributed onto the road network is presented in Figure 11 and Figure 12. The figures presented were used in SIDRA.



Future Weekday  
Morning Peak  
(FSR 1.5:1)



Future Weekday  
Afternoon Peak  
(FSR 1.5:1)




Figure 11 - Future AM Peak Traffic Distribution (FSR 1.5:1) Figure 12 – Future PM Peak Traffic Distribution (FSR 1.5:1)

The projected traffic volumes have been applied to the surveyed traffic turn count volumes and subsequently modelled using SIDRA. The results of this analysis are summarised below with SIDRA outputs provided as Attachment 3.

Table 8 – SIDRA Intersection Modelling Results (Baseline FSR of 1.5:1)

| Period         | Intersection            | Level of Service | Avg. Delay | Deg. Of Sat. | Back of Queue (m) |
|----------------|-------------------------|------------------|------------|--------------|-------------------|
| <b>AM Peak</b> | Rosebery Ave – Crewe Pl | A*               | 4.5        | 0.056        | 0.2               |
|                | Rosebery Ave – Epsom Rd | B*               | 21.9       | 0.541        | 2.4               |
|                | Dalmeny Ave – Epsom Rd  | B                | 22.8       | 0.640        | 109.8             |
| <b>PM Peak</b> | Rosebery Ave – Crewe Pl | A*               | 4.3        | 0.066        | 1.7               |
|                | Rosebery Ave – Epsom Rd | A*               | 11.7       | 0.348        | 1.8               |
|                | Dalmeny Ave – Epsom Rd  | B                | 22.0       | 0.755        | 124.5             |

\*The results presented are based on the worse approach with the greatest average delay.

Under the current developable FSR of 1.5:1, with the addition of 16 in/out movements in the AM Peak and 10 in/out movements in the PM Peak, SIDRA modelling indicates the site will continue to operate well compared with the existing situation.

If the site was only developed under a developable FSR of 1.5:1, the traffic modelling associated with Epsom Road and Dalmeny Avenue intersection indicates the increase in traffic movement on Dalmeny Avenue would not result in any notable impact on the overall operation at this intersection and will continue to operate well within its capacity compared with the existing traffic conditions modelled.

#### 4.4 Intersection Capacity Assessment (Proposal FSR of 2.0:1)

The post development traffic generation associated with an FSR 2.0:1 presented in Table 7 is distributed onto the road network presented in Figure 13 and Figure 14. The figures presented were used in SIDRA.

Future Weekday  
Morning Peak  
(FSR 2.0:1)




Figure 13 - Future AM Peak Traffic Distribution

Future Weekday  
Afternoon Peak  
(FSR 2.0:1)




Figure 14 – Future PM Peak Traffic Distribution

The results of this analysis are summarised below in Table 9 below with SIDRA outputs provided as Attachment 4.

Table 9 – Summary of SIDRA Intersection Modelling Results (2.0:1 FSR)

| Period         | Intersection            | Level of Service | Avg Delay | Deg. Of Sat. | Back of Queue (m) |
|----------------|-------------------------|------------------|-----------|--------------|-------------------|
| <b>AM Peak</b> | Rosebery Ave – Crewe Pl | A*               | 4.5       | 0.056        | 0.2               |
|                | Rosebery Ave – Epsom Rd | B*               | 22.6      | 0.554        | 17.3              |
|                | Dalmeny Ave – Epsom Rd  | B                | 23.0      | 0.643        | 111.3             |
| <b>PM Peak</b> | Rosebery Ave – Crewe Pl | A*               | 4.3       | 0.066        | 1.7               |
|                | Rosebery Ave – Epsom Rd | A*               | 11.7      | 0.352        | 12.8              |
|                | Dalmeny Ave – Epsom Rd  | B                | 23.1      | 0.791        | 128.8             |

\*The results presented are based on the worse approach with the greatest average delay.

The SIDRA modelling results presented in Table 9 indicates the site will continue to operate well within its capacity and will continue to operate satisfactorily.

## 4.5 Assessment of Traffic Generation impacts by increasing the FSR by 0.5:1

The results presented as part of the traffic modelling in sections 4.3 and 4.4, have demonstrated that the increase in traffic movements in and out Dalmeny Avenue onto Epsom Road, shows no notable impact on the overall road network operation. In assessing the impact of increasing the FSR by 0.5:1 above the currently developable FSR of 1.5:1, the traffic modelling associated with Rosebery Avenue and Dalmeny Avenue intersection indicates the increase in traffic movement on Dalmeny Avenue would not result in any notable impact on the overall operation at this intersection. Therefore, the proposal to accommodate a development with a 2.0:1 FSR instead of a 1.5:1 FSR would not result in any detrimental impacts.

Table 10 – Summary of Level of Service Results

| Period         | Intersection            | Existing | FSR 1.5:1<br>[Baseline] | FSR 2.0:1<br>[Proposal] |
|----------------|-------------------------|----------|-------------------------|-------------------------|
| <b>AM Peak</b> | Rosebery Ave – Crewe Pl | A*       | A*                      | A*                      |
|                | Rosebery Ave – Epsom Rd | A*       | B*                      | B*                      |
|                | Dalmeny Ave – Epsom Rd  | B        | B                       | B                       |
| <b>PM Peak</b> | Rosebery Ave – Crewe Pl | A*       | A*                      | A*                      |
|                | Rosebery Ave – Epsom Rd | A*       | A*                      | A*                      |
|                | Dalmeny Ave – Epsom Rd  | B        | B                       | B                       |

\*The results presented are based on the worse approach with the greatest average delay.

Table 11 – Summary of Average Delay (Secs) Results

| Period         | Intersection            | Existing | FSR 1.5:1 | FSR 2.0:1 |
|----------------|-------------------------|----------|-----------|-----------|
| <b>AM Peak</b> | Rosebery Ave – Crewe Pl | 4.5      | 4.5       | 4.5       |
|                | Rosebery Ave – Epsom Rd | 21.3     | 21.9      | 22.6      |
|                | Dalmeny Ave – Epsom Rd  | 22.6     | 22.8      | 23.0      |
| <b>PM Peak</b> | Rosebery Ave – Crewe Pl | 4.3      | 4.3       | 4.3       |
|                | Rosebery Ave – Epsom Rd | 10.3     | 11.7      | 11.7      |
|                | Dalmeny Ave – Epsom Rd  | 22.4     | 22.0      | 23.1      |

Table 12 – Summary of Degree of Saturation Results

| Period         | Intersection            | Existing | FSR 1.5:1 | FSR 2.0:1 |
|----------------|-------------------------|----------|-----------|-----------|
| <b>AM Peak</b> | Rosebery Ave – Crewe Pl | 0.056    | 0.056     | 0.056     |
|                | Rosebery Ave – Epsom Rd | 0.530    | 0.541     | 0.554     |
|                | Dalmeny Ave – Epsom Rd  | 0.638    | 0.640     | 0.643     |
| <b>PM Peak</b> | Rosebery Ave – Crewe Pl | 0.066    | 0.066     | 0.066     |
|                | Rosebery Ave – Epsom Rd | 0.260    | 0.348     | 0.352     |
|                | Dalmeny Ave – Epsom Rd  | 0.777    | 0.755     | 0.791     |

Table 13 – Summary of Back of Queue Distance (m) Results

| Period         | Intersection            | Existing | FSR 1.5:1 | FSR 2.0:1 |
|----------------|-------------------------|----------|-----------|-----------|
| <b>AM Peak</b> | Rosebery Ave – Crewe Pl | 0.2      | 0.2       | 0.2       |
|                | Rosebery Ave – Epsom Rd | 16.5     | 16.8      | 17.3      |
|                | Dalmeny Ave – Epsom Rd  | 108.6    | 109.8     | 111.3     |
| <b>PM Peak</b> | Rosebery Ave – Crewe Pl | 1.7      | 1.7       | 1.7       |
|                | Rosebery Ave – Epsom Rd | 12.5     | 12.6      | 12.8      |
|                | Dalmeny Ave – Epsom Rd  | 126.3    | 124.5     | 128.8     |

## 5 Parking Assessment

---

The parking provision for the development must comply with the requirements presented in Council's Local Environmental Plan 2012 (the LEP) and Development Control Plans 2012 (the DCP). The LEP sets a maximum parking provision calculated for the specific land use that a development cannot exceed.

In reviewing the parking provision requirements associated with this proposal, clause 7.2 of the LEP, states the following:

### 7.2 Interpretation

(2) For the purposes of this Division, land is in Category A, Category B or Category C if it is shown on the Land Use and Transport Integration Map as being in one of those categories. However, land is taken to be in another of those categories if:

- (a) the land is part of a site that includes land in that other category, and
- (b) this Division would permit a greater number of car parking spaces if the land were in that other category.

(3) For the purposes of this Division, land is in Category D, Category E or Category F if it is shown on the Public Transport Accessibility Level Map as being in one of those categories. However, land is taken to be in another of those categories if:

- (a) the land is part of a site that includes land in that other category, and
- (b) this Division would permit a greater number of car parking spaces if the land were in that other category.

(4) More than one provision of this Division may apply in the case of a mixed use development and in such a case:

- (a) the maximum number of car parking spaces is the sum of the number of spaces permitted under each of those provisions, and
- (b) a reference in those provisions to a building, is taken to be a reference to the parts of the building in which the relevant use occurs.

In interpreting the above LEP requirements, it allows for the higher parking provision rate to be adopted for the site should it fall within a Land Category C for the residential component. As such, the following parking provision rates apply to the residential component of the development.

(c) on land in category C:

- i. for each studio dwelling—0.4 spaces, and
- ii. for each 1 bedroom dwelling—0.5 spaces, and
- iii. for each 2 bedroom dwelling—1 space, and
- iv. for each 3 or more bedroom dwelling—1.2 spaces, and
- v. for each dwelling up to 30 dwellings—0.2 spaces, and
- vi. for each dwelling more than 30 and up to 70 dwellings—0.125 spaces, and
- vii. for each dwelling more than 70 dwellings—0.067 spaces.

In assessing the proposal against the baseline allowance to build a scheme with a FSR of 1.5:1, it would result in only 75% of the proposed 2.0:1 development being provided for each type of unit configuration proposed. To

# ATTACHMENT A

determine the maximum parking provision allowed under the existing LEP, the relevant parking provision calculation is presented in Table 14. The table indicates the maximum parking provision associated with the current developable FSR of 1.5:1 is 225 parking spaces.

Table 14 – Parking Provision (Baseline FSR of 1.5:1)

| Use Type  |     |       |   |  | Required Spaces |
|---|-----|-------|---|--|-----------------|
| Studio  | 0   | Units | @ | 0.4 spaces per apartment                 | 0               |
| 1 Bedroom apartment   | 133 | Units | @ | 0.5 spaces per apartment                 | 66.5 (66)       |
| 2 Bedroom apartment   | 107 | Units | @ | 1.0 spaces per apartment                 | 107             |
| 3 Bedroom apartment (inc Terraces)                                | 47  | Units | @ | 1.2 spaces per apartment                 | 56.4 (56)       |
| Visitor Parking   | 30  | Units | @ | 0.2 spaces up to 30 dwellings            | 6               |
| Visitor Parking   | 40  | Units | @ | 0.125 spaces between 30 to 70 dwellings  | 5               |
| Visitor Parking   | 217 | Units | @ | 0.0675 spaces for more than 70 dwellings | 14.6 (15)       |
| <b>FSR 1.5:1 Maximum Parking Spaces (Apartment and Visitors):</b> |     |       |   |  | <b>225</b>      |

In assessing the car park requirements the potential increase in FSR by 0.5:1 to a developable FSR of 2.0:1 may result in a maximum parking provision of 340 parking spaces. This calculation is presented in Table 15 (this is based on a potential yield of 378 apartments and terraces).

Table 15 – Parking Provision (Proposal FSR of 2.0:1)

| Use Type  |     |       |   |  | Required Spaces   |
|---|-----|-------|---|--|-------------------|
| Studio  | 0   | Units | @ | 0.4 spaces per apartment                 | 0                 |
| 1 Bedroom apartment   | 177 | Units | @ | 0.5 spaces per apartment                 | 88.5 (89)         |
| 2 Bedroom apartment   | 143 | Units | @ | 1.0 spaces per apartment                 | 143               |
| 3 Bedroom apartment (including 18 terraces)                       | 63  | Units | @ | 1.2 spaces per apartment                 | 75.6 (76)         |
| Visitor Parking   | 30  | Units | @ | 0.2 spaces up to 30 dwellings            | 6                 |
| Visitor Parking   | 40  | Units | @ | 0.125 spaces between 30 to 70 dwellings  | 5                 |
| Visitor Parking   | 313 | Units | @ | 0.0675 spaces for more than 70 dwellings | 21                |
| <b>FSR 2.0:1 Maximum Parking Spaces (Apartment and Visitors):</b> |     |       |   |  | <b>340</b>        |
| <b>Increase in parking from FSR of 1.5:1</b>                      |     |       |   |  | <b>+85 spaces</b> |

In comparing and assessing the impact of increasing the developable FSR by 0.5:1, it would result in an additional 85 parking spaces being provided on site.

The impact of increasing parking by 85 parking spaces results in an increase in traffic activity by 20 in/out vehicle movements in the AM Peak and 8 in/out movements in the PM Peak. In reviewing the intersection modelling undertaken using an FSR of 1.5:1 and 2.0:1, the increase in vehicle trips in/out of the site during the

# ATTACHMENT A



morning and afternoon peak periods very minor increase in traffic activity adjacent to the site compared with the existing situation (as presented in section 4.1.3). Therefore, the proposal to accommodate a development with a 2.0:1 FSR instead of a 1.5:1 FSR would not result in any detrimental impacts.

# ATTACHMENT A

## 6 Summary

---

This report presents the preliminary traffic assessment findings associated with increasing the FSR from 1.5:1 to 2.0:1 of the subject property, known as 12-40 Rosebery Avenue, Rosebery.

The development proposal considers the traffic generation scenario of a residential development with an FSR of 2.0:1 that may provide up to 365 residential units and 18 terraces. The findings of this assessment indicate this will result in slightly more traffic being generated when compared to developing the site in accordance the current baseline LEP density, (1.0:1 with the inclusion of an additional 0.5:1 under Clause 6.14) a total of 1.5:1.

The project will result in a net increase of up to 23 vehicular trips associated with the site development in the AM and PM Peak accessing the Dalmeny Avenue intersection with Epsom Road compared to its current use.

Traffic modelling of the Dalmeny Avenue and Epsom Road intersection indicates the increase in traffic movement into and out of Dalmeny Avenue under the baseline scenario (FSR 1.5:1) and proposed scenario (FSR 2.0:1) would not result in any notable impact on the overall operation at this intersection, which will continue to operate well within its capacity compared with the existing traffic conditions modelled.

The impact of potentially providing 340 spaces associated with the residential use of the development results in an increase of 85 spaces compared to what is currently permitted under the current allowable FSR of 1.5:1. The basement car parking arrangement is capable of being developed in accordance with the relevant Australian Standards, with full assessment to be undertaken during the Development Application process.

In assessing the impacts of increasing the parking provision on site, it will result in a minor increase vehicle trips entering/exiting the site during the AM and PM Peak. In reviewing this against the findings of the traffic modelling, the proposal for an increase in FSR from 1.5:1 to 2.0:1 to permit a higher residential apartment yield, this report has demonstrated that the increase in traffic movements in and out from dedicated driveways on Dalmeny Avenue shows no notable impact on the overall road network operation and will provide an acceptable level of service during the typical weekday peak periods.

As such this traffic assessment supports the Planning Proposal to increase the floor space ratio (FSR) from a ratio 1.5:1 to 2.0:1.



## Attachment 1 – Architectural Plans

---

## Attachment 2 – SIDRA OUTPUTS (Existing Situation)

---

## MOVEMENT SUMMARY

 **Site: Epsom RD - Rosbery Ave - AM Existing**

New Site  
 Giveway / Yield (Two-Way)

### Movement Performance - Vehicles

| Mov ID             | ODMo<br>v | Demand Flows   |         | Deg. Satn<br>v/c | Average<br>Delay<br>sec | Level of<br>Service | 95% Back of Queue |               | Prop.<br>Queued<br>per veh | Effective<br>Stop Rate<br>per veh | Average<br>Speed<br>km/h |
|--------------------|-----------|----------------|---------|------------------|-------------------------|---------------------|-------------------|---------------|----------------------------|-----------------------------------|--------------------------|
|                    |           | Total<br>veh/h | HV<br>% |                  |                         |                     | Vehicles<br>veh   | Distance<br>m |                            |                                   |                          |
| South: RoadName    |           |                |         |                  |                         |                     |                   |               |                            |                                   |                          |
| 1                  | L2        | 65             | 0.0     | 0.108            | 9.6                     | LOS A               | 0.4               | 3.1           | 0.74                       | 0.86                              | 39.4                     |
| 3                  | R2        | 147            | 0.0     | 0.530            | 26.4                    | LOS B               | 2.4               | 16.5          | 0.94                       | 1.11                              | 33.1                     |
| Approach           |           | 213            | 0.0     | 0.530            | 21.3                    | LOS B               | 2.4               | 16.5          | 0.88                       | 1.03                              | 34.8                     |
| East: Epsom Rd (E) |           |                |         |                  |                         |                     |                   |               |                            |                                   |                          |
| 4                  | L2        | 219            | 0.0     | 0.600            | 5.6                     | LOS A               | 0.0               | 0.0           | 0.00                       | 0.11                              | 57.2                     |
| 5                  | T1        | 941            | 0.0     | 0.600            | 0.1                     | LOS A               | 0.0               | 0.0           | 0.00                       | 0.11                              | 58.8                     |
| Approach           |           | 1160           | 0.0     | 0.600            | 1.2                     | NA                  | 0.0               | 0.0           | 0.00                       | 0.11                              | 58.5                     |
| West: Epsom Rd (w) |           |                |         |                  |                         |                     |                   |               |                            |                                   |                          |
| 11                 | T1        | 802            | 0.0     | 0.411            | 0.1                     | LOS A               | 0.0               | 0.0           | 0.00                       | 0.00                              | 49.9                     |
| 12                 | R2        | 74             | 0.0     | 0.553            | 50.0                    | LOS D               | 2.2               | 15.3          | 0.96                       | 1.08                              | 27.6                     |
| Approach           |           | 876            | 0.0     | 0.553            | 4.3                     | NA                  | 2.2               | 15.3          | 0.08                       | 0.09                              | 46.8                     |
| All Vehicles       |           | 2248           | 0.0     | 0.600            | 4.3                     | NA                  | 2.4               | 16.5          | 0.11                       | 0.19                              | 50.3                     |

## MOVEMENT SUMMARY

 **Site: Epsom Rd - Dalmeny Ave - AM Existing**

New Site  
 Signals - Fixed Time Cycle Time = 120 seconds (User-Given Cycle Time) Variable Sequence Analysis applied.  
 The results are given for the selected output sequence.

### Movement Performance - Vehicles

| Mov ID                  | ODMo<br>v | Demand Flows   |         | Deg. Satn<br>v/c | Average<br>Delay<br>sec | Level of<br>Service | 70% Back of Queue |               | Prop.<br>Queued<br>per veh | Effective<br>Stop Rate<br>per veh | Average<br>Speed<br>km/h |
|-------------------------|-----------|----------------|---------|------------------|-------------------------|---------------------|-------------------|---------------|----------------------------|-----------------------------------|--------------------------|
|                         |           | Total<br>veh/h | HV<br>% |                  |                         |                     | Vehicles<br>veh   | Distance<br>m |                            |                                   |                          |
| South: Dalmeny Ave (NB) |           |                |         |                  |                         |                     |                   |               |                            |                                   |                          |
| 1                       | L2        | 189            | 0.0     | 0.357            | 30.4                    | LOS C               | 5.7               | 40.0          | 0.73                       | 0.73                              | 32.2                     |
| 3                       | R2        | 96             | 0.0     | 0.294            | 34.0                    | LOS C               | 3.0               | 21.0          | 0.89                       | 0.73                              | 31.2                     |
| Approach                |           | 285            | 0.0     | 0.357            | 31.6                    | LOS C               | 5.7               | 40.0          | 0.78                       | 0.73                              | 31.9                     |
| East: Epsom Rd (WB)     |           |                |         |                  |                         |                     |                   |               |                            |                                   |                          |
| 4                       | L2        | 62             | 0.0     | 0.606            | 34.8                    | LOS C               | 15.2              | 106.2         | 0.82                       | 0.88                              | 34.6                     |
| 5                       | T1        | 967            | 0.0     | 0.606            | 31.0                    | LOS C               | 15.5              | 108.6         | 0.82                       | 0.88                              | 34.9                     |
| Approach                |           | 1029           | 0.0     | 0.606            | 31.2                    | LOS C               | 15.5              | 108.6         | 0.82                       | 0.88                              | 34.9                     |
| West: Epsom Rd (EB)     |           |                |         |                  |                         |                     |                   |               |                            |                                   |                          |
| 11                      | T1        | 820            | 0.0     | 0.638            | 6.8                     | LOS A               | 8.3               | 58.2          | 0.46                       | 0.41                              | 45.6                     |
| 12                      | R2        | 108            | 0.0     | 0.638            | 36.9                    | LOS C               | 4.9               | 34.5          | 0.97                       | 0.79                              | 31.2                     |
| Approach                |           | 928            | 0.0     | 0.638            | 10.3                    | LOS A               | 8.3               | 58.2          | 0.52                       | 0.46                              | 43.3                     |
| All Vehicles            |           | 2243           | 0.0     | 0.638            | 22.6                    | LOS B               | 15.5              | 108.6         | 0.69                       | 0.68                              | 37.5                     |

### Movement Performance - Pedestrians

| Mov ID          | Description         | Demand Flow<br>ped/h | Average Delay<br>sec | Level of Service | Average Back of Queue |          | Prop. Queued | Effective Stop Rate<br>per ped |
|-----------------|---------------------|----------------------|----------------------|------------------|-----------------------|----------|--------------|--------------------------------|
|                 |                     |                      |                      |                  | Pedestrian            | Distance |              |                                |
|                 |                     |                      |                      |                  | ped                   | m        |              |                                |
| P1              | South Full Crossing | 26                   | 28.0                 | LOS C            | 0.1                   | 0.1      | 0.68         | 0.68                           |
| P4              | West Full Crossing  | 26                   | 54.2                 | LOS E            | 0.1                   | 0.1      | 0.95         | 0.95                           |
| All Pedestrians |                     | 53                   | 41.1                 | LOS E            |                       |          | 0.82         | 0.82                           |

Level of Service (LOS) Method: SIDRA Pedestrian LOS Method (Based on Average Delay)  
 Pedestrian movement LOS values are based on average delay per pedestrian movement.  
 Intersection LOS value for Pedestrians is based on average delay for all pedestrian movements.

## MOVEMENT SUMMARY

▽ **Site: Rosebery Ave - Crewe PI - AM Existing**

New Site

Giveaway / Yield (Two-Way)

### Movement Performance - Vehicles

| Mov ID          | ODMo<br>v | Demand Flows   |         | Deg. Satn<br>v/c | Average<br>Delay<br>sec | Level of<br>Service | 95% Back of Queue |               | Prop.<br>Queued | Effective<br>Stop Rate<br>per veh | Average<br>Speed<br>km/h |
|-----------------|-----------|----------------|---------|------------------|-------------------------|---------------------|-------------------|---------------|-----------------|-----------------------------------|--------------------------|
|                 |           | Total<br>veh/h | HV<br>% |                  |                         |                     | Vehicles<br>veh   | Distance<br>m |                 |                                   |                          |
| South: RoadName |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 1               | L2        | 21             | 0.0     | 0.129            | 3.4                     | LOS A               | 0.0               | 0.0           | 0.00            | 0.04                              | 40.0                     |
| 2               | T1        | 229            | 0.0     | 0.129            | 0.0                     | LOS A               | 0.0               | 0.0           | 0.00            | 0.04                              | 39.9                     |
| Approach        |           | 251            | 0.0     | 0.129            | 0.3                     | NA                  | 0.0               | 0.0           | 0.00            | 0.04                              | 39.9                     |
| North: RoadName |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 8               | T1        | 203            | 0.0     | 0.160            | 0.9                     | LOS A               | 1.0               | 6.8           | 0.38            | 0.15                              | 38.9                     |
| 9               | R2        | 78             | 0.0     | 0.160            | 4.5                     | LOS A               | 1.0               | 6.8           | 0.38            | 0.15                              | 38.8                     |
| Approach        |           | 281            | 0.0     | 0.160            | 1.9                     | NA                  | 1.0               | 6.8           | 0.38            | 0.15                              | 38.9                     |
| West: RoadName  |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 10              | L2        | 52             | 0.0     | 0.056            | 4.5                     | LOS A               | 0.2               | 1.5           | 0.32            | 0.51                              | 38.2                     |
| 12              | R2        | 14             | 0.0     | 0.056            | 4.6                     | LOS A               | 0.2               | 1.5           | 0.32            | 0.51                              | 37.9                     |
| Approach        |           | 65             | 0.0     | 0.056            | 4.5                     | LOS A               | 0.2               | 1.5           | 0.32            | 0.51                              | 38.1                     |
| All Vehicles    |           | 597            | 0.0     | 0.160            | 1.5                     | NA                  | 1.0               | 6.8           | 0.22            | 0.14                              | 39.2                     |

## MOVEMENT SUMMARY

 **Site: Epsom RD - Rosbery Ave - PM Existing**

New Site  
 Giveway / Yield (Two-Way)

### Movement Performance - Vehicles

| Mov ID             | ODMo<br>v | Demand Flows   |         | Deg. Satn<br>v/c | Average<br>Delay<br>sec | Level of<br>Service | 95% Back of Queue |               | Prop.<br>Queued | Effective<br>Stop Rate<br>per veh | Average<br>Speed<br>km/h |
|--------------------|-----------|----------------|---------|------------------|-------------------------|---------------------|-------------------|---------------|-----------------|-----------------------------------|--------------------------|
|                    |           | Total<br>veh/h | HV<br>% |                  |                         |                     | Vehicles<br>veh   | Distance<br>m |                 |                                   |                          |
| South: RoadName    |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 1                  | L2        | 97             | 0.0     | 0.090            | 6.1                     | LOS A               | 0.4               | 3.0           | 0.61            | 0.68                              | 41.0                     |
| 3                  | R2        | 194            | 0.0     | 0.344            | 14.3                    | LOS A               | 1.8               | 12.5          | 0.89            | 1.03                              | 37.2                     |
| Approach           |           | 291            | 0.0     | 0.344            | 11.5                    | LOS A               | 1.8               | 12.5          | 0.80            | 0.91                              | 38.4                     |
| East: Epsom Rd (E) |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 4                  | L2        | 132            | 0.0     | 0.382            | 4.6                     | LOS A               | 0.0               | 0.0           | 0.00            | 0.10                              | 48.9                     |
| 5                  | T1        | 607            | 0.0     | 0.382            | 0.1                     | LOS A               | 0.0               | 0.0           | 0.00            | 0.10                              | 49.4                     |
| Approach           |           | 739            | 0.0     | 0.382            | 0.9                     | NA                  | 0.0               | 0.0           | 0.00            | 0.10                              | 49.3                     |
| West: Epsom Rd (w) |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 11                 | T1        | 1119           | 0.0     | 0.574            | 0.1                     | LOS A               | 0.0               | 0.0           | 0.00            | 0.00                              | 59.8                     |
| 12                 | R2        | 81             | 0.0     | 0.121            | 10.6                    | LOS A               | 0.5               | 3.7           | 0.67            | 0.85                              | 49.7                     |
| Approach           |           | 1200           | 0.0     | 0.574            | 0.8                     | NA                  | 0.5               | 3.7           | 0.05            | 0.06                              | 59.0                     |
| All Vehicles       |           | 2229           | 0.0     | 0.574            | 2.2                     | NA                  | 1.8               | 12.5          | 0.13            | 0.18                              | 52.0                     |

## MOVEMENT SUMMARY

 **Site: Epsom Rd - Dalmeny Ave - PM Existing**

New Site  
 Signals - Fixed Time Cycle Time = 120 seconds (User-Given Cycle Time) Variable Sequence Analysis applied.  
 The results are given for the selected output sequence.

### Movement Performance - Vehicles

| Mov ID                  | ODMo<br>v | Demand Flows   |         | Deg. Satn<br>v/c | Average<br>Delay<br>sec | Level of<br>Service | 95% Back of Queue |               | Prop.<br>Queued | Effective<br>Stop Rate<br>per veh | Average<br>Speed<br>km/h |
|-------------------------|-----------|----------------|---------|------------------|-------------------------|---------------------|-------------------|---------------|-----------------|-----------------------------------|--------------------------|
|                         |           | Total<br>veh/h | HV<br>% |                  |                         |                     | Vehicles<br>veh   | Distance<br>m |                 |                                   |                          |
| South: Dalmeny Ave (NB) |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 1                       | L2        | 129            | 0.0     | 0.133            | 14.7                    | LOS B               | 3.2               | 22.7          | 0.46            | 0.63                              | 37.4                     |
| 3                       | R2        | 51             | 0.0     | 0.140            | 26.1                    | LOS B               | 1.3               | 9.3           | 0.86            | 0.71                              | 33.5                     |
| Approach                |           | 180            | 0.0     | 0.140            | 17.9                    | LOS B               | 3.2               | 22.7          | 0.58            | 0.65                              | 36.2                     |
| East: Epsom Rd (WB)     |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 4                       | L2        | 74             | 0.0     | 0.777            | 52.1                    | LOS D               | 17.7              | 123.8         | 0.99            | 1.06                              | 29.5                     |
| 5                       | T1        | 609            | 0.0     | 0.777            | 48.4                    | LOS D               | 18.0              | 126.3         | 0.99            | 1.07                              | 29.8                     |
| Approach                |           | 683            | 0.0     | 0.777            | 48.8                    | LOS D               | 18.0              | 126.3         | 0.99            | 1.07                              | 29.8                     |
| West: Epsom Rd (EB)     |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 11                      | T1        | 1177           | 0.0     | 0.662            | 8.1                     | LOS A               | 11.8              | 82.4          | 0.54            | 0.50                              | 44.8                     |
| 12                      | R2        | 136            | 0.0     | 0.662            | 19.5                    | LOS B               | 11.4              | 80.1          | 0.76            | 0.71                              | 37.4                     |
| Approach                |           | 1313           | 0.0     | 0.662            | 9.3                     | LOS A               | 11.8              | 82.4          | 0.57            | 0.52                              | 43.9                     |
| All Vehicles            |           | 2176           | 0.0     | 0.777            | 22.4                    | LOS B               | 18.0              | 126.3         | 0.70            | 0.70                              | 37.6                     |

### Movement Performance - Pedestrians

| Mov ID          | Description         | Demand Flow<br>ped/h | Average Delay<br>sec | Level of Service | Average Back of Queue |          | Prop. Queued | Effective Stop Rate<br>per ped |
|-----------------|---------------------|----------------------|----------------------|------------------|-----------------------|----------|--------------|--------------------------------|
|                 |                     |                      |                      |                  | Pedestrian            | Distance |              |                                |
|                 |                     |                      |                      |                  | ped                   | m        |              |                                |
| P1              | South Full Crossing | 53                   | 54.3                 | LOS E            | 0.2                   | 0.2      | 0.95         | 0.95                           |
| P4              | West Full Crossing  | 53                   | 54.3                 | LOS E            | 0.2                   | 0.2      | 0.95         | 0.95                           |
| All Pedestrians |                     | 105                  | 54.3                 | LOS E            |                       |          | 0.95         | 0.95                           |

Level of Service (LOS) Method: SIDRA Pedestrian LOS Method (Based on Average Delay)  
 Pedestrian movement LOS values are based on average delay per pedestrian movement.  
 Intersection LOS value for Pedestrians is based on average delay for all pedestrian movements.

## MOVEMENT SUMMARY

### ▽ Site: Rosebery Ave - Crewe PI - PM Existing

New Site

Giveaway / Yield (Two-Way)

#### Movement Performance - Vehicles

| Mov ID                         | ODMo<br>v | Demand Flows   |         | Deg. Satn<br>v/c | Average<br>Delay<br>sec | Level of<br>Service | 95% Back of Queue |               | Prop.<br>Queued | Effective<br>Stop Rate<br>per veh | Average<br>Speed<br>km/h |
|--------------------------------|-----------|----------------|---------|------------------|-------------------------|---------------------|-------------------|---------------|-----------------|-----------------------------------|--------------------------|
|                                |           | Total<br>veh/h | HV<br>% |                  |                         |                     | Vehicles<br>veh   | Distance<br>m |                 |                                   |                          |
| <b>South: Rosebery Ave (S)</b> |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 1                              | L2        | 11             | 0.0     | 0.097            | 3.4                     | LOS A               | 0.0               | 0.0           | 0.00            | 0.03                              | 40.1                     |
| 2                              | T1        | 178            | 0.0     | 0.097            | 0.0                     | LOS A               | 0.0               | 0.0           | 0.00            | 0.03                              | 39.9                     |
| Approach                       |           | 188            | 0.0     | 0.097            | 0.2                     | NA                  | 0.0               | 0.0           | 0.00            | 0.03                              | 39.9                     |
| <b>North: Rosebery Ave (N)</b> |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 8                              | T1        | 251            | 0.0     | 0.155            | 0.7                     | LOS A               | 0.9               | 6.6           | 0.33            | 0.07                              | 39.2                     |
| 9                              | R2        | 39             | 0.0     | 0.155            | 4.2                     | LOS A               | 0.9               | 6.6           | 0.33            | 0.07                              | 39.1                     |
| Approach                       |           | 289            | 0.0     | 0.155            | 1.2                     | NA                  | 0.9               | 6.6           | 0.33            | 0.07                              | 39.2                     |
| <b>West: Crewe PI</b>          |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 10                             | L2        | 62             | 0.0     | 0.066            | 4.3                     | LOS A               | 0.2               | 1.7           | 0.28            | 0.50                              | 38.2                     |
| 12                             | R2        | 18             | 0.0     | 0.066            | 4.4                     | LOS A               | 0.2               | 1.7           | 0.28            | 0.50                              | 37.9                     |
| Approach                       |           | 80             | 0.0     | 0.066            | 4.3                     | LOS A               | 0.2               | 1.7           | 0.28            | 0.50                              | 38.2                     |
| All Vehicles                   |           | 558            | 0.0     | 0.155            | 1.3                     | NA                  | 0.9               | 6.6           | 0.21            | 0.12                              | 39.3                     |

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Minor Road Approach LOS values are based on average delay for all vehicle movements.

NA: Intersection LOS and Major Road Approach LOS values are Not Applicable for two-way sign control since the average delay is not a good LOS measure due to zero delays associated with major road movements.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

Gap-Acceptance Capacity: SIDRA Standard (Akçelik M3D).

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

## Attachment 3 – SIDRA OUTPUTS (BASELINE FSR 1.5:1)

---

## MOVEMENT SUMMARY

 **Site: Epsom RD - Rosbery Ave - AM FUTURE 1.5 TO 1 FSR**

New Site  
 Giveway / Yield (Two-Way)

### Movement Performance - Vehicles

| Mov ID             | ODMo<br>v | Demand Flows   |         | Deg. Satn<br>v/c | Average<br>Delay<br>sec | Level of<br>Service | 95% Back of Queue |               | Prop.<br>Queued | Effective<br>Stop Rate<br>per veh | Average<br>Speed<br>km/h |
|--------------------|-----------|----------------|---------|------------------|-------------------------|---------------------|-------------------|---------------|-----------------|-----------------------------------|--------------------------|
|                    |           | Total<br>veh/h | HV<br>% |                  |                         |                     | Vehicles<br>veh   | Distance<br>m |                 |                                   |                          |
| South: RoadName    |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 1                  | L2        | 65             | 0.0     | 0.110            | 9.7                     | LOS A               | 0.5               | 3.2           | 0.74            | 0.86                              | 39.4                     |
| 3                  | R2        | 147            | 0.0     | 0.541            | 27.3                    | LOS B               | 2.4               | 16.9          | 0.94            | 1.12                              | 32.9                     |
| Approach           |           | 213            | 0.0     | 0.541            | 21.9                    | LOS B               | 2.4               | 16.9          | 0.88            | 1.04                              | 34.6                     |
| East: Epsom Rd (E) |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 4                  | L2        | 219            | 0.0     | 0.605            | 4.7                     | LOS A               | 0.0               | 0.0           | 0.00            | 0.10                              | 48.8                     |
| 5                  | T1        | 949            | 0.0     | 0.605            | 0.1                     | LOS A               | 0.0               | 0.0           | 0.00            | 0.10                              | 49.3                     |
| Approach           |           | 1168           | 0.0     | 0.605            | 1.0                     | NA                  | 0.0               | 0.0           | 0.00            | 0.10                              | 49.2                     |
| West: Epsom Rd (w) |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 11                 | T1        | 804            | 0.0     | 0.412            | 0.1                     | LOS A               | 0.0               | 0.0           | 0.00            | 0.00                              | 59.9                     |
| 12                 | R2        | 74             | 0.0     | 0.572            | 53.5                    | LOS D               | 2.3               | 15.9          | 0.96            | 1.08                              | 31.4                     |
| Approach           |           | 878            | 0.0     | 0.572            | 4.5                     | NA                  | 2.3               | 15.9          | 0.08            | 0.09                              | 55.6                     |
| All Vehicles       |           | 2259           | 0.0     | 0.605            | 4.3                     | NA                  | 2.4               | 16.9          | 0.11            | 0.19                              | 49.5                     |

## MOVEMENT SUMMARY

 **Site: Epsom Rd - Dalmeny Ave - AM FUTURE 1.5 TO 1 FSR**

New Site  
 Signals - Fixed Time Cycle Time = 120 seconds (User-Given Cycle Time) Variable Sequence Analysis applied.  
 The results are given for the selected output sequence.

### Movement Performance - Vehicles

| Mov ID                  | ODMo<br>v | Demand Flows   |         | Deg. Satn<br>v/c | Average<br>Delay<br>sec | Level of<br>Service | 70% Back of Queue |               | Prop.<br>Queued | Effective<br>Stop Rate<br>per veh | Average<br>Speed<br>km/h |
|-------------------------|-----------|----------------|---------|------------------|-------------------------|---------------------|-------------------|---------------|-----------------|-----------------------------------|--------------------------|
|                         |           | Total<br>veh/h | HV<br>% |                  |                         |                     | Vehicles<br>veh   | Distance<br>m |                 |                                   |                          |
| South: Dalmeny Ave (NB) |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 1                       | L2        | 198            | 0.0     | 0.376            | 30.6                    | LOS C               | 6.0               | 42.0          | 0.73            | 0.73                              | 32.2                     |
| 3                       | R2        | 100            | 0.0     | 0.307            | 34.1                    | LOS C               | 3.1               | 22.0          | 0.89            | 0.74                              | 31.2                     |
| Approach                |           | 298            | 0.0     | 0.376            | 31.8                    | LOS C               | 6.0               | 42.0          | 0.79            | 0.73                              | 31.8                     |
| East: Epsom Rd (WB)     |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 4                       | L2        | 63             | 0.0     | 0.609            | 35.0                    | LOS C               | 15.3              | 106.9         | 0.82            | 0.88                              | 34.6                     |
| 5                       | T1        | 967            | 0.0     | 0.609            | 31.2                    | LOS C               | 15.7              | 109.8         | 0.82            | 0.88                              | 34.8                     |
| Approach                |           | 1031           | 0.0     | 0.609            | 31.4                    | LOS C               | 15.7              | 109.8         | 0.82            | 0.88                              | 34.8                     |
| West: Epsom Rd (EB)     |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 11                      | T1        | 820            | 0.0     | 0.640            | 6.7                     | LOS A               | 8.4               | 58.8          | 0.46            | 0.41                              | 45.7                     |
| 12                      | R2        | 111            | 0.0     | 0.640            | 37.0                    | LOS C               | 4.9               | 34.4          | 0.97            | 0.80                              | 31.2                     |
| Approach                |           | 931            | 0.0     | 0.640            | 10.3                    | LOS A               | 8.4               | 58.8          | 0.52            | 0.46                              | 43.3                     |
| All Vehicles            |           | 2259           | 0.0     | 0.640            | 22.8                    | LOS B               | 15.7              | 109.8         | 0.69            | 0.69                              | 37.4                     |

### Movement Performance - Pedestrians

| Mov ID          | Description         | Demand Flow<br>ped/h | Average Delay<br>sec | Level of Service | Average Back of Queue |          | Prop. Queued | Effective Stop Rate<br>per ped |
|-----------------|---------------------|----------------------|----------------------|------------------|-----------------------|----------|--------------|--------------------------------|
|                 |                     |                      |                      |                  | Pedestrian            | Distance |              |                                |
|                 |                     |                      |                      |                  | ped                   | m        |              |                                |
| P1              | South Full Crossing | 53                   | 28.1                 | LOS C            | 0.1                   | 0.1      | 0.68         | 0.68                           |
| P4              | West Full Crossing  | 53                   | 54.3                 | LOS E            | 0.2                   | 0.2      | 0.95         | 0.95                           |
| All Pedestrians |                     | 105                  | 41.2                 | LOS E            |                       |          | 0.82         | 0.82                           |



## MOVEMENT SUMMARY

▽ Site: Rosebery Ave - Crewe PI - AM FUTURE [NO CHANGE]

New Site

Giveaway / Yield (Two-Way)

### Movement Performance - Vehicles

| Mov ID          | ODMo<br>v | Demand Flows   |         | Deg. Satn<br>v/c | Average<br>Delay<br>sec | Level of<br>Service | 95% Back of Queue |               | Prop.<br>Queued | Effective<br>Stop Rate<br>per veh | Average<br>Speed<br>km/h |
|-----------------|-----------|----------------|---------|------------------|-------------------------|---------------------|-------------------|---------------|-----------------|-----------------------------------|--------------------------|
|                 |           | Total<br>veh/h | HV<br>% |                  |                         |                     | Vehicles<br>veh   | Distance<br>m |                 |                                   |                          |
| South: RoadName |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 1               | L2        | 21             | 0.0     | 0.129            | 3.4                     | LOS A               | 0.0               | 0.0           | 0.00            | 0.04                              | 40.0                     |
| 2               | T1        | 229            | 0.0     | 0.129            | 0.0                     | LOS A               | 0.0               | 0.0           | 0.00            | 0.04                              | 39.9                     |
| Approach        |           | 251            | 0.0     | 0.129            | 0.3                     | NA                  | 0.0               | 0.0           | 0.00            | 0.04                              | 39.9                     |
| North: RoadName |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 8               | T1        | 203            | 0.0     | 0.160            | 0.9                     | LOS A               | 1.0               | 6.8           | 0.38            | 0.15                              | 38.9                     |
| 9               | R2        | 78             | 0.0     | 0.160            | 4.5                     | LOS A               | 1.0               | 6.8           | 0.38            | 0.15                              | 38.8                     |
| Approach        |           | 281            | 0.0     | 0.160            | 1.9                     | NA                  | 1.0               | 6.8           | 0.38            | 0.15                              | 38.9                     |
| West: RoadName  |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 10              | L2        | 52             | 0.0     | 0.056            | 4.5                     | LOS A               | 0.2               | 1.5           | 0.32            | 0.51                              | 38.2                     |
| 12              | R2        | 14             | 0.0     | 0.056            | 4.6                     | LOS A               | 0.2               | 1.5           | 0.32            | 0.51                              | 37.9                     |
| Approach        |           | 65             | 0.0     | 0.056            | 4.5                     | LOS A               | 0.2               | 1.5           | 0.32            | 0.51                              | 38.1                     |
| All Vehicles    |           | 597            | 0.0     | 0.160            | 1.5                     | NA                  | 1.0               | 6.8           | 0.22            | 0.14                              | 39.2                     |

## MOVEMENT SUMMARY

 **Site: Epsom RD - Rosbery Ave - PM FUTURE 1.5 TO 1 FSR**

New Site  
 Giveway / Yield (Two-Way)

### Movement Performance - Vehicles

| Mov ID             | ODMo<br>v | Demand Flows   |         | Deg. Satn<br>v/c | Average<br>Delay<br>sec | Level of<br>Service | 95% Back of Queue |               | Prop.<br>Queued | Effective<br>Stop Rate<br>per veh | Average<br>Speed<br>km/h |
|--------------------|-----------|----------------|---------|------------------|-------------------------|---------------------|-------------------|---------------|-----------------|-----------------------------------|--------------------------|
|                    |           | Total<br>veh/h | HV<br>% |                  |                         |                     | Vehicles<br>veh   | Distance<br>m |                 |                                   |                          |
| South: RoadName    |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 1                  | L2        | 97             | 0.0     | 0.090            | 6.1                     | LOS A               | 0.4               | 3.0           | 0.61            | 0.68                              | 41.0                     |
| 3                  | R2        | 194            | 0.0     | 0.348            | 14.5                    | LOS A               | 1.8               | 12.6          | 0.89            | 1.03                              | 37.2                     |
| Approach           |           | 291            | 0.0     | 0.348            | 11.7                    | LOS A               | 1.8               | 12.6          | 0.80            | 0.91                              | 38.4                     |
| East: Epsom Rd (E) |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 4                  | L2        | 132            | 0.0     | 0.383            | 4.6                     | LOS A               | 0.0               | 0.0           | 0.00            | 0.10                              | 48.9                     |
| 5                  | T1        | 608            | 0.0     | 0.383            | 0.1                     | LOS A               | 0.0               | 0.0           | 0.00            | 0.10                              | 49.4                     |
| Approach           |           | 740            | 0.0     | 0.383            | 0.9                     | NA                  | 0.0               | 0.0           | 0.00            | 0.10                              | 49.3                     |
| West: Epsom Rd (w) |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 11                 | T1        | 1124           | 0.0     | 0.577            | 0.1                     | LOS A               | 0.0               | 0.0           | 0.00            | 0.00                              | 49.8                     |
| 12                 | R2        | 81             | 0.0     | 0.122            | 9.7                     | LOS A               | 0.5               | 3.7           | 0.67            | 0.83                              | 39.8                     |
| Approach           |           | 1205           | 0.0     | 0.577            | 0.8                     | NA                  | 0.5               | 3.7           | 0.05            | 0.06                              | 49.0                     |
| All Vehicles       |           | 2236           | 0.0     | 0.577            | 2.2                     | NA                  | 1.8               | 12.6          | 0.13            | 0.18                              | 47.4                     |

## MOVEMENT SUMMARY

 **Site: Epsom Rd - Dalmeny Ave - PM FUTURE 1.5 TO 1 FSR**

New Site  
 Signals - Fixed Time Cycle Time = 120 seconds (User-Given Cycle Time) Variable Sequence Analysis applied.  
 The results are given for the selected output sequence.

### Movement Performance - Vehicles

| Mov ID                  | ODMo<br>v | Demand Flows   |         | Deg. Satn<br>v/c | Average<br>Delay<br>sec | Level of<br>Service | 95% Back of Queue |               | Prop.<br>Queued | Effective<br>Stop Rate<br>per veh | Average<br>Speed<br>km/h |
|-------------------------|-----------|----------------|---------|------------------|-------------------------|---------------------|-------------------|---------------|-----------------|-----------------------------------|--------------------------|
|                         |           | Total<br>veh/h | HV<br>% |                  |                         |                     | Vehicles<br>veh   | Distance<br>m |                 |                                   |                          |
| South: Dalmeny Ave (NB) |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 1                       | L2        | 131            | 0.0     | 0.136            | 15.2                    | LOS B               | 3.3               | 23.4          | 0.47            | 0.63                              | 37.2                     |
| 3                       | R2        | 52             | 0.0     | 0.143            | 26.1                    | LOS B               | 1.4               | 9.7           | 0.86            | 0.71                              | 33.5                     |
| Approach                |           | 182            | 0.0     | 0.143            | 18.3                    | LOS B               | 3.3               | 23.4          | 0.58            | 0.65                              | 36.1                     |
| East: Epsom Rd (WB)     |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 4                       | L2        | 77             | 0.0     | 0.755            | 49.7                    | LOS D               | 17.4              | 122.0         | 0.98            | 1.03                              | 30.0                     |
| 5                       | T1        | 609            | 0.0     | 0.755            | 46.0                    | LOS D               | 17.8              | 124.5         | 0.98            | 1.03                              | 30.4                     |
| Approach                |           | 686            | 0.0     | 0.755            | 46.4                    | LOS D               | 17.8              | 124.5         | 0.98            | 1.03                              | 30.4                     |
| West: Epsom Rd (EB)     |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 11                      | T1        | 1177           | 0.0     | 0.673            | 8.5                     | LOS A               | 12.2              | 85.2          | 0.55            | 0.51                              | 44.6                     |
| 12                      | R2        | 141            | 0.0     | 0.673            | 20.8                    | LOS B               | 12.0              | 83.8          | 0.78            | 0.74                              | 36.9                     |
| Approach                |           | 1318           | 0.0     | 0.673            | 9.8                     | LOS A               | 12.2              | 85.2          | 0.58            | 0.53                              | 43.6                     |
| All Vehicles            |           | 2186           | 0.0     | 0.755            | 22.0                    | LOS B               | 17.8              | 124.5         | 0.71            | 0.70                              | 37.8                     |

### Movement Performance - Pedestrians

| Mov ID          | Description         | Demand Flow<br>ped/h | Average Delay<br>sec | Level of Service | Average Back of Queue |               | Prop. Queued | Effective Stop Rate<br>per ped |
|-----------------|---------------------|----------------------|----------------------|------------------|-----------------------|---------------|--------------|--------------------------------|
|                 |                     |                      |                      |                  | Pedestrian<br>ped     | Distance<br>m |              |                                |
| P1              | South Full Crossing | 53                   | 54.3                 | LOS E            | 0.2                   | 0.2           | 0.95         | 0.95                           |
| P4              | West Full Crossing  | 53                   | 54.3                 | LOS E            | 0.2                   | 0.2           | 0.95         | 0.95                           |
| All Pedestrians |                     | 105                  | 54.3                 | LOS E            |                       |               | 0.95         | 0.95                           |

Level of Service (LOS) Method: SIDRA Pedestrian LOS Method (Based on Average Delay)  
 Pedestrian movement LOS values are based on average delay per pedestrian movement.  
 Intersection LOS value for Pedestrians is based on average delay for all pedestrian movements.

## MOVEMENT SUMMARY

**▽ Site: Rosebery Ave - Crewe PI - PM FUTURE [NO CHANGE]**

New Site

Giveaway / Yield (Two-Way)

### Movement Performance - Vehicles

| Mov ID                         | ODMo<br>v | Demand Flows   |         | Deg. Satn<br>v/c | Average<br>Delay<br>sec | Level of<br>Service | 95% Back of Queue |               | Prop.<br>Queued | Effective<br>Stop Rate<br>per veh | Average<br>Speed<br>km/h |
|--------------------------------|-----------|----------------|---------|------------------|-------------------------|---------------------|-------------------|---------------|-----------------|-----------------------------------|--------------------------|
|                                |           | Total<br>veh/h | HV<br>% |                  |                         |                     | Vehicles<br>veh   | Distance<br>m |                 |                                   |                          |
| <b>South: Rosebery Ave (S)</b> |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 1                              | L2        | 11             | 0.0     | 0.097            | 3.4                     | LOS A               | 0.0               | 0.0           | 0.00            | 0.03                              | 40.1                     |
| 2                              | T1        | 178            | 0.0     | 0.097            | 0.0                     | LOS A               | 0.0               | 0.0           | 0.00            | 0.03                              | 39.9                     |
| Approach                       |           | 188            | 0.0     | 0.097            | 0.2                     | NA                  | 0.0               | 0.0           | 0.00            | 0.03                              | 39.9                     |
| <b>North: Rosebery Ave (N)</b> |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 8                              | T1        | 251            | 0.0     | 0.155            | 0.7                     | LOS A               | 0.9               | 6.6           | 0.33            | 0.07                              | 39.2                     |
| 9                              | R2        | 39             | 0.0     | 0.155            | 4.2                     | LOS A               | 0.9               | 6.6           | 0.33            | 0.07                              | 39.1                     |
| Approach                       |           | 289            | 0.0     | 0.155            | 1.2                     | NA                  | 0.9               | 6.6           | 0.33            | 0.07                              | 39.2                     |
| <b>West: Crewe PI</b>          |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 10                             | L2        | 62             | 0.0     | 0.066            | 4.3                     | LOS A               | 0.2               | 1.7           | 0.28            | 0.50                              | 38.2                     |
| 12                             | R2        | 18             | 0.0     | 0.066            | 4.4                     | LOS A               | 0.2               | 1.7           | 0.28            | 0.50                              | 37.9                     |
| Approach                       |           | 80             | 0.0     | 0.066            | 4.3                     | LOS A               | 0.2               | 1.7           | 0.28            | 0.50                              | 38.2                     |
| All Vehicles                   |           | 558            | 0.0     | 0.155            | 1.3                     | NA                  | 0.9               | 6.6           | 0.21            | 0.12                              | 39.3                     |

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Minor Road Approach LOS values are based on average delay for all vehicle movements.

NA: Intersection LOS and Major Road Approach LOS values are Not Applicable for two-way sign control since the average delay is not a good LOS measure due to zero delays associated with major road movements.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

Gap-Acceptance Capacity: SIDRA Standard (Akçelik M3D).

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

## Attachment 4 – SIDRA OUTPUTS (PROPOSAL FSR 2.0:1)

---

## MOVEMENT SUMMARY

 **Site: Epsom RD - Rosbery Ave - AM FUTURE 2.0 TO 1 FSR**

New Site  
 Giveway / Yield (Two-Way)

### Movement Performance - Vehicles

| Mov ID             | ODMo<br>v | Demand Flows   |         | Deg. Satn<br>v/c | Average<br>Delay<br>sec | Level of<br>Service | 95% Back of Queue |               | Prop.<br>Queued | Effective<br>Stop Rate<br>per veh | Average<br>Speed<br>km/h |
|--------------------|-----------|----------------|---------|------------------|-------------------------|---------------------|-------------------|---------------|-----------------|-----------------------------------|--------------------------|
|                    |           | Total<br>veh/h | HV<br>% |                  |                         |                     | Vehicles<br>veh   | Distance<br>m |                 |                                   |                          |
| South: RoadName    |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 1                  | L2        | 65             | 0.0     | 0.112            | 9.9                     | LOS A               | 0.5               | 3.2           | 0.75            | 0.86                              | 39.3                     |
| 3                  | R2        | 147            | 0.0     | 0.556            | 28.4                    | LOS B               | 2.5               | 17.4          | 0.95            | 1.12                              | 32.5                     |
| Approach           |           | 213            | 0.0     | 0.556            | 22.7                    | LOS B               | 2.5               | 17.4          | 0.89            | 1.04                              | 34.4                     |
| East: Epsom Rd (E) |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 4                  | L2        | 219            | 0.0     | 0.610            | 4.7                     | LOS A               | 0.0               | 0.0           | 0.00            | 0.10                              | 48.8                     |
| 5                  | T1        | 960            | 0.0     | 0.610            | 0.1                     | LOS A               | 0.0               | 0.0           | 0.00            | 0.10                              | 49.3                     |
| Approach           |           | 1179           | 0.0     | 0.610            | 1.0                     | NA                  | 0.0               | 0.0           | 0.00            | 0.10                              | 49.2                     |
| West: Epsom Rd (w) |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 11                 | T1        | 807            | 0.0     | 0.414            | 0.1                     | LOS A               | 0.0               | 0.0           | 0.00            | 0.00                              | 59.9                     |
| 12                 | R2        | 74             | 0.0     | 0.596            | 57.2                    | LOS E               | 2.4               | 16.6          | 0.96            | 1.09                              | 30.4                     |
| Approach           |           | 881            | 0.0     | 0.596            | 4.8                     | NA                  | 2.4               | 16.6          | 0.08            | 0.09                              | 55.4                     |
| All Vehicles       |           | 2273           | 0.0     | 0.610            | 4.5                     | NA                  | 2.5               | 17.4          | 0.11            | 0.19                              | 49.3                     |

## MOVEMENT SUMMARY

 **Site: Epsom Rd - Dalmeny Ave - AM FUTURE 2.0 TO 1 FSR**

New Site  
 Signals - Fixed Time Cycle Time = 120 seconds (User-Given Cycle Time) Variable Sequence Analysis applied.  
 The results are given for the selected output sequence.

### Movement Performance - Vehicles

| Mov ID                  | ODMo<br>v | Demand Flows   |         | Deg. Satn<br>v/c | Average<br>Delay<br>sec | Level of<br>Service | 70% Back of Queue |               | Prop.<br>Queued | Effective<br>Stop Rate<br>per veh | Average<br>Speed<br>km/h |
|-------------------------|-----------|----------------|---------|------------------|-------------------------|---------------------|-------------------|---------------|-----------------|-----------------------------------|--------------------------|
|                         |           | Total<br>veh/h | HV<br>% |                  |                         |                     | Vehicles<br>veh   | Distance<br>m |                 |                                   |                          |
| South: Dalmeny Ave (NB) |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 1                       | L2        | 208            | 0.0     | 0.398            | 30.8                    | LOS C               | 6.4               | 44.6          | 0.74            | 0.74                              | 32.1                     |
| 3                       | R2        | 105            | 0.0     | 0.323            | 34.2                    | LOS C               | 3.3               | 23.3          | 0.90            | 0.74                              | 31.2                     |
| Approach                |           | 314            | 0.0     | 0.398            | 31.9                    | LOS C               | 6.4               | 44.6          | 0.79            | 0.74                              | 31.8                     |
| East: Epsom Rd (WB)     |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 4                       | L2        | 65             | 0.0     | 0.613            | 35.3                    | LOS C               | 15.5              | 108.4         | 0.82            | 0.88                              | 34.4                     |
| 5                       | T1        | 967            | 0.0     | 0.613            | 31.6                    | LOS C               | 15.9              | 111.3         | 0.83            | 0.88                              | 34.7                     |
| Approach                |           | 1033           | 0.0     | 0.613            | 31.8                    | LOS C               | 15.9              | 111.3         | 0.83            | 0.88                              | 34.7                     |
| West: Epsom Rd (EB)     |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 11                      | T1        | 820            | 0.0     | 0.643            | 6.7                     | LOS A               | 8.5               | 59.6          | 0.46            | 0.41                              | 45.7                     |
| 12                      | R2        | 114            | 0.0     | 0.643            | 37.0                    | LOS C               | 4.9               | 34.3          | 0.97            | 0.80                              | 31.2                     |
| Approach                |           | 934            | 0.0     | 0.643            | 10.4                    | LOS A               | 8.5               | 59.6          | 0.52            | 0.46                              | 43.3                     |
| All Vehicles            |           | 2280           | 0.0     | 0.643            | 23.0                    | LOS B               | 15.9              | 111.3         | 0.70            | 0.69                              | 37.2                     |

### Movement Performance - Pedestrians

| Mov ID          | Description         | Demand Flow<br>ped/h | Average Delay<br>sec | Level of Service | Average Back of Queue |               | Prop. Queued | Effective Stop Rate<br>per ped |
|-----------------|---------------------|----------------------|----------------------|------------------|-----------------------|---------------|--------------|--------------------------------|
|                 |                     |                      |                      |                  | Pedestrian<br>ped     | Distance<br>m |              |                                |
| P1              | South Full Crossing | 53                   | 28.1                 | LOS C            | 0.1                   | 0.1           | 0.68         | 0.68                           |
| P4              | West Full Crossing  | 53                   | 54.3                 | LOS E            | 0.2                   | 0.2           | 0.95         | 0.95                           |
| All Pedestrians |                     | 105                  | 41.2                 | LOS E            |                       |               | 0.82         | 0.82                           |

Level of Service (LOS) Method: SIDRA Pedestrian LOS Method (Based on Average Delay)  
 Pedestrian movement LOS values are based on average delay per pedestrian movement.  
 Intersection LOS value for Pedestrians is based on average delay for all pedestrian movements.

## MOVEMENT SUMMARY

▽ Site: Rosebery Ave - Crewe PI - AM FUTURE [NO CHANGE]

New Site

Giveaway / Yield (Two-Way)

### Movement Performance - Vehicles

| Mov ID          | ODMo<br>v | Demand Flows   |         | Deg. Satn<br>v/c | Average<br>Delay<br>sec | Level of<br>Service | 95% Back of Queue |               | Prop.<br>Queued | Effective<br>Stop Rate<br>per veh | Average<br>Speed<br>km/h |
|-----------------|-----------|----------------|---------|------------------|-------------------------|---------------------|-------------------|---------------|-----------------|-----------------------------------|--------------------------|
|                 |           | Total<br>veh/h | HV<br>% |                  |                         |                     | Vehicles<br>veh   | Distance<br>m |                 |                                   |                          |
| South: RoadName |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 1               | L2        | 21             | 0.0     | 0.129            | 3.4                     | LOS A               | 0.0               | 0.0           | 0.00            | 0.04                              | 40.0                     |
| 2               | T1        | 229            | 0.0     | 0.129            | 0.0                     | LOS A               | 0.0               | 0.0           | 0.00            | 0.04                              | 39.9                     |
| Approach        |           | 251            | 0.0     | 0.129            | 0.3                     | NA                  | 0.0               | 0.0           | 0.00            | 0.04                              | 39.9                     |
| North: RoadName |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 8               | T1        | 203            | 0.0     | 0.160            | 0.9                     | LOS A               | 1.0               | 6.8           | 0.38            | 0.15                              | 38.9                     |
| 9               | R2        | 78             | 0.0     | 0.160            | 4.5                     | LOS A               | 1.0               | 6.8           | 0.38            | 0.15                              | 38.8                     |
| Approach        |           | 281            | 0.0     | 0.160            | 1.9                     | NA                  | 1.0               | 6.8           | 0.38            | 0.15                              | 38.9                     |
| West: RoadName  |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 10              | L2        | 52             | 0.0     | 0.056            | 4.5                     | LOS A               | 0.2               | 1.5           | 0.32            | 0.51                              | 38.2                     |
| 12              | R2        | 14             | 0.0     | 0.056            | 4.6                     | LOS A               | 0.2               | 1.5           | 0.32            | 0.51                              | 37.9                     |
| Approach        |           | 65             | 0.0     | 0.056            | 4.5                     | LOS A               | 0.2               | 1.5           | 0.32            | 0.51                              | 38.1                     |
| All Vehicles    |           | 597            | 0.0     | 0.160            | 1.5                     | NA                  | 1.0               | 6.8           | 0.22            | 0.14                              | 39.2                     |

## MOVEMENT SUMMARY

 **Site: Epsom RD - Rosbery Ave - PM FUTURE 2.0 TO 1 FSR**

New Site  
 Giveway / Yield (Two-Way)

### Movement Performance - Vehicles

| Mov ID             | ODMo<br>v | Demand Flows   |         | Deg. Satn<br>v/c | Average<br>Delay<br>sec | Level of<br>Service | 95% Back of Queue |               | Prop.<br>Queued | Effective<br>Stop Rate<br>per veh | Average<br>Speed<br>km/h |
|--------------------|-----------|----------------|---------|------------------|-------------------------|---------------------|-------------------|---------------|-----------------|-----------------------------------|--------------------------|
|                    |           | Total<br>veh/h | HV<br>% |                  |                         |                     | Vehicles<br>veh   | Distance<br>m |                 |                                   |                          |
| South: RoadName    |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 1                  | L2        | 97             | 0.0     | 0.091            | 6.1                     | LOS A               | 0.4               | 3.0           | 0.61            | 0.68                              | 41.0                     |
| 3                  | R2        | 194            | 0.0     | 0.352            | 14.6                    | LOS B               | 1.8               | 12.8          | 0.90            | 1.03                              | 37.1                     |
| Approach           |           | 291            | 0.0     | 0.352            | 11.8                    | LOS A               | 1.8               | 12.8          | 0.80            | 0.91                              | 38.3                     |
| East: Epsom Rd (E) |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 4                  | L2        | 132            | 0.0     | 0.384            | 4.6                     | LOS A               | 0.0               | 0.0           | 0.00            | 0.10                              | 48.9                     |
| 5                  | T1        | 611            | 0.0     | 0.384            | 0.1                     | LOS A               | 0.0               | 0.0           | 0.00            | 0.10                              | 49.4                     |
| Approach           |           | 742            | 0.0     | 0.384            | 0.9                     | NA                  | 0.0               | 0.0           | 0.00            | 0.10                              | 49.3                     |
| West: Epsom Rd (w) |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 11                 | T1        | 1128           | 0.0     | 0.579            | 0.1                     | LOS A               | 0.0               | 0.0           | 0.00            | 0.00                              | 49.8                     |
| 12                 | R2        | 81             | 0.0     | 0.122            | 9.7                     | LOS A               | 0.5               | 3.7           | 0.67            | 0.83                              | 39.8                     |
| Approach           |           | 1209           | 0.0     | 0.579            | 0.8                     | NA                  | 0.5               | 3.7           | 0.05            | 0.06                              | 49.0                     |
| All Vehicles       |           | 2242           | 0.0     | 0.579            | 2.2                     | NA                  | 1.8               | 12.8          | 0.13            | 0.18                              | 47.4                     |

## MOVEMENT SUMMARY

 **Site: Epsom Rd - Dalmeny Ave - PM FUTURE 2.0 TO 1 FSR**

New Site  
 Signals - Fixed Time Cycle Time = 120 seconds (User-Given Cycle Time) Variable Sequence Analysis applied.  
 The results are given for the selected output sequence.

### Movement Performance - Vehicles

| Mov ID                  | ODMo<br>v | Demand Flows   |         | Deg. Satn<br>v/c | Average<br>Delay<br>sec | Level of<br>Service | 95% Back of Queue |               | Prop.<br>Queued | Effective<br>Stop Rate<br>per veh | Average<br>Speed<br>km/h |
|-------------------------|-----------|----------------|---------|------------------|-------------------------|---------------------|-------------------|---------------|-----------------|-----------------------------------|--------------------------|
|                         |           | Total<br>veh/h | HV<br>% |                  |                         |                     | Vehicles<br>veh   | Distance<br>m |                 |                                   |                          |
| South: Dalmeny Ave (NB) |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 1                       | L2        | 133            | 0.0     | 0.137            | 14.7                    | LOS B               | 3.3               | 23.3          | 0.47            | 0.63                              | 37.4                     |
| 3                       | R2        | 52             | 0.0     | 0.143            | 26.1                    | LOS B               | 1.4               | 9.5           | 0.86            | 0.71                              | 33.5                     |
| Approach                |           | 184            | 0.0     | 0.143            | 17.9                    | LOS B               | 3.3               | 23.3          | 0.58            | 0.65                              | 36.2                     |
| East: Epsom Rd (WB)     |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 4                       | L2        | 79             | 0.0     | 0.791            | 53.3                    | LOS D               | 18.1              | 126.4         | 1.00            | 1.09                              | 29.1                     |
| 5                       | T1        | 609            | 0.0     | 0.791            | 49.6                    | LOS D               | 18.4              | 128.8         | 1.00            | 1.09                              | 29.5                     |
| Approach                |           | 688            | 0.0     | 0.791            | 50.0                    | LOS D               | 18.4              | 128.8         | 1.00            | 1.09                              | 29.5                     |
| West: Epsom Rd (EB)     |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 11                      | T1        | 1177           | 0.0     | 0.671            | 8.5                     | LOS A               | 12.3              | 85.9          | 0.55            | 0.51                              | 44.6                     |
| 12                      | R2        | 145            | 0.0     | 0.671            | 20.6                    | LOS B               | 12.3              | 85.9          | 0.77            | 0.73                              | 36.9                     |
| Approach                |           | 1322           | 0.0     | 0.671            | 9.8                     | LOS A               | 12.3              | 85.9          | 0.58            | 0.53                              | 43.6                     |
| All Vehicles            |           | 2195           | 0.0     | 0.791            | 23.1                    | LOS B               | 18.4              | 128.8         | 0.71            | 0.72                              | 37.3                     |

### Movement Performance - Pedestrians

| Mov ID          | Description         | Demand Flow<br>ped/h | Average Delay<br>sec | Level of Service | Average Back of Queue |               | Prop. Queued | Effective Stop Rate<br>per ped |
|-----------------|---------------------|----------------------|----------------------|------------------|-----------------------|---------------|--------------|--------------------------------|
|                 |                     |                      |                      |                  | Pedestrian<br>ped     | Distance<br>m |              |                                |
|                 |                     |                      |                      |                  |                       |               |              |                                |
| P1              | South Full Crossing | 53                   | 54.3                 | LOS E            | 0.2                   | 0.2           | 0.95         | 0.95                           |
| P4              | West Full Crossing  | 53                   | 54.3                 | LOS E            | 0.2                   | 0.2           | 0.95         | 0.95                           |
| All Pedestrians |                     | 105                  | 54.3                 | LOS E            |                       |               | 0.95         | 0.95                           |

Level of Service (LOS) Method: SIDRA Pedestrian LOS Method (Based on Average Delay)  
 Pedestrian movement LOS values are based on average delay per pedestrian movement.  
 Intersection LOS value for Pedestrians is based on average delay for all pedestrian movements.

## MOVEMENT SUMMARY

▽ **Site: Rosebery Ave - Crewe PI - PM FUTURE [NO CHANGE]**

New Site

Giveaway / Yield (Two-Way)

### Movement Performance - Vehicles

| Mov ID                         | ODMo<br>v | Demand Flows   |         | Deg. Satn<br>v/c | Average<br>Delay<br>sec | Level of<br>Service | 95% Back of Queue |               | Prop.<br>Queued | Effective<br>Stop Rate<br>per veh | Average<br>Speed<br>km/h |
|--------------------------------|-----------|----------------|---------|------------------|-------------------------|---------------------|-------------------|---------------|-----------------|-----------------------------------|--------------------------|
|                                |           | Total<br>veh/h | HV<br>% |                  |                         |                     | Vehicles<br>veh   | Distance<br>m |                 |                                   |                          |
| <b>South: Rosebery Ave (S)</b> |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 1                              | L2        | 11             | 0.0     | 0.097            | 3.4                     | LOS A               | 0.0               | 0.0           | 0.00            | 0.03                              | 40.1                     |
| 2                              | T1        | 178            | 0.0     | 0.097            | 0.0                     | LOS A               | 0.0               | 0.0           | 0.00            | 0.03                              | 39.9                     |
| Approach                       |           | 188            | 0.0     | 0.097            | 0.2                     | NA                  | 0.0               | 0.0           | 0.00            | 0.03                              | 39.9                     |
| <b>North: Rosebery Ave (N)</b> |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 8                              | T1        | 251            | 0.0     | 0.155            | 0.7                     | LOS A               | 0.9               | 6.6           | 0.33            | 0.07                              | 39.2                     |
| 9                              | R2        | 39             | 0.0     | 0.155            | 4.2                     | LOS A               | 0.9               | 6.6           | 0.33            | 0.07                              | 39.1                     |
| Approach                       |           | 289            | 0.0     | 0.155            | 1.2                     | NA                  | 0.9               | 6.6           | 0.33            | 0.07                              | 39.2                     |
| <b>West: Crewe PI</b>          |           |                |         |                  |                         |                     |                   |               |                 |                                   |                          |
| 10                             | L2        | 62             | 0.0     | 0.066            | 4.3                     | LOS A               | 0.2               | 1.7           | 0.28            | 0.50                              | 38.2                     |
| 12                             | R2        | 18             | 0.0     | 0.066            | 4.4                     | LOS A               | 0.2               | 1.7           | 0.28            | 0.50                              | 37.9                     |
| Approach                       |           | 80             | 0.0     | 0.066            | 4.3                     | LOS A               | 0.2               | 1.7           | 0.28            | 0.50                              | 38.2                     |
| All Vehicles                   |           | 558            | 0.0     | 0.155            | 1.3                     | NA                  | 0.9               | 6.6           | 0.21            | 0.12                              | 39.3                     |

Level of Service (LOS) Method: Delay (RTA NSW).

Vehicle movement LOS values are based on average delay per movement

Minor Road Approach LOS values are based on average delay for all vehicle movements.

NA: Intersection LOS and Major Road Approach LOS values are Not Applicable for two-way sign control since the average delay is not a good LOS measure due to zero delays associated with major road movements.

SIDRA Standard Delay Model is used. Control Delay includes Geometric Delay.

Gap-Acceptance Capacity: SIDRA Standard (Akçelik M3D).

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.