

Attachment A

Recommended Conditions of Consent
--

Terms and Reasons for Conditions

Under section 88(1)(c) of the EP&A Regulation, the consent authority must provide the terms of all conditions and reasons for imposing the conditions other than the conditions prescribed under section 4.17(11) of the EP&A Act. The terms of the conditions and reasons are set out below in Schedules 1 and 2.

SCHEDULE 1

PART A - GENERAL CONDITIONS

(1) APPROVED DEVELOPMENT

- (a) Development must be in accordance with Development Application No. D/2025/1311 dated 5 January 2026 and the following drawings:

Drawing Number	Drawing Name	Date
24_043DA-A-011 – Rev A	Demolition – Level 0	4/12/2025
24_043DA-A-012 – Rev C	Demolition – Level 1	5/03/2026
24_043DA-A-013 – Rev B	Demolition – Level 2	2/03/2026
24_043DA-A-100 – Rev B	Level 0	2/03/2026
24_043DA-A-101 – Rev A	Level 1	4/12/2025
24_043DA-A-102 – Rev A	Level 2	4/12/2025
24_043DA-A-103 – Rev A	Roof	4/12/2025
24_043DA-A-104 – Rev A	Garden Terrace Plan	2/03/2026
24_043DA-A-200 – Rev B	Elevations	2/03/2026
24_043DA-A-2001– Rev B	Elevations	2/03/2026
24_043DA-A-202 – Rev B	Sections	2/03/2026

and as amended by the conditions of this consent.

- (b) In the event of any inconsistency between the approved plans and supplementary documentation, the drawings will prevail.

Reason

To ensure all parties are aware of the approved plans and supporting documentation that applies to the development.

(2) EXTERNAL COLOUR SCHEME (HOUSES)

The external colour scheme is to comprise predominantly earthy tones in keeping with the overall character of the building and/or character of the Heritage Conservation Area. A schedule of colours is to be submitted to and approved by Council's Urban Design and Heritage Manager or Area Coordinator Planning Assessments / Area Planning Manager prior to the issue of any Construction Certificate. The documentation must show the distribution of the colours on the elevation drawings, specify paint types and include colour swatches/colour names and codes.

It is recommended that reference be made to the book "Colour Schemes for Old Australian Houses" by Ian Evans, Clive Lucas and Ian Stapleton.

Reason

To ensure a colour scheme is used that results in an appropriate heritage/streetscape outcome.

(3) NO STRUCTURES ON STREET-FACING ROOF PLANE

No solar hot water heater storage tanks, ventilators, air conditioning units, satellite dishes and antennae or the like are to be placed on the street-facing roof plane of the building.

Reason

To ensure an appropriate heritage/streetscape outcome.

(4) WASTE AND RECYCLING MANAGEMENT – GENERAL

The proposal must comply with the relevant provisions of the Sydney Development Control Plan 2012 and Council's *Guidelines for Waste Management in New Developments 2018*, which requires facilities to promote the safe and efficient storage, separation, collection and handling of waste to maximise resource recovery.

Reason

To ensure that waste and recycling is appropriately managed throughout all phases of the development.

(5) TREES THAT MUST BE RETAINED

- (a) The tree(s) detailed in the table below must be retained and protected in accordance with the conditions throughout development works.
- (b) Approval is NOT granted for the removal of the tree(s) detailed in the table below, which Council has determined to be prominent landscape elements

Tree No	Species:	Location
1	Plumberia acutifolia (Frangipani)	Rear yard

Reason

To identify the trees that cannot be removed, must be retained and protected.

PART B - BEFORE ISSUE OF A CONSTRUCTION CERTIFICATE

(6) DILAPIDATION REPORT – MINOR

Subject to the receipt of permission of the affected landowner, dilapidation report/s of adjoining buildings are to be prepared by an appropriately qualified practising structural engineer and submitted for the approval of the Registered Certifier prior to the issue of a construction certification.

Reason

To ensure that dilapidation reports are prepared and to identify damage to for adjoining/nearby properties resulting from building work on the development site.

(7) STORMWATER AND DRAINAGE - MINOR DEVELOPMENT

The drainage system is to be constructed in accordance with the City's standard requirements as detailed in the City of Sydney's Stormwater Drainage Manual. The development is to be designed so that the flow of pollutants from the site due to stormwater is reduced.

The requirements of Sydney Water regarding the on-site detention (OSD) of stormwater must be ascertained and complied with. Evidence of the on-site detention (OSD) approval must be submitted to City's Public Domain Unit prior to issue of any Construction Certificate other than demolition.

Reason

To ensure the drainage system is constructed in accordance with Council's requirements.

(8) BASIX CERTIFICATE – DETAILS TO BE LODGED WITH A CC

A copy of the required completed BASIX certificate accepted as part of this Development Consent with respect to the proposed residential building works, must be lodged with an application for a construction certificate and the items nominated as part of the subject BASIX certificate must be specified on the plans submitted with the construction certificate application. – See Note.

IMPORTANT NOTE:

Any requirement detailed in the accompanying BASIX Certificate, MUST be included as a specific notation or inclusion on any future Construction Certificate plans and specification in accordance with Part 3 of Schedule 1 of the EP&A Regulation, 2021.

Reason

To ensure BASIX commitments are fulfilled in accordance with the BASIX certificate (prescribed condition under clause 75 EP&A Regulation, 2021).

(9) STRUCTURAL CERTIFICATION FOR DESIGN – BUILDING CODE OF AUSTRALIA (ALL BUILDING CLASSES)

Prior to the issue of a Construction Certificate, structural details and a structural certificate for design by a qualified practising structural engineer and in accordance with Clause A5G3(1)(e) of the *Building Code of Australia* must be submitted to the satisfaction of the Registered Certifier.

Reason

To ensure structural certification is undertaken.

PART C - BEFORE THE COMMENCEMENT OF BUILDING WORK

(10) OTHER REQUIRED APPROVALS

Any structure, attachment or activity which is proposed to be undertaken in, on or above a road reserve or the public domain (including a public footway) must have separate approval(s) obtainable through the lodgement of an application under Section 68 of the Local Government Act 1993 and/or Section 138/139 of the Roads Act 1993 prior to the commencement of work/activities within the road reserve/public domain. Such activities include but not limited to:

- (a) installation of construction-related temporary structures including hoardings/scaffolding;
- (b) installation and/or alterations to advertising/business signs;
- (c) installation and/or alterations to street awnings;
- (d) crane operation and other hoisting activities;
- (e) temporary works (e.g. barricading, road openings, mobile hoisting devices);
- (f) works zones (for loading and unloading from the roadway); and
- (g) temporary ground anchoring and shoring to support a roadway when excavating; and
- (h) any other structure or encroachment including facade elements/architectural features.

Reason

To ensure use of a public place is managed appropriately.

(11) TREE PROTECTION DURING CONSTRUCTION (FOR PRIVATE/PROPERTY TREES)

Before the commencement of the development works, Tree Protection Zone(s) (TPZs) must be established for any tree to be retained in accordance with Australian Standard 4970 'Protection of trees on development sites' and as follows:

- (a) Stockpiling, storage or mixing of materials, washing of equipment, vehicle parking, disposal of liquids, machinery repairs and refuelling, disposal of building materials such as cement slurry, siting of offices or sheds and the lighting of fires, must not occur within within TPZs of any tree to be retained including trees within adjoining properties.
- (b) Excavation must not occur within the SRZ. If excavation is proposed within this zone, Council's Tree Management Officer must be contacted immediately, and the excavation must be carried out in accordance with Council's direction.

- (c) Roots greater than 40mm must not be severed or damaged within the TPZ without written approval from the City of Sydney Tree Team. As required, tree sensitive excavation (i.e hand/air space/hydrovac) and tree sensitive construction/installation methods (i.e. directional boring, redirection of services, pier and beam footings) must be used to ensure the retention and protection of roots greater than 40mm diameter. If hydrovac excavation is used, the works must be supervised by a qualified Arborist (minimum AQF Level 5).
- (d) Tree trunk and major branch protection must be installed prior to the commencement of the development works and be removed at the completion of the project. Tree trunk and major branch protection must include:
 - (i) Tree trunk(s) and/or major branches to 2 metres protected by wrapped thick underlay carpet or similar padding material to limit damage;
 - (ii) Timber planks (50mm x 100mm must be placed around tree trunk(s). The timber planks must be spaced at 100mm intervals, and must be fixed against the trunk with tie wire, or strapping. The hessian and timber planks must not be fixed to the tree in any instance, or in any fashion.
- (e) Consent from Council's Tree Management Officer must be obtained prior to the undertaking of any tree pruning works, including tree roots greater than 40mm in diameter. Only minor pruning works will be approved by Council.

Reason

To ensure the protection and ongoing health of trees.

PART D - WHILE BUILDING WORK IS BEING CARRIED OUT

(12) ASBESTOS REMOVAL WORKS

- (a) All works removing asbestos containing materials must be carried out by a suitably licensed asbestos removalist duly licensed with Safework NSW, holding either a Friable (Class A) or a Non-Friable (Class B) Asbestos Removal Licence which ever applies.

A copy of the relevant licence must be made available to any authorised Council officer on request within 24 hours.

- (b) Five days prior to the commencement of licensed asbestos removal, Safework NSW must be formally notified of the works. All adjoining properties and those opposite the development must be notified in writing of the dates and times when asbestos removal is to be conducted. The notification must identify the licensed asbestos removal contractor and include a contact person for the site together with telephone number and email address.
- (c) All work must be carried out in accordance with the *Work Health and Safety Regulation 2017* and the NSW Government and SafeWork NSW document entitled *How to manage and control asbestos in the work place: Code of Practice (Safework NSW)* December 2011 and the *City of Sydney Managing Asbestos Policy dated 21 October 2013 and associated guidelines*.
- (d) The asbestos removalist must use signs and barricades to clearly indicate the area where the asbestos removal work is being performed. Signs must be placed in positions so that people are aware of where the asbestos removal work area is and should remain in place until removal is completed and clearance to reoccupy has been granted. Responsibilities for the security and safety of the asbestos removal site and removal must be specified in the asbestos removal control plan (where required). This includes inaccessible areas that are likely to contain asbestos.
- (e) Warning signs must be placed so they inform all people nearby that asbestos removal work is taking place in the area. Signs must be placed at all of the main entry points to the asbestos removal work area where asbestos is present. These signs must be weatherproof, constructed of light-weight material and adequately secured so they remain in prominent locations. The signs must be in accordance with AS 1319 -1994 *Safety Signs for the Occupational Environment* for size, illumination, location and maintenance.
- (f) Asbestos waste must only be transported and disposed of at an EPA licensed waste facility.
- (g) No asbestos products are to be reused on the site (i.e. packing pieces, spacers, formwork or fill etc).
- (h) No asbestos laden skips or bins are to be left in any public place without the written approval of Council.

- (i) A site notice board must be located at the main entrance to the site in a prominent position and must have minimum dimensions of 841mm x 594mm (A1) with any text on the notice to be a minimum of 30 point type size.

The site notice board must include the following:

- (i) contact person for the site;
- (ii) telephone and facsimile numbers and email address; and
- (iii) site activities and time frames.

Reason

To ensure that the handling and removal of asbestos from the site is appropriately managed.

(13) FLASHINGS TO BOUNDARY WALLS

A flashing must be provided to prevent water entering between the proposed and existing external boundary walls of the adjoining properties.

Note: Attachments or connections to party walls may require the consent of the adjoining property owner/s.

Reason

To prevent water entering between the walls of adjoining properties

(14) HOURS OF WORK AND NOISE – OUTSIDE CBD

The hours of construction and work on the development must be as follows:

- (a) All work, including building/demolition and excavation work, and activities in the vicinity of the site generating noise associated with preparation for the commencement of work (eg. loading and unloading of goods, transferring of tools etc) in connection with the proposed development must only be carried out between the hours of 7.30am and 5.30pm on Mondays to Fridays, inclusive, and 7.30am and 3.30pm on Saturdays, with safety inspections being permitted at 7.00am on work days, and no work must be carried out on Sundays or public holidays.
- (b) All work, including demolition, excavation and building work must comply with the City of Sydney Code of Practice for Construction Hours/Noise 1992 and Australian Standard 2436 - 2010 Guide to Noise Control on Construction, Maintenance and Demolition Sites.
- (c) Notwithstanding the above, the use of a crane for special operations, including the delivery of materials, hoisting of plant and equipment and erection and dismantling of on-site tower cranes which warrant the on-street use of mobile cranes outside of above hours can occur, subject to a separate application being submitted to and approved by Council under Section 68 of the Local Government Act 1993 and Sections 138/139 of the Roads Act 1993.

Note: Works may be undertaken outside of hours, where it is required to avoid the loss of life, damage to property, to prevent environmental harm and/or to avoid structural damage to the building. Written approval must be given by the Construction Regulation Team, prior to works proceeding.

The *City of Sydney Code of Practice for Construction Hours/Noise 1992* allows extended working hours subject to the approval of an application in accordance with the Code and under Section 4.55 of the *Environmental Planning and Assessment Act 1979*.

Reason

To protect the amenity of the surrounding area.

(15) SURVEY SETOUT

Prior to the commencement of construction all footings, walls and floor slabs adjacent to a boundary must be set out by a registered surveyor.

The building shall be sufficiently set back to ensure that no component of the building (such as the roof, guttering, or downpipes) encroach upon or overhang the boundaries of the site.

The registered surveyor shall provide a survey and report to the Principal Certifier indicating the position of the footings, walls and floor slabs in relation to the boundaries of the allotment.

Reason

To ensure the development does not encroach onto neighbouring properties.

(16) NO OBSTRUCTION OF PUBLIC WAY

Unless otherwise approved by Council, the public way must not be obstructed by any materials, vehicles, waste receptacles, skip-bins or the like. Non-compliance with this requirement may result in the issue of a notice by Council to stop all work on the site.

Reason

To protect the amenity of the public domain.

(17) LOADING AND UNLOADING DURING CONSTRUCTION

The following requirements apply:

- (a) All loading and unloading associated with construction activity must be accommodated on site, where possible.
- (b) If, it is not feasible for loading and unloading to take place on site, a Works Zone on the street may be considered by Council.

- (c) A Works Zone may be required if loading and unloading is not possible on site. If a Works Zone is warranted an application must be made to Council at least 8 weeks prior to commencement of work on the site. An approval for a Works Zone may be given for a specific period and certain hours of the days to meet the particular need for the site for such facilities at various stages of construction. The approval will be reviewed periodically for any adjustment necessitated by the progress of the construction activities.
- (d) Where hoisting activity over the public place is proposed to be undertaken including hoisting from a Works Zone, a separate application under Section 68 of the Local Government Act 1993 and Sections 138/139 of the Roads Act 1993 must be submitted to and approved by Council.

Reason

To protect the amenity of the public domain.

(18) TREE PRUNING – FURTHER APPROVAL REQUIRED

- (a) Consent from Council's Tree Management Officer must be obtained prior to undertaking the pruning of any tree to be retained, including tree roots greater than 40mm diameter.
- (b) Construction access and the location of the works zone must be planned to avoid adversely impacting any tree to be retained. Alternative work zone locations must be provided and suitable size cranes/machinery/equipment utilised to minimise tree pruning requirements. Only minor pruning works will be approved.
- (c) Any approved pruning must be carried out by a qualified Arborist (minimum AQF Level 3) in accordance with Australian Standard 4373 'Pruning of Amenity Trees' and the SafeWork's Code of Practice - Amenity Tree Industry.

Reason

To ensure that pruning works to trees are carried out in an appropriate manner.

(19) TREE SENSITIVE EXCAVATION

- (a) Excavation within the Tree Protection Zone(s) (TPZs) as detailed in the table below must be undertaken using tree sensitive methods (i.e. hand/ air space/hydrovac) and supervised by a qualified Arborist (minimum AQF level 5). To prevent root damage, low pressures must be used for hydrovac excavation with the bark remaining intact.

Tree (Root) Protection Zone Schedule:

Tree No	Species	Tree Location	TPZ Radius (m) from Trunk	SRZ (m) from Trunk
1	<i>Plumberia acutifolia</i> (Frangipani)	Rear Yard	2.5	1.8

- (b) Excavation must not occur within the SRZ. If excavation is proposed within this zone, the Council's Tree Management Officer must be contacted immediately, and the excavation must be carried out in accordance with Council's direction.
- (c) Roots greater than 40mm must not be severed or damaged within the TPZ without written approval from the City of Sydney Tree Team. As required, tree sensitive construction/installation methods (i.e. directional boring, redirection of services, pier and beam footings) must be used to ensure the retention and protection of roots greater than 40mm diameter.
- (d) Trenching must be backfilled as soon as possible, and exposed roots must be covered with mulch or a geotextile fabric and kept in a moist condition and prevented from drying out.
- (e) Any approved root pruning must be carried out by a qualified Arborist (minimum AQF Level 5) in accordance with Australian Standard 4373 'Pruning of Amenity Trees'.
- (f) Compliance with this condition must be addressed in the Tree Protection Compliance Certificate prepared by a qualified Arborist (minimum AQF Level 5).

Reason

To ensure that excavation works to trees are carried out in an appropriate manner.

PART E – BEFORE ISSUE OF AN OCCUPATION CERTIFICATE

(20) SURVEY CERTIFICATE PRIOR TO ISSUE OF OCCUPATION CERTIFICATE

Prior to the issue of any type of Occupation Certificate for the building, a Final Identification Survey prepared and signed by a Surveyor registered under the Surveying & Spatial Information Act 2002 must be submitted at the completion of the building work certifying the location of the building and showing offsets in relation to the boundaries of the allotment.

Any encroachments of the building including gutters and downpipes over the side boundaries or rear lane that are not approved in the DA must be removed, or where approved, appropriate easements under Section 88B of the Conveyancing Act 1919, with terms to the satisfaction of Council, must be lodged with the office of NSW Land Registry Services, and evidence of lodgement provided to the Principal Certifier prior to the issue of any type of Occupation Certificate. Encroachments upon public roads must, if supported, be approved by Council's Area Planning Manager prior to the issue of any type of Occupation Certificate.

Reason

To ensure that either the building does not encroach, or that any encroachments are formalised on title.

PART F – OCCUPATION AND ONGOING USE

(21) OCCUPATION CERTIFICATE TO BE SUBMITTED

An Occupation Certificate must be obtained from the Principal Certifier and a copy submitted to Council prior to commencement of occupation or use of the whole or any part of a new building, an altered portion of, or an extension to an existing building.

Reason

To ensure the site is authorised for occupation.

SCHEDULE 2

PRESCRIBED CONDITIONS

The applicant must comply with all relevant conditions contained in Part 4, Division 2, Subdivision 1 of the *Environmental Planning and Assessment Regulation 2021* which apply to the development:

Refer to the NSW State legislation for full text of the clauses under Part 4, Division 2, Subdivision 1 of the *Environmental Planning and Assessment Regulation 2021*. This can be accessed at: <http://www.legislation.nsw.gov.au>