

Attachment A

Recommended Conditions of Consent
--

CONDITIONS OF CONSENT

SCHEDULE 1

APPROVED DEVELOPMENT/DESIGN MODIFICATIONS/COVENANTS AND CONTRIBUTIONS/USE AND OPERATION

(1) APPROVED DEVELOPMENT

- (a) Development must be in accordance with Development Application No. D/2017/1749 dated 15 December 2017 and the following drawings prepared by Chenchow Little Pty Ltd:

Drawing Number	Drawing Name	Date
DA-00 Rev C	Coverpage	12 December 2017
DA-01 Rev C	Site Analysis Plan	12 December 2017
DA-02 Rev E	Basement Floor Plan	12 December 2017
DA-03 Rev E	Ground Floor Plan	12 December 2017
DA-04 Rev E	First Floor Plan	12 December 2017
DA-05 Rev E	Second Floor Plan	12 December 2017
DA-06 Rev E	Third Floor Plan	12 December 2017
DA-07 Rev E	Attic Floor Plan	12 December 2017
DA-08 Rev E	Roof Plan	12 December 2017
DA-09 Rev E	West Elevations	12 December 2017
DA-10 Rev E	East Elevations	12 December 2017
DA-11 Rev E	North Elevation	12 December 2017
DA-12 Rev E	South Elevation	12 December 2017
DA-13 Rev E	Section A-A	12 December 2017
DA-19 Rev C	Sample board	12 December 2017

Drawing Number	Drawing Name	Date
DA-20 Rev D	Rear dormer detail	12 December 2017
DA-21 Rev C	Fixed Screen Detail	12 December 2017
DA-22 Rev B	Nib Wall Interpretation Detail	12 December 2017

and as amended by the conditions of this consent.

- (b) In the event of any inconsistency between the approved plans and supplementary documentation, the plans will prevail.

(2) DESIGN MODIFICATIONS

The design of the building must be modified as follows:

- (a) The basement is to be reduced in size such that it is confined to the footprint of the garage, with excavation setback 500mm from the boundaries adjoining nos. 522 and 526 Bourke Street.
- (b) A minimum 27sqm of deep soil planting is to be provided in the rear yard. Porous paving is permitted in this location with a maximum width of 1.2 metres providing there is a deep soil area on one side level with the paved area.
- (c) An advanced tree is to be provided in the rear yard of the site.
 - (i) Written confirmation is to be obtained from Council's Area Planning Manager that all tree planting/s have been completed to Council's satisfaction (excluding tree maintenance) prior to the issue of an Occupation Certificate.
 - (ii) Any newly planted tree that fails to establish within 2 years of the initial planting date must be replaced with a tree of comparable qualities.
- (d) The windows within the rear roof extension are to be timber framed.

The details must be submitted to and approved by the Area Planning Manager prior to any Construction Certificate being issued.

(3) UPDATED GEOTECHNICAL AND STRUCTURAL ENGINEERS' REPORTS

Prior to the issue of any Construction Certificate, geotechnical and structural engineers' reports, prepared by suitably qualified engineers experienced in dealing with heritage buildings must be submitted for the approval of the Council's Area Planning Manager. The report should assess the impact that the excavation and demolition works will have on the heritage building and the adjoining properties, including the garage. It should include recommendations of measures to be undertaken during the excavation and demolition work. In particular, the reports must identify the construction methodology of the basement excavation, demonstrate that the works will not adversely impact the structural integrity of the terrace row and neighbouring properties, and manage dewatering. The structural design of the replacement structural components, such as lintels, columns and footings, should be included in the report.

(4) VEHICLE FOOTWAY CROSSING

A separate application is to be made to, and approved by, Council for the construction of any proposed vehicle footway crossing or for the removal of any existing crossing and replacement of the footpath formation where any such crossings are no longer required.

All disused or redundant vehicle crossings and laybacks must be removed and footway, kerb, gutter and road restoration reinstated in accordance with Council's standards, to suit the adjacent finished footway and edge treatment materials, levels and details, or as otherwise directed by Council officers. All construction and replacement works are to be completed in accordance with the approved plans prior to the issue of an Occupation Certificate.

Note: In all cases the construction materials should reinforce the priority of pedestrian movement over that of the crossing vehicle.

(5) PARKING DESIGN

The design, layout, signage, line marking, lighting and physical controls of all off-street parking facilities must comply with the minimum requirements of Australian Standard AS/NZS 2890.1 Parking facilities Part 1: Off-street car parking, AS/NZS 2890.2 Parking facilities Part 2: Off-commercial vehicle facilities and AS/NZS 2890.6 Parking facilities Part 6: Off-street parking for people with disabilities. The details must be submitted to and approved by the Principal Certifier prior to a Construction Certificate being issued.

(6) AIR CONDITIONERS GENERALLY

No air-conditioning equipment is to be visible from the public domain. Equipment and associated wiring shall:

- (a) Not be located on awnings or attached to the face of the building
- (b) Not be located on roofs in such a way that it is visible from any street, footpath or park
- (c) Be visually screened if located 1.8 metres above ground level in other locations
- (d) Wiring shall be fully concealed.

(7) NO AIR CONDITIONING UNITS TO FACADE OR BALCONIES OF BUILDING

Approval is not granted for the installation of individual air conditioning units to the facade or balconies of the building.

(8) FLOOD PLANNING LEVELS

The entrance to the basement is to be located 0.5 metres above the 1% annual exceedance flood level. Amended plans are to be submitted to and approved by Council's Area Planning Manager accordingly prior to the issue of any Construction Certificate. Details of the flood planning levels can be obtained from Council's Public Domain unit.

(9) MATERIALS AND SAMPLES BOARD

A physical materials sample board detailing all proposed finishes, including visible rainwater fittings and building services, must be submitted to and approved by Council's Area Planning Manager prior to any Construction Certificate being issued. The sample board is to be supplemented by elevation plans that identify the location of the materials and colours. The submitted sample board must not include generic material or colour descriptions or use of the terminology 'or similar'.

(10) COMPLIANCE WITH SUBMITTED MATERIALS AND SAMPLES BOARD

The design details of the proposed building facade including all external finishes, colours and glazing must be in accordance with the materials schedule and sample board, and specifications approved under condition 9.

(11) PHOTOVOLTAIC CELLS

The photovoltaic cells are to be installed such that they are flush with the roof of the rear roof extension.

(12) CONSTRUCTION TRAFFIC MANAGEMENT PLAN

- (a) The preliminary Construction Traffic Management Plan submitted with the application has not been approved.
- (b) A final Construction Traffic Management Plan must be submitted to and approved by Council's Area Planning Manager prior to any Construction Certificate being issued. The CTMP must be prepared in accordance with Council's requirements, located at –

<http://www.cityofsydney.nsw.gov.au/business/business-responsibilities/traffic-management/construction-traffic-management-plans>

- (c) The CTMP submitted in accordance with (b) above must be complied with at all times while the development is under construction.

(13) ASBESTOS REMOVAL WORKS

All works removing asbestos containing materials must be carried out by a suitably licensed asbestos removalist duly licensed with Safework NSW, holding either a Friable (Class A) or a Non- Friable (Class B) Asbestos Removal Licence which ever applies.

A copy of the relevant licence shall be made available to any authorised Council officer on request within 24 hours.

(14) STRUCTURAL CERTIFICATION FOR DESIGN – BCA (ALL BUILDING CLASSES)

Prior to the issue of a Construction Certificate, structural details and a Structural Certificate for Design by a qualified practising structural engineer and in accordance with Clause A2.2(a)(iii) of the Building Code of Australia (applicable to Class 2-9 buildings) and Clause 1.2.2(iii) of Volume 2 of the BCA (applicable to Class 1 and 10 buildings) must be submitted to the satisfaction of Council (where Council is the Principal Certifier).

(15) STRUCTURAL CERTIFICATION FOR EXISTING BUILDING – ALTERATIONS AND ADDITIONS

A qualified practising certified structural engineer must provide structural certification to Council (where Council is the Principal Certifier) verifying that the existing structure can adequately support the proposed basement and new loads and the structural design complies with the Structural Provisions of Part B1 (Vol 1) and Part 2.1 (Vol 2) of the *Building Code of Australia* prior to a Construction Certificate being issued. The proposed additional loads and/or alterations must not cause a decrease in the existing structural performance of the building including its performance under earthquake actions (AS1170.4).

(16) FLASHINGS TO BOUNDARY WALLS

A flashing must be provided to prevent water entering between the proposed and existing external boundary walls of the adjoining properties.

Note: Attachments or connections to party walls may require the consent of the adjoining property owner/s.

(17) STRUCTURAL CERTIFICATION FOR PARTY WALLS

Prior to a Construction Certificate being issued, a certificate from a qualified practising structural engineer in accordance with Clause A2.2(a)(iii) of the *Building Code of Australia* must be submitted to the satisfaction of Council (where Council is the Principal Certifier). The Certificate must verify the structural integrity of the existing 'Party Wall(s)' as consequence of the additional loads imposed thereon by the proposal.

(18) DILAPIDATION REPORT – MINOR

Subject to the receipt of permission of the affected landowner, dilapidation report/s of adjoining buildings are to be prepared by an appropriately qualified practising structural engineer and submitted for the approval of the Principal Certifier:

- (a) prior to the commencement of demolition/excavation works; and
- (b) on completion of construction demolition/excavation works.

(19) EROSION AND SEDIMENT CONTROL - LESS THAN 250SQM

Where less than 250 square metres are being disturbed, no formal plan is required however, the site is to be provided with sediment control measures and these must be implemented so that sediment, including soil, excavated material, building material or other materials cannot fall, descend, percolate, be pumped, drained, washed or allowed to flow to the street, stormwater system or waterways.

(20) DEMOLITION, EXCAVATION AND CONSTRUCTION MANAGEMENT

- (a) Prior to the commencement of demolition and/or excavation work the following details must be submitted to and be approved by the Principal Certifier:
 - (i) Plans and elevations showing distances of the subject building from the location of adjoining and common/party walls, and (where applicable) the proposed method of facade retention.
 - (ii) A Demolition Work Method Statement prepared by a licensed demolisher who is registered with the Work Cover Authority. (The demolition by induced collapse, the use of explosives or on-site burning is not permitted.)
 - (iii) An Excavation Work Method Statement prepared by an appropriately qualified person.
 - (iv) A Waste Management Plan for the demolition and or excavation of the proposed development.
- (b) Such statements must, where applicable, be in compliance with AS2601-2001 Demolition of Structures, the *Work, Health and Safety Act 2011* and Regulation; Council's *Policy for Waste Minimisation in New Developments 2005*, the *Waste Avoidance and Resource Recovery Act 2001*, and all other relevant acts and regulations and must include provisions for:
 - (i) A Materials Handling Statement for the removal of refuse from the site in accordance with the *Waste Avoidance and Resource Recovery Act 2001*.
 - (ii) The name and address of the company/contractor undertaking demolition/excavation works.
 - (iii) The name and address of the company/contractor undertaking off site remediation/disposal of excavated materials.
 - (iv) The name and address of the transport contractor.

- (v) The type and quantity of material to be removed from site.
 - (vi) Location and method of waste disposal and recycling.
 - (vii) Proposed truck routes, in accordance with this development consent.
 - (viii) Procedures to be adopted for the prevention of loose or contaminated material, spoil, dust and litter from being deposited onto the public way from trucks and associated equipment and the proposed method of cleaning surrounding roadways from such deposits. (Note: With regard to demolition of buildings, dust emission must be minimised for the full height of the building. A minimum requirement is that perimeter scaffolding, combined with chain wire and shade cloth must be used, together with continuous water spray during the demolition process. Compressed air must not be used to blow dust from the building site).
 - (ix) Measures to control noise emissions from the site.
 - (x) Measures to suppress odours.
 - (xi) Enclosing and making the site safe.
 - (xii) Induction training for on-site personnel.
 - (xiii) Written confirmation that an appropriately qualified Occupational Hygiene Consultant has inspected the building/site for asbestos, contamination and other hazardous materials, in accordance with the procedures acceptable to Work Cover Authority.
 - (xiv) An Asbestos and Hazardous Materials Clearance Certificate by a person approved by the Work Cover Authority.
 - (xv) Disconnection of utilities.
 - (xvi) Fire Fighting. (Fire fighting services on site are to be maintained at all times during demolition work. Access to fire services in the street must not be obstructed).
 - (xvii) Access and egress. (Demolition and excavation activity must not cause damage to or adversely affect the safe access and egress of the subject building or any adjacent buildings).
 - (xviii) Waterproofing of any exposed surfaces of adjoining buildings.
 - (xix) Control of water pollution and leachate and cleaning of vehicles tyres (proposals must be in accordance with the *Protection of the Environmental Operations Act 1997*).
 - (xx) Working hours, in accordance with this development consent.
 - (xxi) Any Work Cover Authority requirements.
- (c) The approved work method statements and a waste management plan as required by this condition must be implemented in full during the period of construction.

(21) GENERAL HERITAGE

- (a) The proposed works are to be carried out in a manner that minimises demolition, alterations and new penetrations/fixings to the significant fabric of the existing building which is listed as a Heritage Item.
- (b) The fabric and features to be retained by the proposal must be properly protected during the process of demolition and construction. The protection measures are to be specified in the construction management plan.
- (c) All conservation and adaptation works are to be in accordance with the Articles of the Australian ICOMOS Burra Charter 1999.
- (d) New services are to be surface mounted rather than chased-in to existing walls to minimise impact on heritage fabric.
- (e) Appropriately qualified tradespersons (as appropriate) are to be commissioned who are skilled in traditional building and engineering trades to carry out the proposed scope of works.
- (f) The new windows and doors on the existing building must match the original material, which is [Select: timber joinery, steel-framed, monel metal, bronze or brass-framed].
- (g) The face brickwork/stone/tiles must not be rendered, painted or coated.
- (h) Where internal partitions meet external walls they must abut window mullions, columns or other such building elements and not glazing.

(22) REINSTATEMENT OF FRONT BALCONIES

The first floor front balcony must be reinstated to its original form and style and decorated with appropriate balustrade panels reflecting the traditional patterns, colour and details. Details are to be submitted to and approved by Council's Area Planning Manager prior to issue of any Construction Certificate.

(23) USE OF CONSERVATION ARCHITECT

An experienced conservation architect is to be commissioned to work with the consultant team throughout the design development, contract documentation and construction stages of the project. The conservation architect is to be involved in the resolution of all matters where existing significant fabric and spaces are to be subject to preservation, restoration, reconstruction, adaptive reuse, recording and demolition. The conservation architect is to be provided with full access to the site and authorised by the applicant to respond directly to Council where information or clarification is required regarding the resolution of heritage issues throughout the project.

Evidence and details of the above commission on the above terms are to be provided to Council prior to commencement of work on site. The conservation architect must sign off the completed project prior to the issue of an Occupation Certificate or the commencement of the use, whichever is earlier.

(24) MATERIALS

New materials, including those for making good, are to match the original materials in terms of colours, finishes, sizes, profile and materials.

(25) PHOTOGRAPHIC ARCHIVAL DOCUMENTATION (MINOR WORKS)

Prior to any Construction Certificate being issued, an archival photographic recording of the terrace house (including the internal elements to be demolished or modified) is to be prepared to Council's satisfaction. The recording may be in either digital or film-based form, or a combination of both, prepared in accordance with the NSW Heritage Office guidelines titled "Photographic Recording of Heritage Items using Film or Digital Capture". One copy of the record is to be submitted to Council to be lodged with Council's Archives.

The form of the recording is to be as follows:

- (a) In A4 format, placed in archival plastic sleeves in an appropriate archival folder.
- (b) The Development Application number must be noted on the front of the folder and in the report.
- (c) Include a summary report detailing the project description, date and authorship of the photographic record, method of documentation and limitations of the photographic record.
- (d) Each negative, slide or digital image is to be cross referenced to a photographic catalogue and photographic base plans.
- (e) Include written confirmation, issued with the authority of both the applicant and the photographer that the City of Sydney is granted a perpetual non-exclusive licence to make use of the copyright in all images supplied, including the right to make copies available to third parties as though they were Council images. The signatures of both the applicant and the photographer must be included.

A digital based recording is to include:

- (f) CD or DVD containing the report in PDF format and the electronic images saved as JPEG, TIFF or PDF files and cross referenced to the digital catalogue sheets and base plans.

A film based recording is to include:

- (g) 35mm film images submitted as contact sheets with equivalent negatives, a selection of black and white prints 200 x 250mm, and 35mm colour transparencies, all labelled and cross-referenced to the catalogue sheets and base plans.

(26) RECYCLING HISTORIC FABRIC

- (a) Original timber flooring is to be reused within the development as indicated on the approved architectural drawings and accompanying structural plans.
- (b) All joinery and stones demolished from the project are to be salvaged and reused whenever possible in the new construction. Salvaged materials surplus to the project should either be stored on-site for future reuse or transferred to an established traditional material dealer.

(27) ARCHAEOLOGICAL DISCOVERY DURING EXCAVATION

- (a) Should any historical relics be unexpectedly discovered on the site during excavation, all excavation or disturbance to the area is to stop immediately and the Heritage Council of NSW should be informed in accordance with section 146 of the *Heritage Act 1977*.
- (b) Should any Aboriginal relics be unexpectedly discovered then all excavation or disturbance of the area is to stop immediately and the Department of Environment and Climate Change is to be informed in accordance with Section 91 of the *National Parks and Wildlife Act, 1974*.

(28) STREET TREE PROTECTION

Street trees must be protected in accordance with the Australian Standard 4970 Protection of Trees on Development Sites. All street trees along the Bourke Street frontage must be protected during the construction works as follows:

- (a) Tree trunk and major limb protection must be undertaken prior to or during the installation of any hoarding or scaffoldings. The protection must be installed by a qualified Arborist (AFQ 2 or 3) and must include:
 - (i) An adequate clearance, minimum 250mm, must be provided between the structure and tree branches, limbs and trunk at all times;
 - (ii) Tree trunk/s and/or major branches, located within 500mm of any hoarding or scaffolding structure, must be protected by wrapped hessian or similar material to limit damage, and
 - (iii) Timber planks (50mm x 100mm or similar) must be placed around tree trunk/s. The timber planks must be spaced at 100mm intervals, and must be fixed against the trunk with tie wire, or strapping. The hessian and timber planks must not be fixed to the tree in any instance, or in any fashion,
 - (iv) Tree trunk and major branch protection is to remain in place for the duration of construction and development works, and must be removed at the completion of the project.
- (b) All hoarding support columns are to be placed a minimum of 300mm from the edge of the existing tree pits/setts, so that no sinking or damage occurs to the existing tree setts. Supporting columns must not be placed on any tree roots that are exposed.

- (c) Materials or goods, including site sheds, must not be stored or placed:
 - (i) around or under the tree canopy; or
 - (ii) within two (2) metres of tree trunks or branches of any street trees.
- (d) Protective fencing (1.8 metre chain wire mesh fencing) must be erected on top of the hoarding on Bourke Street, if any, to protect branches during the construction works.
- (e) Any damage sustained to street tree/s as a result of the erection of hoardings, scaffolding, or due to the loading/unloading of vehicles adjacent the site, must be immediately reported to the Council's Street Tree Contract Coordinator on 9265 9333, in order to determine the appropriate action for maintaining the health and structural integrity of any damaged street tree.

(29) SWIMMING POOL - CONSULTATION WITH ENERGY AUSTRALIA

Energy Australia must be consulted in respect to the location of the proposed swimming pool relative to any overhead electrical wiring within a distance of 9 metres around the pool. Details of consultation with Energy Australia are to be submitted to the Principal Certifier prior to a Construction Certificate being issued.

(30) SWIMMING POOL - WASTE AND OVERFLOW WATERS

Swimming pool waste and overflow waters must be collected and directed to the sewer in accordance with the requirements of Sydney Water, and details are to be submitted with the application for a Construction Certificate to the satisfaction of Council or the accredited certifier and approved by the Principal Certifier.

(31) SWIMMING POOL/SPA

Swimming and/or spa pool/s and pool surrounds must be maintained in accordance with the *Public Health (General) Regulation 2012*. Note: Guidance may also be obtained from the NSW Health Department's *Public Swimming Pool and Spa Pool Guidelines*.

(32) MANAGING NOISE AND SAFETY OF POOLS

- (a) To minimise the impact of the pool on adjoining properties and to ensure the safety of the pool/spa area, the design and construction of the swimming pool/spa and associated equipment and fencing must comply with the following requirements:
 - (i) The *Swimming Pools Act 1992* and Regulations.
 - (ii) The swimming pool must have safety barriers installed in accordance with the requirements of AS 1926.1 - 2007 - 'Safety barriers for swimming pools' and AS 1926.2 - 2007 'Location of safety barriers for swimming pools'.
 - (iii) Australian Standards 1926.3 - Water Recirculation and Filtration; and
 - (iv) *Protection of the Environment Operations Act 1997*

(33) DEWATERING

If any dewatering of the site is to be undertaken, a bore licence may be required from the NSW Office of Water under the provisions of Part V of the Water Act 1912. The NSW Office of Water licences dewatering to allow excavation for construction for a temporary period, usually 12 months.

NOTE: The Department's instructions to Council are that they will not endorse the extraction of groundwater in perpetuity i.e. permanent dewatering around a development site, because it considers such development to be unsuitable. For this reason any proposed basement or other area that requires dewatering on an on-going basis may need to be fully tanked.

(34) BASIX

All commitments listed in each relevant BASIX Certificate for the development must be fulfilled prior to an Occupation Certificate being issued.

(35) HOURS OF WORK AND NOISE – OUTSIDE CBD

The hours of construction and work on the development must be as follows:

- (a) All work, including building/demolition and excavation work, and activities in the vicinity of the site generating noise associated with preparation for the commencement of work (eg. loading and unloading of goods, transferring of tools etc) in connection with the proposed development must only be carried out between the hours of 7.30am and 5.30pm on Mondays to Fridays, inclusive, and 7.30am and 3.30pm on Saturdays, with safety inspections being permitted at 7.00am on work days, and no work must be carried out on Sundays or public holidays.
- (b) Dewatering and truck movements associated with basement excavation are only permitted to be undertaken during the approved hours in (a) above.
- (c) All work, including demolition, excavation and building work must comply with the City of Sydney Code of Practice for Construction Hours/Noise 1992 and Australian Standard 2436 - 2010 Guide to Noise Control on Construction, Maintenance and Demolition Sites.

- (d) Notwithstanding the above, the use of a crane for special operations, including the delivery of materials, hoisting of plant and equipment and erection and dismantling of on site tower cranes which warrant the on-street use of mobile cranes outside of above hours can occur, subject to a permit being issued by Council under Section 68 of the Local Government Act 1993 and/or Section 138 of the Roads Act 1993.

Note: Works may be undertaken outside of hours, where it is required to avoid the loss of life, damage to property, to prevent environmental harm and/or to avoid structural damage to the building. Written approval must be given by the Construction Regulation Unit, prior to works proceeding

The *City of Sydney Code of Practice for Construction Hours/Noise 1992* allows extended working hours subject to the approval of an application in accordance with the Code and under Section 4.55 of the *Environmental Planning and Assessment Act 1979*.

(36) NOTIFICATION OF EXCAVATION WORKS OR USE OF HIGH NOISE EMISSION APPLIANCES/PLANT

The immediately adjoining neighbours must be given a minimum of 48 hours notice that excavation, shoring or underpinning works or use of high noise emission appliances / plant are about to commence.

(37) COVERING OF LOADS

All vehicles involved in the excavation and/or demolition process and departing the property with demolition materials, spoil or loose matter must have their loads fully covered before entering the public roadway.

(38) OCCUPATION CERTIFICATE TO BE SUBMITTED

An Occupation Certificate must be obtained from the Principal Certifier and a copy submitted to Council prior to commencement of occupation or use of the whole or any part of a new building, an altered portion of, or an extension to an existing building.

(39) LOADING AND UNLOADING DURING CONSTRUCTION

The following requirements apply:

- (a) All loading and unloading associated with construction activity must be accommodated on site, where possible.
- (b) If it is not feasible for loading and unloading to take place on site, a Works Zone on the street may be considered by Council.
- (c) A Works Zone may be required if loading and unloading is not possible on site. If a Works Zone is warranted an application must be made to Council at least 8 weeks prior to the commencement of work on the site. An approval for a Works Zone may be given for a specific period and certain hours of the days to meet the particular need for the site for such facilities at various stages of construction.
- (d) Where hoisting activity over the public place is proposed to be undertaken including hoisting from a Works Zone, a separate approval under Section 68 of the Local Government Act must be obtained.

(40) NO OBSTRUCTION OF PUBLIC WAY

The public way must not be obstructed by any materials, vehicles, refuse, skips or the like, under any circumstances. Non-compliance with this requirement will result in the issue of a notice by Council to stop all work on site.

(41) NO WORKS TO BE UNDERTAKEN ON NEIGHBOURING SITES

The development is not permitted to undertake works on neighbouring properties, including shoring and other sub-ground level structures.

SCHEDULE 2

PRESCRIBED CONDITIONS

The prescribed conditions in accordance with Division 8A of the *Environmental Planning and Assessment Regulation 2000* apply:

- Clause 98 Compliance with *Building Code of Australia* and insurance requirements under the *Home Building Act 1989*
- Clause 98A Erection of signs
- Clause 98B Notification of *Home Building Act 1989* requirements
- Clause 98C Conditions relating to entertainment venues
- Clause 98D Conditions relating to maximum capacity signage
- Clause 98E Conditions relating to shoring and adequacy of adjoining property

Refer to the NSW State legislation for full text of the clauses under Division 8A of the *Environmental Planning and Assessment Regulation 2000*. This can be accessed at: <http://www.legislation.nsw.gov.au>