# **Attachment A**

**Recommended Conditions of Consent** 

#### PART A - DEFERRED COMMENCEMENT CONDITIONS

# (CONDITIONS TO BE SATISFIED PRIOR TO CONSENT OPERATING)

• the consent is not to operate until the following conditions are satisfied, within **24 months** of the date of this determination:

#### **SCHEDULE 1**

# **DEFERRED COMMENCEMENT CONDITIONS** (CONDITIONS TO BE SATISFIED PRIOR TO CONSENT OPERATING)

The consent is not to operate until the following conditions are satisfied, within 24 months of the date of this determination:

# (1) VOLUNTARY PLANNING AGREEMENT

- (a) This consent is subject to a Voluntary Planning Agreement (VPA) between the Council of the City of Sydney and Stormac Pty Limited which was placed on public exhibition between 14 May 2018 and 11 June 2018 and shall be executed and submitted to Council
- (b) The guarantee must be provided to Council in accordance with the Voluntary Planning Agreement; and
- (c) The Voluntary Planning Agreement, as executed, must be registered on the title of the land.

# (2) SWEPT PATH ANALYSIS

A swept path analysis is to be submitted and approved by the Council and RMS prior to issue of any construction certificate. The swept path analysis needs to clearly show the width of both Bowden Street and McEvoy Street and demonstrate the maximum size vehicle that will enter and exit to the site in a forward direction.



#### **PART B - CONDITIONS OF CONSENT**

# (ONCE THE CONSENT IS IN OPERATION)

Upon written confirmation from Council that the deferred commencement conditions contained in Part A above have been satisfied, the consent will become operative from the date of that written confirmation, subject to the following conditions of consent and any other additional conditions reasonably arising from consideration of the deferred commencement consent conditions.

#### **SCHEDULE 1A**

# APPROVED DEVELOPMENT/DESIGN MODIFICATIONS/COVENANTS AND CONTRIBUTIONS/USE AND OPERATION

**Note:** Some conditions in Schedule 1A are to be satisfied prior to issue of a Construction Certificate and some are to be satisfied prior to issue of Occupation Certificate, where indicated.

#### (1) APPROVED DEVELOPMENT

(a) Development must be in accordance with Development Application No. D/2017/1073 dated 8 August 2017 and the following drawings prepared by SJB Architects:

| Drawing Number | Drawing Name                      | Date            |
|----------------|-----------------------------------|-----------------|
| DA-0200 '9'    | Floor Plan Ground                 | 30 October 2017 |
| DA-0201 '9'    | Floor Plan Level 01               | 30 October 2017 |
| DA-0202 '9'    | Floor Plan Level 02               | 30 October 2017 |
| DA-0204 '9'    | Floor Plan Roof                   | 30 October 2017 |
| DA-0501 '8'    | North Elevation West<br>Elevation | 24 July 2017    |
| DA-0502 '8'    | South Elevation East<br>Elevation | 24 July 2017    |
| DA-0601 '9'    | Sections 01 & 02                  | 30 October 2017 |

and as amended by the conditions of this consent.

(b) In the event of any inconsistency between the approved plans and supplementary documentation, the plans will prevail.

# (2) COMPLIANCE WITH VOLUNTARY PLANNING AGREEMENT

The terms of the planning agreement entered into in accordance with Deferred Commencement Condition 1 are to be complied with.

#### (3) BUILDING HEIGHT

- (a) The height of the building must not exceed RL 26400 (AHD) to the top of the building roof and RL 26500 (AHD) to the top of the lift overruns.
- (b) Prior to an Occupation Certificate being issued, a Registered Surveyor must provide certification that the height of the building accords with (a) above, to the satisfaction of the Principal Certifier.

#### (4) APPROVED DESIGN ROOF - TOP PLANT

All roof-top plant and associated equipment must be located within the approved building envelope.

# (5) FLOOR SPACE RATIO - ALL OTHER AREAS

The following applies to Floor Space Ratio:

- (a) The Floor Space Ratio for the business use must not exceed 1.98:1 calculated in accordance with the Sydney Local Environmental Plan 2012. For the purposes of the calculation of FSR, the Gross Floor Area of building is 9,155sqm.
- (b) Prior to an Occupation Certificate being issued, a Registered Surveyor must provide certification of the total and component Gross Floor Areas (by use) in the development, utilising the definition under the Sydney Local Environmental Plan 2012, applicable at the time of development consent, to the satisfaction of the Principal Certifier.

# (6) RESTRICTION OF END OF JOURNEY

Prior to an Occupation Certificate being issued or the use commencing, whichever is earlier, a documentary restrictive covenant to the effect that 23sqm of the building has been approved as end of journey floor space and has been excluded from floor space for the purposes of calculating floor space ratio is to be registered on the Title of the development site pursuant to section 88E of the *Conveyancing Act 1919*. The covenant is to be created appurtenant to Council and at no cost to Council.

# (7) HOURS OF OPERATION – SELF-STORAGE

The hours of operation of the self-storage facility use are restricted to between 6.00am and 9.00pm, Monday to Sunday.

# (8) HOURS OF OPERATION – OFFICE/CALL CENTRE/SHOWROOM

The hours of operation of the office, call centre and self-storage facility showroom uses are restricted to between 8.00am and 5.30pm, Monday to Sunday.

#### (9) HOURS OF OPERATION - GROUND FLOOR SHOPS

The hours of operation of the ground floor shop uses are restricted to between 7.00am and 7.00pm, Monday to Sunday.

# (10) SHOPS

The six (6) ground floor shop tenancies fronting McEvoy Street are approved as shops as per the definition of 'shop' in the Sydney Local Environmental Plan 2012. The definition of 'shop' explicitly excludes 'food and drinks premises'. Further applications or Complying Development Certificates can be made to change and fit-out these tenancies as 'food and drink premises' or other permissible uses in the future.

# (11) SIGNAGE STRATEGY

Prior to the issue of any Construction Certificate a signage strategy for the entire development is to be prepared and submitted to Council's Area Planning Manager for approval. The signage strategy must include information and scale drawings of the location, type, construction, materials and total number of signs appropriate for the building. The signage strategy must include all signage zones for the ground floor shop tenancies.

#### (12) COMPLIANCE WITH SUBMITTED MATERIALS AND SAMPLES BOARD

The design details of the proposed building facade including all external finishes, colours and glazing must be in accordance with the materials schedule and sample board 'DA-2201 '9", and specifications prepared by SJB Architects dated 30 October 2017. The feature roof elements facing McEvoy Street are to be translucent opaque white glass as shown on DA-2201/9.

#### (13) EXTERNAL WALLS AND CLADDING FLAMMABILITY

The external walls of the building including attachments must comply with the relevant requirements of the National Construction Code (NCC). Prior to the issue of a Construction Certificate and Occupation Certificate the Certifying Authority and Principal Certifying Authority must:

- (a) Be satisfied that suitable evidence is provided to demonstrate that the products and systems proposed for use or used in the construction of external walls including finishes and claddings such as synthetic or aluminium composite panels comply with the relevant requirements of the NCC; and
- (b) Ensure that the documentation relied upon in the approval processes include an appropriate level of detail to demonstrate compliance with the NCC as proposed and as built.

# (14) PROJECTION OVER McEVOY STREET

The architectural embellishments attached to the building, shown as overhanging the alignment of McEvoy Street (as widened), must be reduced to extend no more than 450mm over McEvoy Street and comply with the provisions of Schedule 4 ("Projections over or into public roads") of the Sydney Development Control Plan 2012.

#### (15) DETAILS OF VEHICLE DOOR OR GATE

Design details of the vehicle entrance and any vehicle roller door, gate or the such to the Bowden Street opening are to be submitted to and approved by Council's Area Planning Manager prior to the issue of a Construction Certificate for above ground building works.

# (16) AFFORDABLE HOUSING CONTRIBUTION - GREEN SQUARE - PAYMENT OF MONEY IN LIEU OF FLOOR SPACE

In accordance with Clause 7.13 of Sydney Local Environmental Plan 2012 and prior to a Construction Certificate being issued, the applicant must provide evidence that a monetary contribution towards the provision of affordable housing has been paid at the office of the Department of Planning or a bank guarantee in favour of The Department of Planning to the value of the required contribution has been lodged. The contribution is \$761,036.49 based on the in lieu monetary contribution rate for non-residential development at \$81.63 per square metre of total non-residential floor area 9,323sqm. Contributions will be indexed in accordance with the formula set out below.

Prior to an Occupation Certificate being issued or the use commencing, whichever is earlier, the applicant must provide evidence that the bank guarantee referred to above has been redeemed as payment of this contribution. If the contribution is paid after the indexation period in which the consent is granted 1 March 2018 to 28 February 2019, the amount of the contribution will be indexed in accordance with the formula set out below.

#### Notes:

(a) Applicants have two payment options:

Option 1 is payment by bank cheque using "Form B - Receipt to Release Certificate of Construction after payment by Bank Cheque". Form B must be obtained from the Green Square Project Team in the City Strategy and Design Unit at the City of Sydney, and then must be lodged with a bank cheque with the NSW Department of Planning.

Option 2 is lodgement of a bank guarantee using "Form A - Receipt to Release Certificate of Construction after lodgement of Bank Guarantee". Form A must be obtained from the Green Square Project Team GSPT@cityofsydney.nsw.gov.au in the City Strategy and Design Unit at the City of Sydney, and then must be lodged with a Bank Guarantee with the NSW Department of Planning.

Where Form A has been used, an occupation certificate will not be released until payment by bank cheque using "Form C - Receipt to Release Certificate of Occupancy after payment by Bank Cheque". Form C must be obtained from the Green Square Project Team GSPT@cityofsydney.nsw.gov.au in the City Strategy and Design Unit at the City of Sydney and then must be lodged with a bank cheque with the NSW Department of Planning.

(b) Applicants are made aware that the contribution amount quoted in this condition may not be final and that a correct indexed affordable housing contribution amount can be obtained from the relevant Form A, B or C at time of payment.

- (c) Forms A, B or C for payment of the affordable housing contribution can only be obtained from the City of Sydney, 456 Kent Street Sydney. Quote the development application number and the relevant Council officer will provide the applicant with an indexed contribution amount which must be paid at the Department of Planning. To arrange payment, contact the Housing Policy Team, NSW Department of Planning on Ph: 9228 6111 or Fax: 9228 6455 to arrange a time for payment.
- (d) The contribution will be indexed on the basis of the Established House Price Index for Sydney as published by the Australian Bureau of Statistics.
- (e) Contributions at Time of Payment = C x HPI2 / HPI1, where:
  - (i) C is the original contribution amount as shown above;
  - (ii) HPI2 is the Established House Price Index: All Groups Index for Sydney available from the Australian Bureau of Statistics at the time of the payment; and
  - (iii) HPI1 is the Established House Price Index: All Groups Index for Sydney available from the Australian Bureau of Statistics that applied at the date of the consent 1 March 2018 to 28 February 2019.

The amount of the monetary contribution is calculated on the total floor area (not a percentage of it). Contribution = (total residential floor area sqm) x residential rate (\$) + (total non-residential floor area (sqm) x non-residential rate (\$) + (total non-residential floor area (sqm) x non-residential rate (\$)

# (17) CONTRIBUTION TOWARDS PUBLIC AMENITIES - CITY OF SYDNEY DEVELOPMENT CONTRIBUTIONS PLAN 2015 - SOUTH PRECINCT

Council has identified the development will increase demand for public amenities and facilities. Pursuant to Section 7.11 of the Environmental Planning and Assessment Act, 1979 (as amended), and the City of Sydney Section 94 Contributions Development Contributions Plan 2015 the following monetary contributions are required towards the cost of public amenities.

| Contribution Category | <u>Amount</u> |
|-----------------------|---------------|
| Open Space            | \$30,807.09   |
| Community Facilities  | \$4,789.51    |
| Traffic and Transport | \$39,107.55   |
| Stormwater Drainage   | \$15,464.43   |
| Total                 | \$90,168.57   |

The City of Sydney will index the above contribution for inflation at the time of payment using the following formula.

Cpayment = Cconsent x (CPIpayment ÷ CPIconsent)

where:

Cpayment is the contribution at time of payment;

Consent is the contribution at the time of consent, as shown above;

CPIpayment is the Consumer Price Index (All Groups Index) for

Sydney published by the Australian Bureau of Statistics

that applies at the time of payment; and

CPI1consent is the Consumer Price Index (All Groups Index) for

Sydney at the date the contribution amount above was calculated being – 113.3 for the December 2017 quarter.

The contribution must be paid prior to the issue of any Construction Certificate in relation to this development.

Please contact Council's Planning Administration staff at planningsystemsadmin@cityofsydney.nsw.gov.au to request a letter confirming the indexed contribution amount payable.

Once the letter confirming the indexed contribution is obtained, payment may be made at any of the City's Neighbourhood Service Centres or the One Stop Shop at Town Hall House. Acceptable payment methods are EFTPOS (debit card only), cash or a bank cheque made payable to the City of Sydney. Personal or company cheques will not be accepted.

### (18) ALLOCATION OF CAR PARKING

The number of car parking spaces to be provided for the development shall not exceed the table below. Details confirming the car parking numbers shall be submitted to the satisfaction of the Certifying Authority prior to the issue of a Construction Certificate.

| Car Parking Type                               | Number |
|--|--------|
| Retail/Office and business car parking         | 4      |
| Retail/Office and business visitor car parking | 6      |
| Accessible visitor car parking                 | 1      |
| Subtotal                                       | 11     |
| Motorcycle parking                             | 1      |
| Medium Rigid Vehicle loading dock(s)           | 1      |
| Total  | 13     |

#### (19) CAR PARKING DESIGN

The design, layout, signage, line marking, lighting and physical controls of all offstreet car parking facilities must comply with the Australian Standard AS/NZS 2890.1 - 2004 Parking facilities Part 1: Off-street car parking and Australian Standard AS/NZS 2890.2 - 2002 Parking facilities Part 2: Off-street commercial vehicle facilities and Australian Standard AS/NZS 2890.6 - 2009 Parking facilities Part 6: Off-street parking for people with disabilities. The details must be submitted to and approved by the Certifying Authority prior to a Construction Certificate being issued.

# (20) BICYCLE PARKING AND END OF TRIP FACILITIES

The minimum number of bicycle parking spaces and end of trip facilities to be provided for the development must comply with the table below.

| User                      | Number of bicycles to be accommodated | Requirements   |
|---------------------------|---------------------------------------|--|
| Staff                     | 6                                     | Class B bicycle parking facility in accordance with AS2890.3 |
| Customer                  | 12                                    | Class C bicycle parking facility in accordance with AS2890.3 |
| End of Trip Facility Type | Number                                |  |
| Showers with change area  | 1                                     |  |
| Personal lockers          | 18                                    |  |

The layout, design and security of bicycle facilities must comply with *Australian Standard AS 2890.3:2015 Parking Facilities Part 3: Bicycle Parking Facilities*. The details must be submitted to and approved by the Certifying Authority confirming prior to the Construction Certificate being issued.

#### (21) COST OF SIGNPOSTING

All costs associated with signposting of any kerbside parking restrictions and traffic management measures associated with the development shall be borne by the developer.

#### (22) ASSOCIATED ROADWAY COSTS

All costs associated with the construction of any new road works including kerb and gutter, road pavement, drainage system and footway shall be borne by the developer. The new road works must be designed and constructed in accordance with the City's "Development Specification for Civil Works Design and Construction".

#### (23) ON-SITE LOADING AREAS AND OPERATION

All loading and unloading associated with the site must be carried out within the site at all times and must not obstruct other properties/units or the public way.

At all times the service vehicle docks, car parking spaces and access driveways must be kept clear of goods and must not be used for storage purposes, including garbage storage.

#### (24) SIGNS AT EGRESS

The following signs must be provided and maintained within the site at the point(s) of vehicle egress:

- Compelling "Give Way to Pedestrians and Bicycles" before crossing a footpath on an existing or identified shared path route.

The signs/ are to be erected prior to issue of an Occupation Certificate and must be maintained in good order at all times by the owners of the building.

# (25) TRAFFIC WORKS

Any proposals for alterations to the public road, involving traffic and parking arrangements, must be designed in accordance with RMS Technical Directives and must be referred to and agreed to by the Local Pedestrian, Cycling and Traffic Calming Committee prior to any work commencing on site.

#### (26) VEHICLE FOOTWAY CROSSING

A separate application is to be made to, and approved by, Council for the construction of any proposed vehicle footway crossing or for the removal of any existing crossing and replacement of the footpath formation where any such crossings are no longer required.

All disused or redundant vehicle crossings and laybacks must be removed and footway, kerb, gutter and road restoration reinstated in accordance with Council's standards, to suit the adjacent finished footway and edge treatment materials, levels and details, or as otherwise directed by Council officers. All construction and replacement works are to be completed in accordance with the approved plans prior to the issue of an Occupation Certificate.

<u>Note</u>: To reinforce the priority of pedestrian movement on the footpath, the footpath paving surface is to be continued over the vehicle crossing.

#### (27) REFLECTIVITY

The Principal Certifier must ensure that the visible light reflectivity from building materials used on the facade of the building does not exceed 20% prior to issue of the Construction Certificate.

#### (28) EXTERNAL LIGHTING

A separate development application is required to be lodged and approved prior to any external floodlighting or illumination of the building or site landscaping.

# (29) NOISE - GENERAL

- (a) The emission of noise associated with the use of the premises including the cumulative operation of any mechanical plant and equipment, and air conditioning shall comply with the following:
  - (i) The L<sub>Aeq, 15 minute</sub> noise level emitted from the use must not exceed the project specific noise level for that receiver as determined in accordance with the *NSW EPA Industrial Noise Policy*. Noise must be measured in accordance with the Industrial Noise Policy and relevant requirements of Australian Standard AS 1055-1997 Acoustics Description and measurement of environmental noise.
  - (ii) Project specific noise levels shall be determined by establishing the existing environmental noise levels, in complete accordance with the assessment L<sub>A90, 15 minute</sub> / rating L<sub>A90, 15 minute</sub> process to be in accordance with the requirements for noise monitoring listed in the NSW EPA Industrial Noise Policy and relevant requirements of Australian Standard AS1055-1997 Standard AS 1055-1997 Acoustics Description and measurement of environmental noise.
  - (iii) Modifying factors in Table 4.1 of the *NSW EPA Industrial Noise Policy* are applicable.

# For internal commercial amenity only

- (b) An L<sub>Aeq,15 minute</sub> noise level emitted from the use must not exceed the L<sub>A90, 15 minute</sub> noise level by more than 3dB in any Octave Band Centre Frequency (31.5 Hz to 8 kHz inclusive) when assessed inside any habitable room of any affected residence or noise sensitive commercial premises provided that;
  - (i) Where the L<sub>A90, 15 minute</sub> noise level is below the threshold of hearing, Tf at any Octave Band Centre Frequency as defined in Table 1 of International Standard ISO 226: 2003- Normal Equal-Loudness-Level Contours then the value of Tf corresponding to that Octave Band Centre Frequency shall be used instead.
  - (ii) The L<sub>Aeq,15 minute</sub> noise level and the L<sub>A90,15 minute</sub> noise level shall both be measured with all external doors and windows of the affected residence closed:
  - (iii) The relevant background noise level (L<sub>A90, 15 minute</sub>) is taken to mean the day, evening or night rating background noise level determined in complete accordance with the methodology outlined in the NSW EPA Industrial Noise Policy and Australian Standard AS1055.1997 Acoustics – Description and measurement of environmental noise.
  - (iv) Background noise shall be established in the absence of all noise emitted from the use but with the ventilation equipment normally servicing the affected residence operating. Background noise measurements are to be representative of the environmental noise levels at the affected location.
  - (v) Modifying factors in Table 4.1 of the *NSW EPA Industrial Noise Policy* are applicable. Internal Noise measurements are not to be corrected for duration.

# (30) DEMOLITION, EXCAVATION AND CONSTRUCTION NOISE AND VIBRATION MANAGEMENT PLAN

A site specific noise management plan shall be submitted to the Council for comment and approval prior to issue of any Construction Certificate.

The Plan must be prepared by a suitably qualified person who possesses the qualifications to render them eligible for membership of the Australian Acoustic Society, Institution of Engineers Australia or the Australian Association of Acoustic Consultants.

The plan must include but not be limited to the following:-

- (a) Identification of noise sensitive receivers near to the site.
- A prediction as to the level of noise impact likely to affect the nearest noise (b) sensitive receivers from the use and proposed number of high noise intrusive appliances intended to be operated onsite. A statement should also be submitted outlining whether or not predicted noise levels will comply with the noise criteria stated within the City of Sydney Construction Hours /Noise Code of Practice 1992 for the typical construction hours of 07.00am to 7.00pm. Where resultant site noise levels are likely to be in exceedance of this noise criteria then a suitable proposal must be given as to the duration and frequency of respite periods that will be afforded to the occupiers of neighbouring property (c) A representative noise measurement (LA90, 15 minute) should be submitted, assessed in the vicinity of any potentially affected receiver locations and measured in accordance with AS 1055:1.2.1997.(d) Confirmation of the level of community consultation that has/is and will be undertaken with Building Managers/ occupiers of the main adjoining noise sensitive properties likely to be most affected by site works and the operation of plant/machinery the demolition and excavation particularly durina Confirmation of noise monitoring methodology that is to be undertaken during the main stages of work at neighbouring noise sensitive properties in order to keep complaints to a minimum and to ensure that noise from site works complies with the noise criteria contained within City's Construction Noise Code.(f) What course of action will be undertaken following receipt of a complaint concerning offensive noise.(g) Details any mitigation measures that have been outlined by an acoustic consultant or otherwise that will be deployed on site to reduce noise impacts on the occupiers of neighbouring noise sensitive property to a minimum.(h) What plant and equipment is to be used on site, the level of sound mitigation measures to be undertaken in each case and the criteria adopted in their selection taking into account the likely noise impacts on the occupiers of neighbouring property and other less intrusive technologies available.

# (31) SIGN ILLUMINATION

- (a) At no time is the intensity, period of intermittency and hours of illumination of the sign to cause objectionable glare or injury to the amenity of the neighbourhood and as such must be designed, installed and used in accordance with AS4282-1997 Control of Obtrusive Effects of Outdoor Lighting.
- (b) The sign(s) must not flash. Signs with flashing, chasing, pulsating or flickering lights are not permitted.

- (c) The maximum night time luminance of any sign is not to exceed 300 cd/sqm.
- (d) Signage is only permitted to be illuminated during approved operating hours.
- (e) Upward facing light sources onto the signage is not permitted.

### (32) SIGNS - SEPARATE DA REQUIRED

A separate development application for any proposed signs additional to those approved as part of this consent (other than exempt or complying signs) must be submitted to and approved by Council prior to the erection or display of any such signs.

# (33) SIGNAGE - ROADS AND MARITIME SERVICES

- (a) Signage displays shall not contain/use:
  - (i) Flashing lights.
  - (ii) Electronically changeable messages.
  - (iii) Animated display, moving parts or simulated movement.
  - (iv) Complex displays that hold a driver's attention beyond "glance appreciation".
  - (v) Displays resembling traffic signs or signals by use of colour, shape or words that can be construed as giving instruction to traffic (ie by using words such as 'halt' or 'stop').
  - (vi) A method of illumination that distracts or dazzles.
- (b) Construction and maintenance activities shall be undertaken wholly within the private property of the site. Where this is not possible, a Road Occupancy Licence (ROL) will be required. A ROL can be obtained through https://myrta.com/oplinc2/pages/security/oplincLogin.jsf
- (c) All works associated with the proposed sign, including maintenance activities, shall be at no cost to Roads and Maritime.

#### (34) SWINGING DOORS OVER PUBLIC WAY

Any access doors to enclosures housing building services and facilities, such as hydrant and sprinkler booster assemblies or the like, must not open over the footway/roadway.

#### **SCHEDULE 1B**

# PRIOR TO CONSTRUCTION CERTIFICATE/COMMENCEMENT OF WORK/HEALTH AND BUILDING

# (35) ALIGNMENT LEVELS - MAJOR DEVELOPMENT

- (a) Proposed building floor levels, basement levels, basement car park entry levels and ground levels shown on the approved Development Application plans are indicative only and have not been approved by this consent.
- (b) Prior to a Construction Certificate being issued for any excavation, civil construction, drainage or building work (whichever is earlier), excluding approved preparatory or demolition work, alignment levels for the building and site frontages must be submitted to and approved by Council. The submission must be prepared by a Registered Surveyor and designed by a suitably qualified engineer, must be in accordance with the City of Sydney's *Public Domain Manual* and must be submitted with a completed and Levels and Gradients Approval Application form (available on the City's website).
- (c) These alignment levels, as approved by Council, are to be incorporated into the plans submitted with the application for a Construction Certificate for any civil, drainage and public domain work as applicable under this consent. If the proposed detailed design of the public domain requires changes to any previously approved Alignment Levels, then an amended Alignment Levels submission must be submitted to and approved by Council to reflect these changes prior to a Construction Certificate being issued for public domain work.

# (36) PAVING MATERIALS

The surface of any material used or proposed to be used for the paving of colonnades, thoroughfares, plazas, arcades and the like which are used by the public must comply with AS/NZS 4586:2004 (including amendments) "Slip resistance classification of new pedestrian surface materials".

# (37) PHOTOGRAPHIC RECORD / DILAPIDATION REPORT - PUBLIC DOMAIN

Prior to an approval for demolition being granted or a Construction Certificate being issued, whichever is earlier, a photographic recording of the public domain site frontages is to be prepared and submitted to Council's satisfaction.

The recording must include clear images of the building facade adjoining the footpath, the footpath, nature strip, kerb and gutter, driveway crossovers and laybacks, kerb ramps, road carriageway, street trees and plantings, parking restriction and traffic signs, and all other existing infrastructure along the street.

The form of the recording is to be as follows:-

- (a) A PDF format report containing all images at a scale that clearly demonstrates the existing site conditions;
- (b) Each image is to be labelled to identify the elements depicted, the direction that the image is viewed towards, and include the name of the relevant street frontage;

- (c) Each image is to be numbered and cross referenced to a site location plan;
- (d) A summary report, prepared by a suitable qualified professional, must be submitted in conjunction with the images detailing the project description, identifying any apparent existing defects, detailing the date and authorship of the photographic record, the method of documentation and limitations of the photographic record;
- (e) Include written confirmation, issued with the authority of both the applicant and the photographer that the City of Sydney is granted a perpetual nonexclusive license to make use of the copyright in all images supplied, including the right to make copies available to third parties as though they were Council images. The signatures of both the applicant and the photographer must be included.

Any damage to the public way including trees, footpaths, kerbs, gutters, road carriageway and the like must immediately be made safe and functional by the applicant. Damage must be fully rectified by the applicant in accordance with the City's standards prior to a Certificate of Completion being issued for Public Domain Works or before an Occupation Certificate is issued for the development, whichever is earlier.

# (38) PRESERVATION OF SURVEY MARKS

All works in City streets must ensure the preservation of existing permanent survey marks (a brass bolt, or a lead plug holding a brass tack, covered by a cast iron box). At least forty-eight hours prior to the commencement of any works in the public way within 1 metre of a permanent survey mark contact must be made with the City's Project Manager Survey / Design Services to arrange for the recovery of the mark.

Prior to the issue of a Construction Certificate, a survey plan, clearly showing the location of all permanent survey marks fronting the site and within 5 metres on each side of the frontages must be submitted to Council.

At least forty-eight hours prior to the commencement of any works in the public way within 1 metre of a permanent survey mark contact must be made with the City's Senior Surveyor to arrange for the recovery of the mark.

A fee must be paid to the Council for the replacement of any permanent survey mark removed or damaged in accordance with the City's Schedule of Fees and Charges (Reinstatement of Survey Box).

#### (39) PROTECTION OF SURVEY INFRASTRUCTURE

Prior to the commencement of any work on site, a statement prepared by a Surveyor registered under the *Surveying Act 2002* must be submitted to Council verifying that a survey has been carried out in accordance with the Surveyor General's Direction No. 11 — Reservation of Survey Infrastructure. Any Permanent Marks proposed to be or have been destroyed must be replaced, and a "Plan of Survey Information" must be lodged at the Land and Property Management Authority.

Reason: To ensure that the survey control infrastructure and cadastral framework are preserved for the public benefit and in accordance with the *Surveying Act* 2002.

#### (40) PUBLIC DOMAIN PLAN

- (a) A detailed Public Domain Plan must be prepared by a suitably qualified architect, urban designer, landscape architect or engineer and must be lodged with Council's Public Domain Section and be approved by Council prior to a Construction Certificate being issued for public domain work or above ground building work, whichever is later.
- (b) The Public Domain Plan must document all works required to ensure that the public domain complies with the City of Sydney's Public Domain Manual, Sydney Streets Code and Sydney Streets Technical Specification, including requirements for road pavement, traffic measures, footway pavement, kerb and gutter, drainage, vehicle crossovers, pedestrian ramps, lighting, street trees and landscaping, signage and other public domain elements. If an Alignment Levels condition applies to the development, the Public Domain Plan submission must incorporate the approved Alignment Levels. If the proposed detailed design of the public domain requires changes to any previously approved Alignment Levels, then an amended Alignment Levels submission must be submitted to and approved by Council to reflect these changes prior to a Construction Certificate being issued for public domain work.
- (c) The works to the public domain are to be completed in accordance with the approved Public Domain Plan and Alignment Levels plans and the *Public Domain Manual* before any Occupation Certificate is issued in respect of the development or before the use commences, whichever is earlier.
- (d) A Public Domain Works Deposit will be required for the public domain works, in accordance with the City of Sydney's adopted fees and charges and the *Public Domain Manual*. The Public Domain Works Deposit must be submitted as an unconditional bank guarantee in favour of Council as security for completion of the obligations under this consent.
- (e) Council's Public Domain section must be contacted to determine the guarantee amount prior to lodgement of the guarantee. The guarantee must be lodged with Council prior to a Construction Certificate being issued.
- (f) The Bank Guarantee will be retained in full until all Public Domain works are completed and the required certifications, warranties and works-asexecuted documentation are submitted and approved by Council in writing. On satisfying the above requirements, 90% of the total securities will be released. The remaining 10% will be retained for the duration of the specified Defects Liability Period.

### (41) PUBLIC DOMAIN WORKS - HOLD POINTS AND HANDOVER

(a) Prior to a Construction Certificate being issued for public domain work, including civil, drainage and subsurface works, , a set of hold points for approved public domain, civil and drainage work is to be determined with

and approved by the City's Public Domain section in accordance with the City of Sydney's *Public Domain Manual* and *Sydney Streets Technical Specification*.

(b) Prior to a Certificate of Completion being issued for public domain works and before the issue of any Occupation Certificate for the development or before the use commences, whichever is earlier, electronic works-asexecuted (as-built) plans and documentation, certified by a suitably qualified, independent professional must be submitted to and accepted by Council for all public domain works. Completion and handover of the constructed public domain works must be undertaken in accordance with the City of Sydney's *Public Domain Manual* and *Sydney Streets Technical Specification*, including requirements for as-built documentation, certification, warranties and the defects liability period.

#### (42) PUBLIC DOMAIN DAMAGE DEPOSIT

A Public Domain Damage Deposit calculated on the basis of **149 lineal metres** of concrete site frontage must be lodged with Council in accordance with the City of Sydney's adopted Schedule of Fees and Charges. The Public Domain Damage Deposit must be submitted as an unconditional bank guarantee in favour of Council as security for repairing any damage to the public domain in the vicinity of the site.

The guarantee must be lodged with Council prior to an approval for demolition being granted or a Construction Certificate being issued, whichever is earlier.

The Bank Guarantee will be retained in full until the final Occupation Certificate has been issued and any rectification works to the footway and Public Domain are completed to Council's satisfaction. On satisfying the above requirements 90% of the total securities will be released, with the remaining 10% to be retained for the duration of the 12 months Defect Liability Period.

#### (43) PUBLIC DOMAIN LIGHTING

- (a) Prior to a Construction Certificate for public domain works or above ground building works being issued, whichever is later, a detailed Public Domain Lighting Plan for pedestrian and street lighting in the public domain must be prepared by a suitably qualified, practicing lighting engineer or lighting designer and must be submitted to and approved by Council. The Lighting Plan must be prepared in accordance with the City of Sydney's Sydney Lights Design Code, Sydney Streets Code, Sydney Streets Technical Specification and Public Domain Manual and must include the following:
  - (i) Vertical and horizontal illuminance plots for the public domain lighting design to demonstrate compliance with all relevant Australian Standards and to meet the lighting categories and requirements specified by the City;
  - (ii) The location, type and category of existing and proposed lights, including details of luminaire specifications, required to ensure compliance with City policies and Australian Standards;
  - (iii) Footing locations and structural details;

- (iv) Location and details of underground electrical reticulation, connections and conduits:
- (v) Certification by a suitably qualified, practicing lighting engineer or lighting designer to certify that the design complies with City policies and all relevant Australian Standards including AS 1158, AS 3000 and AS4282:
- (vi) Structural certification for footing designs by a suitably qualified, practicing engineer to certify that the design complies with City of Sydney policies and Australian Standards.
- (b) The public domain lighting works are to be completed in accordance with the approved plans and the City of Sydney's *Public Domain Manual* before any Occupation Certificate is issued in respect of the development or before the use commences, whichever is earlier.

# (44) TACTILE GROUND SURFACE INDICATORS AND HANDRAILS

All tactile ground surface indicators, handrails and other elements required to provide access into the building / property must be located entirely within the private property boundary.

# (45) DRAINAGE AND SERVICE PIT LIDS

Drainage and service pit lids throughout the public domain shall be heelguard and bicycle safe, finish flush with the adjacent pavement to avoid trip hazards and be clear of obstructions for easy opening and cleaning. Pit lids shall be in accordance with the *City of Sydney's Sydney Streets Design Code* and *Sydney Streets Technical Specification*. Details of drainage and service pit lids shall be submitted and approved by Council prior to a Construction Certificate being issued for the relevant stage of work.

# (46) STORMWATER AND DRAINAGE - MAJOR DEVELOPMENT

- (a) Prior to issue of any Construction Certificate for excavation, civil construction, drainage or building work (whichever is earlier), excluding approved preparatory or demolition work, a detailed engineering design for drainage including calculations and design for the stormwater overland flow path for the development must be:
  - (i) Prepared by a suitably qualified hydraulic or civil engineer to show the proposed method of collection and disposal of stormwater; and
  - (ii) Prepared in accordance with the City of Sydney's Stormwater Drainage Manual, technical specifications, standards and policies, as amended from time to time; and
  - (iii) Submitted to and be approved by the City of Sydney and a copy of the City's letter of approval must be provided to the Principal Certifying Authority.
- (b) For approval of a connection into the City of Sydney's drainage system an "Application for Approval of Stormwater Drainage Connections" must be

submitted to the City, together with an application fee in accordance with the City of Sydney's adopted Schedule of Fees and Charges.

- (i) The application must be approved by the City of Sydney prior to an approval or Construction Certificate being issued for excavation, civil construction, drainage or building work (whichever is earlier), excluding approved preparatory or demolition work.
- (ii) All proposed connections to the City's underground drainage system require the owner to enter into a Deed of Agreement with the City of Sydney and obtain registration on Title of a Positive Covenant prior to an Occupation Certificate being issued, including an Interim Occupation Certificate.

#### **On-site Detention**

- (c) The requirements of Sydney Water with regard to the on-site detention of stormwater must be ascertained and complied with.
  - (i) Evidence of the approval by Sydney Water of the detailed design for on-site detention must be submitted to and be accepted by the City of Sydney and a copy of the City's letter of acceptance must be provided to the Principal Certifying Authority prior to any Construction Certificate being issued, excluding for any approved preparatory, demolition or excavation works.
  - (ii) Prior to the issue of any Occupation Certificate, including any Interim Occupation Certificate, a Positive Covenant must be registered on the property title for all drainage systems involving On-Site Detention (OSD) to ensure maintenance of the approved OSD system regardless of the method of connection.

#### **Stormwater Quality Assessment**

(d) Prior to a Construction Certificate being issued for any excavation, civil construction, drainage or building work (whichever is earlier), but excluding approved preparatory or demolition work, a stormwater quality assessment must be undertaken and must be approved by City of Sydney and a copy of the City's letter of approval must be provided to the Principal Certifying Authority.

The stormwater quality assessment must:

- (i) Be prepared by a suitably qualified hydraulic engineer with experience in Water Sensitive Urban Design;
- (ii) Use modelling from an industry-standard water quality model (e.g. MUSIC Model or equivalent); and
- (iii) Demonstrate through reports, design plans and calculations, what water sensitive urban design and other drainage measures will be used to ensure that the development will achieve the following postdevelopment pollutant loads:
  - reduce the baseline annual pollutant load for litter and vegetation larger than 5mm by 90%;

- b. reduce the baseline annual pollutant load for total suspended solids by 85%;
- c. reduce the baseline annual pollutant load for total phosphorous by 65%;
- d. reduce the baseline annual pollutant load for total nitrogen by 45%.
- (iv) Include certification from a suitably qualified practicing professional that the requirements of parts (d) (i), (ii) and (iii) of this condition have been met.

Prior to the issue of an Occupation Certificate, maintenance schedules of the proposed water sensitive urban design and drainage measures must be submitted to and be approved by the Principal Certifying Authority and a copy provided to the City of Sydney.

# **Completion / Works-as-Executed Documentation**

- (e) Prior to a Certificate of Completion being issued by the City of Sydney for stormwater drainage works:
  - (i) All works for the disposal of stormwater and drainage are to be implemented in accordance with the approved plans, City of Sydney technical specifications. Standards and policies, approval letters and the requirements of this consent.
  - (ii) Works-As-Executed survey, prepared, signed and dated by a Registered Surveyor, must be submitted to and be accepted by the City of Sydney. The plan must be overlaid on a copy of the approved stormwater drainage plans issued with the Construction Certificate, with variations to locations, dimensions, levels and storage volumes clearly marked.
  - (iii) Electronic works-as-executed (as-built) details, certifications, warranties, inspection reports (including Closed Circuit Television reports) and associated documentation for the completed work must be prepared and certified by a suitably qualified hydraulic engineer, in accordance with the requirements of the City of Sydney's technical specifications, the Public Domain Manual, the Stormwater Drainage Manual, the conditions of this consent and all letters of approval issued by the City of Sydney for works in the public domain, and must be submitted to and be accepted by the City of Sydney.
- (f) Prior to the issue of the first Occupation Certificate, including an Interim Occupation Certificate, or before the use commences (whichever is earlier):
  - (i) A copy of the City's Certificate of Completion for all stormwater and drainage work undertaken in the public domain must be provided to the Principal Certifying Authority;
  - (ii) A Works-As-Executed survey, must be prepared, signed, dated and certified by a Registered Surveyor and must be submitted to and be accepted by the Principal Certifying Authority. The Works-as-Executed plan must be overlaid on a copy of the approved stormwater

drainage plans issued with the Construction Certificate, with variations to locations, dimensions, levels and storage volumes clearly marked;

- (iii) A Hydraulic Compliance Certificate and Calculation Sheet must be prepared by a suitably qualified hydraulic engineer (minimum NER), showing approved versus installed hydraulic calculations, and must be submitted to and be accepted by the Principal Certifying Authority;
- (iv) Evidence of Sydney Water's acceptance of the Works-As-Executed documentation, certification and Hydraulic Compliance Certificate and Calculation Sheet must be provided to the Principal Certifying Authority;
- (v) The Principal Certifying Authority must submit a copy of the Works-As-Executed plans, certifications, Hydraulic Compliance Certificate and Calculation Sheet to the City of Sydney.

# (47) INSTALLATION OF DUAL-FLUSH TOILETS

All toilets installed within the development must be of water efficient dual-flush or other water-saving capacity with at least a 4-star rating under the Water Efficiency and Labelling Scheme (WELS). The details must be submitted for the approval of the Principal Certifier, prior to a Construction Certificate being issued.

### (48) INSTALLATION OF WATER EFFICIENT TAPS

All taps and shower heads installed must be water efficient with at least a 4-star rating under the Water Efficiency and Labelling Scheme (WELS). The details are to be submitted for the approval of the Principal Certifier, prior to an Occupation Certificate being issued.

#### (49) INSTALLATION OF WATER EFFICIENT URINALS

New urinal suites, urinals and urinal flushing control mechanisms must use waterless technology. Where it is submitted that this is not feasible, it must be demonstrated that products have been selected with at least a 4-star rating under the Water Efficiency and Labelling Scheme (WELS). Systems must include "smart controls" to reduce unnecessary flushing. Continuous flushing systems are not approved. Details are to be submitted to and approved by the Principal Certifier, prior to a Construction Certificate being issued.

# (50) INTERNAL LIGHTING SYSTEM

The proposed internal lighting system for the commercial office spaces must be designed to provide for the efficient use of energy including the use of energy efficient light fittings, zoned lighting and controls and sensors to ensure automatic switch off during non-working hours. Details of the internal lighting system must be submitted to and approved by the Principal Certifier prior to a Construction Certificate being issued.

# (51) LANDSCAPING OF THE SITE

- (a) A detailed landscape plan, drawn to scale, by a qualified landscape architect or landscape designer, must be submitted to and approved by Council's Area Planning Manager prior to the issue of a Construction Certificate for above ground building works. The plan must include:
  - Location of existing and proposed structures on the site including, but not limited to, existing and proposed trees, paved areas, planted areas on slab, planted areas in natural ground, lighting and other features;
  - (ii) Details of earthworks and soil depths including mounding and retaining walls and planter boxes (if applicable). The minimum soil depths for planting on slab must be 1000mm for trees, 450mm for shrubs and 200mm for groundcovers;
  - (iii) Location, numbers, type and supply of plant species, with reference to NATSPEC (if applicable);
  - (iv) Details of planting procedure and maintenance;
  - (v) Details of drainage, waterproofing and watering systems.
- (b) Prior to the issue of a Construction Certificate, a maintenance plan is to be submitted to and approved by the Principal Certifier. The maintenance plan is to be complied with during occupation of the property.
- (c) All landscaping in the approved plan is to be completed prior to an Occupation Certificate being issued.

#### (52) WASTE AND RECYCLING COLLECTION CONTRACT

Prior to an Occupation Certificate being issued and/or commencement of the use, whichever is earlier, the building owner must ensure that there is a contract with a licensed contractor for the removal of **all waste**. No garbage is to be placed on the public way, e.g. footpaths, roadways, plazas, reserves, at any time.

#### (53) WASTE AND RECYCLING MANAGEMENT - COMMERCIAL

A Waste Management Plan is to be approved by the Principal Certifier prior to a Construction Certificate being issued. The plan must comply with the Council's *Policy for Waste Minimisation in New Developments 2005.* All requirements of the approved Building Waste Management Plan must be implemented during construction of the development.

# UPON COMPLETION OF THE DEVELOPMENT

(c) Prior to an Occupation Certificate being issued or the use commencing, whichever is earlier, the Principal Certifier must ensure that waste handling works have been completed in accordance with: the Waste Management Plan; other relevant development consent conditions; and Council's Policy for Waste Minimisation in New Developments 2005.

# (54) SYDNEY WATER CERTIFICATE (TAP-IN)

- (a) The approved plans must be submitted to Sydney Water's "Tap-in" online service to determine whether the development will affect Sydney Water's sewer and water mains, stormwater drains and/or easements, and if further requirements need to be met. Sydney Water's "Tap-in" online service is available at <a href="www.sydneywater.com.au">www.sydneywater.com.au</a>, (see Plumbing, Building & Development and then Sydney Water "Tap-in").
- (b) The Consent Authority or a Principal Certifier must ensure that Sydney Water has appropriately stamped the plans before the commencement of work.

# (55) CONSTRUCTION TRAFFIC MANAGEMENT PLAN

A Construction Traffic and Pedestrian Management Plan must be submitted to and approved by Council prior to a Construction Certificate being issued.

Construction Traffic and Pedestrian Management Plans are to be prepared in accordance with Standard Requirements for Construction Traffic Management Plan on the City's website

http://www.cityofsydney.nsw.gov.au/business/business-responsibilities/traffic-management/construction-traffic-management-plans and RMS condition as below:

"A Construction Traffic Management Plan detailing construction vehicle routes, number of trucks, hours of operation, access arrangements and traffic control should be submitted to Council for approval prior to the issue of a Construction Certificate."

#### (56) AUSGRID CONDITIONS

- (a) It is recommended for the nominated electrical consultant/contractor to provide a preliminary enquiry to Ausgrid to obtain advice for the connection of the proposed development to the adjacent electricity network infrastructure. An assessment will be carried out based on the enquiry which may include whether or not:
  - The existing network can support the expected electrical load of the development
  - A substation may be required on-site, either a pad mount kiosk or chamber style and;
  - Site conditions or other issues that may impact on the method of supply.

Please direct the developer to Ausgrid's website, www.ausgrid.com.au about how to connect to Ausgrid's network.

(b) All proposed vegetation underneath overhead power lines and above underground cables must comply with the requirements of ISSC 3 Guideline For Managing Vegetation Near Power Lines.

(c) There are existing overhead electricity network assets in McEvoy Street and Bowden Street.

Safework NSW Document – Work Near Overhead Powerlines: Code of Practice, outlines the minimum safety separation requirements between these mains/poles to structures within the development throughout the construction process. It is a statutory requirement that these distances be maintained throughout construction. Special consideration should be given to the positioning and operating of cranes and the location of any scaffolding.

The "as constructed" minimum clearances to the mains should also be considered. These distances are outlined in the Ausgrid Network Standard, NS220 Overhead Design Manual. This document can be sourced from Ausgrid's website, www.ausgrid.com.au

Should the existing overhead mains require relocating due to the minimum safety clearances being compromised in either of the above scenarios, this relocation work is generally at the developers cost.

It is also the responsibility of the developer to ensure that the existing overhead mains have sufficient clearance from all types of vehicles that are expected be entering and leaving the site.

(d) There are existing underground electricity network assets in McEvoy Street and Bowden Street.

Special care should also be taken to ensure that driveways and any other construction activities within the footpath area do not interfere with the existing cables in the footpath. Ausgrid cannot guarantee the depth of cables due to possible changes in ground levels from previous activities after the cables were installed. Hence it is recommended that the developer locate and record the depth of all known underground services prior to any excavation in the area.

Should ground anchors be required in the vicinity of the underground cables, the anchors must not be installed within 300mm of any cable, and the anchors must not pass over the top of any cable.

Safework Australia – Excavation Code of Practice, and Ausgrid's Network Standard NS156 outlines the minimum requirements for working around Ausgrid's underground cables.

# (57) STREET TREE PROTECTION

All Street trees along the frontages of the site must be retained and protected in accordance with the Australian Standard 4970 Protection of Trees on Development Sites and as follows:

- (a) Tree trunk and major limb protection must be undertaken prior to the commencement of works. The protection must be installed and certified by a qualified Arborist (AQF Level 3) and must include:
  - (i) Tree trunk/s and/or major branches must be protected by wrapped hessian or similar material to limit damage, and

- (ii) Timber planks (50mm x 100mm x 2000mm) must be placed around tree trunk/s. The timber planks must be spaced at 100mm intervals, and must be fixed against the trunk with tie wire, or strapping. The hessian and timber planks must not be fixed to the tree in any instance, or in any fashion,
- (iii) Tree trunk and major branch protection is to remain in place for the duration of construction and development works, and must be removed at the completion of the project.
- (b) Young street trees shall be protection by installing three (3) wooden takes around the edge of the tree pit. Hessian shall be wrapped around the stakes. If existing stakes are already in place, these shall suffice as tree protection.
- (c) Temporary signs, or any other items, shall not be fixed or attached to any street tree.
- (d) Materials or goods, including site sheds, must not be stored or placed:
  - (i) around or under the tree canopy; or
  - (ii) within two (2) metres of tree trunks or branches of any street trees.
- (e) Any excavation within in any area known to, or suspected of having street tree roots greater than 40mm diameter must be undertaken by hand.
- (f) Any trenching works for services / hydraulics / drainage etc must not be undertaken within 3 metres of any street tree. Alternative installation methods for services, such as directional boring/drilling, or redirection of services shall be employed where large woody roots greater than 40mm diameter are encountered during the installation of any services.
- (g) Existing sections of kerbs adjacent to any street tree shall not be removed without approval from the Street Tree Coordinator. Removal of kerbs adjacent to mature trees can cause trees to become unstable and fail.
- (h) Any damage sustained to street tree/s as a result of construction activities (including demolition) must be immediately reported to the Council's Street Tree Contract Coordinator on 9265 9333. Any damage to street trees as a result of construction activities may result in a prosecution under the Local Government Act 1993 and/or the Environmental Planning and Assessment Act 1979.

#### (58) STREET TREE PRUNING

- (a) The consent from Council must be obtained prior to the undertaking of any street tree pruning works including tree roots greater than 40mm diameter. Only minor pruning works will be approved by Council.
- (b) Any pruning that is required to accommodate hoardings, scaffolding, or to accommodate the loading/unloading of vehicles, and has been approved by Council, must be carried out by a qualified Arborist (AQF3), and must be in accordance with AS4373 Australian Standards 'Pruning of Amenity Trees'.

(c) The removal of any street tree approved by Council must include complete stump removal and the temporary reinstatement of levels so that no trip or fall hazards exist until suitable replanting occurs. These works must be completed immediately following the trees removal.

# (59) OPERATING HOISTING DEVICES INCLUDING BUILDING MAINTENANCE UNITS OVER A PUBLIC ROAD

If it is proposed to install a building maintenance unit or operate a hoisting device above a road (footpath) including swinging, hoisting material/equipment and slewing any part of the device, a separate application under Section 68 of the Local Government Act 1993 and Section 138 of the Roads Act 1993 must be made to Council to obtain approval.

Note: Building maintenance unit means a power operated suspended platform and associated equipment on a building specifically designed to provide permanent access to the faces of the building for maintenance (Work Health and Safety Regulation 2011).

# (60) APPLICATION FOR HOARDINGS AND SCAFFOLDING INSTALLED ON OR ABOVE A PUBLIC ROAD AND OPERATING HOISTING DEVICES INCLUDING BUILDING MAINTENANCE UNITS OVER A PUBLIC ROAD

- (a) A separate application under Section 68 of the Local Government Act 1993 and Section 138 of the Roads Act 1993 is to be made to Council to erect a hoarding and/or scaffolding (temporary structures) on or above a public road (footway and/or roadway).
- (b) Where an approval (Permit) is granted allowing the placement of temporary structures on or above a public road the structures must comply fully with Council's Hoarding and Scaffolding Policy; Guidelines for Hoardings and Scaffolding; and the conditions of approval (Permit) granted including:
  - (i) maintaining a current and valid approval for the full duration that the temporary structure/s is in place;
  - (ii) maintaining temporary structure/s in a structurally sound and stable condition for the full duration of installation (Clause 2.11.1);
  - (iii) bill posters and graffiti being removed within 24 hours of their placement (Clause 2.11.2);
  - (iv) maintaining temporary structures and the public place adjoining the work site in a clean and tidy condition including repainting and/or repair of graphics (Clauses 2.11.1, 2.11.4, 2.14.1 and 3.9.3);
  - (v) maintaining a watertight deck (Type B hoardings) to prevent liquids including rainwater, falling onto the footway/roadway surfaces (Clauses 3.9.1 and 3.9.4);
  - (vi) approved site sheds on the decks of a Type B hoarding being fully screened from the public place (Clause 3.9.5);
  - (vii) material and equipment not being placed or stored on the deck of Type B hoardings, unless specifically approved by Council (Clause 3.9.4);

- (viii) providing and maintaining operational artificial lighting systems under Type B hoardings including at high-bay truck entry points (Clause 3.9.9); and
- (ix) ensuring all required signage is provided and maintained (Clauses 3.9.3, 3.9.6, 3.9.8, 3.10.1 and 4.2).

If it is proposed to operate a hoisting device including a building maintenance unit above a public road which swings, hoists material/equipment and/or slews any part of the device over the public road, a separate application under Section 68 of the Local Government Act 1993 and Section 138 of the Roads Act 1993 must be made to Council to obtain approval.

Note: 'Building maintenance unit' means a power-operated suspended platform and associated equipment on a building specifically designed to provide permanent access to the faces of the building for maintenance (Work Health and Safety Regulation 2011).

### (61) ASBESTOS REMOVAL WORKS

- (a) All works removing asbestos containing materials must be carried out by a suitably licensed asbestos removalist duly licensed with Safework NSW, holding either a Friable (Class A) or a Non- Friable (Class B) Asbestos Removal Licence which ever applies.
  - A copy of the relevant licence shall be made available to any authorised Council officer on request within 24 hours.
- (b) Five days prior to the commencement of licensed asbestos removal, Safework NSW must be formally notified of the works. All adjoining properties and those opposite the development must be notified in writing of the dates and times when asbestos removal is to be conducted. The notification must identify the licensed asbestos removal contractor and include a contact person for the site together with telephone number and email address.
- (c) All work must be carried out in accordance with the Work Health and Safety Regulation 2011 and the NSW Government and Work Cover document entitled How to manage and control asbestos in the work place: Code of Practice (Safework NSW) December 2011 and the City of Sydney Managing Asbestos Policy dated 21 October 2013 and associated guidelines.
- (d) The asbestos removalist must use signs and barricades to clearly indicate the area where the asbestos removal work is being performed. Signs must be placed in positions so that people are aware of where the asbestos removal work area is and should remain in place until removal is completed and clearance to reoccupy has been granted. Responsibilities for the security and safety of the asbestos removal site and removal must be specified in the asbestos removal control plan (where required). This includes inaccessible areas that are likely to contain asbestos.
- (e) Warning signs must be placed so they inform all people nearby that asbestos removal work is taking place in the area. Signs must be placed at all of the main entry points to the asbestos removal work area where asbestos is present. These signs must be weatherproof, constructed of

light-weight material and adequately secured so they remain in prominent locations. The signs must be in accordance with AS 1319 -1994 Safety Signs for the Occupational Environment for size, illumination, location and maintenance.

- (f) Asbestos waste must only be transported and disposed of at an EPA licensed waste facility.
- (g) No asbestos products are to be reused on the site (i.e. packing pieces, spacers, formwork or fill etc).
- (h) No asbestos laden skips or bins are to be left in any public place without the written approval of Council.
- (i) A site notice board must be located at the main entrance to the site in a prominent position and must have minimum dimensions of 841mm x 594mm (A1) with any text on the notice to be a minimum of 30 point type size.

The site notice board must include the following:

- (i) contact person for the site;
- (ii) telephone and facsimile numbers and email address; and
- (iii) site activities and time frames.

# (62) CLASSIFICATION OF WASTE

Prior to the exportation of waste (including fill or soil) from the site, the waste materials must be classified in accordance with the provisions of the Protection of the *Environment Operations Act 1997* and the *NSW DECC Waste Classification Guidelines, Part1: Classifying Waste (July 2009).* The classification of the material is essential to determine where the waste may be legally taken. The *Protection of the Environment Operations Act 1997* provides for the commission of an offence for both the waste owner and the transporters if the waste is taken to a place that cannot lawfully be used as a waste facility for the particular class of waste. For the transport and disposal of industrial, hazardous or Group A liquid waste advice should be sought from the EPA.

#### (63) DISCHARGE OF CONTAMINATED GROUNDWATER

Contaminated groundwater shall not be discharged into the City's stormwater drainage system.

Options for the disposal of groundwater include disposal to sewer with prior approval from Sydney Water or off-site disposal by a liquid waste transporter for treatment/disposal to an appropriate waste treatment/processing facility.

#### (64) ENVIRONMENTAL MANAGEMENT PLAN

Prior to the commencement of any demolition and remedial works an Environmental Management Plan (EMP) must be prepared for the site and submitted to the City's Area Planning Manager for written approval prior to the commencement of work. The EMP must consider all potential environmental

impacts from the approved works including but not limited to sedimentation control, contamination containment, stockpiles, noise and vibration, odours and dust emissions.

All works must be undertaken onsite in accordance with the approved Environmental Management Plan.

# (65) IMPORTED FILL MATERIALS

All fill imported onto the site shall be validated to ensure the imported fill is suitable for the proposed land use from a contamination perspective. Fill imported on to the site shall also be compatible with the existing soil characteristic for site drainage purposes.

The City may require details of appropriate validation of imported fill material to be submitted with any application for future development of the site. Hence all fill imported onto the site should be validated by either one or both of the following methods during remediation works:

- (a) Imported fill should be accompanied by documentation from the supplier which certifies that the material is not contaminated based upon analyses of the material for the known past history of the site where the material is obtained; and/or
- (b) Sampling and analysis of the fill material shall be conducted in accordance with NSW EPA (1995) Sampling Design Guidelines.

# (66) LAND REMEDIATION (Where Site Auditor engaged)

The site is to be remediated and validated in accordance with the Remedial Action Plan prepared by Argus dated 15 January 2018 reference number ES7095-Rev1 and the Letter of Interim Advice or Section B Site Audit Statement prepared by NSW Environment Protection Authority accredited Site Auditor Rebeka Hall of Zoic Environmental PTY LTD dated 17 January 2018 and reference 17188.IA2 17JAN2018\_RAPendorsement. All remediation work carried out shall be conducted in accordance with the guidelines in force from time to time under the Contaminated Land Management Act 1997.

Any new information which comes to light during remediation, demolition or construction works which has the potential to alter previous conclusions about site contamination must be immediately notified to the Council's Area Planning Manager, the Site Auditor and the Principal Certifying Authority.

Any variations to the approved Remediation Action Plan shall be approved in writing by the Site Auditor and Council's Area Planning Manager prior to the commencement of such work.

#### (67) NOTIFICATION - NEW CONTAMINATION EVIDENCE

Any new information which comes to light during remediation, demolition or construction works which has the potential to alter previous conclusions about site contamination and Acid Sulfate Soils shall be notified to the City's Area Planning Manager and the Principal Certifying Authority immediately.

# (68) SITE AUDIT STATEMENT

Prior to the issue of a construction certificate associated with the built form of the development (excluding building work directly related to remediation), a Section A Site Audit Statement must be obtained from a NSW Environment Protection Authority accredited Site Auditor and submitted to the Council's Area Planning Manager at email address:-

# hbapplications@cityofsydney.nsw.gov.au

The Site Audit Statement must confirm that the site has been remediated in accordance with the approved Remedial Action Plan and clearly state that site is suitable for the proposed use.

- (a) In circumstances where the Site Audit Statement is subject to conditions that require ongoing review by the Auditor or Council, these must be reviewed and must be approved by the Council's Health and Building department in writing through the Area Planning Manager before the Site Audit Statement is issued.
- (b) In circumstances where the Site Audit Statement conditions (if applicable) are not consistent with the consent, the development must not proceed until the inconsistency has been resolved to the satisfaction of Council (such as via a S96 modification of the consent pursuant to the provisions of the *Environmental Planning & Assessment Act 1979*).
- (c) <u>No Occupation Certificate is to be issued</u> by the Principal Certifying Authority unless a Site Audit Statement has been submitted to and approved by Council in accordance with this condition.

#### (69) SITE AUDIT STATEMENT – ENVIRONMENTAL MANAGEMENT PLAN

Where the ongoing land use suitability and release of the Final (Section A) Site Audit Statement is dependent upon the implementation of an Environmental Management Plan (EMP) in relation to any residual contamination remaining onsite, the EMP must be approved by the Site Auditor and the City's Area Planning Manager prior to the issue of the final Site Audit Statement.

The owner of the land is required to comply with the ongoing obligations of any EMP which form part of the final Site Audit Statement for the site.

A covenant shall be registered on the title of the land binding the owners and future owners to be responsible for ongoing maintenance and any future rehabilitation works required in terms of the encapsulated/remaining contaminated materials, including the discharge or prevention of discharge from any contaminants or for any works subsequently required by the NSW Environment Protection Authority

A copy of the revised certificate of land title recording the covenant must be submitted to the City's Area Planning Manager and the Principal Certifying Authority prior to the issue of an Occupation Certificate.

# (70) REGISTRATION OF COVENANT

Prior to the issue of an Occupation Certificate, a covenant must be registered on the title of the land and a copy of the title submitted to the Council's Area Planning Manager and the Principal Certifying Authority.

This covenant must be registered on the title of the land binding the owners and future owners with the responsibility for the ongoing maintenance and rehabilitation works required in terms of the encapsulated/remaining contaminated materials, including the discharge or prevention of discharge from any contaminants or for any works subsequently required by the NSW Environment Protection Authority

A copy of the revised certificate of land title recording the covenant must be submitted to the City's Area Planning Manager and the Principal Certifying Authority prior to the issue of an Occupation Certificate.

# (71) STOCKPILES

- (a) No stockpiles of soil or other materials shall be placed on footpaths or nature strips unless prior approval has been obtained from the City's Construction Regulation Unit.
- (b) All stockpiles of soil or other materials shall be placed away from drainage lines, gutters or stormwater pits or inlets.
- (c) All stockpiles of soil or other materials likely to generate dust or odours shall be covered.
- (d) All stockpiles of contaminated soil shall be stored in a secure area and be covered if remaining more than 24 hours

# (72) MECHANICAL VENTILATION

- (a) The premises must be ventilated in accordance with the *Building Code of Australia* and *AS1668.1 and 2 2012. The Use of Ventilation and Air-Conditioning in Buildings Mechanical Ventilation in Buildings.*
- (b) Details of any mechanical ventilation and/or air conditioning system complying with AS1668.1 and 2 2012 The Use of Ventilation and Air-Conditioning in Buildings Mechanical Ventilation in Buildings, the Building Code of Australia and relevant Australian Standards must be prepared by a suitably qualified person and certified in accordance with Clause A2.2 (a) (iii) of the Building Code of Australia, to the satisfaction of the Certifying Authority prior to the issue of a Construction Certificate.
- (c) Prior to issue of an Occupation Certificate and following the completion, installation, and testing of all the mechanical ventilation systems, a Mechanical Ventilation Certificate of Completion and Performance in accordance with Clause A2.2 (a) (iii) of the Building Code of Australia, must be submitted to the Principal Certifying Authority.

# (73) CONTINUED PERFORMANCE OF MECHANICAL VENTILATION

The required operation and performance of any mechanical ventilation, air pressurisation or other smoke control system must not be impaired by the proposed partitioning layout.

# (74) ACCESS AND FACILITIES FOR PERSONS WITH DISABILITIES

The building must be designed and constructed to provide access and facilities for people with a disability in accordance with the *Building Code of Australia*.

If, in complying with this condition, amendments to the development are required, the design changes must be submitted to and approved by Council prior to a Construction Certificate being issued.

# (75) PHYSICAL MODELS

(a) Prior to a final Occupation Certificate being issued, an accurate 1:500 scale model of the development as constructed must be submitted to Council for the City Model in Town Hall House.

#### Note:

- (i) The models must be constructed in accordance with the Model Specifications available online at <a href="http://www.cityofsydney.nsw.gov.au/development/application-guide/application-process/model-requirements">http://www.cityofsydney.nsw.gov.au/development/application-guide/application-process/model-requirements</a> Council's modellers must be consulted prior to construction of the model.
- (ii) The models are to comply with all of the conditions of the Development Consent.
- (iii) The models must be amended to reflect any further modifications to the approval (under Section 4.55 of the *Environmental Planning and Assessment Act*) that affect the external appearance of the building.

# (76) SUBMISSION OF ELECTRONIC CAD MODELS PRIOR TO OCCUPATION CERTIFICATE

- (a) Prior to an Occupation Certificate being issued, an accurate 1:1 electronic CAD model of the completed development must be submitted to Council for the electronic Visualisation City Model.
- (b) The data required to be submitted within the surveyed location must include and identify:
  - (i) building design above and below ground in accordance with the development consent;
  - (ii) all underground services and utilities, underground structures and basements, known archaeological structures and artefacts;
  - (iii) a current two points on the site boundary clearly marked to show their Northing and Easting MGA (Map Grid of Australia) coordinates, which must be based on Established Marks registered in the Department of

Lands and Property Information's SCIMS Database with a Horizontal Position Equal to or better than Class C.

The data is to be submitted as a DGN or DWG file on a Compact Disc. All modelling is to be referenced to the Map Grid of Australia (MGA) spatially located in the Initial Data Extraction file.

(c) The electronic model must be constructed in accordance with the City's 3D CAD electronic model specification. The specification is available online at <a href="http://www.cityofsydney.nsw.gov.au/development/application-guide/application-process/model-requirements">http://www.cityofsydney.nsw.gov.au/development/application-guide/application-process/model-requirements</a> Council's Modelling staff should be consulted prior to creation of the model. The data is to comply with all of the conditions of the Development Consent.

### (77) DILAPIDATION REPORT -EXCAVATION/DEMOLITION

(a) Subject to the receipt of permission of the affected landowner, dilapidation report/s, including a photographic survey of 140-142 McEvoy Street and 9 Bowden Street are to be prepared by an appropriately qualified structural engineer prior to commencement of demolition/excavation works. A copy of the dilapidation report/s together with the accompanying photographs must be given to the above property owners, and a copy lodged with the Principal Certifier and the Council prior to the issue of a Construction Certificate.

# UPON COMPLETION OF EXCAVATION/DEMOLITION

(b) A second Dilapidation Report/s, including a photographic survey must then be submitted at least one month after the completion of demolition/excavation works. A copy of the second dilapidation report/s, together with the accompanying photographs must be given to the above property owners, and a copy lodged with the Principal Certifier and the Council prior to the issue of an Occupation Certificate.

Any damage to buildings, structures, lawns, trees, sheds, gardens and the like must be fully rectified by the applicant or owner, at no cost to the affected property owner.

Note: Prior to the commencement of the building surveys, the applicant/owner must advise (in writing) all property owners of buildings to be surveyed of what the survey will entail and of the process for making a claim regarding property damage. A copy of this information must be submitted to Council.

#### (78) EROSION AND SEDIMENT CONTROL - MORE THAN 2,500SQM

Prior to the commencement of any works on site, including, but not limited to demolition, excavation or construction work, a Soil and Water Management Plan (SWMP) must be submitted to and be approved by the Principal Certifier.

- (a) The SWMP must identify and respond to all items for Erosion and Sediment Control Plans listed in the condition above, as well as:
  - (i) existing site contours;
  - location and diagrammatic representation of all necessary erosion and sediment control systems or structures used to mitigate or prevent pollution to stormwater;

(iii) Location and engineering details with supporting design calculations for all necessary sediment basins, constructed wetlands, gross pollutant traps, trash racks or biofiltration swales (as relevant).

#### (79) ELECTRICITY SUBSTATION

If required by the applicable energy supplier, the owner must dedicate to the applicable energy supplier, free of cost, an area of land within the development site, but not in any landscaped area or in any area visible from the public domain, to enable an electricity substation to be installed. The size and location of the substation is to be submitted for approval of Council and Ausgrid, prior to a Construction Certificate being issued or the commencement of the use, whichever is earlier.

# (80) UTILITY SERVICES

To ensure that utility authorities are advised of the development:

- (a) Prior to the issue of any Construction Certificate a survey is to be carried out of all utility services within and adjacent to the site including relevant information from utility authorities and excavation if necessary, to determine the position and level of services.
- (b) Prior to the commencement of work the applicant is to obtain written approval from the utility authorities (e.g. Energy Australia, Sydney Water, and Telecommunications Carriers) in connection with the relocation and/or adjustment of the services affected by the construction of the underground structure. Any costs in the relocation, adjustment or support of services are to be the responsibility of the developer.

### **SCHEDULE 1C**

#### DURING CONSTRUCTION/PRIOR TO OCCUPATION/COMPLETION

# (81) OCCUPATION CERTIFICATE TO BE SUBMITTED

An Occupation Certificate must be obtained from the Principal Certifier and a copy submitted to Council prior to commencement of occupation or use of the whole or any part of a new building, an altered portion of, or an extension to an existing building.

# (82) DEDICATION OF ROAD WIDENING

The owner must dedicate, for road purposes, free of cost to Council, a 1.4m road widening along the site frontage to McEvoy Street in accordance with the registered Voluntary Planning Agreement (VPA) for the site. The widening is to be detailed in a plan of subdivision of the land which is to be registered at NSW Land Registry Services.

#### (83) ENCROACHMENTS - PUBLIC WAY

No portion of the structure proposed to be constructed, including gates and doors during opening and closing operations, shall encroach upon Council's footpath area. This condition does not apply to the approved architectural embellishments attached to the building overhanging McEvoy Street (as widened).

# (84) SURVEY

All footings, walls and floor slabs adjacent to a boundary must be set out by a registered surveyor. On commencement of brickwork or wall construction a survey and report, prepared by a Registered Surveyor, must be submitted to the Principal Certifying Authority indicating the position of external walls in relation to the boundaries of the allotment. Any encroachments by the subject building over adjoining boundaries or roads must be removed prior to continuation of building construction work.

# (85) SURVEY CERTIFICATE AT COMPLETION

A survey and report, prepared by a Registered Surveyor, must be submitted at the completion of the building work detailing the location of the building in relation to the boundaries of the allotment by offset measurements and confirming whether the new construction work lies completely within the boundaries of the land.

# (86) HOURS OF WORK AND NOISE - OUTSIDE CBD

The hours of construction and work on the development must be as follows:

- (a) All work, including building/demolition and excavation work, and activities in the vicinity of the site generating noise associated with preparation for the commencement of work (eg. loading and unloading of goods, transferring of tools etc) in connection with the proposed development must only be carried out between the hours of 7.30am and 5.30pm on Mondays to Fridays, inclusive, and 7.30am and 3.30pm on Saturdays, with safety inspections being permitted at 7.00am on work days, and no work must be carried out on Sundays or public holidays.
- (b) All work, including demolition, excavation and building work must comply with the City of Sydney Code of Practice for Construction Hours/Noise 1992 and Australian Standard 2436 - 2010 Guide to Noise Control on Construction, Maintenance and Demolition Sites.
- (c) Notwithstanding the above, the use of a crane for special operations, including the delivery of materials, hoisting of plant and equipment and erection and dismantling of on site tower cranes which warrant the on-street use of mobile cranes outside of above hours can occur, subject to a permit being issued by Council under Section 68 of the Local Government Act 1993 and/or Section 138 of the Roads Act 1993.

Note: Works may be undertaken outside of hours, where it is required to avoid the loss of life, damage to property, to prevent environmental harm and/or to avoid structural damage to the building. Written approval must be given by the Construction Regulation Unit, prior to works proceeding

The City of Sydney Code of Practice for Construction Hours/Noise 1992 allows extended working hours subject to the approval of an application in accordance with the Code and under Section 4.55 of the Environmental Planning and Assessment Act 1979.

# (87) LOADING AND UNLOADING DURING CONSTRUCTION

The following requirements apply:

- (a) All loading and unloading associated with construction activity must be accommodated on site, where possible.
- (b) If it is not feasible for loading and unloading to take place on site, a Works Zone on the street may be considered by Council.
- (c) A Works Zone may be required if loading and unloading is not possible on site. If a Works Zone is warranted an application must be made to Council at least 8 weeks prior to the commencement of work on the site. An approval for a Works Zone may be given for a specific period and certain hours of the days to meet the particular need for the site for such facilities at various stages of construction.
- (d) Where hoisting activity over the public place is proposed to be undertaken including hoisting from a Works Zone, a separate approval under Section 68 of the Local Government Act must be obtained.

# (88) NO OBSTRUCTION OF PUBLIC WAY

The public way must not be obstructed by any materials, vehicles, refuse, skips or the like, under any circumstances. Non-compliance with this requirement will result in the issue of a notice by Council to stop all work on site.

# (89) USE OF MOBILE CRANES

The following requirements apply:

- (a) Mobile cranes operating from the road must not be used as a method of demolishing or constructing a building.
- (b) For operations warranting the on-street use of mobile cranes (such as delivery of materials, hoisting of plant/equipment, erection and dismantling of onsite tower cranes, etc), permits must be obtained from Council for the use of a mobile crane. The permits must be obtained 48 hours beforehand for partial road closures which, in the opinion of Council will create minimal traffic disruptions and 4 weeks beforehand in the case of full road closures and partial road closures which, in the opinion of Council, will create significant traffic disruptions.
- (c) Special operations and the use of mobile cranes must comply with the approved hours of construction. Mobile cranes must not be delivered to the site prior to 7.30am without the prior approval of Council.

# (90) NOTIFICATION OF EXCAVATION WORKS OR USE OF HIGH NOISE EMISSION APPLIANCES/PLANT

The immediately adjoining neighbours must be given a minimum of 48 hours notice that excavation, shoring or underpinning works or use of high noise emission appliances / plant are about to commence.

# (91) SITE NOTICE OF PROJECTS DETAILS AND APPROVALS

A site notice is to be prominently displayed at the boundary to each frontage of the site for the purposes of informing the public of appropriate project details and relevant approvals. The notice(s) is to satisfy all of the following requirements:

- (a) Minimum dimensions of the notice are to measure 841mm x 594mm (A1) with any text on the notice to be a minimum of 30 point type size;
- (b) The notice is to be durable and weatherproof and is to be displayed throughout the construction period;
- (c) A copy of the first page of the development approval, building approval (including any modifications to those approvals) and any civic works approvals is to be posted alongside the notice in weatherproof casing;
- (d) The approved hours of work, the Principal Certifying Authority including contact address and certification details, the name of the site manager, the responsible managing company, its address and 24 hour contact phone number for any enquiries, including construction/noise complaint, and the estimated date of completion of the project are to be displayed on the site notice;
- (e) The notice(s) is to be mounted at eye level on the perimeter hoardings and is also to state that unauthorised entry to the site is not permitted.
- (f) All notices and signs must be displayed in locations as specified in the City's Guidelines for Hoardings and Scaffolding.

### (92) USE OF HIGH NOISE EMISSION APPLIANCES / PLANT

- (a) The operation of high noise emission appliances, plant and/or machinery such as pile – drivers, rock breakers and hydraulic hammers and those which are not listed in Groups B, C, D, E or F of Schedule 1 of the City of Sydney Code of Practice for Construction Hours/Noise 1992 and Australian Standard 2436-2010 Guide to Noise Control on Construction, Maintenance and Demolition Sites is restricted to the hours of 9am to 12.30pm and 2pm to 4.30pm Mondays to Fridays and between 9am and 1.30pm Saturdays
- (b) All reasonable and feasible steps must be undertaken to ensure that the work, including demolition, excavation and building complies with the *City* of Sydney Code of Practice for Construction Hours/Noise 1992 and Australian Standard 2436- 2010 Guide to Noise Control on Construction, Maintenance and Demolition Sites.

#### (93) LIGHTING OF SITE OUTSIDE OF STANDARD CONSTRUCTION HOURS

Lighting of the site while any work is undertaken outside of Council's standard hours of construction must ensure that at no time must the intensity, hours of illumination or location of the lighting cause objectionable glare or injury to the amenity of the neighbourhood or Obtrusive Light in accordance with the definition in Australian Standard AS4282-1997 *Control of the obtrusive effects of outdoor lighting.* If in the opinion of Council, injury is likely to be caused, the intensity, hours of illumination and location of the lighting must be varied so that it does not cause injury to nearby residents.

# (94) COVERING OF LOADS

All vehicles involved in the excavation and/or demolition process and departing the property with demolition materials, spoil or loose matter must have their loads fully covered before entering the public roadway.

# (95) EROSION AND SEDIMENT CONTROL

The Soil and Water Management Plan (SWMP) or Erosion and Sediment Control Plan (ESCP) which has been approved by the Principal Certifier must be implemented in full during the construction period.

During the construction period;

- erosion and sediment controls must be regularly inspected, repaired and maintained in working order sufficient for a 10 year Average Recurrence Interval (ARI) rainfall event;
- (b) erosion and sediment control signage available from Council must be completed and attached to the most prominent structure visible at all times when entering the site for the duration of construction; and
- (c) building operations and stockpiles must not be located on the public footway or any other locations which could lead to the discharge of materials into the stormwater system.

# (96) VEHICLE CLEANSING

Prior to the commencement of work, suitable measures are to be implemented to ensure that sediment and other materials are not tracked onto the roadway by vehicles leaving the site. It is an offence to allow, permit or cause materials to pollute or be placed in a position from which they may pollute waters.

#### (97) STREET NUMBERING - MAJOR DEVELOPMENT

Prior to an Occupation Certificate being issued, street numbers and the building name must be clearly displayed at either end of the ground level frontage in accordance with the *Policy on Numbering of Premises within the City of Sydney*. If new street numbers or a change to street numbers is required, a separate application must be made to Council.

# **SCHEDULE 2**

# PRESCRIBED CONDITIONS

The prescribed conditions in accordance with Division 8A of the *Environmental Planning and Assessment Regulation 2000* apply:

| Clause 98  | Compliance with <i>Building Code of Australia</i> and insurance requirements under the <i>Home Building Act 1989</i> |
|------------|--|
| Clause 98A | Erection of signs  |
| Clause 98B | Notification of Home Building Act 1989 requirements  |
| Clause 98C | Conditions relating to entertainment venues  |
| Clause 98D | Conditions relating to maximum capacity signage  |
| Clause 98E | Conditions relating to shoring and adequacy of adjoining property  |

Refer to the NSW State legislation for full text of the clauses under Division 8A of the *Environmental Planning and Assessment Regulation 2000*. This can be accessed at: <a href="http://www.legislation.nsw.gov.au">http://www.legislation.nsw.gov.au</a>

#### **SCHEDULE 3**

The following are concurrence conditions of the Roads and Maritime Services under clause 104 of SEPP (Infrastructure) 2007:

# (98) ROADS AND MARITIME SERVICES CONDITIONS

(a) The design and construction of the kerb and gutter on McEvoy Street shall be in accordance with Roads and Maritime requirements. Details of these requirements should be obtained from Roads and Maritime Services, Manager Developer Works, Statewide Delivery, Parramatta (telephone 8849 2138).

Detailed design plans of the proposed gutter crossing are to be submitted to Roads and Maritime for approval prior to the issue of a Construction Certificate and commencement of any road works.

A plan checking fee (amount to be advised) and lodgement of a performance bond may be required from the applicant prior to the release of the approved road design plans by Roads and Maritime.

- (b) The proposed driveway on McEvoy Street for the proposed development is to be used for egress only.
- (c) Detailed design plans and hydraulic calculations of any changes to the stormwater drainage systems in McEvoy Street are to be submitted to Roads and Maritime for approval, prior to the commencement of any works.

Details should be forwarded to: suppiah.thillai@rms.nsw.gov.au

A plan checking fee will be payable and a performance bond may be required before Roads and Maritime approval is issued. With regard to the Civil Works requirement please contact the Roads and Maritime Project Engineer, External Works Ph: 8849 2114 or Fax: 8849 2766.

(d) The developer is to submit design drawings and documents relating to the excavation of the site and support structures to Roads and Maritime for assessment, in accordance with Technical Direction GTD2012/001.

The developer is to submit all documentation at least six (6) weeks prior to commencement of construction and is to meet the full cost of the assessment by Roads and Maritime.

Details should be forwarded to: suppiah.thillai@rms.nsw.gov.au

If it is necessary to excavate below the level of the base of the footings of the adjoining roadways, the person acting on the consent shall ensure that the owner/s of the roadway is/are given at least seven (7) day notice of the intention to excavate below the base of the footings. The notice is to include complete details of the work.

(e) A Construction Traffic Management Plan detailing construction vehicle routes, number of trucks, hours of operation, access arrangements and traffic control should be submitted to Council for approval prior to the issue of a Construction Certificate.

- (f) All demolition and construction vehicles are to be contained wholly within the site (or on Bowden Street) and vehicles must enter the site before stopping. A construction zone will not be permitted on McEvoy Street.
- (g) A Road Occupancy Licence should be obtained from Transport Management Centre for any works that may impact on traffic flows on McEvoy Street during construction activities.
- (h) The swept path of the longest vehicle (to service the site) entering and exiting the subject site, as well as manoeuvrability through the site, shall be accordance with AUSTROADS. In this regard, a plan shall be submitted to Council and Roads and Maritime for approval, which shows that the proposed development complies with this requirement.
- (i) The developer shall be responsible for all public utility adjustment/relocation works, necessitated by the above work and as required by the various public utility authorities and/or their agents

#### IMPORTANT ADDITIONAL INFORMATION

**Advisory note**: The State Government has commenced planning for the construction of the CBD South East Light Rail (CSELR). You may need to consider the potential impacts of this project in programming your development. The CSELR route includes Alfred St, George St, Rawson Place, Eddy Ave, Chalmers St, and Devonshire St. For construction and programming information contact the Transport for NSW Infoline on 1800 684 490 or www.transport.nsw.gov.au/projects.

#### The Environmental Planning and Assessment Act 1979 requires you to:

- Obtain a Construction Certificate prior to the commencement of any works. An application may be lodged with Council, or you may apply to a private accredited certifier for a Construction Certificate. An accredited certifier must obtain Council's approval to certain conditions of this development consent, where indicated before issuing the Construction Certificate.
- 2. Note: it is compulsory to lodge digital copies of applications, including plans and documentation if lodging an application with Council. Please refer to the link below for any further information about digital requirements and electronic files.
  - http://www.cityofsydney.nsw.gov.au/development/application-guide/application-process/digital-requirements.
- 3. Nominate a *Principal Certifier* which may be either Council or an accredited certifier and notify Council of that appointment. You **cannot lawfully** commence works without complying with this requirement.
- 4. Give Council at least two days notice of your intention to commence the erection of a building **before** commencing construction works. You cannot lawfully commence works without complying with this requirement.
- 5. Obtain an *Occupation Certificate* before commencing occupation or commencing to use the building or on the completion of other works including the erection of a sign. You cannot lawfully commence occupation or the use of a building without complying with this requirement.

# You may also need to:

- 6. Obtain approval through the lodgement of an application under Section 68 of the *Local Government Act 1993* and Section 138 of the *Roads Act 1993* for an activity which is proposed to be undertaken in, on or above a road reservation (including footways). Such activities include:
  - (a) installation of hoardings/scaffolding;
  - (b) installation and/or alterations to advertising/business signs and street awnings;
  - (c) crane operation and other hoisting activities;
  - (d) temporary works (e.g.: barricading, road openings, mobile hoisting devices);
  - (e) works zone (for loading and unloading from the roadway); and
  - (f) temporary ground anchoring and shoring to support a roadway when excavating.

Application forms are available on the City's website.

- 7. Lodge an *Application for Subdivision* to obtain a *Subdivision Certificate* if a land (including stratum) subdivision is proposed and an Application for Subdivision to obtain *Strata Title Subdivision* under the relevant Strata Titles Act, if strata title of the development is proposed.
- 8. Comply with the Food Act 2003, the Australia New Zealand Food Standards Code, Australian Standard 4674 2004, and register the business with Council if the premises is used for the manufacture, preparation, packing, storing, conveying or delivering of food or beverage for sale.
- 9. Contact Sydney Water regarding the water and sewerage services to this development. For further information go to www.sydneywater.com.au.
- 10. Carry out critical stage inspections in accordance with Section 6.5 of the EP&A Act 1979 and clauses 162A, 162B and 163 of the EP&A Regulation 2000.

Applications and submissions referred to in this consent may be lodged at:

CBD Level 2, Town Hall House, 456 Kent St, Sydney.

KINGS CROSS 50-52 Darlinghurst Rd, Kings Cross.

GLEBE Customer Service Centre, 186 Glebe Point Rd, Glebe.

If you have any enquiries on any aspect of this consent, contact Thomas Irons ph. 02 9265 9438, email tirons@cityofsydney.nsw.gov.au.