

# **Attachment A**

<b>Recommended Conditions of Consent</b>
--

## CONDITIONS OF CONSENT

### SCHEDULE 1A

#### APPROVED DEVELOPMENT/DESIGN MODIFICATIONS/COVENANTS AND CONTRIBUTIONS/USE AND OPERATION

**Note:** Some conditions in Schedule 1A are to be satisfied prior to issue of a Construction Certificate and some are to be satisfied prior to issue of Occupation Certificate, where indicated.

#### (1) APPROVED DEVELOPMENT

- (a) Development must be in accordance with Development Application No. D/2017/1650 dated 28 November 2017 and the following drawings prepared by The Buchan Group:

Drawing Number	Drawing Name	Date
DA-002 Rev 03	Existing Floor Plan- Lower Ground	25 May 2018
DA-003 Rev 03	Existing Floor Plan – Upper Ground	25 May 2018
DA-004 Rev 03	Existing Floor Plan – Level 1	25 May 2018
DA-005 Rev 03	Existing Floor Plan – Level 2	25 May 2018
DA-006 Rev 02	Existing Roof Plan	24 November 2017
DA-007 Rev 03	Existing Elevation – South	25 May 2018
DA-008 Rev 03	Existing Elevation - North	13 June 2018
DA-010 Rev 04	Proposed Floor Plan - Lower Ground	8 August 2018
DA-011 Rev 05	Proposed Floor Plan –Ground	13 August 2018
DA-012 Rev 04	Proposed Floor Plan – Level 1	8 August 2018
DA-013 Rev 04	Proposed Floor Plan – Level 2	8 August 2018
DA-014 Rev 07	Proposed Floor Plan – Level 3	10 September 2018
DA-016 Rev 06	Proposed Roof Plan	13 August 2018
DA-017 Rev 02	Proposed Plant Deck Screening Roof Plan	13 August 2018
DA-020 Rev 05	Proposed Elevation (South)	8 August 2018

Drawing Number	Drawing Name	Date
DA-021 Rev 05	Proposed Elevation (North)	8 August 2018
DA-030 Rev 05	Proposed Section A	13 August 2018
DA-031 Rev 07	Proposed Section B	10 September 2018
DA-050 Rev 04	Material and Finishes	8 August 2018
DA-070 Rev 03	Signage	25 May 2018

and as amended by the conditions of this consent.

- (b) In the event of any inconsistency between the approved plans and supplementary documentation, the plans will prevail.

## (2) DESIGN MODIFICATIONS

The design of the building must be modified as follows:

- (a) A minimum of 10 visitor bicycle parking spaces are to be provided inside the ground floor lobby.
- (b) The northern roof to level 2 is to be Colorbond Spandek roof sheeting and be non-trafficable.
- (c) A detailed architectural design and treatment of the refurbishment works to the Greek Street ground level facade, specifically the replacement of the existing louvres, is to be provided. The louvres are to be replaced with artistic high quality screening treatment that creates visual interest at ground level. The signage of the services is to be integrated into the facade treatment appropriately.
- (d) Details of the contents to the projecting wall sign are required. The colours and design are to be appropriate to the streetscape.

Amended plans incorporating modifications (a)-(d) above are to be submitted to and approved by Council's Area Planning Manager prior to the issue of any Construction Certificate.

## (3) FLOOR SPACE RATIO

The following applies to Floor Space Ratio:

- (a) The Floor Space Ratio for the entire building must not exceed 3.27:1 calculated in accordance with Sydney Local Environmental Plan 2012. For the purposes of the calculation of FSR, the Gross Floor Area of the building is 3,891sqm.
- (b) Prior to an Occupation Certificate being issued, a Registered Surveyor must provide certification of the total and component Gross Floor Areas (by use)

in the building, utilising the definition under Sydney Local Environmental Plan 2012, applicable at the time of development consent, to the satisfaction of the Principal Certifier.

**(4) HOURS OF OPERATION OF EXTERNAL TERRACE**

The hours of operation of the external terrace are restricted to between 7.00am to 10.00pm, Monday to Sunday.

**(5) ASSOCIATED ROADWAY COSTS**

All costs associated with the construction of any new road works including kerb and gutter, road pavement, drainage system and footway shall be borne by the developer. The new road works must be designed and constructed in accordance with the City's "Sydney Streets Technical Specification" including amendments and "Sydney Streets Design Code".

**(6) CAR PARKING LAYOUT AND DESIGN**

The design, layout, signage, line marking, lighting and physical controls of all off-street car parking facilities must comply with the *Australian Standard AS/NZS 2890.1 - 2004 Parking facilities Part 1: Off-street car parking*. The details must be submitted to and approved by the Certifying Authority prior to a Construction Certificate being issued.

**(7) BICYCLE PARKING**

The layout, access and security of bicycle parking facilities must comply with *Australian Standard AS 2890.3:2015 Parking Facilities Part 3: Bicycle Parking Facilities*. To protect the bicycle parking area adjacent to the lobby from reversing car movements, a physical separator is to be installed in compliance with access requirements in the *Australian Standard AS 2890.3:2015 Parking Facilities Part 3: Bicycle Parking Facilities*.

The details must be submitted to and approved by the Certifying Authority or Council confirming prior to the Construction Certificate being issued.

**(8) CHANGES TO KERB SIDE CAR PARKING RESTRICTIONS**

A separate submission must be made for any changes to kerbside parking arrangements. There is no guarantee kerbside parking will be changed or that any change will remain in place for the duration of the development/use.

All costs associated with any parking changes would be borne by the developer.

Note: The applicant is to contact the Area Traffic Engineer to discuss the proposal before making a submission.

**(9) COST OF SIGNPOSTING**

All costs associated with signposting of any kerbside parking restrictions and traffic management measures associated with the development shall be borne by the developer.

**(10) ON-SITE LOADING OPERATION**

All loading and unloading associated with the site must be carried out within the site at all times and must not obstruct other properties/units or the public way.

At all times the service vehicle docks, car parking spaces and access driveways must be kept clear of goods and must not be used for storage purposes, including garbage storage.

**(11) VEHICLE FOOTWAY CROSSING**

A separate application is to be made to, and approved by, Council for the construction of any proposed vehicle footway crossing or for the removal of any existing crossing and replacement of the footpath formation where any such crossings are no longer required.

All disused or redundant vehicle crossings and laybacks must be removed and footway, kerb, gutter and road restoration reinstated in accordance with Council's standards, to suit the adjacent finished footway and edge treatment materials, levels and details, or as otherwise directed by Council officers. All construction and replacement works are to be completed in accordance with the approved plans prior to the issue of an Occupation Certificate.

Note: In all cases the construction materials should reinforce the priority of pedestrian movement over that of the crossing vehicle.

**(12) CONTRIBUTION TOWARDS PUBLIC AMENITIES – CITY OF SYDNEY DEVELOPMENT CONTRIBUTIONS PLAN 2015 – WEST PRECINCT**

Council has identified the development will increase demand for public amenities and facilities. Pursuant to Section 7.11 of the Environmental Planning and Assessment Act, 1979 (as amended), and the City of Sydney Development Contributions Plan 2015 the following monetary contributions are required towards the cost of public amenities.

<u>Contribution Category</u>	<u>Amount</u>
Open Space	\$6,241.15
Community Facilities	\$1,606.02
Traffic and Transport	\$80.30
Stormwater Drainage	\$0.00
Total	\$7,927.47

The City of Sydney will index the above contribution for inflation at the time of payment using the following formula.

$$C_{\text{payment}} = C_{\text{consent}} \times (CPI_{\text{payment}} \div CPI_{\text{consent}})$$

Where:

$$C_{\text{payment}} = \text{Is the contribution at time of payment;}$$

- Cconsent = Is the contribution at the time of consent, as shown above;
- CPIpayment = Is the Consumer Price Index (All Groups Index) for Sydney published by the Australian Bureau of Statistics that applies at the time of payment; and
- CPI1consent = Is the Consumer Price Index (All Groups Index) for Sydney at the date the contribution amount above was calculated being – 114.0 for the June 2018.

The contribution must be paid prior to the issue of any Construction Certificate in relation to this development.

Please contact Council's Planning Administration staff at [planningsystemsadmin@cityofsydney.nsw.gov.au](mailto:planningsystemsadmin@cityofsydney.nsw.gov.au) to request a letter confirming the indexed contribution amount payable.

Once the letter confirming the indexed contribution is obtained, payment may be made at any of the City's Neighbourhood Service Centres or the One Stop Shop at Town Hall House. Acceptable payment methods are EFTPOS (debit card only), cash or a bank cheque made payable to the City of Sydney. Personal or company cheques will not be accepted.

### (13) NOISE - GENERAL

- (a) The emission of noise associated with the use of the premises including the cumulative operation of any mechanical plant and equipment, and air conditioning shall comply with the following:
- (i) The  $L_{Aeq, 15 \text{ minute}}$  noise level emitted from the use must not exceed the project specific noise level for that receiver as determined in accordance with the *NSW EPA Industrial Noise Policy*. Noise must be measured in accordance with the Industrial Noise Policy and relevant requirements of Australian Standard AS 1055-1997 Acoustics – Description and measurement of environmental noise.
  - (ii) Project specific noise levels shall be determined by establishing the existing environmental noise levels, in complete accordance with the assessment  $L_{A90, 15 \text{ minute}}$  / rating  $L_{A90, 15 \text{ minute}}$  process to be in accordance with the requirements for noise monitoring listed in the *NSW EPA Industrial Noise Policy* and relevant requirements of Australian Standard AS1055-1997 Standard AS 1055-1997 Acoustics – Description and measurement of environmental noise.
  - (iii) Modifying factors in Table 4.1 of the *NSW EPA Industrial Noise Policy* are applicable.
- (b) An  $L_{Aeq, 15 \text{ minute}}$  noise level emitted from the use must not exceed the  $L_{A90, 15 \text{ minute}}$  noise level by more than 3dB in any Octave Band Centre Frequency (31.5 Hz to 8 kHz inclusive) when assessed inside any habitable room of any affected residence or noise sensitive commercial premises provided that;
- (i) Where the  $L_{A90, 15 \text{ minute}}$  noise level is below the threshold of hearing, Tf at any Octave Band Centre Frequency as defined in Table 1 of

International Standard ISO 226 : 2003- Normal Equal-Loudness-Level Contours then the value of Tf corresponding to that Octave Band Centre Frequency shall be used instead.

- (ii) The  $L_{Aeq,15\text{ minute}}$  noise level and the  $L_{A90,15\text{ minute}}$  noise level shall both be measured with all external doors and windows of the affected residence closed;
- (iii) The relevant background noise level ( $L_{A90,15\text{ minute}}$ ) is taken to mean the day, evening or night rating background noise level determined in complete accordance with the methodology outlined in the *NSW EPA Industrial Noise Policy* and Australian Standard AS1055.1997 Acoustics – Description and measurement of environmental noise.
- (iv) Background noise shall be established in the absence of all noise emitted from the use but with the ventilation equipment normally servicing the affected residence operating. Background noise measurements are to be representative of the environmental noise levels at the affected location.
- (v) Modifying factors in Table 4.1 of the *NSW EPA Industrial Noise Policy* are applicable. Internal Noise measurements are not to be corrected for duration.

**(14) COMPLIANCE WITH THE ACOUSTIC REPORT PRIOR TO CONSTRUCTION AND OR OCCUPATION CERTIFICATES**

- (a) All performance parameters, requirements, engineering assumptions and recommendations contained in the acoustic report prepared by PKA ACOUSITC CONSULTING, dated 20 November 2017, ref ID: 11032 R01v1, titled DA ACOUSTIC REPORT 19-37 Greek Street, Council Ref 2018/392764 must be implemented as part of the detailed design assessment and implemented into the design drawings prior to the commencement of the use of the premises in accordance with the requirements of below and to the satisfaction of the Principal Certifier.
- (b) Prior to the issue of an Occupation Certificate, a suitable qualified acoustic consultant is to provide a written Acoustic Verification Report to the satisfaction of the Principal Certifier that the development complies with the requirements set out in the Report and in (a) and (b) above.

Note: Suitably qualified Acoustic Consultant means a consultant who possesses the qualifications to render them eligible for membership of the Australian Acoustics Society, Institution of Engineers Australia or the Association of Australian Acoustic Consultants at the grade of member.

**(15) SIGN ILLUMINATION**

- (a) At no time is the intensity, period of intermittency and hours of illumination of the sign to cause objectionable glare or injury to the amenity of the neighbourhood and as such must be designed, installed and used in accordance with AS4282-1997 Control of Obtrusive Effects of Outdoor Lighting.

- (b) The projecting wall sign must not flash. Signs with flashing, chasing, pulsating or flickering lights are not permitted.
- (c) The maximum night time luminance of any sign is not to exceed 300 cd/sqm.
- (d) Signage is only permitted to be illuminated to 7.00am to 10.00pm, Monday to Sunday.
- (e) Upward facing light sources onto the signage is not permitted.

**(16) SIGNAGE GENERAL REQUIREMENTS**

The design of the approved signage must comply with the following:-

- (a) The signage is not to contain reflective materials, colours and finishes.
- (b) The signage is not to incorporate sound, vibration, odour and other emissions.
- (c) The signage is to not have a white background



## SCHEDULE 1B

### PRIOR TO CONSTRUCTION CERTIFICATE/COMMENCEMENT OF WORK/HEALTH AND BUILDING

#### (17) ASBESTOS REMOVAL WORKS

- (a) All works removing asbestos containing materials must be carried out by a suitably licensed asbestos removalist duly licensed with Workcover NSW, holding either a Friable (Class A) or a Non- Friable (Class B) Asbestos Removal Licence which ever applies.
- (b) Five days prior to the commencement of licensed asbestos removal, Workcover must be formally notified of the works. All adjoining properties and those opposite the development must be notified in writing of the dates and times when asbestos removal is to be conducted. The notification is to identify the licensed asbestos removal contractor and include a contact person for the site together with telephone number and email address.
- (c) All works must be carried out in accordance with the *Work Health and Safety Regulation 2011* and the NSW Government and Workcover document entitled *How to manage and control asbestos in the work place: Code of Practice (NSW WorkCover)* and the *City of Sydney Managing Asbestos Policy*.
- (d) The asbestos removalist must use signs and barricades to clearly indicate the area where the asbestos removal work is being performed. Signs must be placed in positions so that people are aware of where the asbestos removal work area is and should remain in place until removal is completed and clearance to reoccupy has been granted. Responsibilities for the security and safety of the asbestos removal site and removal work area should be specified in the asbestos removal control plan (where required). This includes inaccessible areas that are likely to contain asbestos.
- (e) Warning signs must be placed so they inform all people nearby that asbestos removal work is taking place in the area. Signs should be placed at all of the main entry points to the asbestos removal work area where asbestos is present. These signs should be weatherproof, constructed of light-weight material and adequately secured so they remain in prominent locations. The signs should be in accordance with AS 1319-1994 Safety signs for the occupational environment for size, illumination, location and maintenance.
- (f) Asbestos to be disposed of must only be transported to waste facilities licensed to accept asbestos. The names and location of these facilities are listed in Appendix F of the City of Sydney's Managing Asbestos Guidelines.
- (g) No asbestos products are to be reused on the site (i.e. packing pieces, spacers, formwork or fill etc).
- (h) No asbestos laden skips or bins are to be left in any public place without the approval of Council.

- (l) A site notice board must be located at the main entrance to the site in a prominent position and must have minimum dimensions of 841mm x 594mm (A1) with any text on the notice to be a minimum of 30 point type size.

The site notice board must include the following:

- (i) contact person for the site;
- (ii) telephone and facsimile numbers and email address; and
- (iii) site activities and time frames.

#### **(18) ALIGNMENT LEVELS – MAJOR DEVELOPMENT**

- (a) Proposed building floor levels, basement levels, basement car park entry levels and ground levels shown on the approved Development Application plans are indicative only and have not been approved by this consent.
- (b) Prior to a Construction Certificate being issued for any excavation, civil construction, drainage or building work (whichever is earlier), excluding approved preparatory or demolition work, alignment levels for the building and site frontages must be submitted to and approved by Council. The submission must be prepared by a Registered Surveyor and designed by a suitably qualified engineer, must be in accordance with the City of Sydney's *Public Domain Manual* and must be submitted with a completed Levels and Gradients Approval Application form (available on the City's website).
- (c) These alignment levels, as approved by Council, are to be incorporated into the plans submitted with the application for a Construction Certificate for any civil, drainage and public domain work as applicable under this consent. If the proposed detailed design of the public domain requires changes to any previously approved Alignment Levels, then an amended Alignment Levels submission must be submitted to and approved by Council to reflect these changes prior to a Construction Certificate being issued for public domain work.

#### **(19) ACCESS FOR PERSONS WITH DISABILITIES - OFFICE FITOUTS**

In accordance with the *Building Code of Australia* the proposed office layout and design must comply with Australian Standard 1428.1: General requirements for access - New building works.

#### **(20) PHOTOGRAPHIC RECORD / DILAPIDATION REPORT - PUBLIC DOMAIN**

Prior to an approval for demolition being granted or a Construction Certificate being issued, whichever is earlier, a photographic recording of the public domain site frontages is to be prepared and submitted to Council's satisfaction.

The recording must include clear images of the building facade adjoining the footpath, the footpath, nature strip, kerb and gutter, driveway crossovers and laybacks, kerb ramps, road carriageway, street trees and plantings, parking restriction and traffic signs, and all other existing infrastructure along the street.

The form of the recording is to be as follows:-

- (a) A PDF format report containing all images at a scale that clearly demonstrates the existing site conditions;
- (b) Each image is to be labelled to identify the elements depicted, the direction that the image is viewed towards, and include the name of the relevant street frontage;
- (c) Each image is to be numbered and cross referenced to a site location plan;
- (d) A summary report, prepared by a suitable qualified professional, must be submitted in conjunction with the images detailing the project description, identifying any apparent existing defects, detailing the date and authorship of the photographic record, the method of documentation and limitations of the photographic record;
- (e) Include written confirmation, issued with the authority of both the applicant and the photographer that the City of Sydney is granted a perpetual non-exclusive license to make use of the copyright in all images supplied, including the right to make copies available to third parties as though they were Council images. The signatures of both the applicant and the photographer must be included.

Any damage to the public way including trees, footpaths, kerbs, gutters, road carriageway and the like must immediately be made safe and functional by the applicant. Damage must be fully rectified by the applicant in accordance with the City's standards prior to a Certificate of Completion being issued for Public Domain Works or before an Occupation Certificate is issued for the development, whichever is earlier.

## **(21) PUBLIC DOMAIN DAMAGE DEPOSIT**

A Public Domain Damage Deposit calculated on the basis of 46 lineal metres of concrete paving site frontage must be lodged with Council in accordance with the City of Sydney's adopted Schedule of Fees and Charges. The Public Domain Damage Deposit must be submitted as an unconditional bank guarantee in favour of Council as security for repairing any damage to the public domain in the vicinity of the site.

The guarantee must be lodged with Council prior to an approval for demolition being granted or a Construction Certificate being issued, whichever is earlier.

The Bank Guarantee will be retained in full until the final Occupation Certificate has been issued and any rectification works to the footway and Public Domain are completed to Council's satisfaction. On satisfying the above requirements 90% of the total securities will be released, with the remaining 10% to be retained for the duration of the 12 months Defect Liability Period.

## **(22) PRESERVATION OF SURVEY MARKS**

All works in City streets must ensure the preservation of existing permanent survey marks (a brass bolt, or a lead plug holding a brass tack, covered by a cast iron box). At least forty-eight hours prior to the commencement of any works in the public way within 1 metre of a permanent survey mark contact must be made with the City's Project Manager Survey / Design Services to arrange for the recovery of the mark.

Prior to the issue of a Construction Certificate, a survey plan, clearly showing the location of all permanent survey marks fronting the site and within 5 metres on each side of the frontages must be submitted to Council.

At least forty-eight hours prior to the commencement of any works in the public way within 1 metre of a permanent survey mark contact must be made with the City's Senior Surveyor to arrange for the recovery of the mark.

A fee must be paid to the Council for the replacement of any permanent survey mark removed or damaged in accordance with the City's Schedule of Fees and Charges (Reinstatement of Survey Box).

### **(23) PROTECTION OF SURVEY INFRASTRUCTURE**

Prior to the commencement of any work on site, a statement prepared by a Surveyor registered under the *Surveying Act 2002* must be submitted to Council verifying that a survey has been carried out in accordance with the Surveyor General's Direction No. 11 – Reservation of Survey Infrastructure. Any Permanent Marks proposed to be or have been destroyed must be replaced, and a "Plan of Survey Information" must be lodged at the Land and Property Management Authority.

Reason: To ensure that the survey control infrastructure and cadastral framework are preserved for the public benefit and in accordance with the *Surveying Act 2002*.

### **(24) PUBLIC DOMAIN PLAN**

- (a) A detailed Public Domain Plan must be prepared by a suitably qualified architect, urban designer, landscape architect or engineer and must be lodged with Council's Public Domain Section and be approved by Council prior to a Construction Certificate being issued for public domain work or above ground building work, whichever is later.
- (b) The Public Domain Plan must document all works required to ensure that the public domain complies with the City of Sydney's *Public Domain Manual*, *Sydney Streets Code* and *Sydney Streets Technical Specification*, including requirements for road pavement, traffic measures, footway pavement, kerb and gutter, drainage, vehicle crossovers, pedestrian ramps, lighting, street trees and landscaping, signage and other public domain elements. If an Alignment Levels condition applies to the development, the Public Domain Plan submission must incorporate the approved Alignment Levels. If the proposed detailed design of the public domain requires changes to any previously approved Alignment Levels, then an amended Alignment Levels submission must be submitted to and approved by Council to reflect these changes prior to a Construction Certificate being issued for public domain work.
- (c) The works to the public domain are to be completed in accordance with the approved Public Domain Plan and Alignment Levels plans and the *Public Domain Manual* before any Occupation Certificate is issued in respect of the development or before the use commences, whichever is earlier.
- (d) A Public Domain Works Deposit will be required for the public domain works, in accordance with the City of Sydney's adopted fees and charges and the

*Public Domain Manual*. The Public Domain Works Deposit must be submitted as an unconditional bank guarantee in favour of Council as security for completion of the obligations under this consent.

- (e) Council's Public Domain section must be contacted to determine the guarantee amount prior to lodgement of the guarantee. The guarantee must be lodged with Council prior to a Construction Certificate being issued.
- (f) The Bank Guarantee will be retained in full until all Public Domain works are completed and the required certifications, warranties and works-as-executed documentation are submitted and approved by Council in writing. On satisfying the above requirements, 90% of the total securities will be released. The remaining 10% will be retained for the duration of the specified Defects Liability Period.

#### **(25) PUBLIC DOMAIN WORKS - HOLD POINTS AND HANDOVER**

- (a) Prior to a Construction Certificate being issued for public domain work, including civil, drainage and subsurface works, , a set of hold points for approved public domain, civil and drainage work is to be determined with and approved by the City's Public Domain section in accordance with the City of Sydney's *Public Domain Manual* and *Sydney Streets Technical Specification*.
- (b) Prior to a Certificate of Completion being issued for public domain works and before the issue of any Occupation Certificate for the development or before the use commences, whichever is earlier, electronic works-as-executed (as-built) plans and documentation, certified by a suitably qualified, independent professional must be submitted to and accepted by Council for all public domain works. Completion and handover of the constructed public domain works must be undertaken in accordance with the City of Sydney's *Public Domain Manual* and *Sydney Streets Technical Specification*, including requirements for as-built documentation, certification, warranties and the defects liability period.

#### **(26) STORMWATER AND DRAINAGE - MINOR DEVELOPMENT**

The drainage system is to be constructed in accordance with the City's standard requirements as detailed in the City of Sydney's Stormwater Drainage Manual, as amended from time to time.

The development is to be designed so that the flow of pollutants from the site due to stormwater is reduced.

#### **(27) DEFECTS LIABILITY PERIOD – PUBLIC DOMAIN WORKS**

All works to the City's public domain, including rectification of identified defects, are subject to a 12 month defects liability period from the date of final completion. The date of final completion will be nominated by Council on the Certificate of Completion for public domain works.

#### **(28) DRAINAGE AND SERVICE PIT LIDS**

Drainage and service pit lids throughout the public domain shall be heel guard and bicycle safe, finish flush with the adjacent pavement to avoid trip hazards and be

clear of obstructions for easy opening and cleaning. Pit lids shall be in accordance with the *City of Sydney's Sydney Streets Design Code* and *Sydney Streets Technical Specification*. Details of drainage and service pit lids shall be submitted and approved by Council prior to a Construction Certificate being issued for the relevant stage of work.

**(29) TACTILE GROUND SURFACE INDICATORS AND HANDRAILS**

All tactile ground surface indicators, handrails and other elements required to provide access into the building / property must be located entirely within the private property boundary.

**(30) FLOOD PLANNING LEVELS REQUIREMENT**

All openings to the building shall be no less than 0.3m above the surrounding gutter invert at the Street frontage.

**(31) WASTE AND RECYCLING COLLECTION CONTRACT**

Prior to an Occupation Certificate being issued and/or commencement of the use, whichever is earlier, the building owner must ensure that there is a contract with a licensed contractor for the removal of **all waste**. No garbage is to be placed on the public way, e.g. footpaths, roadways, plazas, reserves, at any time.

**(32) WASTE AND RECYCLING MANAGEMENT - COMMERCIAL**

- (a) The Waste Management Plan accompanying this Development Application has not been approved by this consent.
- (b) A Waste Management Plan is to be approved by the Principal Certifier prior to a Construction Certificate being issued. The plan must comply with the Council's *Policy for Waste Minimisation in New Developments 2005*. All requirements of the approved Building Waste Management Plan must be implemented during construction of the development.

**UPON COMPLETION OF THE DEVELOPMENT**

- (c) Prior to an Occupation Certificate being issued or the use commencing, whichever is earlier, the Principal Certifier must ensure that waste handling works have been completed in accordance with: the Waste Management Plan; other relevant development consent conditions; and Council's *Policy for Waste Minimisation in New Developments 2005*.

**(33) DILAPIDATION REPORT – MINOR**

Subject to the receipt of permission of the affected landowner, dilapidation report/s of adjoining buildings are to be prepared by an appropriately qualified practising structural engineer and submitted for the approval of the Principal Certifier:

- (a) prior to the commencement of demolition/excavation works; and
- (b) on completion of construction demolition/excavation works.

**(34) ROAD OPENING PERMIT**

A separate Road Opening Permit under Section 138 of the *Roads Act 1993* must be obtained from Council prior to the commencement of any:

- (a) Excavation in or disturbance of a public way, or
- (b) Excavation on land that, if shoring were not provided, may disturb the surface of a public road (including footpath).

**(35) STRUCTURAL CERTIFICATION FOR EXISTING BUILDING – ALTERATIONS AND ADDITIONS**

A qualified practising certified structural engineer must provide structural certification to Council (where Council is the Principal Certifier) verifying that the existing structure can adequately support the proposed new loads and the structural design complies with the Structural Provisions of Part B1 (Vol 1) and Part 2.1 (Vol 2) of the *Building Code of Australia* prior to a Construction Certificate being issued. The proposed additional loads and/or alterations must not cause a decrease in the existing structural performance of the building including its performance under earthquake actions (AS1170.4).

**(36) BCA COMPLIANCE - ALTERATIONS AND ADDITIONS - UPGRADE OF WHOLE OF THE BUILDING IS REQUIRED (CC REQUIRED)**

- (a) Pursuant to Clause 94 of the Environmental Planning and Assessment Regulation 2000, the *whole building* must comply with the deemed-to-satisfy provisions of the Building Code of Australia (BCA) and the following:
  - i. Fire resistance and stability - Part C1;
  - ii. Compartmentation and separation - Part C2;
  - iii. Protection of openings - Part C3;
  - iv. Provision for escape (access and egress) - Part D1;
  - v. Construction of exits - Part D2;
  - vi. Access for people with disabilities - Part D3;
  - vii. Firefighting equipment - Part E1;
  - viii. Smoke hazard management - Part E2;
  - ix. Lift Installation – Part E3
  - x. Emergency lighting, exit signs and warning systems - Part E4;
  - xi. Sanitary and other facilities - Part F2;
  - xii. Light and ventilation - Part F4;

- (b) If compliance with the deemed-to-satisfy provisions of the BCA and the conditions listed above cannot be achieved, an alternate solution in accordance with Part A0 of the BCA must be prepared by a suitably qualified and accredited person and submitted to the Certifying Authority illustrating how the relevant performance requirements of the BCA are to be satisfied. Prior to a Construction Certificate being issued the Certifying Authority must ensure that the building complies with the Building Code of Australia.
- (c) The BCA matters identified in this condition are not an exhaustive list of non-compliances with the BCA. Any design amendments required to achieve compliance with the BCA must be submitted to Council. Significant amendments may require an application under Section 96 of the Act to be lodged with Council to amend the development approved in this consent.

**(37) ANNUAL FIRE SAFETY STATEMENT FORM**

An annual Fire Safety Statement must be given to Council and the NSW Fire Brigade commencing within 12 months after the date on which the initial Interim/Final Fire Safety Certificate is issued or the use commencing, whichever is earlier.

**(38) WORKS REQUIRING USE OF A PUBLIC PLACE**

Where construction/building works require the use of a public place including a road or footpath, approval under Section 138 of the *Roads Act 1993* is to be obtained from Council prior to the commencement of work. Details of any barricade construction, area of enclosure and period of work are required to be submitted to the satisfaction of Council.

**(39) APPLICATION FOR HOARDINGS AND SCAFFOLDING INSTALLED ON OR ABOVE A PUBLIC ROAD AND OPERATING HOISTING DEVICES INCLUDING BUILDING MAINTENANCE UNITS OVER A PUBLIC ROAD**

- (a) A separate application under Section 68 of the *Local Government Act 1993* and Section 138 of the *Roads Act 1993* is to be made to Council to erect a hoarding and/or scaffolding (temporary structures) on or above a public road (footway and/or roadway).
- (b) Where an approval (Permit) is granted allowing the placement of temporary structures on or above a public road the structures must comply fully with Council's *Hoarding and Scaffolding Policy; Guidelines for Hoardings and Scaffolding*; and the conditions of approval (Permit) granted including:
  - (i) maintaining a current and valid approval for the full duration that the temporary structure/s is in place;
  - (ii) maintaining temporary structure/s in a structurally sound and stable condition for the full duration of installation (Clause 2.11.1);
  - (iii) bill posters and graffiti being removed within 24 hours of their placement (Clause 2.11.2);



- (iv) maintaining temporary structures and the public place adjoining the work site in a clean and tidy condition including repainting and/or repair of graphics (Clauses 2.11.1, 2.11.4, 2.14.1 and 3.9.3);
- (v) maintaining a watertight deck (Type B hoardings) to prevent liquids including rainwater, falling onto the footway/roadway surfaces (Clauses 3.9.1 and 3.9.4);
- (vi) approved site sheds on the decks of a Type B hoarding being fully screened from the public place (Clause 3.9.5);
- (vii) material and equipment not being placed or stored on the deck of Type B hoardings, unless specifically approved by Council (Clause 3.9.4);
- (viii) providing and maintaining operational artificial lighting systems under Type B hoardings including at high-bay truck entry points (Clause 3.9.9); and
- (ix) ensuring all required signage is provided and maintained (Clauses 3.9.3, 3.9.6, 3.9.8, 3.10.1 and 4.2).

If it is proposed to operate a hoisting device including a building maintenance unit above a public road which swings, hoists material/equipment and/or slews any part of the device over the public road, a separate application under Section 68 of the *Local Government Act 1993* and Section 138 of the *Roads Act 1993* must be made to Council to obtain approval.

**Note:** 'Building maintenance unit' means a power-operated suspended platform and associated equipment on a building specifically designed to provide permanent access to the faces of the building for maintenance (*Work Health and Safety Regulation 2011*).

#### **(40) SYDNEY WATER CERTIFICATE (TAP-IN)**

- (a) The approved plans must be submitted to Sydney Water's "Tap-in" online service to determine whether the development will affect Sydney Water's sewer and water mains, stormwater drains and/or easements, and if further requirements need to be met. Sydney Water's "Tap-in" online service is available at [www.sydneywater.com.au](http://www.sydneywater.com.au), (see Plumbing, Building & Development and then Sydney Water "Tap-in").
- (b) The Consent Authority or a Principal Certifier must ensure that Sydney Water has appropriately stamped the plans before the commencement of work.

## SCHEDULE 1C

### DURING CONSTRUCTION/PRIOR TO OCCUPATION/COMPLETION

#### **(41) OCCUPATION CERTIFICATE TO BE SUBMITTED**

An Occupation Certificate must be obtained from the Principal Certifier and a copy submitted to Council prior to commencement of occupation or use of the whole or any part of a new building, an altered portion of, or an extension to an existing building.

#### **(42) HOURS OF WORK AND NOISE – OUTSIDE CBD**

The hours of construction and work on the development must be as follows:

- (a) All work, including building/demolition and excavation work, and activities in the vicinity of the site generating noise associated with preparation for the commencement of work (eg. loading and unloading of goods, transferring of tools etc) in connection with the proposed development must only be carried out between the hours of 7.30am and 5.30pm on Mondays to Fridays, inclusive, and 7.30am and 3.30pm on Saturdays, with safety inspections being permitted at 7.00am on work days, and no work must be carried out on Sundays or public holidays.
- (b) All work, including demolition, excavation and building work must comply with the City of Sydney Code of Practice for Construction Hours/Noise 1992 and Australian Standard 2436 - 2010 Guide to Noise Control on Construction, Maintenance and Demolition Sites.
- (c) Notwithstanding the above, the use of a crane for special operations, including the delivery of materials, hoisting of plant and equipment and erection and dismantling of on site tower cranes which warrant the on-street use of mobile cranes outside of above hours can occur, subject to a permit being issued by Council under Section 68 of the Local Government Act 1993 and/or Section 138 of the Roads Act 1993.

Note: Works may be undertaken outside of hours, where it is required to avoid the loss of life, damage to property, to prevent environmental harm and/or to avoid structural damage to the building. Written approval must be given by the Construction Regulation Unit, prior to works proceeding

The *City of Sydney Code of Practice for Construction Hours/Noise 1992* allows extended working hours subject to the approval of an application in accordance with the Code and under Section 4.55 of the *Environmental Planning and Assessment Act 1979*.

#### **(43) ENCROACHMENTS – NEIGHBOURING PROPERTIES**

No portion of the proposed structure shall encroach onto the adjoining properties.

#### **(44) ENCROACHMENTS – PUBLIC WAY**

No portion of the proposed structure, including gates and doors during opening and closing operations, shall encroach upon Council's footpath area.

**(45) COVERING OF LOADS**

All vehicles involved in the excavation and/or demolition process and departing the property with demolition materials, spoil or loose matter must have their loads fully covered before entering the public roadway.

**(46) VEHICLE CLEANSING**

Prior to the commencement of work, suitable measures are to be implemented to ensure that sediment and other materials are not tracked onto the roadway by vehicles leaving the site. It is an offence to allow, permit or cause materials to pollute or be placed in a position from which they may pollute waters.

**(47) LOADING AND UNLOADING DURING CONSTRUCTION**

The following requirements apply:

- (a) All loading and unloading associated with construction activity must be accommodated on site.
- (b) A Works Zone may be required if loading and unloading is not possible on site. If a Works Zone is warranted an application must be made to Council at least 8 weeks prior to commencement of work on the site. An approval for a Works Zone may be given for a specific period and certain hours of the days to meet the particular need for the site for such facilities at various stages of construction. The approval will be reviewed periodically for any adjustment necessitated by the progress of the construction activities.
- (c) Where hoisting activity over the public place is proposed to be undertaken including hoisting from a Works Zone, a separate approval under Section 68 of the Local Government Act 1993 must be obtained.

**(48) NO OBSTRUCTION OF PUBLIC WAY**

The public way must not be obstructed by any materials, vehicles, refuse, skips or the like, under any circumstances. Non-compliance with this requirement will result in the issue of a notice by Council to stop all work on site.

**(49) USE OF MOBILE CRANES**

The following requirements apply:

- (a) Mobile cranes operating from the road must not be used as a method of demolishing or constructing a building.
- (b) For operations warranting the on-street use of mobile cranes (such as delivery of materials, hoisting of plant/equipment, erection and dismantling of onsite tower cranes, etc), permits must be obtained from Council for the use of a mobile crane. The permits must be obtained 48 hours beforehand for partial road closures which, in the opinion of Council will create minimal traffic disruptions and 4 weeks beforehand in the case of full road closures and partial road closures which, in the opinion of Council, will create significant traffic disruptions.

- (c) Special operations and the use of mobile cranes must comply with the approved hours of construction. Mobile cranes must not be delivered to the site prior to 7.30am without the prior approval of Council.

## **PRESCRIBED CONDITIONS**

**The prescribed conditions in accordance with Division 8A of the *Environmental Planning and Assessment Regulation 2000* apply:**

- Clause 98 Compliance with *Building Code of Australia* and insurance requirements under the *Home Building Act 1989*
- Clause 98A Erection of signs
- Clause 98B Notification of *Home Building Act 1989* requirements
- Clause 98C Conditions relating to entertainment venues
- Clause 98D Conditions relating to maximum capacity signage
- Clause 98E Conditions relating to shoring and adequacy of adjoining property

Refer to the NSW State legislation for full text of the clauses under Division 8A of the *Environmental Planning and Assessment Regulation 2000*. This can be accessed at: <http://www.legislation.nsw.gov.au>