

Attachment A

Recommended Conditions of Consent
--

CONDITIONS OF CONSENT

SCHEDULE 1

APPROVED DEVELOPMENT/DESIGN MODIFICATIONS/COVENANTS AND CONTRIBUTIONS/USE AND OPERATION

(1) APPROVED DEVELOPMENT

- (a) Development must be in accordance with Development Application No. D/2018/1305 dated 30 October 2018 and the following drawings prepared by Tzannes:

Drawing Number	Plan Name	Date
500	Demolition & Excavation Plan – Basement 5	25 October 2018
501	Demolition & Excavation Plan – Basement 4	25 October 2018
502	Demolition & Excavation Plan – Basement 3	25 October 2018
503	Demolition & Excavation Plan – Basement 2	25 October 2018
504	Demolition & Excavation Plan – Basement 1	25 October 2018
505	Demolition & Excavation Plan – Lower Ground	25 October 2018
506	Demolition & Excavation Plan – Ground Floor	25 October 2018
507	Demolition & Excavation Plan – Level 1	25 October 2018

Drawing Number	Plan Name	Date
508	Demolition & Excavation Plan – Level 2-3	22 October 2018
509	Demolition & Excavation Section	26 October 2018

and as amended by the conditions of this consent.

- (b) In the event of any inconsistency between the approved plans and supplementary documentation, the drawings will prevail.

(2) ALIGNMENT LEVELS - PUBLIC DOMAIN

- (a) Proposed building floor levels, basement levels, basement car park entry levels and ground levels shown on the approved Development Application plans are indicative only and have not been approved by this consent.
- (b) Prior to a Construction Certificate being issued for any excavation, civil construction, drainage or building work (whichever is earlier), excluding approved preparatory or demolition work, alignment levels for the building and site frontages must be submitted to and approved by Council. The submission must be prepared by a Registered Surveyor and designed by a suitably qualified engineer, must be in accordance with the City of Sydney's *Public Domain Manual* and must be submitted with a completed and Levels and Gradients Approval Application form (available on the City's website).
- (c) These alignment levels, as approved by Council, are to be incorporated into the plans submitted with the application for a Construction Certificate for any civil, drainage and public domain work as applicable under this consent. If the proposed detailed design of the public domain requires changes to any previously approved Alignment Levels, then an amended Alignment Levels submission must be submitted to and approved by Council to reflect these changes prior to a Construction Certificate being issued for public domain work.

(3) PHOTOGRAPHIC RECORD / DILAPIDATION REPORT - PUBLIC DOMAIN

Prior to an approval for demolition being granted or a Construction Certificate being issued, whichever is earlier, a photographic recording of the public domain site frontages is to be prepared and submitted to Council's satisfaction.

The recording must include clear images of the building facade adjoining the footpath, the footpath, nature strip, kerb and gutter, driveway crossovers and laybacks, kerb ramps, road carriageway, street trees and plantings, parking restriction and traffic signs, and all other existing infrastructure along the street.

The form of the recording is to be as follows:-

- (a) A PDF format report containing all images at a scale that clearly demonstrates the existing site conditions;
- (b) Each image is to be labelled to identify the elements depicted, the direction that the image is viewed towards, and include the name of the relevant street frontage;
- (c) Each image is to be numbered and cross referenced to a site location plan;
- (d) A summary report, prepared by a suitable qualified professional, must be submitted in conjunction with the images detailing the project description, identifying any apparent existing defects, detailing the date and authorship of the photographic record, the method of documentation and limitations of the photographic record;
- (e) Include written confirmation, issued with the authority of both the applicant and the photographer that the City of Sydney is granted a perpetual non-exclusive license to make use of the copyright in all images supplied, including the right to make copies available to third parties as though they were Council images. The signatures of both the applicant and the photographer must be included.

Any damage to the public way including trees, footpaths, kerbs, gutters, road carriageway and the like must immediately be made safe and functional by the applicant. Damage must be fully rectified by the applicant in accordance with the City's standards prior to a Certificate of Completion being issued for Public Domain Works or before an Occupation Certificate is issued for the development, whichever is earlier.

(4) PRESERVATION OF SURVEY MARKS

All works in City streets must ensure the preservation of existing permanent survey marks (a brass bolt, or a lead plug holding a brass tack, covered by a cast iron box). At least forty-eight hours prior to the commencement of any works in the public way within 1 metre of a permanent survey mark contact must be made with the City's Project Manager Survey / Design Services to arrange for the recovery of the mark.

Prior to the issue of a Construction Certificate, a survey plan, clearly showing the location of all permanent survey marks fronting the site and within 5 metres on each side of the frontages must be submitted to Council.

At least forty-eight hours prior to the commencement of any works in the public way within 1 metre of a permanent survey mark contact must be made with the City's Senior Surveyor to arrange for the recovery of the mark.

A fee must be paid to the Council for the replacement of any permanent survey mark removed or damaged in accordance with the City's Schedule of Fees and Charges (Reinstatement of Survey Box).

(5) PROTECTION OF SURVEY INFRASTRUCTURE

Prior to the commencement of any work on site, a statement prepared by a Surveyor registered under the *Surveying and Spatial Information Act 2002* must be submitted to Council verifying that a survey has been carried out in accordance with the Surveyor General's Direction No. 11 – Reservation of Survey Infrastructure. Any Permanent Marks proposed to be or have been destroyed must be replaced, and a "Plan of Survey Information" must be lodged at the NSW Land Registry Services.

Reason: To ensure that the survey control infrastructure and cadastral framework are preserved for the public benefit and in accordance with the *Surveying and Spatial Information Act 2002*.

(6) PUBLIC DOMAIN WORKS BOND

Public Domain Works Deposit will be required as security for the public domain works and for repairing damage that may be caused to the public domain in the vicinity of the site, in accordance with the City of Sydney's adopted fees and charges and the Public Domain Manual. The Public Domain Works Deposit must be submitted as an unconditional bank guarantee or insurance bond as per the Council's Performance Bond Policy in favour of Council as security for completion of the obligations under this consent (Guarantee).

Council's Public Domain section must be contacted to determine the guarantee amount prior to lodgement of the guarantee. The guarantee must be lodged with Council prior to a Construction Certificate being issued.

The Guarantee will be retained in full until all Public Domain works, including rectification of damage to the public domain, are completed to City of Sydney standards and approval and the required certifications, warranties and works-as-executed documentation are submitted and approved by Council in writing. On satisfying the above requirements, 90% of the security will be released. The remaining 10% will be retained for the duration of the specified Defects Liability Period.

(7) PUBLIC DOMAIN WORKS – HOLD POINTS AND HANDOVER

- (a) Prior to a Construction Certificate being issued for public domain work, including civil, drainage and subsurface works, , a set of hold points for approved public domain, civil and drainage work is to be determined with and approved by the City's Public Domain section in accordance with the City of Sydney's *Public Domain Manual* and *Sydney Streets Technical Specification*.
- (b) Prior to a Certificate of Completion being issued for public domain works and before the issue of any Occupation Certificate for the development or before the use commences, whichever is earlier, electronic works-as-executed (as-built) plans and documentation, certified by a suitably qualified, independent professional must be submitted to and accepted by Council for all public domain works. Completion and handover of the constructed public domain works must be undertaken in accordance with the City of Sydney's *Public Domain Manual* and *Sydney Streets Technical Specification*, including requirements for as-built documentation, certification, warranties and the defects liability period.

(8) PUBLIC DOMAIN DAMAGE DEPOSIT

- (a) A Public Domain Damage Deposit calculated on the basis of 30 lineal metres of asphalt site frontage on Riley Street and 63 lineal metres of concrete site frontage on Lower Campbell Street must be lodged with Council in accordance with the City of Sydney's adopted Schedule of Fees and Charges. The Public Domain Damage Deposit must be submitted as an unconditional bank guarantee or insurance bond as per the Council's Performance Bond Policy in favour of Council as security for repairing any damage to the public domain in the vicinity of the site (Guarantee).
- (b) The Guarantee must be lodged with Council prior to an approval for demolition being granted or a Construction Certificate being issued, whichever is earlier.
- (c) The Guarantee in this condition will be retained in full until the Public Domain Works Deposit Guarantee required by this consent is lodged with Council. Upon lodgement of the Public Domain Works Deposit Guarantee, the Guarantee in this condition will be released.

(9) FLOOD MANAGEMENT

Additional information including plans and a statement from a suitably qualified engineer is to be submitted to and approved by Council's Area Planning Manager/Area Planning Coordinator prior to the issue of any Construction Certificate demonstrating that the site will be protected during excavation and construction in accordance with the City's Interim Floodplain Management Policy.

(10) WASTE AND RECYCLING MANAGEMENT - COMMERCIAL

- (a) A Waste and Recycling Management Plan is to be submitted to and approved by Council's Area Planning Manager/Area Planning Coordinator prior to any Construction Certificate being issued. The plan must comply with the Council's *Guidelines for Waste Management in New Developments 2018*. All requirements of the approved Building Waste and Recycling Management Plan must be implemented during construction of the development.

UPON COMPLETION OF THE DEVELOPMENT

- (b) Prior to an Occupation Certificate being issued or the use commencing, whichever is earlier, the Principal Certifier must ensure that waste handling works have been completed in accordance with: the Waste and Recycling Management Plan; other relevant development consent conditions; and Council's *Guidelines for Waste Management in New Developments 2018*.

(11) COMPLIANCE WITH DEMOLITION, EXCAVATION & CONSTRUCTION NOISE AND VIBRATION MANAGEMENT PLAN

- (a) All works conducted on site which form part of this development must be carried out in accordance with the submitted Demolition and Excavation Noise and Vibration Management Plan prepared by Acoustic Studio dated 23 October 2018 TRIM 2018/560391.
- (b) Where all such control measures have been implemented and the resultant noise and/ or vibration levels at any sensitive receiver still exceed the council's applicable criteria stated in the Construction Hours/Noise Code 1992 and are giving rise to sustained complaints then the contractor must provide regular, appropriate and sustained periods of respite in consultation with Council's Health and Building unit. Approval to vary the authorised noise and vibration levels must be received in writing by the proponent from Council prior to activities being undertaken that exceed sanctioned emission levels. (Use where respite periods not specified under the approved DEC NMP).

Such periods must be set and agreed to by Council's Health and Building Unit.

(12) NOISE – COMMERCIAL PLANT / INDUSTRIAL DEVELOPMENT

- (a) Noise from commercial plant and industrial development must not exceed a project amenity/intrusiveness noise level or maximum noise level in accordance with relevant requirements of the NSW EPA [Noise Policy for Industry 2017 \(NPfl\)](#) unless agreed to by the City's Area Planning Manager. Further:
 - (i) Background noise monitoring must be carried out in accordance with the long-term methodology in [Fact Sheet B](#) of the NPfl unless otherwise agreed by the City's Area Planning Manager.
 - (ii) Commercial plant is limited to heating, ventilation, air conditioning, refrigeration and energy generation equipment.
- (b) An $L_{Aeq,15 \text{ minute}}$ (noise level) emitted from the development must not exceed the $L_{A90, 15 \text{ minute}}$ (background noise level) by more than 3dB when assessed inside any habitable room of any affected residence or noise sensitive commercial premises at any time. Further:
 - (i) The noise level and the background noise level shall both be measured with all external doors and windows of the affected residence closed.
 - (ii) Background noise measurements must not include noise from the development but may include noise from necessary ventilation at the affected premise.
- (c) Corrections in [Fact Sheet C](#) of the NPfl are applicable to relevant noise from the development measured in accordance with this condition, however duration corrections are excluded from commercial noise.

(13) CLASSIFICATION OF WASTE

Prior to the exportation of waste (including fill or soil) from the site, the waste materials must be classified in accordance with the provisions of the Protection of the *Environment Operations Act 1997* and the *NSW DECC Waste Classification Guidelines, Part1: Classifying Waste (July 2009)*. The classification of the material is essential to determine where the waste may be legally taken. The *Protection of the Environment Operations Act 1997* provides for the commission of an offence for both the waste owner and the transporters if the waste is taken to a place that cannot lawfully be used as a waste facility for the particular class of waste. For the transport and disposal of industrial, hazardous or Group A liquid waste advice should be sought from the EPA.

(14) ASBESTOS REMOVAL WORKS

- (a) All works removing asbestos containing materials must be carried out by a suitably licensed asbestos removalist duly licensed with Safework NSW, holding either a Friable (Class A) or a Non- Friable (Class B) Asbestos Removal Licence which ever applies.
 - (i) A copy of the relevant licence shall be made available to any authorised Council officer on request within 24 hours.
- (b) Five days prior to the commencement of licensed asbestos removal, Safework NSW must be formally notified of the works. All adjoining properties and those opposite the development must be notified in writing of the dates and times when asbestos removal is to be conducted. The notification must identify the licensed asbestos removal contractor and include a contact person for the site together with telephone number and email address.
- (c) All work must be carried out in accordance with the *Work Health and Safety Regulation 2011* and the NSW Government and Work Cover document entitled *How to manage and control asbestos in the work place: Code of Practice (Safework NSW) December 2011* and the *City of Sydney Managing Asbestos Policy dated 21 October 2013 and associated guidelines*.
- (d) The asbestos removalist must use signs and barricades to clearly indicate the area where the asbestos removal work is being performed. Signs must be placed in positions so that people are aware of where the asbestos removal work area is and should remain in place until removal is completed and clearance to reoccupy has been granted. Responsibilities for the security and safety of the asbestos removal site and removal must be specified in the asbestos removal control plan (where required). This includes inaccessible areas that are likely to contain asbestos.

- (e) Warning signs must be placed so they inform all people nearby that asbestos removal work is taking place in the area. Signs must be placed at all of the main entry points to the asbestos removal work area where asbestos is present. These signs must be weatherproof, constructed of light-weight material and adequately secured so they remain in prominent locations. The signs must be in accordance with AS 1319 - 1994 *Safety Signs for the Occupational Environment* for size, illumination, location and maintenance.
- (f) Asbestos waste must only be transported and disposed of at an EPA licensed waste facility.
- (g) No asbestos products are to be reused on the site (i.e. packing pieces, spacers, formwork or fill etc).
- (h) No asbestos laden skips or bins are to be left in any public place without the written approval of Council.
- (i) A site notice board must be located at the main entrance to the site in a prominent position and must have minimum dimensions of 841mm x 594mm (A1) with any text on the notice to be a minimum of 30 point type size.
- (j) The site notice board must include the following:
 - (i) contact person for the site;
 - (ii) telephone and facsimile numbers and email address; and
 - (iii) site activities and time frames.

(15) HOURS OF WORK AND NOISE

The hours of construction and work on the development must be as follows:

- (a) All work, including building/demolition and excavation work, and activities in the vicinity of the site generating noise associated with preparation for the commencement of work (eg. loading and unloading of goods, transferring of tools etc) in connection with the proposed development must only be carried out between the hours of 7.30am and 5.30pm on Mondays to Fridays, inclusive, and 7.30am and 3.30pm on Saturdays, with safety inspections being permitted at 7.00am on work days, and no work must be carried out on Sundays or public holidays.
- (b) All work, including demolition, excavation and building work must comply with the City of Sydney Code of Practice for Construction Hours/Noise 1992 and Australian Standard 2436 - 2010 Guide to Noise Control on Construction, Maintenance and Demolition Sites.
- (c) Notwithstanding the above, the use of a crane for special operations, including the delivery of materials, hoisting of plant and equipment and erection and dismantling of on site tower cranes which warrant the on-street use of mobile cranes outside of above hours can occur, subject to a permit being issued by Council under Section 68 of the Local Government Act 1993 and/or Section 138 of the Roads Act 1993.

Note: Works may be undertaken outside of hours, where it is required to avoid the loss of life, damage to property, to prevent environmental harm and/or to avoid structural damage to the building. Written approval must be given by the Construction Regulation Unit, prior to works proceeding

The *City of Sydney Code of Practice for Construction Hours/Noise 1992* allows extended working hours subject to the approval of an application in accordance with the Code and under Section 4.55 of the *Environmental Planning and Assessment Act 1979*.

(16) USE OF HIGH NOISE EMISSION APPLIANCES / PLANT

(a) The operation of high noise emission appliances, plant and/or machinery such as pile – drivers, rock breakers and hydraulic hammers and those which are not listed in Groups B, C, D, E or F of Schedule 1 of the *City of Sydney Code of Practice for Construction Hours/Noise 1992* and Australian Standard 2436-2010 *Guide to Noise Control on Construction, Maintenance and Demolition Sites* is restricted to the hours of:

- 8:00am to 11:00am Monday to Friday
- 12:00pm to 3:00pm Monday to Friday
- 8:00am to 11:00am Saturday
- 12.00pm to 3.00pm Saturday

(b) All reasonable and feasible steps must be undertaken to ensure that the work, including demolition, excavation and building complies with the *City of Sydney Code of Practice for Construction Hours/Noise 1992* and Australian Standard 2436- 2010 *Guide to Noise Control on Construction, Maintenance and Demolition Sites*.

(17) NOTIFICATION OF EXCAVATION WORKS OR USE OF HIGH NOISE EMISSION APPLIANCES/PLANT

The immediately adjoining neighbours must be given a minimum of 48 hours notice that excavation, shoring or underpinning works or use of high noise emission appliances / plant are about to commence.

(18) HAZARDOUS AND INDUSTRIAL WASTE

Hazardous and/or industrial waste arising from the demolition/operational activities must be removed and/or transported in accordance with the requirements of the NSW Work Cover Authority pursuant to the provisions of the following:

- (a) Protection of the Environment Operations Act 1997
- (b) Protection of the Environment Operations (Waste) Regulation 2005
- (c) Waste Avoidance and Resource Recovery Act 2001

- (d) Work Health and Safety Act 2011
- (e) Work Health and Safety Regulation 2011.

(19) COVERING OF LOADS

All vehicles involved in the excavation and/or demolition process and departing the property with demolition materials, spoil or loose matter must have their loads fully covered before entering the public roadway.

(20) VEHICLE CLEANSING

Prior to the commencement of work, suitable measures are to be implemented to ensure that sediment and other materials are not tracked onto the roadway by vehicles leaving the site. It is an offence to allow, permit or cause materials to pollute or be placed in a position from which they may pollute waters.

(21) CONSTRUCTION TRAFFIC MANAGEMENT PLAN

- (a) The Construction Traffic Management Plan submitted during the assessment of the application has not been approved by this consent.

- (b) A Construction Traffic Management Plan must be submitted to and approved by Council's Area Planning Manager/Area Planning Coordinator prior to the issue of any Construction Certificate. The CTMP must be prepared in accordance with Council's requirements, located at –

<http://www.cityofsydney.nsw.gov.au/business/business-responsibilities/traffic-management/construction-traffic-management-plans>

and in consultation with the Transport for NSW Sydney Coordination Office.

- (c) The CTMP must not permit vehicles parking on Lower Campbell Street that will inhibit vehicular ingress and egress from neighbouring properties.
- (d) The development must be undertaken in accordance with the CTMP approved under (b) above.

(22) DEMOLITION, EXCAVATION AND CONSTRUCTION MANAGEMENT

- (a) Prior to the commencement of demolition and/or excavation work the following details must be submitted to and be approved by the Principal Certifier:

- (i) Plans and elevations showing distances of the subject building from the location of adjoining and common/party walls, and (where applicable) the proposed method of facade retention.

- (ii) A Demolition Work Method Statement prepared by a licensed demolisher who is registered with the Work Cover Authority. (The demolition by induced collapse, the use of explosives or on-site burning is not permitted.)
- (iii) An Excavation Work Method Statement prepared by an appropriately qualified person.
- (iv) A Waste Management Plan for the demolition and or excavation of the proposed development.
- (v) Plans and elevations showing the location, construction and installation of temporary site fencing and any temporary structures used in connection with the construction of the development.

Note: Temporary structures, including hoardings and scaffolding, proposed for erection on City-owned and controlled land (footways and roadways), must comply with the City's *Guidelines for Hoardings and Scaffolding* and be approved by Council under the provisions of the Local Government Act 1993 and the Roads Act 1993 prior to installation.

- (b) Such statements must, where applicable, be in compliance with AS2601-2001 Demolition of Structures, the *Work, Health and Safety Act 2011* and Regulation; Council's *Policy for Waste Minimisation in New Developments 2005*, the *Waste Avoidance and Resource Recovery Act 2001*, and all other relevant acts and regulations and must include provisions for:
 - (i) A Materials Handling Statement for the removal of refuse from the site in accordance with the *Waste Avoidance and Resource Recovery Act 2001*.
 - (ii) The name and address of the company/contractor undertaking demolition/excavation works.
 - (iii) The name and address of the company/contractor undertaking off site remediation/disposal of excavated materials.
 - (iv) The name and address of the transport contractor.
 - (v) The type and quantity of material to be removed from site.
 - (vi) Location and method of waste disposal and recycling.
 - (vii) Proposed truck routes, in accordance with this development consent.

- (viii) Procedures to be adopted for the prevention of loose or contaminated material, spoil, dust and litter from being deposited onto the public way from trucks and associated equipment and the proposed method of cleaning surrounding roadways from such deposits. (Note: With regard to demolition of buildings, dust emission must be minimised for the full height of the building. A minimum requirement is that perimeter scaffolding, combined with chain wire and shade cloth must be used, together with continuous water spray during the demolition process. Compressed air must not be used to blow dust from the building site).
 - (ix) Measures to control noise emissions from the site.
 - (x) Measures to suppress odours.
 - (xi) Enclosing and making the site safe.
 - (xii) Induction training for on-site personnel.
 - (xiii) Written confirmation that an appropriately qualified Occupational Hygiene Consultant has inspected the building/site for asbestos, contamination and other hazardous materials, in accordance with the procedures acceptable to Work Cover Authority.
 - (xiv) An Asbestos and Hazardous Materials Clearance Certificate by a person approved by the Work Cover Authority.
 - (xv) Disconnection of utilities.
 - (xvi) Fire Fighting. (Fire fighting services on site are to be maintained at all times during demolition work. Access to fire services in the street must not be obstructed).
 - (xvii) Access and egress. (Demolition and excavation activity must not cause damage to or adversely affect the safe access and egress of the subject building or any adjacent buildings).
 - (xviii) Waterproofing of any exposed surfaces of adjoining buildings.
 - (xix) Control of water pollution and leachate and cleaning of vehicles tyres (proposals must be in accordance with the *Protection of the Environmental Operations Act 1997*).
 - (xx) Working hours, in accordance with this development consent.
 - (xxi) Any Work Cover Authority requirements.
- (c) The approved work method statements and a waste management plan as required by this condition must be implemented in full during the period of construction.

(23) DILAPIDATION REPORT

- (a) Subject to the receipt of permission of the affected landowner, dilapidation report/s, including a photographic survey of the properties adjoining the site to the south, 277-285 Crown Street, 261-265 Crown Street, 58 and 60 Lower Campbell Street are to be prepared by an appropriately qualified structural engineer prior to commencement of demolition/excavation works. A copy of the dilapidation report/s together with the accompanying photographs must be given to the above property owners, and a copy lodged with the Principal Certifier and the Council prior to the issue of a Construction Certificate.

UPON COMPLETION OF EXCAVATION/DEMOLITION

- (b) A second Dilapidation Report/s, including a photographic survey must then be submitted at least one month after the completion of demolition/excavation works. A copy of the second dilapidation report/s, together with the accompanying photographs must be given to the above property owners, and a copy lodged with the Principal Certifier and the Council prior to the issue of an Occupation Certificate.

Any damage to buildings, structures, lawns, trees, sheds, gardens and the like must be fully rectified by the applicant or owner, at no cost to the affected property owner.

Note: Prior to the commencement of the building surveys, the applicant/owner must advise (in writing) all property owners of buildings to be surveyed of what the survey will entail and of the process for making a claim regarding property damage. A copy of this information must be submitted to Council.

(24) EROSION AND SEDIMENT CONTROL

Prior to the commencement of demolition/excavation/construction work, an Erosion and Sediment Control Plan (ESCP) must be submitted to and be approved by the Principal Certifier. The ESCP must:

- (a) Conform to the specifications and standards contained in Managing Urban Stormwater: Soils and Construction (Landcom, 2004); the Guidelines for Erosion and Sediment Control on Building Sites (City of Sydney, 2004); and the *NSW Protection of the Environment Operations Act 1997*.
- (b) Include a drawing(s) that clearly shows:
- (i) location of site boundaries and adjoining roads
 - (ii) approximate grades and indications of direction(s) of fall
 - (iii) approximate location of trees and other vegetation, showing items for removal or retention
 - (iv) location of site access, proposed roads and other impervious areas
 - (v) existing and proposed drainage patterns with stormwater discharge points

- (vi) north point and scale
- (c) Specify how soil conservation measures will be conducted on site including:
 - (i) timing of works
 - (ii) locations of lands where a protective ground cover will, as far as is practicable, be maintained
 - (iii) access protection measures
 - (iv) nature and extent of earthworks, including the amount of any cut and fill
 - (v) where applicable, the diversion of runoff from upslope lands around the disturbed areas
 - (vi) location of all soil and other material stockpiles including topsoil storage, protection and reuse methodology
 - (vii) procedures by which stormwater is to be collected and treated prior to discharge including details of any proposed pollution control device(s)
 - (viii) frequency and nature of any maintenance program
 - (ix) other site-specific soil or water conservation structures.

(25) TEMPORARY GROUND ANCHORS, TEMPORARY SHORING AND PERMANENT BASEMENT/RETAINING WALLS AFFECTING THE ROAD RESERVE

For temporary shoring including ground anchors affecting the road reserve, a separate application under Section 138 of the *Roads Act 1993* must be lodged with Council.

(26) TEMPORARY STRUCTURES (HOARDINGS, SCAFFOLDING AND OTHER STRUCTURES) INSTALLED ON PUBLIC ROADS THAT REQUIRE DEVELOPMENT CONTENT

The following forms of temporary structures (hoardings, scaffolding and other structures) proposed for installation on public roads and in connection with the construction of the approved development require Council approval (development consent):

- (a) Type B hoardings that span over roads such as laneways;
- (b) Type B hoardings that propose more than a single storey of site sheds installed on a hoarding deck;
- (c) Type A and Type B hoardings with or without scaffolding that project beyond the side boundaries of adjoining properties;
- (d) fenced work compounds at roadway/footway level;

- (e) hoardings/scaffolding associated with works on heritage-listed buildings;
or
- (f) any other large and/or potentially high environmental impact temporary structures, as determined by Council.

A separate development application must be submitted and approved by Council prior to the installation of any temporary structure listed above.

(27) APPLICATION FOR HOARDINGS AND SCAFFOLDING INSTALLED ON OR ABOVE A PUBLIC ROAD AND OPERATING HOISTING DEVICES INCLUDING BUILDING MAINTENANCE UNITS OVER A PUBLIC ROAD

- (a) A separate application under Section 68 of the *Local Government Act 1993* and Section 138 of the *Roads Act 1993* is to be made to Council to erect a hoarding and/or scaffolding (temporary structures) on or above a public road (footway and/or roadway).
- (b) Where an approval (Permit) is granted allowing the placement of temporary structures on or above a public road the structures must comply fully with Council's *Hoarding and Scaffolding Policy; Guidelines for Hoardings and Scaffolding*; and the conditions of approval (Permit) granted including:
 - (i) maintaining a current and valid approval for the full duration that the temporary structure/s is in place;
 - (ii) maintaining temporary structure/s in a structurally sound and stable condition for the full duration of installation (Clause 2.11.1);
 - (iii) bill posters and graffiti being removed within 24 hours of their placement (Clause 2.11.2);
 - (iv) maintaining temporary structures and the public place adjoining the work site in a clean and tidy condition including repainting and/or repair of graphics (Clauses 2.11.1, 2.11.4, 2.14.1 and 3.9.3);
 - (v) maintaining a watertight deck (Type B hoardings) to prevent liquids including rainwater, falling onto the footway/roadway surfaces (Clauses 3.9.1 and 3.9.4);
 - (vi) approved site sheds on the decks of a Type B hoarding being fully screened from the public place (Clause 3.9.5);
 - (vii) material and equipment not being placed or stored on the deck of Type B hoardings, unless specifically approved by Council (Clause 3.9.4);
 - (viii) providing and maintaining operational artificial lighting systems under Type B hoardings including at high-bay truck entry points (Clause 3.9.9); and
 - (ix) ensuring all required signage is provided and maintained (Clauses 3.9.3, 3.9.6, 3.9.8, 3.10.1 and 4.2).

If it is proposed to operate a hoisting device including a building maintenance unit above a public road which swings, hoists material/equipment and/or slews any part of the device over the public road, a separate application under Section 68 of the *Local Government Act 1993* and Section 138 of the *Roads Act 1993* must be made to Council to obtain approval.

Note: 'Building maintenance unit' means a power-operated suspended platform and associated equipment on a building specifically designed to provide permanent access to the faces of the building for maintenance (*Work Health and Safety Regulation 2011*).

SCHEDULE 2

PRESCRIBED CONDITIONS

The prescribed conditions in accordance with Division 8A of the *Environmental Planning and Assessment Regulation 2000* apply:

- Clause 98 Compliance with *Building Code of Australia* and insurance requirements under the *Home Building Act 1989*
- Clause 98A Erection of signs
- Clause 98B Notification of *Home Building Act 1989* requirements
- Clause 98C Conditions relating to entertainment venues
- Clause 98D Conditions relating to maximum capacity signage
- Clause 98E Conditions relating to shoring and adequacy of adjoining property

Refer to the NSW State legislation for full text of the clauses under Division 8A of the *Environmental Planning and Assessment Regulation 2000*. This can be accessed at: <http://www.legislation.nsw.gov.au>