

Attachment A

Recommended Conditions of Consent
--

CONDITIONS OF CONSENT

SCHEDULE 1

APPROVED DEVELOPMENT/DESIGN MODIFICATIONS/COVENANTS AND CONTRIBUTIONS/USE AND OPERATION

(1) APPROVED DEVELOPMENT

- (a) Development must be in accordance with Development Application No. D/2018/761 dated 6 July 2018 and the following drawings prepared by Bureau SRH Architects:

Drawing Number	Drawing Name	Date
DA000 Rev 4	Title Page	29 January 2019
DA002 Rev 2	Storage Plan	29 January 2019
DA103 Rev 7	Lower Ground Floor	29 January 2019
DA104 Rev 7	Ground Floor	29 January 2019
DA105 Rev 7	First Floor	29 January 2019
DA106 Rev 7	Second Floor	29 January 2019
DA107 Rev 7	Third Floor	29 January 2019
DA108 Rev 5	Roof Plan	29 January 2019
DA200 Rev 6	North Elevation	29 January 2019
DA201 Rev 6	South Elevation	29 January 2019
DA203 Rev 4	East Elevation	29 January 2019
DA301 Rev 7	Section AA	29 January 2019
DA302 Rev 6	Section BB	29 January 2019
DA303 Rev 6	Section CC	29 January 2019
DA304 Rev 5	Section DD	29 January 2019

Drawing Number	Drawing Name	Date
EX100 Rev 3	Existing Lower Ground Floor Plan	29 January 2019
EX101 Rev 3	Existing Ground Floor	29 January 2019
EX102 Rev 3	Existing and Demolition Roof	29 January 2019
EX200 Rev 2	Existing Section i + ii	29 January 2019
EX201 Rev 2	Existing Section iii	29 January 2019

and as amended by the conditions of this consent.

- (b) In the event of any inconsistency between the approved plans and supplementary documentation, the drawings will prevail.

(2) SECTION 7.11 CONTRIBUTIONS PAYABLE - CONTRIBUTION TOWARDS PUBLIC AMENITIES – CITY OF SYDNEY DEVELOPMENT CONTRIBUTIONS PLAN 2015 – EAST PRECINCT

Council has identified the development will increase demand for public amenities and facilities. Pursuant to Section 7.11 of the Environmental Planning and Assessment Act, 1979 (as amended), and the City of Sydney Development Contributions Plan 2015 the following monetary contributions are required towards the cost of public amenities.

<u>Contribution Category</u>	<u>Amount</u>
Open Space	\$32,851.96
Community Facilities	\$16,081.80
Traffic and Transport	\$1,029.84
Total	\$49,963.60

The City of Sydney will index the above contribution for inflation at the time of payment using the following formula.

$$C_{\text{payment}} = C_{\text{consent}} \times (CPI_{\text{payment}} \div CPI_{\text{consent}})$$

Where:

C_{payment} = Is the contribution at time of payment;

C_{consent} = Is the contribution at the time of consent, as shown above;

CPIpayment = Is the Consumer Price Index (All Groups Index) for Sydney published by the Australian Bureau of Statistics that applies at the time of payment; and

CPI1consent = Is the Consumer Price Index (All Groups Index) for Sydney at the date the contribution amount above was calculated being – 115.1 for the March 2019 quarter.

The contribution must be paid prior to the issue of any Construction Certificate in relation to this development.

Please contact Council's Planning Administration staff at planningsystemsadmin@cityofsydney.nsw.gov.au to request a letter confirming the indexed contribution amount payable.

Once the letter confirming the indexed contribution is obtained, payment may be made at any of the City's Neighbourhood Service Centres or the One Stop Shop at Town Hall House. Acceptable payment methods are EFTPOS (debit card only), cash (up to 10K only), Credit Card (up to 50K only) or a bank cheque made payable to the City of Sydney. Personal or company cheques will not be accepted.

(3) DESIGN MODIFICATIONS

The design of the building must be modified as follows:

- (a) A minimum distance of two metres (measured vertically and diagonally) is to be provided between the top of the hit-and-miss brickwork at ground level and the bottom of the hit-and-miss brickwork at first floor level.
- (b) The retail units are to be consolidated into one. No access is to be provided between the retail unit and the residential lobby corridor.
- (c) The air conditioning units as shown on the stamped plans are not approved.
- (d) The balustrades to the rear of balconies of apartment 4 are to be removed, and the top of the planter boxes raised to a minimum height of 1.1 metres from finished floor level.
- (e) The residential waste room and bulky waste room are to be consolidated and the entrance located between the lift lobby and rear of the terrace. The commercial waste room is to be accessed from the rear of the retail premises. Access from the retail unit to the toilet and commercial waste room is to be amended accordingly.

The modifications are to be submitted to and approved by Council's Area Coordinator Planning Assessments / Area Planning Manager prior to the issue of any Construction Certificate.

(4) IMPACT ON HERITAGE FABRIC

Elevations are to be provided at a scale of 1:10 illustrating:

- (a) The works required to the front balconies of the terraces to provide fire separation between the retail and residential uses.

The works are to be designed in consultation with a qualified heritage architect to ensure the contributory features of the terraces are not adversely impacted by the works listed above. Amended plans are to be submitted to and approved by Council's Area Coordinator Planning Assessments / Area Planning Manager prior to the issue of any Construction Certificate.

(5) GENERAL HERITAGE

- (a) The proposed works are to be carried out in a manner that minimises demolition, alterations and new penetrations/fixings to the significant fabric of the existing building which is listed as a Heritage Item.
- (b) New services are to be surface mounted rather than chased-in to existing walls to minimise impact on heritage fabric.
- (c) Appropriately qualified tradespersons (as appropriate) are to be commissioned who are skilled in traditional building and engineering trades to carry out the proposed scope of works.
- (d) Where internal partitions meet external walls they must abut window mullions, columns or other such building elements and not glazing.

(6) MATERIALS FOR MAKING GOOD

New materials for making good and repairs, are to match the existing in terms of colours, finishes, sizes, profile and properties.

(7) FLOOR SPACE RATIO

The following applies to Floor Space Ratio:

- (a) The Floor Space Ratio for the development use must not exceed 2.5:1 calculated in accordance with Sydney Local Environmental Plan 2012. For the purposes of the calculation of FSR, the maximum Gross Floor Area is 561sqm.
- (b) Prior to an Occupation Certificate being issued, a Registered Surveyor must provide certification of the total and component Gross Floor Areas (by use) in the development, utilising the definition under Sydney Local Environmental Plan 2012, applicable at the time of development consent, to the satisfaction of the Principal Certifier.

(8) EXTERNAL SHADE SCREENS

Operable shade screens are to be provided to north facing windows of apartments 2-4. The screens are to be compatible with the architecture of the building and be of high quality material. Details of the screens are to be approved by Council's Area Coordinator Planning Assessments / Area Planning Manager prior to any Construction Certificate being issued.

(9) CONSOLIDATION OF AIR CONDITIONING UNITS IN THE BASEMENT

Approval is not granted for the installation of individual air conditioning units to the facade or balconies of the building.

If air conditioning units are to be provided for the residential or retail units, they must be located within a consolidated area of the basement to the satisfaction of the Principal Certifier.

(10) MATERIALS AND SAMPLES BOARD

A physical material sample board which specifies all proposed materials, finishes and colours, (including visible rainwater goods and services) keyed to each building elevation must be submitted to and approved by Council's Area Coordinator Planning Assessments / Area Planning Manager prior to any Construction Certificate being issued. The materials and samples board must not include generic material or colour descriptions, or use terminology such as 'or similar'.

(11) COMPLIANCE WITH SUBMITTED MATERIALS AND SAMPLES BOARD

The design details of the proposed building facade including all external finishes, colours and glazing must be in accordance with the materials schedule and sample board, and specifications approved under condition 10.

(12) LANDSCAPING OF THE SITE

- (a) A detailed landscape plan, drawn to scale by a qualified landscape architect or landscape designer, must be submitted to and approved by Council's Area Coordinator Planning Assessments / Area Planning Manager prior to the issue of any Construction Certificate for above ground building works. The plan must include:
 - (i) Location of existing and proposed structures on the site including, but not limited to, existing and proposed trees, paved areas, planted areas on slab, planted areas in natural ground, lighting and other features;
 - (ii) Details of earthworks and soil depths including mounding and retaining walls and planter boxes (if applicable). The minimum soil depths for planting on slab must be 1000mm for trees, 450mm for shrubs and 200mm for groundcovers;
 - (iii) Location, numbers, type and supply of plant species, with reference to NATSPEC (if applicable);
 - (iv) Details of planting procedure and maintenance;
 - (v) Details of drainage, waterproofing and watering systems.
- (b) Prior to the issue of any Construction Certificate, a maintenance plan is to be submitted to and approved by the Principal Certifier. The maintenance plan is to be complied with during occupation of the property.

- (c) All landscaping in the approved plan is to be completed prior to an Occupation Certificate being issued.

(13) TIMBER FRONT DORMERS

- (a) The front dormer must use timber joinery and double-hung windows and must be a rectangular, timber framed, vertically proportioned, double hung sash window with a ratio of 1.5:1 measured from base to top of the window frame.
- (b) The dormers must be symmetrically placed on the roof plane.
- (c) The total external width of the dormer including frames must not exceed 1200mm (exclusive of eave overhangs and gutters) and the eave and gable overhang must not exceed 100mm.
- (d) Glazing must not be used in the gable or sides of the dormer.
- (e) Roof materials must match the roof material and the roof pitch must be between 32 degrees and 45 degrees.
- (f) The external joinery must be detailed in a manner appropriate to the style and period of the building.
- (g) The architraves that cover the side walls and boxed window frames should not exceed 150mm in width.

Details of the dormer (at a scale of 1:20) and profile must be submitted to and approved by the Principal Certifier prior to the issue of any Construction Certificate.

(14) WINDOWS LOCATED WITHIN THREE METRES OF A BOUNDARY

Where any window located within proximity of a property boundary requires treatment for fire separation, blade walls not already shown on the plan are not to be constructed without receiving the approval of Council's Area Coordinator Planning Assessments / Area Planning Manager prior to any Construction Certificate being issued. Alternatively, the windows are to be either protected by drenchers or relocated.

(15) GROUND FLOOR HOURS OF OPERATION

The hours of operation for the retail premises are restricted to between 9am and 7pm Monday to Friday, 9am and 2pm Saturday and 9am and 5pm Sunday.

(16) ALIGNMENT LEVELS

- (a) Proposed building floor levels, basement levels, basement car park entry levels and ground levels shown on the approved Development Application plans are indicative only and have not been approved by this consent.

- (b) Prior to a Construction Certificate being issued for any excavation, civil construction, drainage or building work (whichever is earlier), excluding approved preparatory or demolition work, alignment levels for the building and site frontages must be submitted to and approved by Council. The submission must be prepared by a Registered Surveyor and designed by a suitably qualified engineer, must be in accordance with the City of Sydney's *Public Domain Manual* and must be submitted with a completed and Levels and Gradients Approval Application form (available on the City's website).
- (c) These alignment levels, as approved by Council, are to be incorporated into the plans submitted with the application for a Construction Certificate for any civil, drainage and public domain work as applicable under this consent. If the proposed detailed design of the public domain requires changes to any previously approved Alignment Levels, then an amended Alignment Levels submission must be submitted to and approved by Council to reflect these changes prior to a Construction Certificate being issued for public domain work.

(17) PHOTOGRAPHIC RECORD / DILAPIDATION REPORT (PUBLIC DOMAIN)

Prior to an approval for demolition being granted or a Construction Certificate being issued, whichever is earlier, a photographic recording of the public domain site frontages is to be prepared and submitted to Council's satisfaction.

The recording must include clear images of the building facade adjoining the footpath, the footpath, nature strip, kerb and gutter, driveway crossovers and laybacks, kerb ramps, road carriageway, street trees and plantings, parking restriction and traffic signs, and all other existing infrastructure along the street.

The form of the recording is to be as follows:-

- (a) A PDF format report containing all images at a scale that clearly demonstrates the existing site conditions;
- (b) Each image is to be labelled to identify the elements depicted, the direction that the image is viewed towards, and include the name of the relevant street frontage;
- (c) Each image is to be numbered and cross referenced to a site location plan;
- (d) A summary report, prepared by a suitable qualified professional, must be submitted in conjunction with the images detailing the project description, identifying any apparent existing defects, detailing the date and authorship of the photographic record, the method of documentation and limitations of the photographic record;
- (e) Include written confirmation, issued with the authority of both the applicant and the photographer that the City of Sydney is granted a perpetual non-exclusive license to make use of the copyright in all images supplied, including the right to make copies available to third parties as though they were Council images. The signatures of both the applicant and the photographer must be included.

Any damage to the public way including trees, footpaths, kerbs, gutters, road carriageway and the like must immediately be made safe and functional by the applicant. Damage must be fully rectified by the applicant in accordance with the City's standards prior to a Certificate of Completion being issued for Public Domain Works or before an Occupation Certificate is issued for the development, whichever is earlier.

(18) PUBLIC DOMAIN PLAN

- (a) A detailed Public Domain Plan must be prepared by a suitably qualified architect, urban designer, landscape architect or engineer and must be lodged with Council's Public Domain Section and be approved by Council prior to a Construction Certificate being issued for public domain work or above ground building work, whichever is later.
- (b) The Public Domain Plan must document all works required to ensure that the public domain complies with the City of Sydney's *Public Domain Manual*, *Sydney Streets Code* and *Sydney Streets Technical Specification*, including requirements for road pavement, traffic measures, footway pavement, kerb and gutter, drainage, vehicle crossovers, pedestrian ramps, lighting, street trees and landscaping, signage and other public domain elements. If an Alignment Levels condition applies to the development, the Public Domain Plan submission must incorporate the approved Alignment Levels. If the proposed detailed design of the public domain requires changes to any previously approved Alignment Levels, then an amended Alignment Levels submission must be submitted to and approved by Council to reflect these changes prior to a Construction Certificate being issued for public domain work.
- (c) The works to the public domain are to be completed in accordance with the approved Public Domain Plan and Alignment Levels plans and the *Public Domain Manual* before any Occupation Certificate is issued in respect of the development or before the use commences, whichever is earlier.
- (d) A Public Domain Works Deposit will be required for the public domain works, in accordance with the City of Sydney's adopted fees and charges and the *Public Domain Manual*. The Public Domain Works Deposit must be submitted as an unconditional bank guarantee in favour of Council as security for completion of the obligations under this consent.
- (e) Council's Public Domain section must be contacted to determine the guarantee amount prior to lodgement of the guarantee. The guarantee must be lodged with Council prior to a Construction Certificate being issued.
- (f) The Bank Guarantee will be retained in full until all Public Domain works are completed and the required certifications, warranties and works-as-executed documentation are submitted and approved by Council in writing. On satisfying the above requirements, 90% of the total securities will be released. The remaining 10% will be retained for the duration of the specified Defects Liability Period.

(19) PUBLIC DOMAIN WORKS - HOLD POINTS AND HANDOVER

- (a) Prior to a Construction Certificate being issued for public domain work, including civil, drainage and subsurface works, a set of hold points for approved public domain, civil and drainage work is to be determined with and approved by the City's Public Domain section in accordance with the City of Sydney's *Public Domain Manual* and *Sydney Streets Technical Specification*.
- (b) Prior to a Certificate of Completion being issued for public domain works and before the issue of any Occupation Certificate for the development or before the use commences, whichever is earlier, electronic works-as-executed (as-built) plans and documentation, certified by a suitably qualified, independent professional must be submitted to and accepted by Council for all public domain works. Completion and handover of the constructed public domain works must be undertaken in accordance with the City of Sydney's *Public Domain Manual* and *Sydney Streets Technical Specification*, including requirements for as-built documentation, certification, warranties and the defects liability period.

(20) STORMWATER AND DRAINAGE

- (a) Prior to an approval or Construction Certificate being issued for excavation, civil construction, drainage or building work (whichever is earlier), excluding approved preparatory or demolition work a detailed drainage engineering design, calculations and design for the stormwater overland flow path for the development must be:
 - (i) prepared by a suitably qualified hydraulic or civil engineer to show the proposed method of collection and disposal of stormwater; and
 - (ii) prepared in accordance with the City of Sydney's *Stormwater Drainage Manual*, technical specifications, standards and policies, as amended from time to time; and
 - (iii) submitted to and be approved by the City of Sydney and a copy of the City's letter of approval must be provided to the Principal Certifying Authority.
- (b) For approval of a connection into the City of Sydney's drainage system an "Application for Approval of Stormwater Drainage Connections" must be submitted to the City, together with an application fee in accordance with the City of Sydney's adopted Schedule of Fees and Charges.
 - (i) The application must be approved by the City of Sydney prior to an approval or Construction Certificate being issued for excavation, civil construction, drainage or building work (whichever is earlier), excluding approved preparatory or demolition work.
 - (ii) All proposed connections to the City's underground drainage system require the owner to enter into a Deed of Agreement with the City of Sydney and obtain registration on Title of a Positive Covenant prior to an Occupation Certificate being issued, including an Interim Occupation Certificate.

On-site Detention

- (c) The requirements of Sydney Water with regard to the on-site detention of stormwater must be ascertained and complied with.
 - (i) Evidence of the approval by Sydney Water of the detailed design of the on-site detention must be submitted to and be accepted by the City of Sydney and a copy of the City's letter of acceptance must be provided to the Principal Certifying Authority prior to a Construction Certificate being issued, excluding for any approved preparatory, demolition or excavation works.
 - (ii) Prior to the issue of an Occupation Certificate, including an Interim Occupation Certificate, a Positive Covenant must be registered on the property title for all drainage systems involving On-Site Detention (OSD) to ensure maintenance of the approved OSD system regardless of the method of connection.

Stormwater Quality Assessment

- (d) Prior to a Construction Certificate being issued for any excavation, civil construction, drainage or building work (whichever is earlier), but excluding approved preparatory or demolition work, a stormwater quality assessment must be undertaken and must be approved by City of Sydney and a copy of the City's letter of approval must be provided to the Principal Certifying Authority.

A stormwater quality assessment must be undertaken by a suitably qualified drainage engineer to demonstrate how the development will be designed to ensure that the flow of post-development pollutants from the site due to stormwater will be reduced. The water quality assessment must be submitted to and be approved by the City of Sydney and a copy of the City's letter of approval must be provided to the Principal Certifying Authority prior to a Construction Certificate being issued for any excavation, civil construction, drainage or building work (whichever is earlier), excluding approved preparatory or demolition work.

Prior to the issue of an Occupation Certificate, maintenance schedules of the proposed water sensitive urban design and drainage measures must be submitted to and be approved by the Principal Certifying Authority and a copy provided to the City of Sydney.

Completion / Works-as-Executed Documentation

- (e) Prior to a Certificate of Completion being issued by the City of Sydney for stormwater drainage works:
 - (i) All works for the disposal of stormwater and drainage are to be implemented in accordance with the approved plans, City of Sydney technical specifications. Standards and policies, approval letters and the requirements of this consent.

- (ii) a Works-As-Executed survey, prepared, signed and dated by a Registered Surveyor, must be submitted to and be accepted by the City of Sydney. The plan must be overlaid on a copy of the approved stormwater drainage plans issued with the Construction Certificate, with variations to locations, dimensions, levels and storage volumes clearly marked.
 - (iii) Electronic works-as-executed (as-built) details, certifications, warranties, inspection reports (including Closed Circuit Television reports) and associated documentation for the completed work must be prepared and certified by a suitably qualified hydraulic engineer, in accordance with the requirements of the City of Sydney's technical specifications, the *Public Domain Manual*, the *Stormwater Drainage Manual*, the conditions of this consent and all letters of approval issued by the City of Sydney for works in the public domain, and must be submitted to and be accepted by the City of Sydney.
- (f) Prior to the issue of the first Occupation Certificate, including an Interim Occupation Certificate, or before the use commences (whichever is earlier):
- (i) A copy of the City's Certificate of Completion for all stormwater and drainage work undertaken in the public domain must be provided to the Principal Certifying Authority;
 - (ii) a Works-As-Executed survey, must be prepared, signed, dated and certified by a Registered Surveyor and must be submitted to and be accepted by the Principal Certifying Authority. The Works-as-Executed plan must be overlaid on a copy of the approved stormwater drainage plans issued with the Construction Certificate, with variations to locations, dimensions, levels and storage volumes clearly marked;
 - (iii) a Hydraulic Compliance Certificate and Calculation Sheet must be prepared by a suitably qualified hydraulic engineer (minimum NER), showing approved versus installed hydraulic calculations, and must be submitted to and be accepted by the Principal Certifying Authority;
 - (iv) evidence of Sydney Water's acceptance of the Works-As-Executed documentation, certification and Hydraulic Compliance Certificate and Calculation Sheet must be provided to the Principal Certifying Authority;
 - (v) The Principal Certifying Authority must submit a copy of the Works-As-Executed plans, certifications, Hydraulic Compliance Certificate and Calculation Sheet to the City of Sydney.

(21) ALCOVE LIGHTING

The proposed alcove(s) must be fitted with a sensor-activated vandal proof security light. The light shall be maintained in good working order to Council's satisfaction. The intensity, colour, and illumination must be varied if, at any time in the opinion of the consent authority, adverse impact or Obtrusive Light in accordance with the definition in Australian Standard AS4282-1997 Control of the obtrusive effects of outdoor is being caused to the amenity of the area.

(22) NOISE

- (a) Noise from commercial plant and industrial development must not exceed a project amenity/intrusiveness noise level or maximum noise level in accordance with relevant requirements of the NSW EPA [Noise Policy for Industry 2017 \(NPfl\)](#) unless agreed to by the City's Area Planning Manager. Further:
- (i) Background noise monitoring must be carried out in accordance with the long-term methodology in [Fact Sheet B](#) of the NPfl unless otherwise agreed by the City's Area Planning Manager.
 - (ii) Commercial plant is limited to heating, ventilation, air conditioning, refrigeration and energy generation equipment.
- (b) An $L_{Aeq,15 \text{ minute}}$ (noise level) emitted from the development must not exceed the $L_{A90, 15 \text{ minute}}$ (background noise level) by more than 3dB when assessed inside any habitable room of any affected residence or noise sensitive commercial premises at any time. Further:
- (i) The noise level and the background noise level shall both be measured with all external doors and windows of the affected residence closed.
 - (ii) Background noise measurements must not include noise from the development but may include noise from necessary ventilation at the affected premise.
- (c) Corrections in [Fact Sheet C](#) of the NPfl are applicable to relevant noise from the development measured in accordance with this condition, however duration corrections are excluded from commercial noise.

(23) BICYCLE PARKING AND END OF TRIP FACILITIES

- (a) The minimum number of bicycle parking spaces to be provided for the development must comply with the table below.

Bicycle Parking Type	Number	Requirements
Residential	4	Spaces must be Class 2 bicycle facilities

Notes:

- (i) If a basement storage area on title that is large enough to store a bike and is no smaller than a class 1 bike locker this can be counted as a space.
- (b) The layout, design and security of bicycle facilities must comply with the minimum requirements of Australian Standard AS 2890.3 Parking Facilities Part 3: Bicycle Parking Facilities. The details must be submitted to and approved by the Principal Certifier confirming prior to the Construction Certificate being issued.

(24) WASTE AND RECYCLING MANAGEMENT

- (a) A Waste and Recycling Management Plan is to be submitted to and approved by Council's Area Coordinator Planning Assessments / Area Planning Manager prior to a Construction Certificate being issued. The plan must comply with the Council's *Guidelines for Waste Management in New Developments 2018*. All requirements of the approved Waste and Recycling Management Plan must be implemented during construction of the development.
- (b) The building must incorporate designated areas or separate garbage rooms constructed in accordance with Council's *Guidelines for Waste Management in New Developments 2018*, to facilitate the separation of commercial waste and recycling from residential waste and recycling.

UPON COMPLETION OF THE DEVELOPMENT

- (c) Prior to an Occupation Certificate being issued or the use commencing, whichever is earlier, the Principal Certifier must obtain Council's approval of the waste and recycling management facilities provided in the development and ensure arrangements are in place for domestic waste collection by Council.

(25) WASTE ROOM AND WASTE COLLECTION

- (a) The nominated waste and recycling storage areas must be constructed to meet the relevant conditions required by the City's Waste Minimisation in New Developments Policy 2005.
- (b) A minimum 8m² in dedicated space(s) for residential bulky waste storage must be provided.
- (c) Commercial waste and recycling receptacles and bulky waste must be stored on the property at all times and must not be placed on kerbside for collection.
- (d) Commercial waste and recycling receptacles must be stored in a separated area from residential waste and recycling receptacles and commercial tenants must not have access to residential bins or waste rooms.
- (e) Unimpeded access must be provided for collection from the waste and recycling storage location(s) at all times.

- (f) Waste and recycling containers will not be supplied until construction in developments is completed unless otherwise organised with waste services.
- (g) The development must have a residential rating or applied for a residential rating prior to a City Of Sydney waste service commencing.
- (h) Commercial and residential waste service collections and waste storage arrangements must be conducted in accordance with the City's Waste Policy – Local Approvals Policy for Managing Waste in Public Places (2013).
- (i) Waste receptacles or garbage bins must not be stored on the public footways adjoining the development prior to collection or at any other time

(26) WASTE AND RECYCLING COLLECTION CONTRACT

- (a) The collection of waste and recycling must only occur between 7.00am and 8.00pm weekdays and 9.00am and 5.00pm weekends and public holidays, to avoid noise disruption to the surrounding area.
- (b) Prior to an Occupation Certificate being issued and/or commencement of the use, whichever is earlier, the building owner must ensure that there is a contract with a licensed contractor for the removal of all waste. No garbage is to be placed on the public way, e.g. footpaths, roadways, plazas, reserves, at any time.

(27) LAND SUBDIVISION

Any proposal to subdivide the site, including any stratum subdivision of the building, will require a separate application to Council to obtain development consent for the proposal and subsequent issue of the Subdivision Certificate under Section 109J of the *Environmental Planning and Assessment Act 1979*.

(28) STRATA SUBDIVISION

Any proposal for strata subdivision of the site will require development consent and therefore the lodgment of a separate development application or complying development application, and subsequent approval from Council, or an accredited certifier, of the Strata Plan and issue of a Strata Certificate under the *Strata Schemes Development Act 2015*.

(29) CONSTRUCTION TRAFFIC MANAGEMENT PLAN

- (a) A Construction Traffic Management Plan (CTMP) must be submitted to and approved by Council prior to a Construction Certificate being issued.
- (b) The CTMP must be prepared in accordance with the City's guidelines found at:

<https://www.cityofsydney.nsw.gov.au/business/doing-business-with-us/business-responsibilities/traffic-management/construction-traffic-management-plans>

- (c) The development must be undertaken in accordance with the approved CTMP.

(30) DEMOLITION, EXCAVATION AND CONSTRUCTION MANAGEMENT

- (a) Prior to the commencement of demolition and/or excavation work the following details must be submitted to and be approved by the Principal Certifier:
 - (i) Plans and elevations showing distances of the subject building from the location of adjoining and common/party walls, and (where applicable) the proposed method of facade retention.
 - (ii) A Demolition Work Method Statement prepared by a licensed demolisher who is registered with the Work Cover Authority. (The demolition by induced collapse, the use of explosives or on-site burning is not permitted.)
 - (iii) An Excavation Work Method Statement prepared by an appropriately qualified person.
 - (iv) A Waste Management Plan for the demolition and or excavation of the proposed development.
 - (v) Plans and elevations showing the location, construction and installation of temporary site fencing and any temporary structures used in connection with the construction of the development.

Note: Temporary structures, including hoardings and scaffolding, proposed for erection on City-owned and controlled land (footways and roadways), must comply with the City's *Guidelines for Hoardings and Scaffolding* and be approved by Council under the provisions of the Local Government Act 1993 and the Roads Act 1993 prior to installation.

- (b) Such statements must, where applicable, be in compliance with AS2601-2001 Demolition of Structures, the *Work, Health and Safety Act 2011* and Regulation; Council's *Policy for Waste Minimisation in New Developments 2005*, the *Waste Avoidance and Resource Recovery Act 2001*, and all other relevant acts and regulations and must include provisions for:
 - (i) A Materials Handling Statement for the removal of refuse from the site in accordance with the *Waste Avoidance and Resource Recovery Act 2001*.
 - (ii) The name and address of the company/contractor undertaking demolition/excavation works.
 - (iii) The name and address of the company/contractor undertaking off site remediation/disposal of excavated materials.
 - (iv) The name and address of the transport contractor.
 - (v) The type and quantity of material to be removed from site.

- (vi) Location and method of waste disposal and recycling.
 - (vii) Proposed truck routes, in accordance with this development consent.
 - (viii) Procedures to be adopted for the prevention of loose or contaminated material, spoil, dust and litter from being deposited onto the public way from trucks and associated equipment and the proposed method of cleaning surrounding roadways from such deposits. (Note: With regard to demolition of buildings, dust emission must be minimised for the full height of the building. A minimum requirement is that perimeter scaffolding, combined with chain wire and shade cloth must be used, together with continuous water spray during the demolition process. Compressed air must not be used to blow dust from the building site).
 - (ix) Measures to control noise emissions from the site.
 - (x) Measures to suppress odours.
 - (xi) Enclosing and making the site safe.
 - (xii) Induction training for on-site personnel.
 - (xiii) Written confirmation that an appropriately qualified Occupational Hygiene Consultant has inspected the building/site for asbestos, contamination and other hazardous materials, in accordance with the procedures acceptable to Work Cover Authority.
 - (xiv) An Asbestos and Hazardous Materials Clearance Certificate by a person approved by the Work Cover Authority.
 - (xv) Disconnection of utilities.
 - (xvi) Fire Fighting. (Fire fighting services on site are to be maintained at all times during demolition work. Access to fire services in the street must not be obstructed).
 - (xvii) Access and egress. (Demolition and excavation activity must not cause damage to or adversely affect the safe access and egress of the subject building or any adjacent buildings).
 - (xviii) Waterproofing of any exposed surfaces of adjoining buildings.
 - (xix) Control of water pollution and leachate and cleaning of vehicles tyres (proposals must be in accordance with the *Protection of the Environmental Operations Act 1997*).
 - (xx) Working hours, in accordance with this development consent.
 - (xxi) Any Work Cover Authority requirements.
- (c) The approved work method statements and a waste management plan as required by this condition must be implemented in full during the period of construction.

(31) STREET TREE PROTECTION

Street trees must be protected in accordance with the Australian Standard 4970 Protection of Trees on Development Sites. All street trees must be protected during the construction works as follows:

- (a) Tree trunk and major limb protection must be undertaken prior to or during the installation of any hoarding or scaffoldings. The protection must be installed by a qualified Arborist (AFQ 2 or 3) and must include:
 - (i) An adequate clearance, minimum 250mm, must be provided between the structure and tree branches, limbs and trunk at all times;
 - (ii) Tree trunk/s and/or major branches, located within 500mm of any hoarding or scaffolding structure, must be protected by wrapped hessian or similar material to limit damage, and
 - (iii) Timber planks (50mm x 100mm or similar) must be placed around tree trunk/s. The timber planks must be spaced at 100mm intervals, and must be fixed against the trunk with tie wire, or strapping. The hessian and timber planks must not be fixed to the tree in any instance, or in any fashion,
 - (iv) Tree trunk and major branch protection is to remain in place for the duration of construction and development works, and must be removed at the completion of the project.
- (b) All hoarding support columns are to be placed a minimum of 300mm from the edge of the existing tree pits/setts, so that no sinking or damage occurs to the existing tree setts. Supporting columns must not be placed on any tree roots that are exposed.
- (c) Materials or goods, including site sheds, must not be stored or placed:
 - (i) around or under the tree canopy; or
 - (ii) within two (2) metres of tree trunks or branches of any street trees.
- (d) Protective fencing (1.8 metre chain wire mesh fencing) must be erected on top of the hoarding [Tree Management Team to insert location of hoarding and affected trees] to protect branches during the construction works.
- (e) Any damage sustained to street tree/s as a result of the erection of hoardings, scaffolding, or due to the loading/unloading of vehicles adjacent the site, must be immediately reported to the Council's Street Tree Contract Coordinator on 9265 9333, in order to determine the appropriate action for maintaining the health and structural integrity of any damaged street tree.

(32) DEMOLITION, EXCAVATION AND CONSTRUCTION NOISE AND VIBRATION MANAGEMENT PLAN

A site specific noise management plan shall be submitted to the Council for comment and approval prior to issue of any Construction Certificate.

The Plan must be prepared by a suitably qualified person who possesses the qualifications to render them eligible for membership of the Australian Acoustic Society, Institution of Engineers Australia or the Australian Association of Acoustic Consultants.

The plan must include but not be limited to the following:-

- (a) identification of noise sensitive receivers near to the site.
- (b) A prediction as to the level of noise impact likely to affect the nearest noise sensitive receivers from the use and proposed number of high noise intrusive appliances intended to be operated onsite. A statement should also be submitted outlining whether or not predicted noise levels will comply with the noise criteria stated within the *City of Sydney Construction Hours /Noise Code of Practice 1992* for the typical construction hours of 07.00am to 7.00pm. Where resultant site noise levels are likely to be in exceedance of this noise criteria then a suitable proposal must be given as to the duration and frequency of respite periods that will be afforded to the occupiers of neighbouring property.(c) A representative background noise measurement ($L_{A90, 15 \text{ minute}}$) should be submitted, assessed in the vicinity of any potentially affected receiver locations and measured in accordance with AS 1055:1.2.1997.(d) Confirmation of the level of community consultation that has/is and will be undertaken with Building Managers/ occupiers of the main adjoining noise sensitive properties likely to be most affected by site works and the operation of plant/machinery particularly during the demolition and excavation phases.(e) Confirmation of noise monitoring methodology that is to be undertaken during the main stages of work at neighbouring noise sensitive properties in order to keep complaints to a minimum and to ensure that noise from site works complies with the noise criteria contained within City's Construction Noise Code.(f) What course of action will be undertaken following receipt of a complaint concerning offensive noise.(g) Details of any noise mitigation measures that have been outlined by an acoustic consultant or otherwise that will be deployed on site to reduce noise impacts on the occupiers of neighbouring noise sensitive property to a minimum.(h) What plant and equipment is to be used on site, the level of sound mitigation measures to be undertaken in each case and the criteria adopted in their selection taking into account the likely noise impacts on the occupiers of neighbouring property and other less intrusive technologies available.

(33) COMPLIANCE WITH DEMOLITION, EXCAVATION & CONSTRUCTION NOISE AND VIBRATION MANAGEMENT PLAN

- (a) All works conducted on site which form part of this development must be carried out in accordance with the submitted Demolition, Excavation and Construction Management Plan approved under condition 34.

- (b) Where all such control measures have been implemented and the resultant noise and/ or vibration levels at any sensitive receiver still exceed the council's applicable criteria stated in the Construction Hours/Noise Code 1992 and are giving rise to sustained complaints then the contractor must provide regular, appropriate and sustained periods of respite in consultation with Council's Health and Building unit. Approval to vary the authorised noise and vibration levels must be received in writing by the proponent from Council prior to activities being undertaken that exceed sanctioned emission levels. (Use where respite periods not specified under the approved DEC NMP)

Such periods must be set and agreed to by Council's Health and Building Unit.

SCHEDULE 1B

PRIOR TO CONSTRUCTION CERTIFICATE/COMMENCEMENT OF WORK/HEALTH AND BUILDING

(34) DEFECTS LIABILITY PERIOD – PUBLIC DOMAIN WORKS

All works to the City's public domain, including rectification of identified defects, are subject to a 12 month defects liability period from the date of final completion. The date of final completion will be nominated by Council on the Certificate of Completion for public domain works.

(35) DRAINAGE AND SERVICE PIT LIDS

Drainage and service pit lids throughout the public domain shall be heelguard and bicycle safe, finish flush with the adjacent pavement to avoid trip hazards and be clear of obstructions for easy opening and cleaning. Pit lids shall be in accordance with the *City of Sydney's Sydney Streets Design Code* and *Sydney Streets Technical Specification*. Details of drainage and service pit lids shall be submitted and approved by Council prior to a Construction Certificate being issued for the relevant stage of work.

(36) PUBLIC DOMAIN DAMAGE DEPOSIT

A Public Domain Damage Deposit calculated on the basis of 13 lineal metres of Asphalt site frontage on Foveaux Street and 13 lineal metres of Asphalt site frontage on Sophia Lane must be lodged with Council in accordance with the City of Sydney's adopted Schedule of Fees and Charges. The Public Domain Damage Deposit must be submitted as an unconditional bank guarantee in favour of Council as security for repairing any damage to the public domain in the vicinity of the site.

The guarantee must be lodged with Council prior to an approval for demolition being granted or a Construction Certificate being issued, whichever is earlier.

The Bank Guarantee will be retained in full until the final Occupation Certificate has been issued and any rectification works to the footway and Public Domain are completed to Council's satisfaction. On satisfying the above requirements 90% of the total securities will be released, with the remaining 10% to be retained for the duration of the 12 months Defect Liability Period.

(37) TACTILE GROUND SURFACE INDICATORS AND HANDRAILS

All tactile ground surface indicators, handrails and other elements required to provide access into the building / property must be located entirely within the private property boundary.

(38) PUBLIC DOMAIN LIGHTING

- (a) Prior to a Construction Certificate for public domain works or above ground building works being issued, whichever is later, a detailed Public Domain Lighting Plan for pedestrian and street lighting in the public domain must be prepared by a suitably qualified, practicing lighting engineer or lighting designer and must be submitted to and approved by Council. The Lighting Plan must be prepared in accordance with the City of Sydney's Sydney Lights Design Code, Sydney Streets Code, *Sydney Streets Technical Specification* and *Public Domain Manual* and must include the following:
- (i) Vertical and horizontal illuminance plots for the public domain lighting design to demonstrate compliance with all relevant Australian Standards and to meet the lighting categories and requirements specified by the City;
 - (ii) The location, type and category of existing and proposed lights, including details of luminaire specifications, required to ensure compliance with City policies and Australian Standards;
 - (iii) Footing locations and structural details;
 - (iv) Location and details of underground electrical reticulation, connections and conduits;
 - (v) Certification by a suitably qualified, practicing lighting engineer or lighting designer to certify that the design complies with City policies and all relevant Australian Standards including AS 1158, AS 3000 and AS4282;
 - (vi) Structural certification for footing designs by a suitably qualified, practicing engineer to certify that the design complies with City of Sydney policies and Australian Standards.
- (b) The public domain lighting works are to be completed in accordance with the approved plans and the City of Sydney's *Public Domain Manual* before any Occupation Certificate is issued in respect of the development or before the use commences, whichever is earlier.

(39) SYDNEY WATER CERTIFICATE

A Section 73 Compliance Certificate under the Sydney Water Act 1994 must be obtained from Sydney Water Corporation.

Application must be made through an authorised Water Servicing Coordinator. Please refer to the Building Developing and Plumbing section on the web site www.sydneywater.com.au then refer to "Water Servicing Coordinator" under "Developing Your Land" or telephone 13 20 92 for assistance.

Following the submission of the application a "Notice of Requirements" will advise of water and sewer infrastructure to be built and charges to be paid. Please make early contact with the Coordinator, since building of water/sewer infrastructure can be time consuming and may impact on other services and building, driveway or landscape design.

The Section 73 Certificate must be submitted to Council or the Principal Certifier prior to an Occupation Certificate or subdivision/strata certificate being issued.

(40) ACCESS AND FACILITIES FOR PERSONS WITH DISABILITIES

The building must be designed and constructed to provide access and facilities for people with a disability in accordance with the *Building Code of Australia*.

If, in complying with this condition, amendments to the development are required, the design changes must be submitted to and approved by Council prior to a Construction Certificate being issued.

(41) ACCESS FOR PERSONS WITH DISABILITIES - OFFICE / SHOP FITOUTS

In accordance with the *Building Code of Australia* the proposed office / shop layout and design must comply with Australian Standard 1428.1: General requirements for access - New building works.

(42) DILAPIDATION REPORT

Subject to the receipt of permission of the affected landowner, dilapidation report/s of adjoining buildings are to be prepared by an appropriately qualified practising structural engineer and submitted for the approval of the Principal Certifier:

- (a) prior to the commencement of demolition/excavation works; and
- (b) on completion of construction demolition/excavation works.

(43) EROSION AND SEDIMENT CONTROL - LESS THAN 250SQM

Where less than 250 square metres are being disturbed, no formal plan is required however, the site is to be provided with sediment control measures and these must be implemented so that sediment, including soil, excavated material, building material or other materials cannot fall, descend, percolate, be pumped, drained, washed or allowed to flow to the street, stormwater system or waterways.

(44) ROAD OPENING PERMIT

A separate Road Opening Permit under Section 138 of the *Roads Act 1993* must be obtained from Council prior to the commencement of any:

- (a) Excavation in or disturbance of a public way, or
- (b) Excavation on land that, if shoring were not provided, may disturb the surface of a public road (including footpath).

(45) APPLICATION FOR HOARDINGS AND SCAFFOLDING INSTALLED ON OR ABOVE A PUBLIC ROAD AND OPERATING HOISTING DEVICES INCLUDING BUILDING MAINTENANCE UNITS OVER A PUBLIC ROAD

- (a) A separate application under Section 68 of the *Local Government Act 1993* and Section 138 of the *Roads Act 1993* is to be made to Council to erect a hoarding and/or scaffolding (temporary structures) on or above a public road (footway and/or roadway).
- (b) Where an approval (Permit) is granted allowing the placement of temporary structures on or above a public road the structures must comply fully with Council's *Hoarding and Scaffolding Policy; Guidelines for Hoardings and Scaffolding*; and the conditions of approval (Permit) granted including:
 - (i) maintaining a current and valid approval for the full duration that the temporary structure/s is in place;
 - (ii) maintaining temporary structure/s in a structurally sound and stable condition for the full duration of installation (Clause 2.11.1);
 - (iii) bill posters and graffiti being removed within 24 hours of their placement (Clause 2.11.2);
 - (iv) maintaining temporary structures and the public place adjoining the work site in a clean and tidy condition including repainting and/or repair of graphics (Clauses 2.11.1, 2.11.4, 2.14.1 and 3.9.3);
 - (v) maintaining a watertight deck (Type B hoardings) to prevent liquids including rainwater, falling onto the footway/roadway surfaces (Clauses 3.9.1 and 3.9.4);
 - (vi) approved site sheds on the decks of a Type B hoarding being fully screened from the public place (Clause 3.9.5);
 - (vii) material and equipment not being placed or stored on the deck of Type B hoardings, unless specifically approved by Council (Clause 3.9.4);
 - (viii) providing and maintaining operational artificial lighting systems under Type B hoardings including at high-bay truck entry points (Clause 3.9.9); and
 - (ix) ensuring all required signage is provided and maintained (Clauses 3.9.3, 3.9.6, 3.9.8, 3.10.1 and 4.2).

If it is proposed to operate a hoisting device including a building maintenance unit above a public road which swings, hoists material/equipment and/or slews any part of the device over the public road, a separate application under Section 68 of the *Local Government Act 1993* and Section 138 of the *Roads Act 1993* must be made to Council to obtain approval.

Note: 'Building maintenance unit' means a power-operated suspended platform and associated equipment on a building specifically designed to provide permanent access to the faces of the building for maintenance (*Work Health and Safety Regulation 2011*).

(46) WORKS REQUIRING USE OF A PUBLIC PLACE

Where construction/building works require the use of a public place including a road or footpath, approval under Section 138 of the *Roads Act 1993* is to be obtained from Council prior to the commencement of work. Details of any barricade construction, area of enclosure and period of work are required to be submitted to the satisfaction of Council.

(47) ELECTRICITY SUBSTATION

If required by the applicable energy supplier, the owner must dedicate to the applicable energy supplier, free of cost, an area of land within the development site, but not in any landscaped area or in any area visible from the public domain, to enable an electricity substation to be installed. The size and location of the substation is to be submitted for approval of Council and Ausgrid, prior to a Construction Certificate being issued or the commencement of the use, whichever is earlier.

(48) TELECOMMUNICATIONS IN NEW DEVELOPMENTS

Prior to the issue of the Subdivision or Construction Certificate in connection with a development, the developer (whether or not a constitutional corporation) is to provide evidence satisfactory to the Principal Certifier that arrangements have been made for:

- (a) the installation of fibre-ready facilities to all individual lots and/or premises in a real estate development project so as to enable fibre to be readily connected to any premises that is being or may be constructed on those lots. Demonstrate that the carrier has confirmed in writing that they are satisfied that the fibre ready facilities are fit for purpose; and
- (b) the provision of fixed-line telecommunications infrastructure in the fibre-ready facilities to all individual lots and/or premises in a real estate development project demonstrated through an agreement with a carrier.

Note: real estate development project has the meanings given in section 372Q of the Telecommunications Act.

(49) TELECOMMUNICATIONS PROVISIONS

- (a) Appropriate space and access for ducting and cabling is to be provided within the plant area and to each apartment within the building within for a minimum of three telecommunication carriers or other providers of broad-band access by ground or satellite delivery. The details must be submitted for the approval of the Principal Certifier prior to a Construction Certificate being issued.

- (b) A separate DA must be submitted prior to the installation of any external telecommunication apparatus, or the like.

(50) UTILITY SERVICES

To ensure that utility authorities are advised of the development:

- (a) Prior to the issue of any Construction Certificate a survey is to be carried out of all utility services within and adjacent to the site including relevant information from utility authorities and excavation if necessary, to determine the position and level of services.
- (b) Prior to the commencement of work the applicant is to obtain written approval from the utility authorities (e.g. Energy Australia, Sydney Water, and Telecommunications Carriers) in connection with the relocation and/or adjustment of the services affected by the construction of the underground structure. Any costs in the relocation, adjustment or support of services are to be the responsibility of the developer.

SCHEDULE 1C

DURING CONSTRUCTION/PRIOR TO OCCUPATION/COMPLETION

(51) OCCUPATION CERTIFICATE TO BE SUBMITTED

An Occupation Certificate must be obtained from the Principal Certifier and a copy submitted to Council prior to commencement of occupation or use of the whole or any part of a new building, an altered portion of, or an extension to an existing building.

(52) HOURS OF WORK AND NOISE

The hours of construction and work on the development must be as follows:

- (a) All work, including building/demolition and excavation work, and activities in the vicinity of the site generating noise associated with preparation for the commencement of work (eg. loading and unloading of goods, transferring of tools etc) in connection with the proposed development must only be carried out between the hours of 7.30am and 5.30pm on Mondays to Fridays, inclusive, and 7.30am and 3.30pm on Saturdays, with safety inspections being permitted at 7.00am on work days, and no work must be carried out on Sundays or public holidays.
- (b) All work, including demolition, excavation and building work must comply with the City of Sydney Code of Practice for Construction Hours/Noise 1992 and Australian Standard 2436 - 2010 Guide to Noise Control on Construction, Maintenance and Demolition Sites.
- (c) Notwithstanding the above, the use of a crane for special operations, including the delivery of materials, hoisting of plant and equipment and erection and dismantling of on site tower cranes which warrant the on-street use of mobile cranes outside of above hours can occur, subject to a permit being issued by Council under Section 68 of the Local Government Act 1993 and/or Section 138 of the Roads Act 1993.

Note: Works may be undertaken outside of hours, where it is required to avoid the loss of life, damage to property, to prevent environmental harm and/or to avoid structural damage to the building. Written approval must be given by the Construction Regulation Unit, prior to works proceeding

The *City of Sydney Code of Practice for Construction Hours/Noise 1992* allows extended working hours subject to the approval of an application in accordance with the Code and under Section 4.55 of the *Environmental Planning and Assessment Act 1979*.

(53) BUILDING HEIGHT

- (a) The height of the building must not exceed RL 52.28 (AHD) to the top of the building.
- (b) Prior to an Occupation Certificate being issued, a Registered Surveyor must provide certification that the height of the building accords with (a) above, to the satisfaction of the Principal Certifier.

(54) BASIX

All commitments listed in each relevant BASIX Certificates (935533M-04 and A339525_02) for the development must be fulfilled prior to an Occupation Certificate being issued.

(55) LOADING AND UNLOADING DURING CONSTRUCTION

The following requirements apply:

- (a) All loading and unloading associated with construction activity must be accommodated on site, where possible.
- (b) If, it is not feasible for loading and unloading to take place on site, a Works Zone on the street may be considered by Council.
- (c) A Works Zone may be required if loading and unloading is not possible on site. If a Works Zone is warranted an application must be made to Council at least 8 weeks prior to commencement of work on the site. An approval for a Works Zone may be given for a specific period and certain hours of the days to meet the particular need for the site for such facilities at various stages of construction. The approval will be reviewed periodically for any adjustment necessitated by the progress of the construction activities.
- (d) Where hoisting activity over the public place is proposed to be undertaken including hoisting from a Works Zone, a separate approval under Section 68 of the Local Government Act 1993 must be obtained.

(56) NO OBSTRUCTION OF PUBLIC WAY

The public way must not be obstructed by any materials, vehicles, refuse, skips or the like, under any circumstances. Non-compliance with this requirement will result in the issue of a notice by Council to stop all work on site.

(57) STREET NUMBERING – SINGLE DWELLINGS/MINOR DEVELOPMENT

Prior to an Occupation Certificate being issued, a street number must be clearly displayed at in accordance with the *Policy on Numbering of Premises within the City of Sydney*. If new street numbers or a change to street numbers is required, a separate application must be made to Council.

(58) COVERING OF LOADS

All vehicles involved in the excavation and/or demolition process and departing the property with demolition materials, spoil or loose matter must have their loads fully covered before entering the public roadway.

(59) ARCHAEOLOGICAL DISCOVERY DURING EXCAVATION

- (a) Should any relics be unexpectedly discovered on the site during excavation, all excavation or disturbance to the area is to stop immediately and the Heritage Council of NSW should be informed in accordance with section 146 of the Heritage Act 1977.
- (b) Should any Aboriginal objects be unexpectedly discovered then all excavation or disturbance of the area is to stop immediately and NSW Government Office of Environment and Heritage is to be informed in accordance with Section 89A of the *National Parks and Wildlife Act 1974*
- (c) Should any archaeological remains or Aboriginal objects be discovered, a copy of recording of the finds and the final archaeological summary report is to be submitted to Council prior to the Occupational Certificate;
- (d) if the discovery is on Council's land, Council must be informed.

(60) SUBMISSION OF ELECTRONIC CAD MODELS PRIOR TO OCCUPATION CERTIFICATE

- (a) Prior to an Occupation Certificate being issued, an accurate 1:1 electronic CAD model of the completed development must be submitted to Council for the electronic Visualisation City Model.
- (b) The data required to be submitted within the surveyed location must include and identify:
 - (i) building design above and below ground in accordance with the development consent;
 - (ii) all underground services and utilities, underground structures and basements, known archaeological structures and artefacts;
 - (iii) a current two points on the site boundary clearly marked to show their Northing and Easting MGA (Map Grid of Australia) coordinates, which must be based on Established Marks registered in the Department of Lands and Property Information's SCIMS Database with a Horizontal Position Equal to or better than Class C.

The data is to be submitted as a DGN or DWG file on a Compact Disc. All modelling is to be referenced to the Map Grid of Australia (MGA) spatially located in the Initial Data Extraction file.

- (c) The electronic model must be constructed in accordance with the City's 3D CAD electronic model specification. The specification is available online at <http://www.cityofsydney.nsw.gov.au/development/application-guide/application-process/model-requirements> Council's Modelling staff should be consulted prior to creation of the model. The data is to comply with all of the conditions of the Development Consent.

SCHEDULE 2

PRESCRIBED CONDITIONS

The prescribed conditions in accordance with Division 8A of the *Environmental Planning and Assessment Regulation 2000* apply:

- Clause 98 Compliance with *Building Code of Australia* and insurance requirements under the *Home Building Act 1989*
- Clause 98A Erection of signs
- Clause 98B Notification of *Home Building Act 1989* requirements
- Clause 98C Conditions relating to entertainment venues
- Clause 98D Conditions relating to maximum capacity signage
- Clause 98E Conditions relating to shoring and adequacy of adjoining property

Refer to the NSW State legislation for full text of the clauses under Division 8A of the *Environmental Planning and Assessment Regulation 2000*. This can be accessed at: <http://www.legislation.nsw.gov.au>