


Signs		Approximate Speed Of Traffic Km/h	Recommended Taper Length In Meters		
			Traffic Control At Beginning Of Taper	Lateral Shift Taper	Merge Taper
Size	A	45 Or Less	15	0	15
Spacing	D	46 - 55	15	15	30
		56 - 65	30	30	60
Advance warning area to transition area.	D	66 - 75	N/A	70	115
		76 - 85	N/A	80	130
D = Speed Limit (In Meters)		86 - 95	N/A	90	145
		96 - 105	N/A	100	160
Class 2 reflective signs required for Day and Class 1 reflective signs for night		Greater than 105	N/A	110	180

NOTES:

1. ALL SIGNAGE TO BE INSTALLED IN ACCORDANCE WITH RMS "TRAFFIC CONTROL AT WORKSITES" MANUAL AND AS1742.3.
2. ALL SIGNAGE AND DELINEATION MUST BE INSTALLED BY RMS CERTIFIED TRAFFIC CONTROLLER(S) ONLY.



Date: 10/04/2019 **Author:** Herme Caldeira **Project:** 437-443 Wattle St - Ultimo
Client: Heworth Construction **Ticket Number:** 0051831265 **Herme F B Caldeira TCP No.:** 0004
SCALE: NOT TO SCALE

Comments:
 Trenching works (Storm water) within Blackwattle Ln. Road closure required with traffic controllers on duty to monitor works area and to maintain driveway access for residents.

NSW Transport Roads & Maritime Services

Prepare a Work Zone Traffic Management Plan
 Card No. 0051831265

This qualification enables you to prepare Traffic Management Plans and conduct inspections on Traffic Management Plans.

HERME-FELLIPO BORDONI CALDEIRA

Expiry Date: 11/10/2021

This card is not a proof of identity.