

Attachment A

Recommended Conditions of Consent

2 EDWARD STREET, PYRMONT

D/2019/726

SCHEDULE 1A

APPROVED DEVELOPMENT/DESIGN MODIFICATIONS/COVENANTS AND CONTRIBUTIONS/USE AND OPERATION

Note: Some conditions in Schedule 1A are to be satisfied prior to issue of a Construction Certificate and some are to be satisfied prior to issue of Occupation Certificate, where indicated.

(1) APPROVED DEVELOPMENT

- (a) Development must be in accordance with Development Application No. D/2019/726 dated 10 July 2019 and the following drawings prepared by Gray Puksand:

Drawing Number	Drawing Name	Date
DA01 (Revision DA8)	Ground Floor Plan	16 January 2020
DA02 (Revision DA5)	Basement B1 Plan	12 November 2019
DA03 (Revision DA6)	Ground Floor Main Entry Plan	11 November 2019
DA04 (Revision DA7)	End of Trip Facilities – Ground Level	16 January 2020
DA06 (Revision DA9)	Pirrama Road Elevation	3 December 2019
DA07 (Revision DA6)	Internal Elevations – Entry Lobby	3 December 2019
DA08 (Revision DA4)	Internal Elevations – Entry Lobby Sheet 2	16 October 2019
DA09 (Revision DA5)	Section Plans - Main Entry Lobby	4 November 2019
DA10 (Revision DA3)	Awning Plan and Sections	16 October 2019

Drawing Number	Drawing Name	Date
DA11 (Revision DA3)	Sun Shading Sections	5 November 2019
DA13	Signage Location – Proposed Facade	6 November 2019
DA14	Location Plan	6 November 2019
DA15	Facility Identification Plan FI.01	6 November 2019
DA16	Facility Identification Plan FI.02	6 November 2019
DA17	Facility Identification Plan FI.01	6 November 2019

and as amended by the conditions of this consent.

- (b) In the event of any inconsistency between the approved plans and supplementary documentation, the plans will prevail.

(2) DESIGN MODIFICATIONS

The ground floor plan must be modified as follows:

- (a) The entry and exit driveways from Edward Street must be reversed to maintain the existing condition:
- (i) entry using the northern driveway; and
 - (ii) exit using the southern driveway.

The modifications are to be submitted to and approved by the Accredited Certifier prior to the issue of any Construction Certificate.

(3) LOADING DOCK MANAGEMENT PLAN

- (a) An amended Loading Dock Management Plan, must be submitted to and approved by Council's Area Planning Manager prior to any Occupation Certificate being issued.
- (b) The plan must identify how the loading area (loading dock and service bays) will be managed and used by all building tenants and users of the site.

- (c) The plan shall be managed either by a schedule showing all tenants when they can use the area, or by a register managed on site to allow tenants to reserve a time period for their deliveries. Once approved, this management plan must be provided to all tenants and external users of the loading area.

(4) BICYCLE FACILITIES WAY FINDING PLAN

A way finding parking plan must be submitted showing all the signage to the bicycle facilities from street level. These plans must be submitted to and approved by the Accredited Certifier prior to any Construction Certificate being issued.

(5) SECTION 7.11 CONTRIBUTIONS PAYABLE - CONTRIBUTION TOWARDS PUBLIC AMENITIES – CITY OF SYDNEY DEVELOPMENT CONTRIBUTIONS PLAN 2015 – WEST PRECINCT

Council has identified the development will increase demand for public amenities and facilities. Pursuant to Section 7.11 of the Environmental Planning and Assessment Act, 1979 (as amended), and the City of Sydney Development Contributions Plan 2015 the following monetary contributions are required towards the cost of public amenities.

<u>Contribution Category</u>	<u>Amount</u>
Open Space	\$13,401.01
Community Facilities	\$3,448.44
Traffic and Transport	\$172.42
Stormwater Drainage	\$0.00
Total	\$17,021.87

The City of Sydney will index the above contribution for inflation at the time of payment using the following formula.

$$C_{\text{payment}} = C_{\text{consent}} \times (CPI_{\text{payment}} \div CPI_{\text{consent}})$$

Where:

C_{payment} = Is the contribution at time of payment;

C_{consent} = Is the contribution at the time of consent, as shown above;

CPI_{payment} = Is the Consumer Price Index (All Groups Index) for Sydney published by the Australian Bureau of Statistics that applies at the time of payment; and

CPI_{consent} = Is the Consumer Price Index (All Groups Index) for Sydney at the date the contribution amount above was calculated being 116.5 for the September 2019 quarter.

The contribution must be paid prior to the issue of any Construction Certificate in relation to this development.

Please contact Council's Planning Administration staff at planningsystemsadmin@cityofsydney.nsw.gov.au to request a letter confirming the indexed contribution amount payable.

Once the letter confirming the indexed contribution is obtained, payment may be made at any of the City's Neighbourhood Service Centres or the One Stop Shop at Town Hall House. Acceptable payment methods are EFTPOS (debit card only), cash (up to 10K only), Credit Card (up to 50K only) or a bank cheque made payable to the City of Sydney. Personal or company cheques will not be accepted.

(6) AFFORDABLE HOUSING CONTRIBUTION - ULTIMO PYRMONT - PAYMENT IN LIEU OF FLOOR SPACE CONTRIBUTION

The Affordable Housing Contribution is as follows:

- (a) Prior to a Construction Certificate being issued and pursuant to Sydney LEP 2012 and the adopted City West Affordable Housing Program, the applicant must pay a monetary contribution towards the provision of affordable housing. The contribution is \$8,538.42. If the contribution is paid after 30 June of the year in which this consent is granted, the amount of the contribution must be indexed in accordance with the adopted City West Affordable Housing Program.
- (b) To make payment contact Councils Planning Assessment Unit email: planningsystemsadmin@cityofsydney.nsw.gov.au who will index the amount, then provide you with written confirmation of the amount payable and details of how to make the payment at the Department of Planning & Environment.
- (c) Payment can be made either by bank cheque to the value of the required contribution (made in favour of City West Housing Pty Ltd) or alternatively a satisfactory bank guarantee is to be provided to the value of the required contribution. Evidence of payment or lodgment of a bank guarantee must be provided to the Accredited Certifier prior to issue of a construction certificate.
- (d) Prior to issue of an Occupation Certificate being issued or the use commencing, whichever is earlier, the applicant must provide evidence to the Accredited Certifier that the bank guarantee referred to in (c) above has been redeemed as payment of the contribution.

Note: All affordable housing contribution payments (and lodgment of bank guarantees) for Ultimo-Pyrmont are paid at the Dept of Planning & Environment.

(7) FLOOR SPACE RATIO - ALL OTHER AREAS

The following applies to Floor Space Ratio:

- (a) The Floor Space Ratio for the business use must not exceed 3.89:1 calculated in accordance with Sydney Local Environmental Plan 2012. For the purposes of the calculation of FSR, the total Gross Floor Area is 17,080sqm.
- (b) Prior to an Occupation Certificate being issued, a Registered Surveyor must provide certification of the total and component Gross Floor Areas (by use)

in the development, utilising the definition under Sydney Local Environmental Plan 2012, applicable at the time of development consent, to the satisfaction of the Principal Certifier.

(8) SERVICE VEHICLE SIZE LIMIT

The size of vehicles servicing the property must not exceed 7 metres.

(9) CONSTRUCTION PEDESTRIAN AND TRAFFIC MANAGEMENT PLAN

A Construction Pedestrian Traffic Management Plan (CPTMP) must be submitted to and approved by Council's assessing officers prior to any Construction Certificate being issued. Prior to being submitted to Council, written confirmation must be provided that the CPTMP has been submitted to and approved by the Light Rail Operator in consultation with Transport for NSW.

The CPTMP needs to specify matters including, but not limited to, the following:

- (a) Location of any proposed work zone(s);
- (b) Haulage route(s);
- (c) Construction vehicle access arrangements;
- (d) Proposed construction hours;
- (e) Predicted number of construction vehicle movements and detail of vehicle types, noting that vehicle movements are to be minimised during peak periods;
- (f) Construction program and construction methodology;
- (g) Any potential impacts to general traffic, cyclists, pedestrians and light rail and bus services within the vicinity of the site from construction vehicles during the construction of the proposed works;
- (h) Cumulative construction impacts of projects including Sydney Light Rail Project. Existing CPTMPs for developments within or around the development site should be referenced in the CPTMP to ensure that coordination of work activities are managed to minimise impacts on the CBD road network; and
- (i) Proposed mitigation measures. Should any impacts be identified, the duration of the impacts and measures proposed to mitigate any associated general traffic, public transport, pedestrian and cyclist impacts should be clearly identified and included in the CPTMP.

The applicant shall submit a copy of the final plan to the Accredited Certifier (PCA).

(10) HOURS OF OPERATION - MINOR DEVELOPMENT

The hours of operation for the food and drink premises are restricted to between 7.00am and 5.00pm, Monday to Wednesdays, 7.00am and 10.00pm Thursdays and Fridays; and Closed Saturdays, Sundays and public holidays.

(11) NOISE – COMMERCIAL PLANT / INDUSTRIAL DEVELOPMENT

- (a) Noise from commercial plant and industrial development must not exceed a project amenity/intrusiveness noise level or maximum noise level in accordance with relevant requirements of the NSW EPA [Noise Policy for Industry 2017 \(NPfl\)](#) unless agreed to by the City's Area Planning Manager. Further:
- (i) Background noise monitoring must be carried out in accordance with the long-term methodology in [Fact Sheet B](#) of the NPfl unless otherwise agreed by the City's Area Planning Manager.
 - (ii) Commercial plant is limited to heating, ventilation, air conditioning, refrigeration and energy generation equipment.
- (b) An $L_{Aeq,15\text{ minute}}$ (noise level) emitted from the development must not exceed the $L_{A90,15\text{ minute}}$ (background noise level) by more than 3dB when assessed inside any habitable room of any affected residence or noise sensitive commercial premises at any time. Further:
- (i) The noise level and the background noise level shall both be measured with all external doors and windows of the affected residence closed.
 - (ii) Background noise measurements must not include noise from the development but may include noise from necessary ventilation at the affected premise.
- (c) Corrections in [Fact Sheet C](#) of the NPfl are applicable to relevant noise from the development measured in accordance with this condition, however duration corrections are excluded from commercial noise.

(12) PUBLIC DOMAIN DAMAGE DEPOSIT

- (a) A Public Domain Damage Deposit calculated on the basis of square metres of Asphalt site frontage must be lodged with Council in accordance with the City of Sydney's adopted Schedule of Fees and Charges. The Public Domain Damage Deposit must be submitted as an unconditional bank guarantee or insurance bond as per the Council's Performance Bond Policy in favour of Council as security for repairing any damage to the public domain in the vicinity of the site (Guarantee).
- (b) Council's Public Domain section must be contacted to determine the guarantee amount prior to lodgement of the guarantee. The Guarantee must be lodged with Council prior to an approval for demolition being granted or a Construction Certificate being issued, whichever is earlier.
- (c) The Guarantee in this condition will be retained in full until the Public Domain Works Deposit Guarantee if required by this consent is lodged with Council. Upon lodgement of the Public Domain Works Deposit Guarantee, the Guarantee in this condition will be released.

If no public domain works are required the Guarantee in this condition will be retained in full until the final Occupation Certificate has been issued and any rectification works to the footway and Public Domain are completed to Council's satisfaction. The Guarantee will be released in full unless rectification works are required where upon 90% of the total securities will be released, with the

remaining 10% to be retained for the duration of a 6 months Defect Liability Period.

(13) BICYCLE PARKING AND END OF TRIP FACILITIES

- (a) The minimum number of bicycle parking spaces and end of trip facilities to be provided for the development must comply with the table below.

Bicycle Parking Type	Number	Requirements
Non-residential	68	Spaces must be Class 2 bicycle facilities
End of Trip Facility Type	Number	
Showers with change area	10	
Personal lockers	106	

Notes:

- (i) If a basement storage area on title that is large enough to store a bike and is no smaller than a class 1 bike locker this can be counted as a space.
- (b) The layout, design and security of bicycle facilities must comply with the minimum requirements of Australian Standard AS 2890.3 Parking Facilities Part 3: Bicycle Parking Facilities. The details must be submitted to and approved by the Accredited Certifier confirming prior to the Construction Certificate being issued.

(14) MATERIALS AND SAMPLES SCHEDULE – MINOR DEVELOPMENT

- (a) A detailed materials, colours and finishes schedule (including visible rainwater goods and services) keyed to each building elevation must be submitted to and approved by Council's Area Planning Manager prior to any Construction Certificate being issued. The materials and samples schedule/board must not include generic material or colour descriptions, or use terminology such as 'or similar'.
- (b) The materials, colours and finishes schedule must clearly illustrate the colour of proposed sun shade screens at the northern boundary.

(15) AWNING USE AND MAINTENANCE

- (a) The footpath awning may be trafficable for maintenance purposes only, however must not be used as a verandah or balcony.
- (b) The awning must be inspected and maintained to ensure the structural integrity, aesthetic and functional quality of the awning.

(16) EXTERNAL LIGHTING

A separate development application is required to be lodged and approved prior to any external floodlighting or illumination of the building.

(17) UNDER AWNING LIGHTING

Illumination from the under awning lighting, when measured from any place in the public domain, must comply with the following:

- (a) the horizontal luminance level must not exceed 200 lux (including reflectivity from exterior finishes). The lux level may be increased to 220 lux in some areas in Central Sydney CBD;
- (b) the horizontal illuminance uniformity ratio (E_{avg}/E_{min}) must not exceed 4:1 to ensure safe movement of pedestrians;
- (c) the intensity, colour, period of intermittency and hours of illumination must be varied if, at any time in the opinion of the Council, adverse impact or Obtrusive Light in accordance with the definition in Australian Standard AS4282-1997 *Control of the obtrusive effects of outdoor lighting* is being caused to the amenity of the area;
- (d) where nearby residents are located above the level of the under awning lighting, details are to be provided to show that light is not directed upwards toward such residences; and
- (e) batten type fluorescent lighting is not permitted to be used for under awning lighting.

(18) REFLECTIVITY

The Accredited Certifier must ensure that the visible light reflectivity from building materials used on the facade of the building does not exceed 20% prior to issue of the Construction Certificate.

(19) ERECTION OF SIGN

The sign is to be erected in a secure manner to ensure safety and its installation is not to involve measures that would cause irreversible damage to the building.

(20) SIGN ILLUMINATION

- (a) At no time is the intensity, period of intermittency and hours of illumination of the signs to cause objectionable glare or injury to the amenity of the neighbourhood and as such must be designed, installed and used in accordance with AS4282-1997 *Control of Obtrusive Effects of Outdoor Lighting*.
- (b) The sign(s) must not flash. Signs with flashing, chasing, pulsating or flickering lights are not permitted.
- (c) The maximum night time luminance of any sign is not to exceed 300 cd/sqm.
- (d) Upward facing light sources onto the signage are not permitted.

SCHEDULE 1B

PRIOR TO CONSTRUCTION CERTIFICATE/COMMENCEMENT OF WORK/HEALTH AND BUILDING

(21) ASSOCIATED ROADWAY COSTS

All costs associated with the construction of any new road works including kerb and gutter, road pavement, drainage system and footway shall be borne by the developer. The new road works must be designed and constructed in accordance with the City's "Sydney Streets Technical Specification" including amendments and "Sydney Streets Design Code".

(22) ALIGNMENT LEVELS – MINOR DEVELOPMENT

- (a) Where ground floor levels of existing buildings are being retained, alignment levels for the buildings and site frontages of those buildings must be submitted to and approved by Council prior to a Construction Certificate being issued for public domain works or above ground building works, whichever is earlier. The submission must be prepared by a Registered Surveyor or suitably qualified engineer and must be submitted with a completed Application for Public Domain Levels and Gradients (available on the City's website).
- (b) If a *Public Domain Plan* condition applies to the development consent the *Public Domain Plan* submission must incorporate the approved Alignment Levels. If the proposed detailed design of the public domain requires changes to any previously approved Alignment Levels, then an amended Alignment Levels submission must be submitted to and approved by Council to reflect these changes prior to a Construction Certificate being issued for public domain work.

(23) PHOTOGRAPHIC RECORD / DILAPIDATION REPORT - PUBLIC DOMAIN

Prior to an approval for demolition being granted or a Construction Certificate being issued, whichever is earlier, a photographic recording of the public domain site frontages is to be prepared and submitted to Council's satisfaction.

The recording must include clear images of the building facade adjoining the footpath, the footpath, nature strip, kerb and gutter, driveway crossovers and laybacks, kerb ramps, road carriageway, street trees and plantings, parking restriction and traffic signs, and all other existing infrastructure along the street.

The form of the recording is to be as follows:-

- (a) A PDF format report containing all images at a scale that clearly demonstrates the existing site conditions;
- (b) Each image is to be labelled to identify the elements depicted, the direction that the image is viewed towards, and include the name of the relevant street frontage;
- (c) Each image is to be numbered and cross referenced to a site location plan;
- (d) A summary report, prepared by a suitable qualified professional, must be submitted in conjunction with the images detailing the project description, identifying any apparent existing defects, detailing the date and authorship

of the photographic record, the method of documentation and limitations of the photographic record;

- (e) Include written confirmation, issued with the authority of both the applicant and the photographer that the City of Sydney is granted a perpetual non-exclusive license to make use of the copyright in all images supplied, including the right to make copies available to third parties as though they were Council images. The signatures of both the applicant and the photographer must be included.

Any damage to the public way including trees, footpaths, kerbs, gutters, road carriageway and the like must immediately be made safe and functional by the applicant. Damage must be fully rectified by the applicant in accordance with the City's standards prior to a Certificate of Completion being issued for Public Domain Works or before an Occupation Certificate is issued for the development, whichever is earlier.

(24) PRESERVATION OF SURVEY MARKS

All works in City streets must ensure the preservation of existing permanent survey marks (a brass bolt, or a lead plug holding a brass tack, covered by a cast iron box). At least forty-eight hours prior to the commencement of any works in the public way within 1 metre of a permanent survey mark contact must be made with the City's Project Manager Survey / Design Services to arrange for the recovery of the mark.

Prior to the issue of a Construction Certificate, a survey plan, clearly showing the location of all permanent survey marks fronting the site and within 5 metres on each side of the frontages must be submitted to Council.

At least forty-eight hours prior to the commencement of any works in the public way within 1 metre of a permanent survey mark contact must be made with the City's Senior Surveyor to arrange for the recovery of the mark.

A fee must be paid to the Council for the replacement of any permanent survey mark removed or damaged in accordance with the City's Schedule of Fees and Charges (Reinstatement of Survey Box).

(25) PROTECTION OF SURVEY INFRASTRUCTURE

Prior to the commencement of any work on site, a statement prepared by a Surveyor registered under the *Surveying and Spatial Information Act 2002* must be submitted to Council verifying that a survey has been carried out in accordance with the Surveyor General's Direction No. 11 – Reservation of Survey Infrastructure. Any Permanent Marks proposed to be or have been destroyed must be replaced, and a "Plan of Survey Information" must be lodged at the NSW Land Registry Services.

Reason: To ensure that the survey control infrastructure and cadastral framework are preserved for the public benefit and in accordance with the *Surveying and Spatial Information Act 2002*.

(26) STORMWATER AND DRAINAGE - MINOR DEVELOPMENT

- (a) The drainage system is to be constructed in accordance with the City's standard requirements as detailed in the City of Sydney's Stormwater Drainage Manual, as amended from time to time.

The development is to be designed so that the flow of pollutants from the site due to stormwater is reduced.

- (b) For approval of a connection into the City of Sydney's drainage system an "Application for Approval of Stormwater Drainage Connections" must be submitted to the City, together with an application fee in accordance with the City of Sydney's adopted Schedule of Fees and Charges.
 - (i) The application must be approved by the City of Sydney prior to an approval or Construction Certificate being issued for excavation, civil construction, drainage or building work (whichever is earlier), excluding approved preparatory or demolition work.
 - (ii) All proposed connections to the City's underground drainage system require the owner to enter into a Deed of Agreement with the City of Sydney and obtain registration on Title of a Positive Covenant prior to an Occupation Certificate being issued, including an Interim Occupation Certificate.
- (c) Where a drainage system includes On-site Detention (OSD), the following requirements must be satisfied prior to the issue of any Occupation Certificate, including any Interim Occupation Certificate:
 - (i) A Positive Covenant must be registered on the title for all drainage systems involving OSD to ensure the maintenance of the approved OSD system regardless of the method of connection;
 - (ii) A Works-As-Executed survey must be prepared, signed, dated and certified by a Registered Surveyor and must be submitted to and accepted by the Principal Certifier. The Works-As-Executed plan must be overlaid on a copy of the approved stormwater drainage plans issued with the Construction Certificate, with variations to locations, dimensions, levels and storage volumes clearly marked;
 - (iii) A Hydraulic Compliance Certificate and Calculation Sheet must be prepared by a suitably qualified hydraulic engineer (minimum NER), showing approved versus installed hydraulic calculations, and must be submitted to and be accepted by the Principal Certifier;
 - (iv) Evidence of Sydney Water's acceptance of the Works-As-Executed documentation, certification and Hydraulic Compliance Certificate and Calculation Sheet must be provided to the Principal Certifier;
 - (v) The Accredited Certifier must submit a copy of the Works-As-Executed plans, certifications, Hydraulic Compliance Certificate and Calculation Sheet to the City of Sydney.

(27) STRUCTURAL CERTIFICATION FOR EXISTING BUILDING – ALTERATIONS AND ADDITIONS

A qualified practising certified structural engineer must provide structural certification to Council (where Council is the Principal Certifier) verifying that the existing structure can adequately support the proposed new loads and the structural design complies with the Structural Provisions of Part B1 (Vol 1) and Part 2.1 (Vol 2) of the *Building Code of Australia* prior to a Construction Certificate being issued. The proposed additional loads and/or alterations must not cause a decrease in the existing structural performance of the building including its performance under earthquake actions (AS1170.4).

(28) CONSTRUCTION AND FITOUT OF FOOD PREMISES

The construction, fitout and finishes of the food premises must comply with Standard 3.2.3 of the Australian and New Zealand Food Standards Code under the *Food Act 2003* and AS 4674 – 2004 Design, Construction and Fitout of Food Premises.

Note: Copies of AS 4674-2004 may be obtained from the Standards Australia Customer Service on telephone 1300 65 46 46 or by visiting the website www.standards.com.au.

Copies of the Food Standards Code (Australia) may be obtained by contacting the Food Standards Australia and New Zealand Authority on telephone (02) 6271 2222, email info@foodstandards.gov.au or by visiting the website www.foodstandards.gov.au.

(29) MECHANICAL VENTILATION

- (a) The premises must be ventilated in accordance with the *Building Code of Australia* and AS1668.1 and AS1668.2 - *The Use of Ventilation and Air-conditioning in Buildings - Mechanical Ventilation in Buildings*.
- (b) Details of any mechanical ventilation and/or air conditioning system complying with AS1668.1 and AS1668.2 - *The Use of Ventilation and Air-conditioning in Buildings - Mechanical Ventilation in Buildings*, the *Building Code of Australia* and relevant Australian Standards must be prepared and certified in accordance with Clause A5.2(1)(e) of the *Building Code of Australia*, to the satisfaction of the Accredited Certifier prior to the issue of a Construction Certificate.
- (c) Prior to issue of any Occupation Certificate and following the completion, installation, and testing of all the mechanical ventilation systems, a Mechanical Ventilation Certificate of Completion and Performance in accordance with Clause A5.2(1)(e) of the *Building Code of Australia*, must be submitted to the Principal Certifier.

(30) FOOD PREMISES – DETAILED PLANS

- (a) Detailed and scaled plans of all kitchen, bar, food preparation, waste and storage areas, food handler toilets and all areas associated with the food business must be prepared in accordance with the *Australia New Zealand Food Standards Code – 3.2.3 – Food Premises and Equipment* under the *Food Act 2003* and *AS 4674 - Design, Construction and Fit-out of Food Premises*.
- (b) Prior to the Issue of a Construction Certificate the plans required by (a) of this condition must be submitted to and approved in writing by the Principal Certifier.

(31) GREASE AND LIQUID WASTE TRAPS

- (a) A grease trap if required by Sydney Water must be installed in accordance with Sydney Water requirements and:
 - (i) Must be installed by a suitably qualified and licensed plumber in accordance with the *Plumbing Code of Australia*;
 - (ii) The grease trap must not be located in any kitchen, food preparation or food storage area;
 - (iii) Be suitably constructed and installed in a location which allows it to be easily and effectively cleaned and emptied; and
 - (iv) Be suitably constructed and located as not to encourage the harbourage of pests and be effectively pest proofed.
- (b) In-sink and in-floor waste bucket traps must be installed in all sinks and floor wastes in all commercial kitchens and food preparation areas and must be carried out by a suitably qualified and licensed plumber in accordance with the *Plumbing Code of Australia*.

(32) NO FOOD PREPARATION (PRE-PACKAGED FOODS ONLY)

This approval does not include the preparation and processing of food at the premises, and relates only to the sale of food sold and served in the supplier's original package.

(33) PERSONAL LOCKERS

Clothing lockers or change rooms for male and female staff must be provided in the premises or a dedicated, separate and isolated space for personal items must be provided in a separate location to the food handling and storage areas, in accordance with *AS4674 - Design, Construction and Fit out of Food Premises*.

(34) ADDITIONAL REQUIREMENTS ON PLANS – SINKS AND HAND WASH BASINS

Prior to the issue of a Construction Certificate, amended scale plans confirming the position of all sinks and hand wash basins within the food premises must be submitted to and approved by Council's Health and Building Unit.. The location and accessibility of sinks and hand wash basins must comply with the requirements of *AS4674 Design, Construction and Fit-out of Food Premises* and

(35) COOLROOMS

Cool room(s), refrigerated chambers and strong-rooms must be constructed in accordance with G 1.2 of the *Building Code of Australia*, and:

- (a) The floor of the coolroom must be graded to the door and a floor trapped waste outlet must be located outside the coolroom as near as possible to the door opening.
- (b) All proposed shelving in the coolroom must be free-standing, constructed of galvanised steel angle section or other approved material with the lowest shelf at least 150mm clear of the floor.
- (c) The floor of the coolroom must be constructed of impermeable concrete or coated, topped or otherwise finished with an impervious material to a smooth even surface and coved at the intersections with the walls to a minimum radius of 25mm.
- (d) Must be fitted with a door that can be opened at all times from inside without a key.
- (e) An approved audible alarm device must be located outside the coolroom(s) but controllable only from within the coolroom(s) and must be able to achieve a sound pressure level outside the chamber or coolroom(s) of 90 d B (A) when measured 3 metres from a sounding device.

(36) HOT WATER SERVICE

The capacity of the hot water service must ensure that a constant supply of hot water is provided to the premises at all times for all sinks and basins including hand wash basin/s. The temperature of the hot water provided to the sinks must be in accordance with *AS4674 – Design, Construction and Fit-out of Food Premises* and the *Australia New Zealand Food Standards Code 3.2.2 - Food Safety Practices* and general requirements.

(37) NOTIFICATION OF CONDUCT OF FOOD BUSINESS

- (a) The use shall not commence until the food business has notified Council with their food business details in accordance with the *Food Act 2003* and *The Australia New Zealand Food Standards Code – 3.2.2 – Food Safety Practices and General Requirements, Clause 4*.
- (b) An Occupation Certificate will not be issued until such notification has been received by Council in accordance with Clause (a) of this condition.

Note: Registration forms are available on Council's website www.cityofsydney.nsw.gov.au.

(38) WASTE STORAGE AREA

- (a) To ensure the adequate storage and collection of waste from the food premises, all garbage and recyclable materials emanating from the premises must be stored in a designated waste storage area. The waste storage area must be designed and constructed in accordance with *AS 4674 – Design, Construction and Fit-out of Food Premises, Australia New Zealand Food Standards Code 3.2.3 – Food Premises and Equipment* and comply with the *Council Policy for Waste Minimisation in New Developments*, and must be:
 - (i) Provided with a hose tap connected to the water supply.
 - (ii) Paved with impervious floor materials.
 - (iii) Coved at the intersection of the floor and walls.
 - (iv) Graded and drained to a waste disposal system in accordance with the requirements of the relevant regulatory authority (Sydney Water).
 - (v) Adequately ventilated (mechanically or naturally) so that odour emissions do not cause offensive odour or air pollution as defined by the *Protection of the Environment Operations Act 1997* or a nuisance.
 - (vi) Fitted with appropriate interventions to meet fire safety standards in accordance with the *Building Code of Australia*.
 - (vii) Provided with the appropriate number and size of bins adequate for the storage of waste generated by the business, including recycling.
 - (viii) Appropriately managed so that it does not attract pests or create litter.
- (b) Detailed plans and specifications for the construction of the waste storage area must be submitted to and approved by the Accredited Certifier prior to the issue of the Construction Certificate and must be constructed in accordance with such plans and specifications prior to the issuance of an Occupation Certificate.

(39) WASTE AND RECYCLING MANAGEMENT - COMMERCIAL

- (a) A Waste and Recycling Management Plan is to be approved by the Accredited Certifier prior to a Construction Certificate being issued. The plan must comply with the Council's *Guidelines for Waste Management in New Developments 2018*. All requirements of the approved Building Waste and Recycling Management Plan must be implemented during construction of the development.

UPON COMPLETION OF THE DEVELOPMENT

- (b) Prior to an Occupation Certificate being issued or the use commencing, whichever is earlier, the Accredited Certifier must ensure that waste handling works have been completed in accordance with: the Waste and Recycling Management Plan; other relevant development consent conditions; and Council's *Guidelines for Waste Management in New Developments 2018*.

(40) WASTE/RECYCLING COLLECTION

- (a) The collection of waste and recycling must only occur during the designated zone collection times as outlined in the City's Waste Policy – Local Approvals Policy for Managing Waste in Public Places 2017.
- (b) Garbage and recycling must not be placed on the street for collection.
- (c) Bulky waste collection is to be serviced as per the Waste Management Plan provided.

(41) WASTE AND RECYCLING MANAGEMENT - MINOR

The proposal must comply with the relevant provisions of Council's *Guidelines for Waste Management in New Developments 2018* which requires facilities to minimise and manage waste and recycling generated by the proposal.

(42) TACTILE GROUND SURFACE INDICATORS AND HANDRAILS

All tactile ground surface indicators, handrails and other elements required to provide access into the building / property must be located entirely within the private property boundary.

(43) ASBESTOS REMOVAL WORKS

- (a) All works removing asbestos containing materials must be carried out by a suitably licensed asbestos removalist duly licensed with Safework NSW, holding either a Friable (Class A) or a Non- Friable (Class B) Asbestos Removal Licence which ever applies.

A copy of the relevant licence shall be made available to any authorised Council officer on request within 24 hours.

- (b) Five days prior to the commencement of licensed asbestos removal, Safework NSW must be formally notified of the works. All adjoining properties and those opposite the development must be notified in writing of the dates and times when asbestos removal is to be conducted. The notification must identify the licensed asbestos removal contractor and include a contact person for the site together with telephone number and email address.
- (c) All work must be carried out in accordance with the *Work Health and Safety Regulation 2011* and the NSW Government and Work Cover document entitled *How to manage and control asbestos in the work place: Code of Practice (Safework NSW) December 2011* and the *City of Sydney Managing Asbestos Policy dated 21 October 2013 and associated guidelines*.
- (d) The asbestos removalist must use signs and barricades to clearly indicate the area where the asbestos removal work is being performed. Signs must be placed in positions so that people are aware of where the asbestos removal work area is and should remain in place until removal is completed and clearance to reoccupy has been granted. Responsibilities for the security and safety of the asbestos removal site and removal must be

specified in the asbestos removal control plan (where required). This includes inaccessible areas that are likely to contain asbestos.

- (e) Warning signs must be placed so they inform all people nearby that asbestos removal work is taking place in the area. Signs must be placed at all of the main entry points to the asbestos removal work area where asbestos is present. These signs must be weatherproof, constructed of light-weight material and adequately secured so they remain in prominent locations. The signs must be in accordance with AS 1319 -1994 *Safety Signs for the Occupational Environment* for size, illumination, location and maintenance.
- (f) Asbestos waste must only be transported and disposed of at an EPA licensed waste facility.
- (g) No asbestos products are to be reused on the site (i.e. packing pieces, spacers, formwork or fill etc).
- (h) No asbestos laden skips or bins are to be left in any public place without the written approval of Council.
- (i) A site notice board must be located at the main entrance to the site in a prominent position and must have minimum dimensions of 841mm x 594mm (A1) with any text on the notice to be a minimum of 30 point type size.

The site notice board must include the following:

- (i) contact person for the site;
- (ii) telephone and facsimile numbers and email address; and
- (iii) site activities and time frames.

(44) STREET TREE PROTECTION

Street trees must be protected in accordance with the Australian Standard 4970 Protection of Trees on Development Sites. All street trees must be protected during the construction works as follows:

- (a) Tree trunk and major limb protection must be undertaken prior to or during the installation of any hoarding or scaffoldings. The protection must be installed by a qualified Arborist (AFQ 2 or 3) and must include:
 - (i) An adequate clearance, minimum 250mm, must be provided between the structure and tree branches, limbs and trunk at all times;
 - (ii) Tree trunk/s and/or major branches, located within 500mm of any hoarding or scaffolding structure, must be protected by wrapped hessian or similar material to limit damage, and
 - (iii) Timber planks (50mm x 100mm or similar) must be placed around tree trunk/s. The timber planks must be spaced at 100mm intervals, and must be fixed against the trunk with tie wire, or strapping. The hessian and timber planks must not be fixed to the tree in any instance, or in any fashion,

- (iv) Tree trunk and major branch protection is to remain in place for the duration of construction and development works, and must be removed at the completion of the project.
- (b) All hoarding support columns are to be placed a minimum of 300mm from the edge of the existing tree pits/setts, so that no sinking or damage occurs to the existing tree setts. Supporting columns must not be placed on any tree roots that are exposed.
- (c) Materials or goods, including site sheds, must not be stored or placed:
 - (i) around or under the tree canopy; or
 - (ii) within two (2) metres of tree trunks or branches of any street trees.
- (d) Protective fencing (1.8 metre chain wire mesh fencing) must be erected on top of the hoarding [Tree Management Team to insert location of hoarding and affected trees] to protect branches during the construction works.
- (e) Any damage sustained to street tree/s as a result of the erection of hoardings, scaffolding, or due to the loading/unloading of vehicles adjacent the site, must be immediately reported to the Council's Street Tree Contract Coordinator on 9265 9333, in order to determine the appropriate action for maintaining the health and structural integrity of any damaged street tree.

(45) STREET TREE PRUNING AND REMOVAL

- (a) The consent from Council must be obtained prior to the undertaking of any street tree pruning works including tree roots greater than 40mm diameter. Only minor pruning works will be approved by Council.
- (b) Any pruning that is required to accommodate hoardings, scaffolding, or to accommodate the loading/unloading of vehicles, and has been approved by Council, must be carried out by a qualified Arborist (AQF3), and must be in accordance with AS4373 Australian Standards 'Pruning of Amenity Trees'.
- (c) The removal of any street tree approved by Council must include complete stump removal and the temporary reinstatement of levels so that no trip or fall hazards exist until suitable replanting occurs. These works must be completed immediately following the trees removal.

(46) TREE PROTECTION DURING CONSTRUCTION

Stockpiling, storage or mixing of materials, washing of equipment, vehicle parking, disposal of liquids, machinery repairs and refuelling, disposal of building materials such as cement slurry, siting of offices or sheds and the lighting of fires, must not occur within 5m of the trunk of any tree to be retained.

(47) TREE TRUNK PROTECTION

The tree/s must be protected in accordance with the Australian Standard AS4970 Protection of Trees on Development Sites. All trees must be protected during the construction works as follows:

- (a) Tree trunk and major limb protection shall be undertaken prior to the issuing of the Construction Certificate. The protection shall be installed by a qualified Arborist with a minimum AQF level 2 and must include:
 - (i) Tree trunk/s and/or major branches must be protected by wrapped hessian or similar material to limit damage;
 - (ii) Timber planks (50mm x 100mm or similar) shall be placed around tree trunk/s. The timber planks shall be spaced at 100mm intervals, and must be fixed against the trunk with tie wire, or strapping. The hessian and timber planks must not be fixed to the tree in any instance, or in any fashion;
 - (iii) Tree trunk and major branch protection is to remain in place for the duration of construction and development works, and shall be removed at the completion of the project.

SCHEDULE 1C

DURING CONSTRUCTION/PRIOR TO OCCUPATION/COMPLETION

(48) OCCUPATION CERTIFICATE TO BE SUBMITTED

An Occupation Certificate must be obtained from the Accredited Certifier and a copy submitted to Council prior to commencement of occupation or use of the whole or any part of a new building, an altered portion of, or an extension to an existing building.

(49) HOURS OF WORK AND NOISE – OUTSIDE CBD

The hours of construction and work on the development must be as follows:

- (a) All work, including building/demolition and excavation work, and activities in the vicinity of the site generating noise associated with preparation for the commencement of work (eg. loading and unloading of goods, transferring of tools etc) in connection with the proposed development must only be carried out between the hours of 7.30am and 5.30pm on Mondays to Fridays, inclusive, and 7.30am and 3.30pm on Saturdays, with safety inspections being permitted at 7.00am on work days, and no work must be carried out on Sundays or public holidays.
- (b) All work, including demolition, excavation and building work must comply with the City of Sydney Code of Practice for Construction Hours/Noise 1992 and Australian Standard 2436 - 2010 Guide to Noise Control on Construction, Maintenance and Demolition Sites.

- (c) Notwithstanding the above, the use of a crane for special operations, including the delivery of materials, hoisting of plant and equipment and erection and dismantling of on site tower cranes which warrant the on-street use of mobile cranes outside of above hours can occur, subject to a permit being issued by Council under Section 68 of the Local Government Act 1993 and/or Section 138 of the Roads Act 1993.

Note: Works may be undertaken outside of hours, where it is required to avoid the loss of life, damage to property, to prevent environmental harm and/or to avoid structural damage to the building. Written approval must be given by the Construction Regulation Unit, prior to works proceeding

The *City of Sydney Code of Practice for Construction Hours/Noise 1992* allows extended working hours subject to the approval of an application in accordance with the Code and under Section 4.55 of the *Environmental Planning and Assessment Act 1979*.

(50) PROTECTION OF STONE KERBS

- (a) The existing stone kerbs on the Pirrama Road and Edward Street frontages of the site are to be retained and properly protected during construction works.
- (b) To avoid damage to stone kerbs during construction works for the development, temporary removal and storage of the stone kerbs may be approved by Council. Removed, serviceable stone kerbs (i.e. those that are in good condition as agreed by Council officers) must be re-installed in accordance with the City of Sydney's standard details and specifications after the construction works have been completed. Note: A temporary concrete kerb will need to be constructed to retain the footpath until the stone kerbs can be reinstalled. The removed stone kerbs are to be reinstalled prior to the issue of an Occupation Certificate. Note: all costs associated with the works are to be at no cost to the Council.
- (c) Damaged kerbs are to be replaced to match existing to Council's satisfaction or as otherwise advised by Council officers.
- (d) Where new crossings or temporary crossings are to be constructed to access the property, the affected kerb stones should be salvaged and reused wherever possible.
- (e) All new driveway laybacks and kerbs are to be constructed with stone kerbs to match existing stones or as specified by City officers. All unused stone kerbs are to be salvaged and returned to the City's store.
- (f) Council approval is required before kerbs are removed.
- (g) Council approval is required prior to the cutting of existing stone kerbs for stormwater kerb outlets.

(51) EROSION AND SEDIMENT CONTROL - LESS THAN 250SQM

Where less than 250 square metres are being disturbed, no formal plan is required however, the site is to be provided with sediment control measures and these must be implemented so that sediment, including soil, excavated material, building material or other materials cannot fall, descend, percolate, be pumped, drained, washed or allowed to flow to the street, stormwater system or waterways.

(52) WORKS REQUIRING USE OF A PUBLIC PLACE

Where construction/building works require the use of a public place including a road or footpath, approval under Section 138 of the *Roads Act 1993* is to be obtained from Council prior to the commencement of work. Details of any barricade construction, area of enclosure and period of work are required to be submitted to the satisfaction of Council.

(53) TEMPORARY STRUCTURES (HOARDINGS, SCAFFOLDING AND OTHER STRUCTURES) INSTALLED ON PUBLIC ROADS THAT REQUIRE DEVELOPMENT CONTENT

The following forms of temporary structures (hoardings, scaffolding and other structures) proposed for installation on public roads and in connection with the construction of the approved development require Council approval (development consent):

- (a) Type B hoardings that span over roads such as laneways;
- (b) Type B hoardings that propose more than a single storey of site sheds installed on a hoarding deck;
- (c) Type A and Type B hoardings with or without scaffolding that project beyond the side boundaries of adjoining properties;
- (d) fenced work compounds at roadway/footway level;
- (e) hoardings/scaffolding associated with works on heritage-listed buildings; or
- (f) any other large and/or potentially high environmental impact temporary structures, as determined by Council.

A separate development application must be submitted and approved by Council prior to the installation of any temporary structure listed above.

(54) SYDNEY WATER CERTIFICATE (TAP-IN)

- (a) The approved plans must be submitted to Sydney Water's "Tap-in" online service to determine whether the development will affect Sydney Water's sewer and water mains, stormwater drains and/or easements, and if further requirements need to be met. Sydney Water's "Tap-in" online service is available at www.sydneywater.com.au, (see Plumbing, Building & Development and then Sydney Water "Tap-in").
- (b) The Consent Authority or a Accredited Certifier must ensure that Sydney Water has appropriately stamped the plans before the commencement of work.

(55) ENCROACHMENTS – NEIGHBOURING PROPERTIES

No portion of the proposed structure shall encroach onto the adjoining properties.

(56) ENCROACHMENTS – PUBLIC WAY

No portion of the proposed structure, including gates and doors during opening and closing operations, shall encroach upon Council's footpath area.

(57) COVERING OF LOADS

All vehicles involved in the excavation and/or demolition process and departing the property with demolition materials, spoil or loose matter must have their loads fully covered before entering the public roadway.

(58) LOADING AND UNLOADING DURING CONSTRUCTION

The following requirements apply:

- (a) No building materials or vehicles may be stored or parked within the right of access noted as (AM) in DP1001757.
- (b) All loading and unloading associated with construction activity must be accommodated on site, where possible.
- (b) If, it is not feasible for loading and unloading to take place on site, a Works Zone on the street may be considered by Council.
- (c) A Works Zone may be required if loading and unloading is not possible on site. If a Works Zone is warranted an application must be made to Council at least 8 weeks prior to commencement of work on the site. An approval for a Works Zone may be given for a specific period and certain hours of the days to meet the particular need for the site for such facilities at various stages of construction. The approval will be reviewed periodically for any adjustment necessitated by the progress of the construction activities.
- (d) Where hoisting activity over the public place is proposed to be undertaken including hoisting from a Works Zone, a separate approval under Section 68 of the Local Government Act 1993 must be obtained.

(59) NO OBSTRUCTION OF PUBLIC WAY

The public way must not be obstructed by any materials, vehicles, refuse, skips or the like, under any circumstances. Non-compliance with this requirement will result in the issue of a notice by Council to stop all work on site.

(60) USE OF MOBILE CRANES

The following requirements apply:

- (a) Mobile cranes operating from the road must not be used as a method of demolishing or constructing a building.
- (b) For special operations including the delivery of materials, hoisting of plant and equipment and erection and dismantling of on site tower cranes which warrant the on-street use of mobile cranes, permits must be obtained from Council for the use of a mobile crane. The permits must be obtained 48 hours beforehand for partial road closures which, in the opinion of Council will create minimal traffic disruptions and 4 weeks beforehand in the case of full road closures and partial road closures which, in the opinion of Council, will create significant traffic disruptions.

- (c) The use of a crane for special operations, including the delivery of materials, hoisting of plant and equipment and erection and dismantling of on site tower cranes which warrant the on-street use of mobile cranes outside of approved hours of construction can occur, subject to a permit being issued by Council under Section 68 of the Local Government Act 1993 and/or Section 138 of the Roads Act 1993.

SCHEDULE 2

PRESCRIBED CONDITIONS

The prescribed conditions in accordance with Division 8A of the *Environmental Planning and Assessment Regulation 2000* apply:

- Clause 98 Compliance with *Building Code of Australia* and insurance requirements under the *Home Building Act 1989*
- Clause 98A Erection of signs
- Clause 98B Notification of *Home Building Act 1989* requirements
- Clause 98C Conditions relating to entertainment venues
- Clause 98D Conditions relating to maximum capacity signage
- Clause 98E Conditions relating to shoring and adequacy of adjoining property

Refer to the NSW State legislation for full text of the clauses under Division 8A of the *Environmental Planning and Assessment Regulation 2000*. This can be accessed at: <http://www.legislation.nsw.gov.au>

SCHEDULE 3

SYDNEY TRAINS AND TFNSW CONDITIONS

(61) LOCATION OF ASSETS

Prior to the issue of a Construction Certificate, the Applicant shall undertake a dial before you dig search to establish the existence and location of any rail services. Persons performing the dial before you dig search shall use equipment that will not have any impact on rail services and signalling. Should rail services be identified within the subject development site, the Applicant must discuss with Sydney Trains as to whether these services are to be relocated or incorporated within the development site.

(62) CONSTRUCTION WITHIN RAIL CORRIDOR

No work is permitted within the rail corridor, or any easements which benefit Sydney Trains/RailCorp, at any time, unless the prior approval of, or an Agreement with, Sydney Trains/RailCorp has been obtained by the Applicant. The Accredited Certifier is not to issue the Construction Certificate until written confirmation has been received from Sydney Trains confirming that this condition has been satisfied.

The applicant shall adhere to the terms of the right of carriageway easement, not at any stage block access from Edward Street, and should make provision for easy and ongoing 24/7 LIGHT RAIL OPERATOR (Transdev) access by rail vehicles, plant and equipment to support maintenance and emergency activities.

(63) LIAISON WITH SYDNEY TRAINS

The Applicant must ensure that at all times they have a representative (which has been notified to Sydney Trains in writing), who:

- (a) oversees the carrying out of the Applicant's obligations under the conditions of this consent and in accordance with correspondence issued by Sydney Trains;
- (b) acts as the authorised representative of the Applicant; and
- (c) is available (or has a delegate notified in writing to Sydney Trains that is available) on a 7 day a week basis to liaise with the representative of Sydney Trains, as notified to the Applicant.
- (d) Without in any way limiting the operation of any other condition of this consent, the Applicant must, during demolition, excavation and construction works, consult in good faith with Sydney Trains in relation to the carrying out of the development works and must respond or provide documentation as soon as practicable to any queries raised by Sydney Trains in relation to the works.

- (e) Where a condition of consent requires consultation with Sydney Trains, the Applicant shall forward all requests and/or documentation to the relevant Sydney Trains external party interface team. In this instance the relevant interface team is Central Interface and they can be contacted via email on Central Interface@transport.nsw.gov.au.
- (f) Copies of any certificates, drawings, approvals/certification or documents endorsed by, given to or issued by Sydney Trains or RailCorp must be submitted to Council for its records prior to the issuing of the applicable Construction Certificate or Occupation Certificate.
- (g) Any conditions issued as part of Sydney Trains approval/certification of any documentation for compliance with the Sydney Trains conditions of consent, those approval/certification conditions will also form part of the consent conditions that the Applicant is required to comply with.