











TRAFFIC CONTROLLERS ADVISING PEDESTRIANS AND BLOCKING SECOND FLOOR OF THE FOOD COURT

LEGEND:	
	WORK AREA
	TRAFFIC CONTROLLER
	PEDESTRIAN PATH
	ARROW BOARD
	BOLLARDS AND DANGER TAPE
	FENCE PANELS

NOTES

- TCP IMPLEMENTATION**  
SSC DOES NOT ACCEPT LIABILITY FOR OR ENDORSE THE USE OF THE TCP UNLESS THE USER HAS BEEN ADVISED OF THE REQUIRED QUALIFICATIONS TO CARRY OUT SUCH WORKS.
- VEHICLE MOVEMENT PLAN**  
TRAFFIC CONTROLLER SHALL BE POSITIONED UNDER THE DIRECTION OF THE TRAFFIC CONTROLLER WITH THE TRAFFIC FLOW ON DESIGNATED UHF CHANNEL.
- RECOMMENDED TAPER LENGTH**  
APPROXIMATE TAPER LENGTHS FOR LATERAL MERGE AT INTERSECTIONS:  

APPROXIMATE TAPER LENGTH (M)	15	30	45	60	75	90	105	120	135	150	165	180
45 OR LESS	15	30	45	60	75	90	105	120	135	150	165	180
46 - 55	15	30	45	60	75	90	105	120	135	150	165	180
56 - 65	15	30	45	60	75	90	105	120	135	150	165	180
66 - 75	15	30	45	60	75	90	105	120	135	150	165	180
76 - 85	15	30	45	60	75	90	105	120	135	150	165	180
86 - 95	15	30	45	60	75	90	105	120	135	150	165	180
96 - 105	15	30	45	60	75	90	105	120	135	150	165	180
106 - 115	15	30	45	60	75	90	105	120	135	150	165	180
116 - 125	15	30	45	60	75	90	105	120	135	150	165	180
126 - 135	15	30	45	60	75	90	105	120	135	150	165	180
136 - 145	15	30	45	60	75	90	105	120	135	150	165	180
146 - 155	15	30	45	60	75	90	105	120	135	150	165	180
156 - 165	15	30	45	60	75	90	105	120	135	150	165	180
166 - 175	15	30	45	60	75	90	105	120	135	150	165	180
176 - 185	15	30	45	60	75	90	105	120	135	150	165	180
186 - 195	15	30	45	60	75	90	105	120	135	150	165	180
196 - 205	15	30	45	60	75	90	105	120	135	150	165	180
206 - 215	15	30	45	60	75	90	105	120	135	150	165	180
216 - 225	15	30	45	60	75	90	105	120	135	150	165	180
226 - 235	15	30	45	60	75	90	105	120	135	150	165	180
236 - 245	15	30	45	60	75	90	105	120	135	150	165	180
246 - 255	15	30	45	60	75	90	105	120	135	150	165	180
256 - 265	15	30	45	60	75	90	105	120	135	150	165	180
266 - 275	15	30	45	60	75	90	105	120	135	150	165	180
276 - 285	15	30	45	60	75	90	105	120	135	150	165	180
286 - 295	15	30	45	60	75	90	105	120	135	150	165	180
296 - 305	15	30	45	60	75	90	105	120	135	150	165	180
306 - 315	15	30	45	60	75	90	105	120	135	150	165	180
316 - 325	15	30	45	60	75	90	105	120	135	150	165	180
326 - 335	15	30	45	60	75	90	105	120	135	150	165	180
336 - 345	15	30	45	60	75	90	105	120	135	150	165	180
346 - 355	15	30	45	60	75	90	105	120	135	150	165	180
356 - 365	15	30	45	60	75	90	105	120	135	150	165	180
366 - 375	15	30	45	60	75	90	105	120	135	150	165	180
376 - 385	15	30	45	60	75	90	105	120	135	150	165	180
386 - 395	15	30	45	60	75	90	105	120	135	150	165	180
396 - 405	15	30	45	60	75	90	105	120	135	150	165	180
406 - 415	15	30	45	60	75	90	105	120	135	150	165	180
416 - 425	15	30	45	60	75	90	105	120	135	150	165	180
426 - 435	15	30	45	60	75	90	105	120	135	150	165	180
436 - 445	15	30	45	60	75	90	105	120	135	150	165	180
446 - 455	15	30	45	60	75	90	105	120	135	150	165	180
456 - 465	15	30	45	60	75	90	105	120	135	150	165	180
466 - 475	15	30	45	60	75	90	105	120	135	150	165	180
476 - 485	15	30	45	60	75	90	105	120	135	150	165	180
486 - 495	15	30	45	60	75	90	105	120	135	150	165	180
496 - 505	15	30	45	60	75	90	105	120	135	150	165	180
506 - 515	15	30	45	60	75	90	105	120	135	150	165	180
516 - 525	15	30	45	60	75	90	105	120	135	150	165	180
526 - 535	15	30	45	60	75	90	105	120	135	150	165	180
536 - 545	15	30	45	60	75	90	105	120	135	150	165	180
546 - 555	15	30	45	60	75	90	105	120	135	150	165	180
556 - 565	15	30	45	60	75	90	105	120	135	150	165	180
566 - 575	15	30	45	60	75	90	105	120	135	150	165	180
576 - 585	15	30	45	60	75	90	105	120	135	150	165	180
586 - 595	15	30	45	60	75	90	105	120	135	150	165	180
596 - 605	15	30	45	60	75	90	105	120	135	150	165	180
606 - 615	15	30	45	60	75	90	105	120	135	150	165	180
616 - 625	15	30	45	60	75	90	105	120	135	150	165	180
626 - 635	15	30	45	60	75	90	105	120	135	150	165	180
636 - 645	15	30	45	60	75	90	105	120	135	150	165	180
646 - 655	15	30	45	60	75	90	105	120	135	150	165	180
656 - 665	15	30	45	60	75	90	105	120	135	150	165	180
666 - 675	15	30	45	60	75	90	105	120	135	150	165	180
676 - 685	15	30	45	60	75	90	105	120	135	150	165	180
686 - 695	15	30	45	60	75	90	105	120	135	150	165	180
696 - 705	15	30	45	60	75	90	105	120	135	150	165	180
706 - 715	15	30	45	60	75	90	105	120	135	150	165	180
716 - 725	15	30	45	60	75	90	105	120	135	150	165	180
726 - 735	15	30	45	60	75	90	105	120	135	150	165	180
736 - 745	15	30	45	60	75	90	105	120	135	150	165	180
746 - 755	15	30	45	60	75	90	105	120	135	150	165	180
756 - 765	15	30	45	60	75	90	105	120	135	150	165	180
766 - 775	15	30	45	60	75	90	105	120	135	150	165	180
776 - 785	15	30	45	60	75	90	105	120	135	150	165	180
786 - 795	15	30	45	60	75	90	105	120	135	150	165	180
796 - 805	15	30	45	60	75	90	105	120	135	150	165	180
806 - 815	15	30	45	60	75	90	105	120	135	150	165	180
816 - 825	15	30	45	60	75	90	105	120	135	150	165	180
826 - 835	15	30	45	60	75	90	105	120	135	150	165	180
836 - 845	15	30	45	60	75	90	105	120	135	150	165	180
846 - 855	15	30	45	60	75	90	105	120	135	150	165	180
856 - 865	15	30	45	60	75	90	105	120	135	150	165	180
866 - 875	15	30	45	60	75	90	105	120	135	150	165	180
876 - 885	15	30	45	60	75	90	105	120	135	150	165	180
886 - 895	15	30	45	60	75	90	105	120	135	150	165	180
896 - 905	15	30	45	60	75	90	105	120	135	150	165	180
906 - 915	15	30	45	60	75	90	105	120	135	150	165	180
916 - 925	15	30	45	60	75	90	105	120	135	150	165	180
926 - 935	15	30	45	60	75	90	105	120	135	150	165	180
936 - 945	15	30	45	60	75	90	105	120	135	150	165	180
946 - 955	15	30	45	60	75	90	105	120	135	150	165	180
956 - 965	15	30	45	60	75	90	105	120	135	150	165	180
966 - 975	15	30	45	60	75	90	105	120	135	150	165	180
976 - 985	15	30	45	60	75	90	105	120	135	150	165	180
986 - 995	15	30	45	60	75	90	105	120	135	150	165	180
996 - 1005	15	30	45	60	75	90	105	120	135	150	165	180
- VEHICLE MOVEMENT PLAN**  
TRAFFIC CONTROLLER SHALL BE POSITIONED UNDER THE DIRECTION OF THE TRAFFIC CONTROLLER WITH THE TRAFFIC FLOW ON DESIGNATED UHF CHANNEL.
- RECOMMENDED TAPER LENGTH**  
APPROXIMATE TAPER LENGTHS FOR LATERAL MERGE AT INTERSECTIONS:  

APPROXIMATE TAPER LENGTH (M)	15	30	45	60	75	90	105	120	135	150	165	180
45 OR LESS	15	30	45	60	75	90	105	120	135	150	165	180
46 - 55	15	30	45	60	75	90	105	120	135	150	165	180
56 - 65	15	30	45	60	75	90	105	120	135	150	165	180
66 - 75	15	30	45	60	75	90	105	120	135	150	165	180
76 - 85	15	30	45	60	75	90	105	120	135	150	165	180
86 - 95	15	30	45	60	75	90	105	120	135	150	165	180
96 - 105	15	30	45	60	75	90	105	120	135	150	165	180
106 - 115	15	30	45	60	75	90	105	120	135	150	165	180
116 - 125	15	30	45	60	75	90	105	120	135	150	165	180
126 - 135	15	30	45	60	75	90	105	120	135	150	165	180
136 - 145	15	30	45	60								