

Attachment A

Recommended Conditions of Consent

CONDITIONS OF CONSENT

SCHEDULE 1A

APPROVED DEVELOPMENT/DESIGN MODIFICATIONS/COVENANTS AND CONTRIBUTIONS/USE AND OPERATION

Note: Some conditions in Schedule 1A are to be satisfied prior to issue of a Construction Certificate and some are to be satisfied prior to issue of Occupation Certificate, where indicated.

(1) APPROVED DEVELOPMENT

- (a) Development must be in accordance with Development Application No. D/2020/1090 dated 22 October 2020 and the following drawings prepared by DesignInc:

Drawing Number	Drawing Title	Drawing Date
DA-010	Floor Plan Basement	10/02/2021
DA-011	Floor Plan Ground Floor	10/02/2021
DA-012	Floor Plan Level 1	10/02/2021
DA-013	Floor Plan Level 2	10/02/2021
DA-014	Roof Plan	10/02/2021
DA-020	Elevation Street – Church Street	10/02/2021
DA-021	Elevation Street – Fitzgerald Street	10/02/2021
DA-022	Elevation Courtyard	10/02/2021
DA-023	Elevation – North Boundary	10/02/2021
DA-024	Elevation – South Boundary	10/02/2021
DA-033	Section	10/02/2021
DA-050	Privacy Screen Detail	10/02/2021

and as amended by the conditions of this consent.

- (b) In the event of any inconsistency between the approved plans and supplementary documentation, the plans will prevail.

(2) DESIGN MODIFICATIONS

The design of the building must be modified as follows:

- (a) The development is to provide a total of 4 boarding rooms which are capable of being adaptable for a person with a disability in accordance with the Building Code of Australia (it is noted 2 such rooms are identified in the plans). The nominated accessible boarding rooms are to be illustrated on the floor plans and demonstrate (in a checklist) compliance with Australian Standard AS4299.

The modifications are to be submitted to and approved by Council's Area Planning Manager prior to the issue of a Construction Certificate.

(3) SECTION 7.11 CONTRIBUTIONS PAYABLE - CONTRIBUTION TOWARDS PUBLIC AMENITIES – CITY OF SYDNEY DEVELOPMENT CONTRIBUTIONS PLAN 2015 – SOUTH PRECINCT

Council has identified the development will increase demand for public amenities and facilities. Pursuant to Section 7.11 of the Environmental Planning and Assessment Act, 1979 (as amended), and the City of Sydney Development Contributions Plan 2015 the following monetary contributions are required towards the cost of public amenities.

<u>Contribution Category</u>	<u>Amount</u>
Open Space	\$173,125.50
Community Facilities	\$34,243.43
Traffic and Transport	\$49,340.45
Stormwater Drainage	\$19,510.86
Total	\$276,220.24

The City of Sydney will index the above contribution for inflation at the time of payment using the following formula.

$$C_{\text{payment}} = C_{\text{consent}} \times (CPI_{\text{payment}} \div CPI_{\text{consent}})$$

Where:

C_{payment} = Is the contribution at time of payment;

C_{consent} = Is the contribution at the time of consent, as shown above;

CPI_{payment} = Is the Consumer Price Index (All Groups Index) for Sydney published by the Australian Bureau of Statistics that applies at the time of payment; and

CPI_{consent} = Is the Consumer Price Index (All Groups Index) for Sydney at the date the contribution amount above was calculated being – 118 for the December 2020 quarter.

The contribution must be paid prior to the issue of any Construction Certificate in relation to this development.

Please contact Council's Planning Administration staff at planningsystemsadmin@cityofsydney.nsw.gov.au to request a letter confirming the indexed contribution amount payable.

Once the letter confirming the indexed contribution is obtained, payment may be made at any of the City's Neighbourhood Service Centres or the One Stop Shop at Town Hall House. Acceptable payment methods are EFTPOS (debit card only), cash (up to 10K only), Credit Card (up to 50K only) or a bank cheque made payable to the City of Sydney. Personal or company cheques will not be accepted.

(4) BUILDING HEIGHT

- (a) The height of the building must not exceed RL 38.51 (AHD) to the top of the building.
- (b) Prior to an Occupation Certificate being issued, a Registered Surveyor must provide certification that the height of the building accords with (a) above, to the satisfaction of the Principal Certifier.

(5) FLOOR SPACE RATIO - ALL OTHER AREAS

The following applies to Floor Space Ratio:

- (a) The Floor Space Ratio for the development must not exceed 1.42:1 based on the total site area of 590.7sqm. For the purposes of the calculation of FSR, the Gross Floor Area of the development must not exceed 843.3sqm.

(6) MATERIALS AND SAMPLES SCHEDULE

A detailed materials, colours and finishes schedule (including visible rainwater goods and services) keyed to each building elevation must be submitted to and approved by Council's Area Planning Manager prior to a Construction Certificate being issued.

The materials and samples schedule/board must not include generic material or colour descriptions, or use terminology such as 'or similar'. The external colour scheme is to be sympathetic Heritage Conservation Area.

(7) BICYCLE PARKING

The minimum number of bicycle parking spaces to be provided for the development must comply with the table below.

User	Number of bicycles to be accommodated	Requirements
Boarding House	24	Class B bicycle parking facility in accordance with AS2890.3 At least 20% bicycle parking must be horizontal.

The layout, design and security of bicycle facilities must comply with *Australian Standard AS 2890.3:2015 Parking Facilities Part 3: Bicycle Parking Facilities and Section 3.11.3 of DCP 2012*. The details must be submitted to and approved by the Council confirming prior to the Construction Certificate being issued.

(8) BOARDING HOUSE - USE AND OPERATION

The use and operation of the premises must comply with the requirements of Schedule 2 (Standards for Places of Shared Accommodation) of the Local Government (General) Regulation, 2005 under the Local Government Act 1993, the Public Health Act, 2010, the Boarding Houses Act 2012 and regulations thereunder and the *Sydney Development Control Plan 2012 – 4.4.1*.

(9) ACCOMMODATION - REGISTRATION AND CARETAKER

Prior to the issuing of any Occupation Certificate, Council's Health and Building Unit must be advised in writing of the business name, address, owner or company name, 24 hour contact details for the site manager, and the number of occupants approved for the premises. A caretaker/manager must be contactable 24 hours a day.

(10) HEALTH DATABASE REGISTRATION

The business is to be registered with Council's Health and Building Unit prior to the issue of any Occupation Certificate. Registration forms are available on Council's website www.cityofsydney.nsw.gov.au or by calling Council's Health Unit on 02 9265 9333.

(11) RESTRICTION ON BOARDING HOUSE

The building must be used as a boarding house only.

(12) SIGN DISPLAYING CONTACT DETAILS FOR BOARDING HOUSE MANAGER

- (a) A sign must be placed in a clearly visible position at the boarding house entrance displaying the name of the manager and mobile phone number. The signage text shall be written in bold letters with a height of no less than 25mm on a contrasting background that can be read without entering the premises.
- (b) Details of the sign design, content and location within the site must be submitted to and approved by Council's Area Coordinator Planning Assessments / Area Planning Manager prior to the issue of a Construction Certificate.

(13) COMPLIANCE WITH THE ACOUSTIC REPORT PRIOR TO CONSTRUCTION AND OR OCCUPATION CERTIFICATES

- (a) All relevant performance parameters (including but not limited to requirements, engineering assumptions and recommendations) in the Acoustic Report prepared by Acoustic Logic, reference 20200894.1/1210A/R1/WY, revision 1, 12th October 2020, Trim 2020/496692 must be implemented in the development prior to the commencement of its use.

- (b) Prior to the issue of any relevant Construction Certificate, the final construction drawings and final construction methodology must be assessed and reported to be in accordance with the requirements of the DA Acoustic Report in (a) above, with reference to relevant documentation. This must be done by a Suitably Qualified Acoustic Consultant* (see definition below). This work will be to the satisfaction of the accredited certifier.
- (c) Prior to the issue of any Occupation Certificate, a Suitably Qualified Acoustic Consultant* is to provide a written Acoustic Verification Report to the satisfaction of the Principal Certifier that the development complies with the requirements set out in the Report and in (a) and (b) above.

Note: *Suitably Qualified Acoustic Consultant* means a consultant who possesses the qualifications to render them eligible for membership of the Australian Acoustics Society, Institution of Engineers Australia or the Association of Australian Acoustic Consultants at the grade of member.

- (d) All physical aspects of the building's structure installed in order to meet performance parameters in accordance with this condition must be maintained at all times.

(14) NO SPEAKERS OR MUSIC OUTSIDE

Speakers and/or noise amplification equipment must not be installed and music must not be played in any of the outdoor areas associated with the premises including the public domain. Speakers located within the premises must not be placed so as to direct the playing of music towards the outdoor areas associated with the premises.

(15) PLAN OF MANAGEMENT

The use must always be operated / managed in accordance with the Plan of Management, prepared by Perica & Associates Urban Planning Pty Ltd dated September 2020 that has been approved by Council. In the event of any inconsistency, the conditions of this consent will prevail over the Plan of Management.

(16) AIR CONDITIONERS

The air conditioner/s must comply with the requirements of Protection of the Environment Operations (Noise Control) Regulation 2017 and shall not:

- (a) emit noise that is audible within a habitable room in any other residential property (regardless of whether any door or window to that room is open):
 - (i) before 8.00am and after 10.00pm on any Saturday, Sunday or public holiday; or
 - (ii) before 7.00am and after 10.00pm on any other day; or
- (b) emit a sound pressure level when measured at the boundary of any other residential property, at a time other than those *specified* in (i) and (ii) above, which exceeds the background (LA90, 15minutes) by more than 5dB(A). The source noise level must be measured as a LAeq 15 minute.

- (c) If the air-conditioning units cannot achieve inaudibility in habitable rooms of other residential properties during the prescribed times outlined in point (a) above, the air conditioning units must not be used outside of these hours.

(17) RESTRICTION ON STRATA SUBDIVISION

In accordance with the provisions of Clause 52 of the *State Environmental Planning Policy (Affordable Rental Housing) 2009* and the *Sydney Development Control Plan 2012*, the boarding house cannot be strata subdivided.

SCHEDULE 1B

PRIOR TO CONSTRUCTION CERTIFICATE/COMMENCEMENT OF WORK/HEALTH AND BUILDING

(18) ADAPTABLE HOUSING

Prior to a Construction Certificate being issued, information from an appropriately qualified access consultant is to be submitted to the Accredited Certifier:

- (a) confirming that the required number of residential units as per condition 2 are able to be adapted for people with a disability in accordance with the *Building Code of Australia*; and
- (b) demonstrating (in a checklist) compliance with Australian Standard AS4299.

(19) ACCESS AND FACILITIES FOR PERSONS WITH DISABILITIES

The building must be designed and constructed to provide access and facilities for people with a disability in accordance with the *Building Code of Australia*.

If, in complying with this condition, amendments to the development are required, the design changes must be submitted to and approved by Council prior to a Construction Certificate being issued.

(20) BASIX CERTIFICATE – DETAILS TO BE LODGED WITH A CC

A copy of the required completed BASIX certificate with respect to the proposed building works, must be lodged with an application for a construction certificate and the items nominated as part of the subject BASIX certificate must be specified on the plans submitted with the construction certificate application. – See Note.

IMPORTANT NOTE:

Any requirement detailed in the accompanying BASIX Certificate, MUST be included as a specific notation or inclusion on any future Construction Certificate plans and specification in accordance with Part 3 of Schedule 1 of the EP&A Regulation, 2000.

(21) TREES APPROVED FOR REMOVAL

- (a) All trees detailed in Table 1 below are approved for removal. Tree removal must not occur until the Construction Certificate has been issued.

Table 1 – Tree Removal:

Tree No	Botanical/Common Name	Location
5	<i>Ficus microcarpa var. hillii</i> (Hills Fig)	Front yard of subject site
6	<i>Cupressus torulosa</i> (Bhutan Cypress)	

Refer to the *Arboricultural Impact Assessment (AIA) Report prepared by Arboreport dated 25 September 2020 for tree numbering and location.*

- (b) All tree removal works must be carried out by a qualified Arborist, with a minimum Level 3 AQF in arboriculture and in accordance with WorkCover's Code of Practice – Amenity Tree Industry.

(22) TREES THAT MUST BE PROTECTED

- (a) Trees numbered 1, 2, 3, 4, 7, 8, 9, 10, 11 and 12 in the Arboricultural Impact Assessment report prepared by Seasoned Tree Consultancy dated 26 March 2020 must be protected in accordance with the conditions of consent throughout the construction and development.
- (b) The entry footpath from Church Street within the TPZ of T1/T2 must be on or above existing grade and not require the pruning of any street tree roots.
- (c) The existing retaining / boundary wall within the TPZ of T7 and T8 must be retained to the height of the existing soil levels with 2 Raper Street.

If the retaining wall is deemed structurally unsound by a structural engineer and the wall cannot be retained, a Work Methodology Statement by a qualified AQF Level 5 Arborist for the demolition and construction of the new retaining / boundary wall, must be submitted to and approved by Council's Area Planning Manager prior to the issue of a Construction Certificate.

(23) LANDSCAPING OF THE SITE (TREES)

- (a) The Concept Landscape Plan prepared by Conzept Landscape Architects dated 12 October 2020 'Revision C is not approved.
- (b) A detailed landscape plan, drawn to scale, by a qualified landscape architect or landscape designer, must be submitted to and approved by Council's Area Planning Manager prior to the issue of a Construction Certificate. The plan must include:
 - (i) deep soil setback area to Church Street must provide large-medium sized canopy tree plantings;
 - (ii) location of existing and proposed structures on the site including, but not limited to, existing and proposed trees, paved areas, planted areas on slab, planted areas in natural ground, lighting and other features;
 - (iii) details of earthworks and soil depths including mounding and retaining walls and planter boxes (if applicable). The minimum soil depths for planting on slab must be 1000mm for trees, 450mm for shrubs and 200mm for groundcovers;
 - (iv) location, numbers, type and supply of plant species, with reference to the relevant Australian Standard;
 - (v) the design must provide a minimum 15% canopy cover across the site. This must be provided by 40% of the species having a mature minimum height of 6-8 metres and 60% mature minimum height of 10-15 metres;

- (vi) palms, fruit trees and species recognised to have a short life span will not be accepted as suitable replacements;
 - (vii) new trees must be planted in natural ground (deep soil areas) with adequate soil volumes to allow maturity to be achieved;
 - (viii) new trees must be appropriately located away from existing buildings and structures to allow maturity to be achieved without restriction;
 - (ix) details of planting procedure and maintenance; and
 - (x) details of drainage, waterproofing and watering systems.
- (c) Prior to the issue of a Construction Certificate, a maintenance plan is to be submitted to and approved by the Principal Certifying Authority. The maintenance plan is to be complied with during occupation of the property.
 - (d) All landscaping in the approved plan is to be completed prior to an Occupation Certificate being issued.

(24) TREE PROTECTION PLANS

All detailed architectural, building, engineering (structural, stormwater and drainage services) and landscape documentation submitted for the Construction Certificate shall clearly show on all drawings the retention of trees as required by these conditions of consent, the position of their trunks, full diameter of their canopies, Structural Root Zones (SRZs) and Tree Protection Zones (TPZs).

(25) TREE PROTECTION DURING CONSTRUCTION

All trees within and adjoining the property must be protected in accordance with the Australian Standard 4970 Protection of Trees on Development Sites and as follows:

- (a) Stockpiling, storage or mixing of materials, washing of equipment, vehicle parking, disposal of liquids, machinery repairs and refuelling, disposal of building materials such as cement slurry, siting of offices or sheds and the lighting of fires, must not occur within 6 metres of the trunk of any tree (including trees in adjoining properties).
- (b) Excavation (except for localised siting of pier) must not occur within 3 metres of any tree (including trees in adjoining properties). If excavation is proposed within this zone, the Council's Tree Management Officer must be contacted immediately and the excavation must be carried out in accordance with Council's direction.
- (c) Excavations for the footings where they are within 3 metres of any tree (including trees in adjoining properties) must be undertaken using non-destructive methods (such as by hand) to ensure no tree roots greater than 30mm diameter are damaged, pruned or removed.
- (d) Footings shall be relocated / realigned if any tree root greater than 30mm in diameter is encounter during excavations. A minimum of 150mm clearance shall be provided between the tree root and footing.

- (e) Tree trunk and/or major limb protection shall be undertaken prior to the commencement of any works. The protection shall be installed and certified by a qualified Arborist (minimum AQF 3) and must include;
 - (i) tree trunk/s and/or major branches must be protected by wrapped hessian or similar material to limit damage, and
 - (ii) timber planks (50mm x 100mm or similar) shall be placed around tree trunk/s. The timber planks shall be spaced at 100mm intervals, and must be fixed against the trunk with tie wire, or strapping. The hessian and timber planks must not be fixed to the tree in any instance, or in any fashion.
- (f) Tree trunk and major branch protection is to remain in place for the duration of construction and development works, and shall be removed at the completion of the project.
- (g) The consent from Council's Tree Management Officer must be obtained prior to the undertaking of any tree pruning works, including tree roots greater than 30mm in diameter. Only minor pruning works will be approved by Council.

(26) STREET TREE PROTECTION

All street trees directly outside the site must be retained and protected in accordance with the Australian Standard 4970 Protection of Trees on Development Sites. All street trees must be protected during the construction works as follows:

- (a) Tree trunk and major limb protection must be undertaken prior to the commencement of any works. The protection must be installed and certified by a qualified Arborist (AQF level 3) and must include:
 - (i) An adequate clearance, minimum 250mm, must be provided between the structure and tree branches, limbs and trunks at all times.
 - (ii) Tree trunk/s and/or major branches, must be protected by wrapped hessian or similar material to limit damage.
 - (iii) Timber planks (50mm x 100mm or similar) must be placed around tree trunk/s. The timber planks must be spaced at 100mm intervals, and must be fixed against the trunk with tie wire, or strapping. The hessian and timber planks must not be fixed to the tree in any instance, or in any fashion.
 - (iv) Tree trunk and major branch protection is to remain in place for the duration of construction and development works, and must be removed at the completion of the project.
- (b) All hoarding support columns are to be placed a minimum of 300mm from the edge of the existing tree pits/setts, so that no sinking or damage occurs to the existing tree setts. Supporting columns must not be placed on any tree roots that are exposed.

- (c) Young street trees shall be protection by installing three (3) wooden stakes around the edge of the tree pit. Hessian shall be wrapped around the stakes. If existing stakes are already in place, these shall suffice as tree protection.
- (d) Temporary signs, or any other items, shall not be fixed or attached to any street tree.
- (e) Materials or goods, including site sheds, must not be stored or placed:
 - (i) around or under the tree canopy; or
 - (ii) within two (2) metres of tree trunks or branches of any street trees.
- (f) Any excavation within in any area known to, or suspected of, having street tree roots greater than 30mm diameter must be undertaken by hand.
- (g) Any trenching works for services / hydraulics / drainage etc must not be undertaken within 4 metres of any street tree. Alternative installation methods for services, such as directional boring/drilling, or redirection of services shall be employed where large woody roots greater than 30mm diameter are encountered during the installation of any services.
- (h) Existing sections of kerbs adjacent to any street tree must not be removed without approval from the Council's Tree Management Officer.
- (i) Any damage sustained to street tree/s as a result of construction activities (including demolition) must be immediately reported to the Council's Tree Management Officer on 9265 9333. Any damage to street trees as a result of construction activities may result in a prosecution under the Local Government Act 1993 and the Environmental Planning and Assessment Act 1979.

(27) SITE SUPERVISION AND REPORTING

- (a) An Arborist with minimum qualifications in Arboriculture of Level 5 (under the Australian Qualification Framework) must oversee various stages of work within the Tree Protection Zone of any tree listed for retention. The Arborist must certify compliance with each key milestone as detailed below:
 - (i) installation of tree protection measures;
 - (ii) during demolition of any ground surface materials (paving, concrete, grass etc) or retaining walls within the Tree Protection Zone (TPZ) of any tree to be retained;
 - (iii) during any excavation and trenching which has been approved by Council within the TPZ of any tree to be retained; and
 - (iv) during any Landscape works within the TPZ of any tree to be retained.
- (b) An Arboricultural Compliance Report which includes photographic evidence and details of the health and condition of trees, must be

submitted to Council's Area Planning Manager at each hold-point listed below:

- (i) certification tree protection measures have been installed in accordance with the conditions prior to the commencement of works;
- (ii) certification of compliance with each key milestone listed above within 48 hours of completion;
- (iii) monthly reporting for the duration of construction and development within the site;
- (iv) details of any other works undertaken on any tree to be retained or within TPZ/s; and
- (v) a final compliance report shall be submitted prior to the issuing of the Occupation Certificate.

(28) TREE PRUNING

- (a) A 'Pruning Specification Report' prepared by a qualified Arborist (minimum AQF Level 5) must be submitted to and approved by Council's Area Planning Manager prior to the issuing of the Construction Certificate. The report must include:
 - (i) number of branches and orientation, branch diameter, percentage of canopy to be pruned/removed for all development works including hoarding, scaffolding, piling and rigging etc.;
 - (ii) photos with individual branches which are recommended for pruning/removal to be clearly marked. (Please note reports which include photos with a single vertical line as the area recommended for pruning will not be accepted);
 - (iii) a maximum of 5% canopy removal and maximum of 100mm diameter branches will be permitted by Council;
 - (iv) pruning work must be specified in accordance with *Australian Standard 4373-2007, Pruning of Amenity Trees*; and
 - (v) tree removal must not be recommended in this report.
- (b) All approved tree pruning works must be carried out by a qualified Arborist, with a minimum Level 3 AQF in arboriculture and in accordance with WorkCover's Code of Practice – Amenity Tree Industry.
- (c) Any pruning works carried out under this consent must not result in the death of the tree, the creation of a hazard or in excessive or inappropriate amounts of pruning, which result in the overall shape of the tree becoming unbalanced and/or unstable.

(29) CONSTRUCTION TRAFFIC AND PEDESTRIAN MANAGEMENT PLAN

A Construction Traffic and Pedestrian Management Plan must be submitted to and approved by Council prior to a Construction Certificate being issued.

Construction Traffic and Pedestrian Management Plans are to be prepared in accordance with Standard Requirements for Construction Traffic Management Plan on the City's website

<http://www.cityofsydney.nsw.gov.au/business/business-responsibilities/traffic-management/construction-traffic-management-plans>

(30) ASSOCIATED ROADWAY COSTS

All costs associated with the construction of any new road works including kerb and gutter, road pavement, drainage system and footway shall be borne by the developer. The new road works must be designed and constructed in accordance with the City's *Sydney Streets Technical Specification* including amendments and *Sydney Streets Code*.

(31) COST OF SIGNPOSTING

All costs associated with signposting of any kerbside parking restrictions and traffic management measures associated with the development shall be borne by the developer.

(32) PHOTOGRAPHIC RECORD / DILAPIDATION REPORT - PUBLIC DOMAIN

Prior to an approval for demolition being granted or a Construction Certificate being issued, whichever is earlier, a photographic recording of the public domain site frontages is to be prepared and submitted to Council's satisfaction.

The recording must include clear images of the building facade adjoining the footpath, the footpath, nature strip, kerb and gutter, driveway crossovers and laybacks, kerb ramps, road carriageway, street trees and plantings, parking restriction and traffic signs, and all other existing infrastructure along the street.

The form of the recording is to be as follows:

- (a) a PDF format report containing all images at a scale that clearly demonstrates the existing site conditions;
- (b) each image is to be labelled to identify the elements depicted, the direction that the image is viewed towards, and include the name of the relevant street frontage;
- (c) each image is to be numbered and cross referenced to a site location plan;
- (d) a summary report, prepared by a suitable qualified professional, must be submitted in conjunction with the images detailing the project description, identifying any apparent existing defects, detailing the date and authorship of the photographic record, the method of documentation and limitations of the photographic record; and
- (e) include written confirmation, issued with the authority of both the applicant and the photographer that the City of Sydney is granted a perpetual non-exclusive license to make use of the copyright in all images supplied, including the right to make copies available to third parties as though they were Council images. The signatures of both the applicant and the photographer must be included.

Any damage to the public way including trees, footpaths, kerbs, gutters, road carriageway and the like must immediately be made safe and functional by the applicant. Damage must be fully rectified by the applicant in accordance with the City's standards prior to a Certificate of Completion being issued for Public Domain Works or before an Occupation Certificate is issued for the development, whichever is earlier.

(33) SURVEY INFRASTRUCTURE – IDENTIFICATION AND RECOVERY

Under Section 24 of the Surveying and Spatial Information Act 2002, it is an offence to remove, damage, destroy, displace, obliterate or deface any survey mark unless authorised to do so by the Surveyor-General. Accordingly, the applicant must, where possible, ensure the preservation of existing survey infrastructure undisturbed and in its original state or else provide evidence of the Surveyor-General's authorisation to remove or replace marks.

Prior to the issue of any Construction Certificate, documentary evidence must be prepared by a Registered Surveyor and submitted to and approved by Council's Area Planning Manager / Coordinator. This evidence must include either:

- (a) a copy of any Surveyor-General's Approval for Survey Mark Removal granted by NSW Spatial Services for the subject site, including all documentation submitted as part of that application (for example the survey mark audit schedule, strategy plan and strategy report); or
- (b) a letter, signed by a current NSW Registered Land Surveyor and including his or her Board of Surveying and Spatial Information (BOSSI) identification number, stating that all investigations required under Surveyor-General's Direction No.11 have been made for the subject site and that no survey infrastructure will be affected by the proposal.

Council's Principal Surveyor may request further information and/or add conditions to any Surveyor-General's Approval at their discretion.

(34) PUBLIC DOMAIN LEVELS AND GRADIENTS

Prior to the issue of any Construction Certificate, a Public Domain Levels and Gradients submission for the building and site frontages must be submitted to and approved by the City's Public Domain Unit. The submission, must be prepared in accordance with the City's *Public Domain Manual* and submitted with a completed *Application for Public Domain Levels and Gradients*. Information on how to complete the submission can be downloaded from the City's website at <https://www.cityofsydney.nsw.gov.au/development/public-domain-works/da-associated-works>.

Any requirements to comply with Disability Discrimination Act at the entrance to a building or publicly accessible space must be resolved inside the site boundary.

Note: Public Domain Levels and Gradients plans are to be included with Public Domain Plan – Detailed Documentation for Construction Condition submission.

(35) STORMWATER DRAINAGE DESIGN

Prior to issue of any Construction Certificate a detailed stormwater management plan prepared by suitable qualified and experienced professionals demonstrating compliance with the requirements of the cities Storm water Drainage Technical Specification A4.

The submission must include the following;

The requirements of Sydney Water about the on-site detention (OSD) of stormwater must be ascertained and complied with. Evidence of the approval must be submitted to Council prior to any Construction Certificate other than demolition.

- (a) Note: A Deed of Agreement for all proposed connections to the City's drainage system, and a Positive Covenant for all OSD systems may be required prior to issue of any Occupation Certificate.
- (b) Note: The total discharge per site from kerb outlets must not exceed 25Litres/sec. If site discharge is greater, a connection must be made to a Council kerb inlet pit. If no kerb inlet pit exists, an extension of the Council storm water pipe system is required with a minimum 375mm diameter RCP.

(36) PUBLIC DOMAIN PLAN DETAILED DOCUMENTATION FOR CONSTRUCTION

A detailed public domain plan and all relevant documentation must be submitted to and approved by the City's Public Domain Unit prior to the construction of any public domain works. This Plan must document all works required to ensure that the public domain for both site frontages complies with the City of Sydney's *Public Domain Manual, Sydney Streets Code, Sydney Street Tree Masterplan, Sydney Lights Design Code, Sydney Streets Technical Specification* and *Sydney's Parks Code*. The plan must consider road pavement, traffic measures, footway pavement, kerb and gutter, drainage, vehicle crossovers, pedestrian ramps, lighting, street trees and landscaping, signage and other public domain elements. The documentation must be *checked, accurate, and comply with specified requirements*. Plans must be based on an accurate survey, to scale and fully coordinated across all disciplines and submissions. The supplied documentation must be to construction standard and will be approved under Section 138 of the Roads Act.

The Public Domain Manual and all other relevant documents are available for download from Council's website at <https://www.cityofsydney.nsw.gov.au/development/public-domain-works/da-associated-works>.

The Public Domain Plan documentation must be submitted with an *Application for Public Domain Plan Assessment* and include the approved Public Domain Levels and Gradients documentation. If the proposed detailed design of the public domain requires changes to any previously approved levels, an *Application for Public Domain Levels and Gradients* must be submitted to and approved by the Public Domain Unit to reflect these changes prior to an approval being issued for the construction of public domain work.

Note: Stamped plans will be issued for construction and approved under Section 138 of the Roads Act.

(37) SECTION 138 ROADS ACT APPROVAL

Approval under Section 138 of the *Roads Act 1993* must be obtained from Council prior to the commencement of any excavation in or disturbance of a public way for the construction of approved public domain works.

(38) HOLD POINTS

Prior to an approval being issued for the construction of public domain work, including civil, drainage and subsurface works, a set of hold points for approved public domain, civil and drainage work is to be provided by the City's Public Domain Unit in accordance with the City's *Public Domain Manual* and *Sydney Streets Technical Specification* (an approved list of hold points will be included in the Public Domain works Approval letter). These hold points must be adhered to during construction works.

(39) DRAINAGE CONNECTION

For approval of a connection into the City of Sydney's drainage system an "*Application for Approval of Stormwater Drainage Connections*" must be submitted to the City, together with an application fee in accordance with the City of Sydney's adopted Schedule of Fees and Charges. This must be approved prior to the issue of a Construction Certificate for the public domain.

This is not required if the site storm water connection is made to the kerb and gutter.

(40) PUBLIC DOMAIN WORKS BOND

A Public Domain Works Bond will be required as security for the public domain works and for repairing damage that may be caused to the public domain in the vicinity of the site, in accordance with the City of Sydney's adopted fees and charges and the *Public Domain Manual*. The Public Domain Works Bond must be submitted as cash, an unconditional bank guarantee or insurance bond as per the Council's Performance Bond Policy in favour of the City as security for completion of the obligations under this consent (Guarantee).

The City's Public Domain Unit must be contacted to determine the guarantee amount prior to lodgement of the guarantee. The guarantee must be lodged with the City prior to an approval being issued for the Public Domain Plan.

The Guarantee will be retained in full until all Public Domain works, including rectification of damage to the public domain, are completed to City of Sydney standards and approval and the required certifications, warranties and works-as-executed documentation are submitted and approved by the City in writing. On satisfying the above requirements, 90% of the security will be released. The remaining 10% will be retained for the duration of the specified Defects Liability Period.

(41) DEFECTS LIABILITY PERIOD – PUBLIC DOMAIN WORKS

All works to the City's public domain, including rectification of identified defects, are subject to a 6-month defects liability period from the date of final completion. The date of final completion will be nominated by Council on the Certificate of Practical Completion for public domain works.

(42) NO OBSTRUCTIONS

All public footways and paths of travel must be free from obstructions. If services are required to be relocated to clear paths of travel, then this must be undertaken at the developer's expense. All obstructions are to be removed prior to the issue of any Occupation Certificate.

(43) PUBLIC DOMAIN WORKS COMPLETION

The Public Domain works are to be constructed in accordance with the Public Domain Works Approval, approved stamped plans for Gradients and Levels, Stormwater, Public Domain Lighting, the City of Sydney's *Public Domain Manual*, *Stormwater Drainage Manual*, *Sydney Lights Design Code* and *Sydney Streets Technical Specification*.

The public domain work must be inspected, and a Certificate of Practical Completion must be issued by Council's Public Domain Officer prior to the issue of any Occupation Certificate or before the commencement of use, whichever is earlier.

(44) PUBLIC DOMAIN COMPLETION - WORK AS EXECUTED DOCUMENTATION

Prior to a Certificate of Practical Completion being issued for public domain works, works-as-executed (As-Built) plans and documentation, must be submitted to and accepted by the City of Sydney for all public domain works, including where required Stormwater, Public Domain Lighting and Road construction. These works must be certified by a suitably qualified, independent professional. Details of the documentation required for approval will be advised by the City's Public Domain Unit.

(45) STORMWATER COMPLETION DEED OF AGREEMENT AND POSITIVE COVENANT

Prior to the issue of any Occupation Certificate:

- (a) The Owner is required to enter into a Deed of Agreement with the City of Sydney and obtain registration of Title of a Positive Covenant for all proposed connections to the City's underground drainage system. The deed and positive covenant will contain terms reasonably required by the City and will be drafted by the City's Legal Services Unit at the cost of the applicant, in accordance with the City's Fees and Charges.
- (b) A Positive Covenant must be registered on the property title for all drainage systems involving On-Site Detention (OSD) to ensure maintenance of the approved OSD system regardless of the method of connection. The positive covenant will contain terms reasonably required

by the City and will be drafted by the City's solicitor at the cost of the applicant, in accordance with the City's Fees and Charges.

(46) PUBLIC DOMAIN DAMAGE BOND

- (a) A Public Domain Damage Bond calculated based on 45 square metres of concrete site frontage must be lodged with Council in accordance with the City of Sydney's adopted Schedule of Fees and Charges. The Public Domain Damage Bond must be submitted as an unconditional bank guarantee or insurance bond as per the Council's Performance Bond Policy in favour of Council as security for repairing any damage to the public domain in the vicinity of the site (Guarantee).
- (b) The Guarantee must be lodged with Council prior to an approval for demolition being granted or any Construction Certificate being issued, whichever is earlier.
- (c) The Guarantee in this condition will be retained in full until the Public Domain Works Deposit Guarantee is lodged with Council. Upon lodgement of the Public Domain Works Deposit Guarantee, the Guarantee in this condition will be released.

(47) DRAINAGE AND SERVICE PIT LIDS

All existing or proposed drainage and service pit lids throughout the public domain shall be to City of Sydney specifications and heel / bicycle safe, slip resistant, infill with material to match surrounding surface, finished flush with the adjacent pavement to avoid trip hazards and be clear of obstructions for easy opening and cleaning. Infill pit lids are to be detailed where specified by the Council's Public Domain Officer. Private pits are not permitted within the public domain. All details of pit lids must be shown on the public domain plan and must be approved by the City's Public Domain Unit prior to the issue of an approval for public domain works.

(48) DILAPIDATION REPORT – MAJOR EXCAVATION/DEMOLITION

- (a) Subject to the receipt of permission of the affected landowner, dilapidation report/s, including a photographic survey of 178 Church Street, 184 Church Street, 33 Fitzgerald Street, 2 Rapper Street and 4-6 Rapper Street are to be prepared by an appropriately qualified structural engineer prior to commencement of demolition/excavation works. A copy of the dilapidation report/s together with the accompanying photographs must be given to the above property owners, and a copy lodged with the Accredited Certifier and the Council prior to the issue of a Construction Certificate.

UPON COMPLETION OF EXCAVATION/DEMOLITION

- (b) A second Dilapidation Report/s, including a photographic survey must then be submitted at least one month after the completion of demolition/excavation works. A copy of the second dilapidation report/s, together with the accompanying photographs must be given to the above property owners, and a copy lodged with the Principal Certifier and the Council prior to the issue of any Occupation Certificate.

Any damage to buildings, structures, lawns, trees, sheds, gardens and the like must be fully rectified by the applicant or owner, at no cost to the affected property owner.

Note: Prior to the commencement of the building surveys, the applicant/owner must advise (in writing) all property owners of buildings to be surveyed of what the survey will entail and of the process for making a claim regarding property damage. A copy of this information must be submitted to Council.

(49) SYDNEY WATER CERTIFICATE

A Section 73 Compliance Certificate under the Sydney Water Act 1994 must be obtained from Sydney Water Corporation.

Application must be made through an authorised Water Servicing Coordinator. Please refer to the Building Developing and Plumbing section on the web site www.sydneywater.com.au then refer to "Water Servicing Coordinator" under "Developing Your Land" or telephone 13 20 92 for assistance.

Following the submission of the application a "Notice of Requirements" will advise of water and sewer infrastructure to be built and charges to be paid. Please make early contact with the Coordinator, since building of water/sewer infrastructure can be time consuming and may impact on other services and building, driveway or landscape design.

The Section 73 Certificate must be submitted to Council or the Principal Certifier prior to an Occupation Certificate or subdivision/strata certificate being issued.

(50) MECHANICAL VENTILATION

- (a) The premises must be ventilated in accordance with the *Building Code of Australia* and *AS1668.1 and AS1668.2 - The Use of Ventilation and Air-conditioning in Buildings - Mechanical Ventilation in Buildings*.
- (b) Details of any mechanical ventilation and/or air conditioning system complying with *AS1668.1 and AS1668.2 - The Use of Ventilation and Air-conditioning in Buildings - Mechanical Ventilation in Buildings*, the *Building Code of Australia* and relevant Australian Standards must be prepared and certified in accordance with Clause A5.2(1)(e) of the *Building Code of Australia*, to the satisfaction of the Accredited Certifier prior to the issue of a Construction Certificate.
- (c) Prior to issue of any Occupation Certificate and following the completion, installation, and testing of all the mechanical ventilation systems, a Mechanical Ventilation Certificate of Completion and Performance in accordance with Clause A5.2(1)(e) of the *Building Code of Australia*, must be submitted to the Principal Certifier.

(51) WASTE AND RECYCLING COLLECTION CONTRACT

Prior to any Occupation Certificate being issued and/or commencement of the use, whichever is earlier, the building owner must ensure that there is a contract with a licensed contractor for the removal of **all waste**. No garbage is to be

placed on the public way, e.g. footpaths, roadways, plazas, reserves, at any time.

(52) WASTE AND RECYCLING MANAGEMENT

The proposal must comply with the relevant provisions of Council's *Guidelines for Waste Management in New Developments 2018* which requires facilities to minimise and manage waste and recycling generated by the proposal.

(53) WASTE AND RECYCLING MANAGEMENT

Prior to any Occupation Certificate being issued or the use commencing, whichever is earlier, the Principal Certifier must ensure that waste handling works have been completed in accordance with the Waste and Recycling Management Plan; other relevant development consent conditions; and Council's *Guidelines for Waste Management in New Developments 2018*.

(54) CLASSIFICATION OF WASTE

Prior to the exportation of waste (including fill or soil) from the site, the waste materials must be classified in accordance with the provisions of the Protection of the *Environment Operations Act 1997* and the *NSW DECC Waste Classification Guidelines, Part1: Classifying Waste (July 2009)*. The classification of the material is essential to determine where the waste may be legally taken. The *Protection of the Environment Operations Act 1997* provides for the commission of an offence for both the waste owner and the transporters if the waste is taken to a place that cannot lawfully be used as a waste facility for the particular class of waste. For the transport and disposal of industrial, hazardous or Group A liquid waste advice should be sought from the EPA.

(55) IMPORTED FILL MATERIALS

All fill imported onto the site shall be validated to ensure the imported fill is suitable for the proposed land use from a contamination perspective. Fill imported on to the site shall also be compatible with the existing soil characteristic for site drainage purposes.

The City may require details of appropriate validation of imported fill material to be submitted with any application for future development of the site. Hence all fill imported onto the site should be validated by either one or both of the following methods during remediation works:

- (a) Imported fill must be accompanied by documentation from the supplier which certifies that the material is not contaminated based upon analyses of the material for the known past history of the site where the material is obtained; and/or
- (b) Sampling and analysis of the fill material shall be conducted in accordance with NSW EPA (1995) Sampling Design Guidelines.

(56) NOTIFICATION – NEW CONTAMINATION EVIDENCE

Any new information which comes to light during remediation, demolition or construction works which has the potential to alter previous conclusions about

site contamination shall be notified to Council's Area Planning Manager and the Principal Certifier.

(57) ASBESTOS REMOVAL WORKS

- (a) All works removing asbestos containing materials must be carried out by a suitably licensed asbestos removalist duly licensed with Safework NSW, holding either a Friable (Class A) or a Non-Friable (Class B) Asbestos Removal Licence, whichever applies.

A copy of the relevant licence shall be made available to any authorised Council officer on request within 24 hours.

- (b) Five days prior to the commencement of licensed asbestos removal, Safework NSW must be formally notified of the works. All adjoining properties and those opposite the development must be notified in writing of the dates and times when asbestos removal is to be conducted. The notification must identify the licensed asbestos removal contractor and include a contact person for the site together with telephone number and email address.
- (c) All work must be carried out in accordance with the *Work Health and Safety Regulation 2017* and the NSW Government and SafeWork NSW document entitled *How to manage and control asbestos in the work place: Code of Practice (Safework NSW) December 2011* and the *City of Sydney Managing Asbestos Policy dated 21 October 2013 and associated guidelines*.
- (d) The asbestos removalist must use signs and barricades to clearly indicate the area where the asbestos removal work is being performed. Signs must be placed in positions so that people are aware of where the asbestos removal work area is and should remain in place until removal is completed and clearance to reoccupy has been granted. Responsibilities for the security and safety of the asbestos removal site and removal must be specified in the asbestos removal control plan (where required). This includes inaccessible areas that are likely to contain asbestos.
- (e) Warning signs must be placed so they inform all people nearby that asbestos removal work is taking place in the area. Signs must be placed at all of the main entry points to the asbestos removal work area where asbestos is present. These signs must be weatherproof, constructed of light-weight material and adequately secured so they remain in prominent locations. The signs must be in accordance with AS 1319 -1994 *Safety Signs for the Occupational Environment* for size, illumination, location and maintenance.
- (f) Asbestos waste must only be transported and disposed of at an EPA licensed waste facility.
- (g) No asbestos products are to be reused on the site (i.e. packing pieces, spacers, formwork or fill etc).
- (h) No asbestos laden skips or bins are to be left in any public place without the written approval of Council.

- (i) A site notice board must be located at the main entrance to the site in a prominent position and must have minimum dimensions of 841mm x 594mm (A1) with any text on the notice to be a minimum of 30 point type size.

The site notice board must include the following:

- (i) contact person for the site;
- (ii) telephone and facsimile numbers and email address; and
- (iii) site activities and time frames.

(58) STOCKPILES

- (a) No stockpiles of soil or other materials shall be placed on footpaths or nature strips unless prior approval has been obtained from the City's Construction Regulation Team.
- (b) All stockpiles of soil or other materials shall be placed away from drainage lines, gutters or stormwater pits or inlets.
- (c) All stockpiles of soil or other materials likely to generate dust or odours shall be covered.
- (d) All stockpiles of contaminated soil shall be stored in a secure area and be covered if remaining more than 24 hours

(59) UTILITY SERVICES

To ensure that utility authorities are advised of the development:

- (a) Prior to the issue of a Construction Certificate a survey is to be carried out of all utility services within and adjacent to the site including relevant information from utility authorities and excavation if necessary, to determine the position and level of services.
- (b) Prior to the commencement of work the applicant is to obtain written approval from the utility authorities (e.g. Energy Australia, Sydney Water, and Telecommunications Carriers) in connection with the relocation and/or adjustment of the services affected by the construction of the underground structure. Any costs in the relocation, adjustment or support of services are to be the responsibility of the developer.

(60) APPLICATION FOR HOARDINGS AND SCAFFOLDING INSTALLED ON OR ABOVE A PUBLIC ROAD AND OPERATING HOISTING DEVICES INCLUDING BUILDING MAINTENANCE UNITS OVER A PUBLIC ROAD

- (a) Where a hoarding and/or scaffolding (temporary structures) are proposed to be installed on or above a road reservation (footway and/or roadway), a separate application under Section 68 of the *Local Government Act 1993* and Sections 138/139 of the *Roads Act 1993* must be submitted to and approved by Council for such structures.

- (b) Where an approval (Permit) is granted allowing the placement of temporary structures on or above a public road the structures must comply fully with Council's *Hoardings and Scaffolding Policy; Guidelines for Hoardings and Scaffolding*; and the conditions of approval (Permit) granted including:
- (i) maintaining a current and valid approval for the full duration that the temporary structure/s is in place;
 - (ii) maintaining temporary structure/s in a structurally sound and stable condition for the full duration of installation (Clause 2.11.1);
 - (iii) bill posters and graffiti being removed within 24 hours of their placement (Clause 2.11.2);
 - (iv) maintaining temporary structures and the public place adjoining the work site in a clean and tidy condition including repainting and/or repair of graphics (Clauses 2.11.1, 2.11.4, 2.14.1 and 3.9.3);
 - (v) maintaining a watertight deck (Type B hoardings) to prevent liquids including rainwater, falling onto the footway/roadway surfaces (Clauses 3.9.1 and 3.9.4);
 - (vi) approved site sheds on the decks of a Type B hoarding being fully screened from the public place (Clause 3.9.5);
 - (vii) material and equipment not being placed or stored on the deck of Type B hoardings, unless specifically approved by Council (Clause 3.9.4);
 - (viii) providing and maintaining operational artificial lighting systems under Type B hoardings including at high-bay truck entry points (Clause 3.9.9); and
 - (ix) ensuring all required signage, artwork or historic images are provided and fully maintained to the City's requirements (Clauses 3.4, 3.9.3, 3.9.6, 3.9.8, 3.10.1 and 4.2).

If it is proposed to operate a hoisting device including a building maintenance unit above a public road which swings, hoists material/equipment and/or slews/wind vanes any part of the device over the public road, a separate application under Section 68 of the *Local Government Act 1993* and Sections 138/139 of the *Roads Act 1993* must be made to Council to obtain approval.

Note: 'Building maintenance unit' means a power-operated suspended platform and associated equipment on a building specifically designed to provide permanent access to the faces of the building for maintenance (*Work Health and Safety Regulation 2017*).

(61) WORKS REQUIRING USE OF A PUBLIC PLACE

Where construction/building works require the use of a public place including a road or footpath, a separate application under Sections 138/139 of the *Roads Act 1993* must be submitted to and approved by Council prior to the commencement of work. Details of any barricade construction, area of

enclosure and period of work are required to be submitted to the satisfaction of Council.

(62) FLASHINGS TO BOUNDARY WALLS

A flashing must be provided to prevent water entering between the proposed and existing external boundary walls of the adjoining properties.

Note: Attachments or connections to party walls may require the consent of the adjoining property owner/s.

(63) PRODUCTS BANNED UNDER THE BUILDING PRODUCTS (SAFETY) ACT 2017

- (a) No building products that are banned, or products that are subject to a ban if used in a particular way, under the Building Products (Safety) Act 2017 are to be used in the construction of the development approved in this development consent.
- (b) Prior to the issue of any Occupation Certificate, the principal certifier is to confirm that none of the building products used on the building are subject to a building product use ban under the Building Products (Safety) Act 2017 or, if a product is only subject to a ban if used in a particular way that it is not used in any way contrary to the Building Products (Safety) Act 2017.

(64) EXTERNAL WALLS AND CLADDING FLAMMABILITY

The external walls of the building including attachments must comply with the relevant requirements of the Building Code of Australia (BCA). Prior to the issue of a Construction Certificate and Occupation Certificate the Accredited Certifier and the Principal Certifier must:

- (a) be satisfied that suitable evidence is provided to demonstrate that the products and systems proposed for use or used in the construction of external walls including finishes and claddings such as synthetic or aluminium composite panels comply with the relevant requirements of the BCA; and
- (b) ensure that the documentation relied upon in the approval processes include an appropriate level of detail to demonstrate compliance with the BCA as proposed and as built.

(65) ELECTRICITY SUBSTATION

If required by the applicable energy supplier, the owner must dedicate to the applicable energy supplier, free of cost, an area of land within the development site, but not in any landscaped area or in any area visible from the public domain, to enable an electricity substation to be installed. The size and location of the substation is to be submitted for approval of Council and Ausgrid, prior to a Construction Certificate being issued or the commencement of the use, whichever is earlier.

(66) LETTERBOXES

- (a) Details of the location and design of all letterboxes are to be submitted to and approved by Council's Area Coordinator Planning Assessments / Area Planning Manager prior to the issue of a Construction Certificate.
- (b) Letterboxes are to be discreetly located, shall not obstruct and/or dominate the public way and shall be of a type and specification that minimises opportunities for mail theft.
- (c) Where possible, consideration should be given to locating letterboxes within secure building lobbies.

Note: The applicant is strongly advised to contact Australia Post to discuss how the letterboxes within the lobby will be accessed.

(67) EROSION AND SEDIMENT CONTROL - BETWEEN 250 AND 2,500SQM

Prior to the commencement of demolition/excavation/construction work, an Erosion and Sediment Control Plan (ESCP) must be submitted to and be approved by the Principal Certifier. The ESCP must:

- (a) Conform to the specifications and standards contained in *Managing Urban Stormwater: Soils and Construction* (Landcom, 2004); the *Guidelines for Erosion and Sediment Control on Building Sites* (City of Sydney, 2004); and the *NSW Protection of the Environment Operations Act 1997*.
- (b) Include a drawing(s) that clearly shows:
 - (i) location of site boundaries and adjoining roads
 - (ii) approximate grades and indications of direction(s) of fall
 - (iii) approximate location of trees and other vegetation, showing items for removal or retention
 - (iv) location of site access, proposed roads and other impervious areas
 - (v) existing and proposed drainage patterns with stormwater discharge points
 - (vi) north point and scale
- (c) Specify how soil conservation measures will be conducted on site including:
 - (i) timing of works
 - (ii) locations of lands where a protective ground cover will, as far as is practicable, be maintained
 - (iii) access protection measures
 - (iv) nature and extent of earthworks, including the amount of any cut and fill

- (v) where applicable, the diversion of runoff from upslope lands around the disturbed areas
- (vi) location of all soil and other material stockpiles including topsoil storage, protection and reuse methodology
- (vii) procedures by which stormwater is to be collected and treated prior to discharge including details of any proposed pollution control device(s)
- (viii) frequency and nature of any maintenance program
- (ix) other site-specific soil or water conservation structures.

(68) WASTE/RECYCLING COLLECTION

- (a) The collection of waste and recycling must only occur during the designated zone collection times as outlined in the City's Waste Policy – Local Approvals Policy for Managing Waste in Public Places 2017.
- (b) Garbage and recycling must not be placed on the street for collection more than half an hour before the scheduled collection time. Bins and containers are to be removed from the street within half an hour of collection.

SCHEDULE 1C

DURING CONSTRUCTION/PRIOR TO OCCUPATION/COMPLETION

(69) OCCUPATION CERTIFICATE TO BE SUBMITTED

An Occupation Certificate must be obtained from the Principal Certifier and a copy submitted to Council prior to commencement of occupation or use of the whole or any part of a new building, an altered portion of, or an extension to an existing building.

(70) BASIX

All commitments listed in each relevant BASIX Certificate for the development must be fulfilled prior to any Occupation Certificate being issued.

(71) HOURS OF WORK AND NOISE – OUTSIDE CBD

The hours of construction and work on the development must be as follows:

- (a) All work, including building/demolition and excavation work, and activities in the vicinity of the site generating noise associated with preparation for the commencement of work (eg. loading and unloading of goods, transferring of tools etc) in connection with the proposed development must only be carried out between the hours of 7.30am and 5.30pm on Mondays to Fridays, inclusive, and 7.30am and 3.30pm on Saturdays, with safety inspections being permitted at 7.00am on work days, and no work must be carried out on Sundays or public holidays.
- (b) All work, including demolition, excavation and building work must comply with the City of Sydney Code of Practice for Construction Hours/Noise 1992 and Australian Standard 2436 - 2010 Guide to Noise Control on Construction, Maintenance and Demolition Sites.
- (c) Notwithstanding the above, the use of a crane for special operations, including the delivery of materials, hoisting of plant and equipment and erection and dismantling of on site tower cranes which warrant the on-street use of mobile cranes outside of above hours can occur, subject to a permit being issued by Council under Section 68 of the Local Government Act 1993 and/or Section 138 of the Roads Act 1993.

Note: Works may be undertaken outside of hours, where it is required to avoid the loss of life, damage to property, to prevent environmental harm and/or to avoid structural damage to the building. Written approval must be given by the Construction Regulation Unit, prior to works proceeding

The *City of Sydney Code of Practice for Construction Hours/Noise 1992* allows extended working hours subject to the approval of an application in accordance with the Code and under Section 4.55 of the *Environmental Planning and Assessment Act 1979*.

(72) LOADING AND UNLOADING DURING CONSTRUCTION

The following requirements apply:

- (a) All loading and unloading associated with construction activity must be accommodated on site.
- (b) If, during excavation, it is not feasible for loading and unloading to take place on site, a Works Zone on the street may be considered by Council.
- (c) A Works Zone may be required if loading and unloading is not possible on site. If a Works Zone is warranted an application must be made to Council at least 8 weeks prior to commencement of work on the site. An approval for a Works Zone may be given for a specific period and certain hours of the days to meet the particular need for the site for such facilities at various stages of construction. The approval will be reviewed periodically for any adjustment necessitated by the progress of the construction activities.
- (d) In addition to any approved Works Zone, provision must be made for loading and unloading to be accommodated on site once the development has reached ground level.
- (e) The structural design of the building must allow the basement and/or the ground floor to be used as a loading and unloading area for the construction of the remainder of the development.
- (f) Where hoisting activity over the public place is proposed to be undertaken including hoisting from a Works Zone, a separate approval under Section 68 of the Local Government Act 1993 must be obtained.

(73) NO OBSTRUCTION OF PUBLIC WAY

The public way must not be obstructed by any materials, vehicles, refuse, skips or the like, under any circumstances. Non-compliance with this requirement will result in the issue of a notice by Council to stop all work on site.

(74) USE OF MOBILE CRANES

The following requirements apply:

- (a) Mobile cranes operating from the road must not be used as a method of demolishing or constructing a building.
- (b) For operations warranting the on-street use of mobile cranes (such as delivery of materials, hoisting of plant/equipment, erection and dismantling of onsite tower cranes, etc), permits must be obtained from Council for the use of a mobile crane. The permits must be obtained 48 hours beforehand for partial road closures which, in the opinion of Council will create minimal traffic disruptions and 4 weeks beforehand in the case of full road closures and partial road closures which, in the opinion of Council, will create significant traffic disruptions.
- (c) Special operations and the use of mobile cranes must comply with the approved hours of construction. Mobile cranes must not be delivered to the site prior to 7.30am without the prior approval of Council.

(75) ARCHAEOLOGICAL DISCOVERY DURING EXCAVATION

- (a) Should any relics be unexpectedly discovered on the site during excavation, all excavation or disturbance to the area is to stop immediately and the Heritage Council of NSW should be informed in accordance with section 146 of the Heritage Act 1977.
- (b) Should any Aboriginal objects be unexpectedly discovered then all excavation or disturbance of the area is to stop immediately and NSW Government Office of Environment and Heritage is to be informed in accordance with Section 89A of the *National Parks and Wildlife Act 1974*.
- (c) Should any archaeological remains or Aboriginal objects be discovered, a copy of recording of the finds and the final archaeological summary report is to be submitted to Council prior to the issue of any Occupational Certificate.
- (d) If the discovery is on Council's land, Council must be informed.

(76) NOTIFICATION OF EXCAVATION WORKS OR USE OF HIGH NOISE EMISSION APPLIANCES/PLANT

The immediately adjoining neighbours must be given a minimum of 48 hours' notice that excavation, shoring or underpinning works or use of high noise emission appliances / plant are about to commence.

(77) USE OF HIGH NOISE EMISSION APPLIANCES / PLANT

- (a) The operation of high noise emission appliances, plant and/or machinery such as pile – drivers, rock breakers and hydraulic hammers and those which are not listed in Groups B, C, D, E or F of Schedule 1 of the *City of Sydney Code of Practice for Construction Hours/Noise 1992* and Australian Standard 2436-2010 *Guide to Noise Control on Construction, Maintenance and Demolition Sites* is restricted to the hours of (EHO to specify hours)
- (b) All reasonable and feasible steps must be undertaken to ensure that the work, including demolition, excavation and building complies with the *City of Sydney Code of Practice for Construction Hours/Noise 1992* and Australian Standard 2436- 2010 *Guide to Noise Control on Construction, Maintenance and Demolition Sites*.

(78) CONNECTION TO SEWERS OF SYDNEY WATER CORPORATION

Waste water arising from the use must be directed to the sewers of the Sydney Water Corporation (SWC) under a Trade Waste License Agreement. The pre-treatment of wastewater may be a requirement of the Corporation prior to discharge to the sewer. Details of the Corporation's requirements should be obtained prior to the commencement of construction work.

(79) COVERING OF LOADS

All vehicles involved in the excavation and/or demolition process and departing the property with demolition materials, spoil or loose matter must have their loads fully covered before entering the public roadway.

(80) HAZARDOUS AND INDUSTRIAL WASTE

Hazardous and/or industrial waste arising from the demolition/operational activities must be removed and/or transported in accordance with the requirements of the NSW Work Cover Authority pursuant to the provisions of the following:

- (a) *Protection of the Environment Operations Act 1997*
- (b) *Protection of the Environment Operations (Waste) Regulation 2005*
- (c) *Waste Avoidance and Resource Recovery Act 2001*
- (d) *Work Health and Safety Act 2011*
- (e) *Work Health and Safety Regulation 2017.*

(81) ENCROACHMENTS – NEIGHBOURING PROPERTIES

No portion of the proposed structure shall encroach onto the adjoining properties.

(82) ENCROACHMENTS – PUBLIC WAY

No portion of the proposed structure, including gates and doors during opening and closing operations, shall encroach upon Council's footpath area.

(83) SURVEY

All footings, walls and floor slabs adjacent to a boundary must be set out by a registered surveyor. On commencement of brickwork or wall construction a survey and report, prepared by a Registered Surveyor, must be submitted to the Principal Certifier indicating the position of external walls in relation to the boundaries of the allotment. Any encroachments by the subject building over adjoining boundaries or roads must be removed prior to continuation of building construction work.

(84) SURVEY CERTIFICATE AT COMPLETION

A Survey Certificate prepared by a Registered Surveyor must be submitted to the Principal Certifier at the completion of the building work certifying the location of the building in relation to the boundaries of the allotment.

SCHEDULE 2

PRESCRIBED CONDITIONS

The prescribed conditions in accordance with Division 8A of the *Environmental Planning and Assessment Regulation 2000* apply:

- Clause 98 Compliance with *Building Code of Australia* and insurance requirements under the *Home Building Act 1989*
- Clause 98A Erection of signs
- Clause 98B Notification of *Home Building Act 1989* requirements
- Clause 98C Conditions relating to entertainment venues
- Clause 98D Conditions relating to maximum capacity signage
- Clause 98E Conditions relating to shoring and adequacy of adjoining property

Refer to the NSW State legislation for full text of the clauses under Division 8A of the *Environmental Planning and Assessment Regulation 2000*. This can be accessed at: <http://www.legislation.nsw.gov.au>