

Attachment A

Recommended Conditions of Consent

DEFERRED COMMENCEMENT CONDITION

(1) ROAD WIDENING ORDER TO BE REVOKED, VARIED OR OTHERWISE REMOVED

Subject to the consent of the relevant roads authority, the Road Widening Order affecting the Elizabeth Street frontage of the site (Gazetted 30 June 1950), insofar as it affects the subject site is to be:

- (a) Revoked by order published in the Government Gazette under Section 27(1)(b) of the Roads Act 1993; or
- (b) Varied so as not to apply to the subject site by order published in the Government Gazette under Section 27(1)(a) of the Roads Act 1993; or
- (c) Otherwise removed or declared invalid.

Evidence of the above relevant matter(s) must be produced to the consent authority, within 24 months of the date of the determination, otherwise the consent will lapse.

Under section 76(4) of the EP&A Regulation, the consent authority will notify you in writing if the matters above have been satisfied and the date from which this consent operates.

The conditions of development consent below apply from the date that this consent operates.

Note: Section 76(3) of the EP&A Regulation enables a consent authority to specify the period within which the applicant must produce evidence to the consent authority sufficient enough to enable it to be satisfied as to the relevant matter(s) that it requires before a deferred commencement consent can operate. Where a period is specified under section 76(3), a deferred commencement consent will lapse if the applicant has not produced sufficient evidence for the consent authority to be satisfied of the relevant matters on the expiration of the specified period.

Where the applicant produces evidence of the relevant matters in accordance with section 76(4) of the EP&A Regulation, the consent authority must notify the applicant whether or not it is satisfied as to the relevant matter(s). If the consent authority has not notified the applicant within 28 days after receiving the applicant's evidence, the consent authority is taken to have notified the applicant that it is not satisfied about the relevant matter(s) on the date on which that period expires, for the purposes of section 8.7 of the EP&A Act (see sections 76(4), (5) and (6) of the EP&A Regulation).

Terms and Reasons for Conditions

Under section 88(1)(c) of the EP&A Regulation, the consent authority must provide the terms of all conditions and reasons for imposing the conditions other than the conditions prescribed under section 4.17(11) of the EP&A Act. The terms of the conditions and reasons are set out below.

GENERAL CONDITIONS

(1) APPROVED DEVELOPMENT

- (a) Development must be in accordance with Development Application No. D/2022/600 dated 20 June 2022 and the following drawings prepared by SJB Architects:

Drawing Number	Drawing Name	Date
DA-0101 Rev 5	Demolition Plan – Ground Floor	16-03-2023
DA-0102 Rev 5	Demolition Plan – Level 01	16-03-2023
DA-0103 Rev 4	Proposed Site Plan	16-03-2023
DA-0200 Rev 10	Floor Plan – Basement 2	17-03-2023
DA-0201 Rev 10	Floor Plan – Basement 1	17-03-2023
DA-0202 Rev 12	Floor Plan – Level 00	17-03-2023
DA-0203 Rev 12	Floor Plan – Level 01	17-03-2023
DA-0204 Rev 10	Floor Plan – Level 02	17-03-2023
DA-0205 Rev 10	Floor Plan – Level 03	17-03-2023
DA-0206 Rev 13	Floor Plan – Level 04	17-03-2023
DA-0209 Rev 12	Floor Plan – Roof	17-03-2023
DA-0501 Rev 10	Elevation Sheet 1	17-03-2023
DA-0502 Rev 10	Elevation Sheet 2	17-03-2023

Drawing Number	Drawing Name	Date
DA-0503 Rev 10	Elevation Sheet 3	17-03-2023
DA-0504 Rev 10	Elevation Sheet 4	17-03-2023
DA-0601 Rev 11	North – South Section	17-03-2023
DA-0602 Rev 11	West – East Section	17-03-2023

and as amended by the conditions of this consent.

- (b) In the event of any inconsistency between the approved plans and supplementary documentation, the drawings will prevail.

Reason

To ensure all parties are aware of the approved plans and supporting documentation that applies to the development.

(2) DESIGN MODIFICATIONS

The design of the building must be modified as follows:

- (a) The basement carpark must be setback 5.5 metres from the northern property boundary (Goodlet Street) to allow for the retention of the existing paperbark street trees.
- (b) The signage zone shown on the corner of Goodlet and Elizabeth Street is not approved and is to be deleted from the plans.
- (c) The letterboxes are to be relocated to a secure location.
- (d) The design of the footpath awning on Cleveland Street is to be amended so that the clearance height between the footpath and the kerb is no less than 3.2m at any given point.
- (e) The architectural plans are to be amended to include markups and additional annotations regarding requirements and output capacity for PV systems. To maintain consistency with sustainability reporting in the development application; annotations are required to clearly identify a photovoltaic system, totalling a peak capacity in line with previously reported 45 kWp.

The modifications are to be submitted to and approved by Council’s Area Coordinator Planning Assessments / Area Planning Manager Planning prior to the issue of a construction certificate.

Reason

To require amendments to the approved plans and supporting documentation following assessment of the development.

(3) BUILDING HEIGHT

- (a) The height of the building must not exceed RL 57.40 (AHD) to the top of the building (excluding photovoltaic panels).
- (b) Prior to an Occupation Certificate being issued, a Registered Surveyor must provide certification that the height of the building accords with (a) above, to the satisfaction of the Principal Certifier.

Reason

To ensure the constructed development complies with the approved height.

(4) FLOOR SPACE RATIO - ALL OTHER AREAS

The following applies to Floor Space Ratio:

- (a) The Floor Space Ratio on the northern land parcel (Lot 1 in DP 100535) must not exceed 2.41:1 and for the southern land parcel (Lot 3 in DP 575329) must not exceed 2.1:1 calculated in accordance with Sydney Local Environmental Plan 2012. For the purposes of the calculation of FSR, the Gross Floor Area on the northern land parcel is 2,595 sqm, and for the southern land parcel is 536 sqm, and the total Gross Floor Area is 3,131 sqm.
- (b) Prior to an Occupation Certificate being issued, a Registered Surveyor must provide certification of the total Gross Floor Areas in the development, utilising the definition under Sydney Local Environmental Plan 2012, applicable at the time of development consent, to the satisfaction of the Principal Certifier.

Reason

To ensure the constructed development complies with the approved floor space ratio.

(5) USE - SEPARATE DA REQUIRED

No consent is granted or implied for the fit-out or specific use of the ground floor retail tenancies.

A development consent or Complying Development Certificate (as appropriate) is required to be obtained for the fit-out and use of each individual tenancy prior to that fit-out or use commencing.

Reason

To require separate consent to be obtained for a use.

(6) SIGNS - SEPARATE DA REQUIRED

A separate development application for any proposed signs additional to those approved as part of this consent (other than exempt or complying signs) must be submitted to and approved by Council prior to the erection or display of any such signs.

Reason

To require separate consent to be obtained for any additional signs.

(7) APPROVED DESIGN ROOF - TOP PLANT

All roof-top plant and associated equipment (excluding photovoltaic panels) must be located within the approved building envelope.

Reason

To ensure the constructed development complies with the approved height.

(8) AFFORDABLE HOUSING CONTRIBUTION – RESIDUAL LAND OR CENTRAL SYDNEY – PAYMENT IN LIEU OF FLOOR SPACE CONTRIBUTION – PRIOR TO CONSTRUCTION CERTIFICATE

- (a) In accordance with the City of Sydney Affordable Housing Program and prior to the issue of a Construction Certificate, the applicant must provide evidence that a monetary contribution towards the provision of affordable housing has been paid to the City of Sydney Council.
- (b) The contribution is \$233,772.01 (to be indexed in accordance with (c)). This is calculated by establishing the sum of the equivalent monetary contribution \$10,611.53 multiplied by 0.5% of the total floor area for non-residential development (4,406 sqm).
- (c) If the contribution is paid after the indexation period in which the consent is granted, being March 2023 to February 2024, the above contribution will be adjusted according to the Sydney LGA median strata dwelling price ('MDP') using the following formula.
- (d) Contribution payable at Time of Payment = $C \times \text{MDP2} / \text{MDP1}$, where:
 - (i) C is the original total contribution amount payable to the City of Sydney as shown above;
 - (ii) MDP2 is the Median Strata Dwelling Price in Sydney LGA taken from the most recent NSW Government Rent and Sales Report at the time of indexation of the equivalent monetary contribution rate; and
 - (iii) MDP1 is the Median Strata Dwelling Price in Sydney LGA taken from the NSW Government Rent and Sales Report used to establish the current equivalent monetary contribution rate, being 1 March 2023 to 29 February 2024.

Contact Council's Planning Assessment Unit at planningsystemsadmin@cityofsydney.nsw.gov.au for written confirmation of the amount payable, with indexation as necessary, prior to payment.

Reason

To ensure development contributions are paid to contribute to the provision of essential affordable rental housing infrastructure.

(9) SECTION 7.11 CONTRIBUTIONS PAYABLE - CONTRIBUTION TOWARDS PUBLIC AMENITIES – CITY OF SYDNEY DEVELOPMENT CONTRIBUTIONS PLAN 2015 – EAST PRECINCT

Council has identified the development will increase demand for public amenities and facilities. Pursuant to Section 7.11 of the Environmental Planning and Assessment Act, 1979 (as amended), and the City of Sydney Development Contributions Plan 2015 the following monetary contributions are required towards the cost of public amenities.

<u>Contribution Category</u>	<u>Amount</u>
Open Space	\$91,925.58
Community Facilities	\$86,616.34
Traffic and Transport	\$14,410.78
Stormwater Drainage	\$0.00
Total	\$192,952.70

The City of Sydney will index the above contribution for inflation at the time of payment using the following formula.

$$C_{\text{payment}} = C_{\text{consent}} \times (CPI_{\text{payment}} \div CPI_{\text{consent}})$$

Where:

C_{payment} = Is the contribution at time of payment;

C_{consent} = Is the contribution at the time of consent, as shown above;

CPI_{payment} = Is the Consumer Price Index (All Groups Index) for Sydney published by the Australian Bureau of Statistics that applies at the time of payment; and

CPI_{consent} = Is the Consumer Price Index (All Groups Index) for Sydney at the date the contribution amount above was calculated being 134 for the June 2023 quarter.

The contribution must be paid prior to the issue of any Construction Certificate in relation to this development.

Please contact Council's Planning Administration staff at planningsystemsadmin@cityofsydney.nsw.gov.au to request a letter confirming the indexed contribution amount payable.

Once the letter confirming the indexed contribution is obtained, payment may be made at any of the City's Neighbourhood Service Centres or the One Stop Shop at Town Hall House. Acceptable payment methods are EFTPOS (debit card only), cash (up to 10K only), Credit Card (up to 50K only) or a bank cheque made payable to the City of Sydney. Personal or company cheques will not be accepted.

Reason

To ensure development contributions are paid to address the increased demand for public amenities and services resulting from the approved development.

(10) VEHICLE FOOTWAY CROSSING

A separate application is to be made to, and approved by, Council for the construction of any proposed vehicle footway crossing or for the removal of any existing crossing and replacement of the footpath formation where any such crossings are no longer required.

All disused or redundant vehicle crossings and laybacks must be removed and footway, kerb, gutter and road restoration reinstated in accordance with Council's standards, to suit the adjacent finished footway and edge treatment materials, levels and details, or as otherwise directed by Council officers. All construction and replacement works are to be completed in accordance with the approved plans prior to the issue of any Occupation Certificate.

Note: In all cases the construction materials should reinforce the priority of pedestrian movement over that of the crossing vehicle.

Reason

To ensure all relevant approvals for traffic and parking works are obtained and designed in accordance with Council requirements.

(11) SERVICE VEHICLE SIZE LIMIT

The size of vehicles servicing the property must be a maximum length of 6.4m.

Reason

To maintain the orderly operation of vehicle parking and loading areas.

(12) VEHICLE ACCESS

The site must be configured to allow all vehicles to be driven onto and off the site in a forward direction.

Reason

To ensure orderly traffic movements on and around the site.

(13) ASSOCIATED ROADWAY COSTS

All costs associated with the construction of any new road works including kerb and gutter, road pavement, drainage system and footway shall be borne by the developer. The new road works must be designed and constructed in accordance with the City's "Sydney Streets Technical Specification" including amendments and "Sydney Streets Design Code".

Reason

To ensure all roadway works are designed and constructed in accordance with Council requirements.

(14) COST OF SIGNPOSTING

All costs associated with signposting for any kerbside parking restrictions and traffic management measures associated with the development shall be borne by the developer.

Reason

To ensure all associated roadway works costs are borne by the developer.

(15) CHANGES TO KERB SIDE PARKING RESTRICTIONS

A separate submission must be made to the Local Pedestrian, Cycling and Traffic Calming Committee via the City Infrastructure and Traffic Operations Unit seeking the City's approval for any changes to kerb side parking arrangements. There is no guarantee kerb side parking will be changed, or that any change will remain in place for the duration of the development use.

The submission must include two plans. One showing the existing kerb side parking restriction signs and stems, the second showing the proposed kerb side parking restriction signs and stems. Both plans must include chainages to all signs and stems from the kerb line of the nearest intersection.

All costs associated with the parking proposal will be borne by the developer.

Note: As parking in the LGA is at a premium, it is recommended that the applicant should approach the Area Traffic Engineer to discuss the proposal before making a submission.

Reason

To require separate consent to be obtained for changes to kerb side parking arrangements.

(16) EXTERNAL LIGHTING

A separate development application is required to be lodged and approved prior to any external floodlighting or illumination of the building or site landscaping.

Reason

To clarify that consent has not been granted for the external floodlighting or illumination of the development.

(17) SWINGING DOORS OVER PUBLIC WAY

Any access doors to enclosures housing building services and facilities, such as hydrant and sprinkler booster assemblies or the like, must not open over the footway/roadway.

Reason

To ensure no element of the development obstructs the use of the public way.

(18) MATERIALS FOR MAKING GOOD

New materials for making good and repairs to retained elements are to match the existing in terms of sizes, profile and properties.

Reason

To ensure appropriate materials and finishes are used.

(19) RETENTION OF FEATURES

The fireplace located in the southwestern corner on the first floor of 502-514 Elizabeth Street, and the surviving 'in-go' shopfront of the same building are to be retained.

Reason

To protect the heritage of the building.

(20) WASTE AND RECYCLING MANAGEMENT - GENERAL

The proposal must comply with the relevant provisions of Council's *Guidelines for Waste Management in New Developments 2018* which requires facilities to promote the efficient storage, separation, collection and handling of waste to maximise resources recovery.

Reason

To ensure that waste and recycling is appropriately managed.

(21) TREES THAT MUST BE RETAINED

The existing trees detailed in Table 2 below be retained and protected in accordance with the conditions throughout construction and development.

Table 2 – Tree Retention:

Approval is NOT granted for the removal of the following trees, which Council has determined to be prominent landscape elements.

Tree No	Species:	Location
1 to 3	<i>Melaleuca quinquenervia</i> / Broad-leafed Paperbark	Goodlet Street (Street Tree)

Reason

To identify the trees that cannot be removed, must be retained and protected.

(22) PUBLIC ART

Public art must be installed to the City’s satisfaction prior to the issue of any Occupation Certificate.

- (a) The public artwork must be in accordance with Preliminary Public Art Plan, UAP Reference P3145, dated May 2023 the *Sydney DCP 2012*, the *Public Art Policy*, and the *Interim Guidelines: Public art in private developments*.
- (b) A Detailed Public Art Plan with final details of the proposed public artwork must be submitted to and approved by Council’s Area Planning Manager prior to issue of any Construction Certificate for above ground works.
- (c) Public artwork must be installed to the City’s satisfaction, inspected and approved and the Final Public Art Report submitted and approved by Council’s Area Planning Manager prior to the issue of any Occupation Certificate.

Note: Public Art must be reviewed and endorsed by the City’s Public Art Team and/or the Public Art Advisory Panel prior to submission for Council approval. Further information is available online at <http://www.cityofsydney.nsw.gov.au/explore/arts-and-culture/public-art> Please contact the Public Art Team at publicartreferrals@cityofsydney.nsw.gov.au for further information.

Reason

To ensure public art is installed to the City’s satisfaction.

BUILDING WORK

BEFORE ISSUE OF A CONSTRUCTION CERTIFICATE

(23) PHYSICAL MODELS

- (a) Prior to the issue of any Construction Certificate an accurate 1:500 scale model of the development as approved must be submitted to and approved by Council’s Area Coordinator Planning Assessments/Area Planning Manager for the City Model in Town Hall House.

Note:

- (i) The models must be constructed in accordance with the Model Specifications available online at <http://www.cityofsydney.nsw.gov.au/development/application-guide/application-process/model-requirements> Council's modellers must be consulted prior to construction of the model.
- (ii) The models are to comply with all of the conditions of the Development Consent.
- (iii) The models must be amended to reflect any further modifications to the approval (under Section 4.55 of the *Environmental Planning and Assessment Act*) that affect the external appearance of the building.

Reason

To ensure the provision of an appropriate physical model of the development.

(24) SUBMISSION OF ELECTRONIC CAD MODELS PRIOR TO CONSTRUCTION CERTIFICATE

- (a) Prior to any Construction Certificate being issued, an accurate 1:1 electronic CAD model of the approved development must be submitted to and approved by Council's Area Coordinator Planning Assessments/Area Planning Manager for the electronic Visualisation City Model.
- (b) The data required to be submitted within the surveyed location must include and identify:
 - (i) building design above and below ground in accordance with the development consent;
 - (ii) all underground services and utilities, underground structures and basements, known archaeological structures and artefacts;
 - (iii) a current two points on the site boundary clearly marked to show their Northing and Easting MGA (Map Grid of Australia) coordinates, which must be based on Established Marks registered in the Department of Lands and Property Information's SCIMS Database with a Horizontal Position Equal to or better than Class C.

The data is to be submitted as a DGN or DWG file on a Compact Disc. All modelling is to be referenced to the Map Grid of Australia (MGA) spatially located in the Initial Data Extraction file.

- (c) The electronic model must be constructed in accordance with the City's 3D CAD electronic model specification. The specification is available online at <http://www.cityofsydney.nsw.gov.au/development/application-guide/application-process/model-requirements> Council's Modelling staff should be consulted prior to creation of the model. The data is to comply with all of the conditions of the Development Consent.

Reason

To ensure the provision of an appropriate electronic model of the development.

(25) REFLECTIVITY

Prior to issue of the Construction Certificate the Registered Certifier must ensure that the visible light reflectivity from building materials used on the facade of the building does not exceed 20%.

Reason

To ensure the development does not result in adverse reflectivity impacts and to protect the amenity of the public domain.

(26) LANDSCAPING OF THE SITE

This condition applies to landscape at ground level only.

- (a) A detailed landscape design including plans and details drawn to scale, and technical specification, by a registered landscape architect, must be submitted to and approved by Council's Area Coordinator Planning Assessments / Area Planning Manager prior to the issue of a Construction Certificate. These documents must include:
 - (i) Location of existing and proposed planting on the site including existing and proposed trees, planting in natural ground, and planting on structure.
 - (ii) Details of earthworks and soil depths including finished levels and any mounding. The minimum soil depths for planting on structure must be 1000mm for trees, 450mm for shrubs and 200mm for groundcovers, excluding mulch and drainage layers.
 - (iii) Planting details, and location, numbers, type and supply size of plant species, with reference to Australian Standards and preference for drought resistant species that contribute to habitat creation and biodiversity.
 - (iv) Details of drainage, waterproofing and watering systems.
 - (v) Landscape maintenance plan. This plan is to be complied with during occupation of the property.
- (b) All landscaping in the approved plan is to be complete prior to an Occupation Certificate being issued.

Reason

To ensure the development is supported by a good quality, buildable landscape scheme that meets the City's controls.

(27) ACCESSIBLE GREEN ROOFS

This condition applies to Level 2-3 planters and Level 4 communal rooftop.

- (a) A detailed green roof design including plans and details drawn to scale, and technical specification, by a registered landscape architect, must be submitted to and approved by Council's Area Coordinator Planning Assessments / Area Planning Manager prior to the issue of a Construction Certificate. These documents must include:
- (i) A statement that includes details of proposed use of the green roof, accessibility, and any noise and privacy treatments.
 - (ii) Location and details of existing and proposed services, walls, balustrades, hard surfaces, furniture, screens and shade structures, fixings and other structural elements that may interrupt waterproofing, including cross-sectional details of all components.
 - (iii) Engineers report confirming structural capacity of building for proposed roof terrace loads.
 - (iv) Details of soil types and depth including any mounding. The minimum soil depths for planting on structure must be 1000mm for trees, 450mm for shrubs and 200mm for groundcovers, excluding mulch and drainage layers.
 - (v) Planting details, and location, numbers, type and supply size of plant species, with reference to Australian Standards and preference for drought resistant species that contribute to habitat creation and biodiversity.
 - (vi) Details of drainage and irrigation systems, including overflow provisions and water retention cells in the drainage layer.
 - (viii) Green roof maintenance plan. This plan is to be complied with during occupation of the property and must include any relevant maintenance methodology for safe working at height such as access requirements, location of any anchor points, gates, and transport of materials and green waste.
- (b) Prior to the issue of an Occupation Certificate, structural and waterproofing certifications for the green roof are to be submitted to and approved by the Principal Certifying Authority.
- (c) All landscaping in the approved plan must be complete prior to the issue of an Occupation Certificate.

Reason

To ensure that the accessible green roof is designed to accommodate suitable landscaping and to ensure that adequate maintenance procedures are put in place.

(28) INACCESSIBLE GREEN ROOFS

This condition applies to the green roof to screen the PV panels and plant areas.

- (a) A detailed green roof design including plans and details drawn to scale, and technical specification, by a registered landscape architect, must be submitted to and approved by Council's Area Coordinator Planning Assessments / Area Planning Manager prior to the issue of a Construction Certificate. These documents must include:
- (i) Location and details of existing and proposed services, walls, fixings and other structural elements that may interrupt waterproofing, including cross-sectional details of all components.
 - (ii) Engineers report confirming structural capacity of building for proposed green roof loads.
 - (iii) Details of soil types and depth including any mounding.
 - (iv) Details of drainage and irrigation systems, including overflow provisions and water retention cells in the drainage layer.
 - (v) Planting details, and location, numbers, type and supply size of plant species, with reference to Australian Standards and preference for drought resistant species that contribute to habitat creation and biodiversity.
 - (vi) Green roof maintenance plan. This plan is to be complied with during occupation of the property and must include any relevant maintenance methodology for safe working at height such as access requirements, location of any anchor points, gates, and transport of materials and green waste.
 - (vii) A plan outlining the intended strategy for decommissioning if planting works fail. This is to ensure green roof maintained is throughout its life.
- (b) Prior to the issue of an Occupation Certificate, structural and waterproofing certifications for the green roof are to be submitted to and approved by the Principal Certifying Authority.
- (c) All landscaping in the approved plan must be complete prior to the issue of an Occupation Certificate.
- (d) Inaccessible green roofs must remain inaccessible for the lifetime of the property.

Reason

To ensure that the inaccessible green roof is designed to accommodate suitable landscaping and to ensure that adequate maintenance procedures are put in place.

(29) MATERIALS AND SAMPLES BOARD – MAJOR DEVELOPMENT

A physical material sample board which specifies all proposed materials, finishes and colours, (including visible rainwater goods and services) keyed to each building elevation must be submitted to and approved by Council's Area Coordinator Planning Assessments / Area Planning Manager prior to a

Construction Certificate being issued. The materials and samples board must not include generic material or colour descriptions or use terminology such as 'or similar'.

Reason

To require the submission of a materials and samples board following assessment of the development.

(30) COMPLIANCE WITH THE ACOUSTIC REPORT PRIOR TO CONSTRUCTION AND OR OCCUPATION CERTIFICATES

- (a) All relevant performance parameters (including but not limited to requirements, engineering assumptions and recommendations) in the DA Acoustic Report prepared by Acoustic Logic, dated 3/11/2022, ref 20211192.1/0311A/R1/WY, titled DA Acoustic Assessment, Council Ref 2022/608038-08 must be implemented in the development prior to the commencement of its use.
- (b) Prior to the issue of any relevant Construction Certificate, the final construction drawings and final construction methodology must be assessed and reported to be in accordance with the requirements of the DA Acoustic Report in (a) above, with reference to relevant documentation. This must be done by a Suitably Qualified Acoustic Consultant* (see definition below). This work will be to the satisfaction of the Registered Certifier.
- (c) Prior to the issue of any Occupation Certificate, a Suitably Qualified Acoustic Consultant* is to provide a written Acoustic Verification Report to the satisfaction of the Principal Certifier that the development complies with the requirements set out in the Report and in (a) and (b) above.

Note: Suitably Qualified Acoustic Consultant means a consultant who possesses the qualifications to join the Australian Acoustical Society, Institution of Engineers Australia (grade of member) or the Association of Australasian Acoustical Consultants (grade of member firm).

- (d) All physical aspects of the building's structure installed in order to meet performance parameters in accordance with this condition must be maintained at all times.

Reason

To ensure all parties are aware of the supporting documentation that applies to the development.

(31) DEMOLITION, EXCAVATION AND CONSTRUCTION NOISE AND VIBRATION MANAGEMENT PLAN

A site-specific noise management plan must be submitted to the Council for comment and approval prior to issue of any Construction Certificate. The Plan must be prepared by a suitably qualified acoustic consultant who is a person who possesses the qualifications to join the Australian Acoustic Society, Institution of Engineers Australia (grade of member) or the Association of

Australasian Acoustic Consultants (grade of member firm). The plan must include but not be limited to the following:-

- (a) identification of noise sensitive receivers near to the site.
- (b) A prediction as to the level of noise impact likely to affect the nearest noise sensitive receivers from the use and proposed number of high noise intrusive appliances intended to be operated onsite. A statement should also be submitted outlining whether or not predicted noise levels will comply with the noise criteria stated within the *City of Sydney Construction Hours /Noise Code of Practice 1992* for the typical construction hours of 07.00am to 7.00pm. Where resultant site noise levels are likely to be in exceedance of this noise criteria then a suitable proposal must be given as to the duration and frequency of respite periods that will be afforded to the occupiers of neighbouring property.
- (c) A representative background noise measurement ($L_{A90, 15 \text{ minute}}$) should be submitted, assessed in the vicinity of any potentially affected receiver locations and measured in accordance with AS 1055:1.2.1997.
- (d) Confirmation of the level of community consultation that has/is and will be undertaken with Building Managers/ occupiers of the main adjoining noise sensitive properties likely to be most affected by site works and the operation of plant/machinery particularly during the demolition and excavation phases.
- (e) Confirmation of noise monitoring methodology that is to be undertaken during the main stages of work at neighbouring noise sensitive properties in order to keep complaints to a minimum and to ensure that noise from site works complies with the noise criteria contained within City's Construction Noise Code.
- (f) What course of action will be undertaken following receipt of a complaint concerning offensive noise.
- (g) Details of any noise mitigation measures that have been outlined by an acoustic consultant or otherwise that will be deployed on site to reduce noise impacts on the occupiers of neighbouring noise sensitive property to a minimum.
- (h) What plant and equipment is to be used on site, the level of sound mitigation measures to be undertaken in each case and the criteria adopted in their selection taking into account the likely noise impacts on the occupiers of neighbouring property and other less intrusive technologies available.

Reason

To ensure an adequate construction noise and vibration management plan is prepared.

(32) PARKING DESIGN

The design, layout, signage, line marking, lighting and physical controls of all off-street parking facilities must comply with the minimum requirements of Australian Standard AS/NZS 2890.1 Parking facilities Part 1: Off-street car parking, AS/NZS 2890.2 Parking facilities Part 2: Off-commercial vehicle facilities and AS/NZS 2890.6 Parking facilities Part 6: Off-street parking for people with disabilities. The details must be submitted to and approved by the Registered Certifier prior to a Construction Certificate being issued.

Reason

To ensure parking facilities are designed in accordance with the Australian Standards.

(33) ALLOCATION OF PARKING

The number of car parking spaces to be provided for the development must comply with the table below. Details confirming the parking numbers must be submitted to the satisfaction of the Registered Certifier prior to the issue of a Construction Certificate.

Car Parking Type	Number
Office and business parking	16
Accessible office and business parking	2
Retail parking	8
Subtotal	26
Motorcycle parking	3
Small Rigid Vehicle loading dock(s)	1
Total	30

Reason

To ensure the allocation of parking is in accordance with the Council's DCP.

(34) BICYCLE PARKING AND END OF TRIP FACILITIES

- (a) The minimum number of bicycle parking spaces and end of trip facilities to be provided within the site boundary for the development must comply with the table below.

Bicycle Parking Type	Number	Requirements
Non-residential	20	Spaces must be Class 2 bicycle facilities
Non-residential visitor	13	Spaces must be Class 3 bicycle rails
End of Trip Facility Type	Number	
Showers with change area	2	
Personal lockers	20	

All bicycle parking spaces and end of trip facility must be provided on private land. The public domain cannot be used to satisfy this condition.

- (b) The layout, design and security of bicycle facilities must comply with the minimum requirements of Australian Standard AS 2890.3 Parking Facilities Part 3: Bicycle Parking Facilities. The details must be submitted to and approved by the Registered Certifier confirming prior to and form part of the Construction Certificate being issued.

Reason

To ensure the allocation of bicycle parking onsite that is in accordance with Australian Standards and the Council's DCP.

(35) MECHANICAL PARKING FACILITIES (CAR LIFT)

The following details being submitted to an approved by the Principal Certifying Authority prior to the issue of the issue of a Construction Certificate:

- (a) A review of the proposed installation by the manufacturer and its suitability for implementation in accordance with the manufacturer's specifications including but not limited to compliance with AS/NZS 2890.1 2004 and its references to AS/NZS 28590.6.
- (b) The predicted noise and vibration levels arising from the car parking area received by occupiers of the building, including references to relevant Standards.
- (c) Any further information requested by the Principal Certifying Authority.

(36) PHOTOGRAPHIC ARCHIVAL DOCUMENTATION (MAJOR WORKS)

Prior to a Construction Certificate being issued, an archival photographic recording of 502-514 Elizabeth Street, Surry Hills and 272-276 Cleveland Street, Surry Hills is to be prepared to Council's satisfaction. The recording is to be in digital form, prepared in accordance with the NSW Heritage Division of the Department of Environment and Heritage guidelines titled "Photographic Recording of Heritage Items using Film or Digital Capture". One copy of the record is to be submitted to Council to be lodged with Council's Archives.

Procedure

For buildings or structures with heritage significance, the archival documentation, and the number and type of selected enlarged photographs required will be determined by the significance and quality of the building or structure. For a scope of work, refer to Council's Heritage Specialist to determine the particular architectural/design features of the building/site that may need to be recorded.

For buildings or structures with no heritage significance the archival documentation requirements are less comprehensive and may just be limited to contextual and exterior photographs only. However, this will depend upon the type, complexity and significance of the building, and should be confirmed with Council's Area Coordinator Planning Assessments / Area Planning Manager, and if necessary, Council's Urban Design and Heritage Manager.

Because significant fabric may remain concealed and only be exposed during construction works, the archival recording is to be undertaken in stages, prior to the removal of any significant building fabric or furnishings from the site, during the removal of fabric on site that exposes significant building fabric or furnishings, and after work has been completed on site, as considered appropriate by the conservation architect commissioned for the project, and submitted as two parts as follows.

- (a) The first submission of the archival recording of significant building fabric or furnishings is to be prior to the removal of any significant building fabric or furnishings from the site, and must be submitted to and approved by Council prior to the commencement of any work on site and prior to a Construction Certificate being issued.
- (b) The second submission of the archival recording is of significant building fabric or furnishings that is exposed during demolition or construction and after work has been completed on site and must be submitted to Council prior to any Occupation Certificate being issued.

The form of recording is to be a photographic documentation of the site and its context, and the exteriors and interiors of the existing building(s) photographed, where appropriate, using a camera/lens capable of 'perspective correction'.

- (c) For each of the two submissions listed above in (a) and (b), the digital form of the recording is to be as follows:
 - (i) The Development Application number and the Condition of Consent number must be noted.

- (ii) Include a summary report detailing the project description, date and authorship of the photographic record, method of documentation and limitations of the photographic record.
- (iii) The electronic images are to be taken with a minimum 8 megapixel camera, saved as JPEG TIFF or PDF files with a size of approximately 4-6MB, and cross referenced to the digital catalogue sheets and base plans. Choose only images that are necessary to document the process and avoid duplicate images.
- (iv) Include written confirmation, issued with the authority of both the applicant and the photographer that the City of Sydney is granted a perpetual non-exclusive licence to make use of the copyright in all images supplied, including the right to make copies available to third parties as though they were Council images. The signatures of both the applicant and the photographer must be included.
- (v) The report can be submitted on a USB, or digital file transfer in PDF/A format (created directly from the digital original), with a digital catalogue of images with the following data for each location, image subject/description and date.

Reason

To ensure appropriate archival documentation of the building.

(37) ARCHAEOLOGICAL ASSESSMENT

An archaeological assessment undertaken by a suitably qualified archaeologist must be submitted to and approved by Council's Urban Design and Heritage Manager prior to the issue of a Construction Certificate. The report must assess whether the proposed works have the potential to disturb any archaeological remains and the need for any archaeological investigation prior to commencement of any works on site. The report should also recommend measures and documentation to be undertaken during the process of demolition and excavation work.

Recommendations by the archaeological assessment are to be implemented during the process of demolition and excavation work.

Should the assessment report suggest the site may contain relics and the proposed work may disturb them, council may request the applicant to amend the proposal so that the relics are properly protected or interpreted.

Reason

To ensure that the archaeology of the site is appropriately managed and protected.

(38) SALVAGE, REUSE AND RECYCLING OF TRADITIONAL BUILDING MATERIALS – MAJOR DEVELOPMENT

Stone, bricks, roof tiles joinery and decorative architectural elements to be demolished, which include stairs, windows and doors, chimney pieces and ceiling roses must be salvaged and where possible reused on the project.

Salvaged building materials surplus to the project must either be stored on site for future reuse or transferred to an established second building material dealer for recycling.

Documentation of the salvage methodology must be submitted to and approved by Council's Urban Design and Heritage Manager / Area Planning Manager prior to the issue of a Construction Certificate.

Reason

To ensure the salvaging and reuse of traditional building materials.

(39) HERITAGE CONSERVATION WORKS

- (a) Prior to the issue of the Construction Certificate, a schedule of conservation works to be undertaken concurrently with the works is to be submitted to Council's Urban Design and Heritage Manager for approval.
- (b) The schedule is to detail the conservation of all fabric identified as having a heritage significance/ value including but not limited to the following: stonework, brickwork, door and window joinery, glazing, hardware, pavements, tiling, fireplaces, roof plumbing, roofing and painting.
- (c) The schedule is to be supported by outline specifications, methodologies and detailed architectural sections, elevations and plans at 1:20 and 1:5 scales. The details should incorporate any structural and/or building services design for the building.
- (d) The proposed works are to be carried out in a manner that minimises demolition, alterations and new penetrations/fixings to the significant fabric of the existing building. Any departure from approved plans requiring additional demolition/chasing of significant fabric is to be discussed with City of Sydney Heritage Specialists for acceptance.
- (e) All conservation and adaptation works are to be in accordance with the Articles of the Australian ICOMOS Burra Charter 2013. Appropriately qualified contractors and tradespersons are to be commissioned who are skilled in traditional building and engineering trades to carry out the proposed scope of works within the heritage building.
- (f) **INSPECTION AND APPROVAL:** The conservation works are to be inspected by Council Heritage Specialists and be implemented to the satisfaction of Council's Urban Design and Heritage Manager prior to the issue of any Occupation Certificate or commencement of the use, whichever is the earlier.

Reason

To ensure the carrying out of appropriate heritage conservation works.

(40) USE OF HERITAGE CONSULTANT - MAJOR DEVELOPMENT

- (a) An experienced heritage consultant is to be commissioned to work with the consultant team throughout the design development, contract documentation and construction stages of the project. The conservation architect is to be involved in the resolution of all matters where existing significant fabric and spaces are to be subject to preservation, restoration, reconstruction, adaptive reuse, recording and demolition. The heritage consultant is to be provided with full access to the site and authorised by the applicant to respond directly to Council where information or clarification is required regarding the resolution of heritage issues throughout the project.
- (b) Evidence and details of the above commission on the above terms are to be provided to Council prior to the issue of any Construction Certificate or commencement of work on site whichever is the earlier.
- (c) Throughout the documentation and construction stages of the approved works the experienced heritage consultant is to:
 - (i) Undertake site inspections of not less than fortnightly intervals.
 - (ii) Maintain a diary of site inspections that includes photographs of the works, details of heritage advice and decisions arising out of each inspection and any further physical evidence uncovered during the works.
 - (iii) Compile a final report, including the diary, verifying how the heritage conditions have been satisfied, and the works completed in accordance with the Conservation Management Plan.
- (d) Upon completion of the works, the final report is to be submitted for approval by Council's Urban Design and Heritage Manager / Area Coordinator Planning Assessments / Area Planning Manager prior to the issue of any Occupation Certificate or the commencement of the use, whichever is earlier.

Reason

To ensure that the implementation of the approved development is carried out in a manner that does not have adverse heritage impacts.

(41) CONSTRUCTION TRAFFIC MANAGEMENT PLAN

- (a) A Construction Traffic Management Plan must be submitted to and approved by Council prior to a Construction Certificate being issued.
- (b) The approved plan must be complied with during any demolition and/or construction work.

Reason

To ensure that the impacts of construction traffic is appropriately managed.

(42) PUBLIC DOMAIN TREE PLANTING AND MAINTENANCE

- (a) A Tree Planting Plan must be submitted and approved by the City's Public Domain Unit prior to the issuing of any Construction Certificate. The plan must include and be consistent with the following requirements:

- (i) Tree species shall be consistent with the City's Street Tree Master Plan (refer to relevant precinct plans) or other relevant guidance document. Species substitutes will not be accepted.
- (ii) Tree pits must be located and constructed in accordance with the City's Street Tree Master Plan (Technical Guidelines) or other relevant guidance document.
- (iii) The tree pit design must include structural soils or structural cells to support pavements in accordance with the Street Tree Master Plan (Technical Guidelines).
- (iv) Indicate the chosen tree planting arrangement, being a choice of one of two options, being:

Undertake all tree supply, planting, and maintenance requirements to the required standards and to the satisfaction of the City's Tree Management.

OR

Pay a fee for the City to supply, plant, and maintain each required tree on the applicant's behalf. The fee is consistent with the City's Schedule of Fees and Charges.

- (b) If opting to undertake all tree supply, planting, and maintenance requirements, the following requirement must be met:

- (i) The trees must be a minimum container size of 100 litres at the time of planting.
- (ii) All new trees must be grown in accordance with the Australian Standard 2303:2015 'Tree stock for landscape use' and meet the requirements of this standard at the time of planting.
- (iii) Certification from the tree supplier must be submitted to the City's Tree Management Officer and Public Domain Officer, prior to the trees being planted. The certification must confirm the tree(s) have been grown and comply with the requirements of AS2302. Any new trees that do not conform will be rejected by the City.
- (iv) The trees must be planted by a qualified Arborist or Horticulturist (AQF Level 3) and be planted before the issuing of the final Occupation Certificate.
- (v) All new trees must be inspected and approved by the City's Tree Management Officer (or their representative) at the following milestones: before planting with planting pits excavated; after planting; and at the end of the maintenance period.

- (vi) All trees planted in accordance with the approved Tree Planting Plan must be maintained by a qualified Horticulturist or Arborist (minimum AQF Level 3) for a minimum period of 12 months, commencing from the date of planting. Maintenance includes, but is not limited to, watering, weeding, removal of rubbish from tree base, pruning, fertilizing, pest and disease control and any other operations to maintain a healthy robust tree.
- (vii) At the end of the 12 month maintenance period, written acceptance of the tree/s must be obtained from the City before release of the public domain bond.
- (viii) If a tree fails to thrive and successfully establish during the maintenance period, then City will request payment for a replacement tree and establishment period according to the City's Schedule of Fees and Charges.

Reason

To ensure that details of street trees to be planted are approved, the works are carried out in an appropriate manner and the trees are maintained following installation.

(43) SITE SUPERVISION AND REPORTING

- (a) An Arborist with minimum qualifications in Arboriculture of Level 5 (under the Australian Qualification Framework) must oversee various stages of work within the Tree Protection Zone of any tree listed for retention. The Arborist must certify compliance with each key milestone detailed below:
 - (i) The installation of tree protection measures prior to the commencement of any construction works;
 - (ii) During demolition of any ground surface materials (pavers, concrete, grass etc.) within the Tree Protection Zone (TPZ) of any tree to be retained;
 - (iii) During construction of the specify structure/deck/concrete slab etc);
 - (iv) During any excavation and trenching within the TPZ which has been approved by Council;
 - (v) During any Landscape works within the TPZ which has been approved by Council.
- (b) An Arboricultural Compliance Report which includes photographic evidence and provides details on the health and structure of tree/s must be submitted to and acknowledged by Council's Area Planning Coordinator | Area Planning Manager at each hold point listed below:
 - (i) Certification that tree protection measures have been installed in accordance with these consent conditions;

- (ii) Certification of compliance with each key milestone listed above within 48 hours of completion;
 - (iii) Monthly reporting for the duration of construction and development works within the site;
 - (iv) Details of any other works undertaken on any tree to be retained or any works within the TPZ which has been approved by Council.
- (c) A final compliance report must be submitted to and approved by Council's Area Planning Coordinator | Area Planning Manager prior to the issue of any Occupation Certificate.

Reason

To ensure the protection and ongoing health of trees on the site.

(44) LANDSCAPING OF THE SITE (TREES)

- (a) A detailed landscape plan, drawn to scale, by a qualified landscape architect or landscape designer, must be submitted to and approved by Council's Area Planning Manager prior to the issue of a Construction Certificate. The plan must include:
 - (i) Location of existing and proposed structures on the site including, but not limited to, existing and proposed trees, paved areas, planted areas on slab, planted areas in natural ground, lighting and other features.
 - (ii) Details of earthworks and soil depths including mounding and retaining walls and planter boxes (if applicable). The minimum soil depths for planting on slab must be 1000mm for trees, 450mm for shrubs and 200mm for groundcovers.
 - (iii) Location, numbers, type and supply of plant species, with reference to the relevant Australian Standard.
 - (iv) The design must provide a minimum 15% canopy cover across the site. This must be provided by 30% of the species having a mature height of 6-8 metres, 30% mature height of 10-15 metres and 40% mature heights of 20-30 metres.
 - (v) Tree selection shall include a diverse range of species which must be consistent with the expected mature heights and growth within the Sydney area (mature heights must not solely rely on plant literature).
 - (vi) New trees must be planted with adequate soil volumes to allow maturity to be achieved. Planter boxes will not be accepted for tree planting.
 - (vii) New trees must be appropriately located away from existing buildings and structures to allow maturity to be achieved without restriction.
 - (viii) Details of planting procedure and maintenance.

- (ix) Details of drainage, waterproofing and watering systems.
- (x) Prior to the issue of a Construction Certificate, a maintenance plan is to be submitted to and approved by the Principal Certifying Authority. The maintenance plan is to be complied with during occupation of the property.
- (xi) All landscaping in the approved plan is to be completed prior to an Occupation Certificate being issued.

Reason

To ensure sufficient canopy cover is provided and healthy trees are established and maintained on the site.

(45) ENERGY EFFICIENCY OF BUILDINGS

The design of the building and its services must achieve a Base Building National Australian Built Environment Rating System (NABERS) Energy Commitment Agreement of 5.5 stars as per the Department of Planning, Industry and Environment (DPIE). This is to be demonstrated by:

- (a) Entering into a Commitment Agreement with DPIE, to deliver this star rating for the base building:

The applicant must provide a copy of the signed Commitment Agreement contract with their Construction Certificate application; and

- (b) Providing a copy of the independent energy assessment report to NABERS administration and submitting the same report with the Construction Certificate application. This report must be based on the same documents as those submitted with the Construction Certificate.

Note: Definitions referred to above are as follows:

- (i) Commitment Agreement means an agreement that is set out in accordance with DPIE. The NABERS Commitment Agreement, which is signed between DPIE and the applicant/building owner/building manager, to design, build and commission the premises to achieve an agreed star rating.
- (ii) Star rating refers to the benchmarking system applied by DPIE for measuring the energy efficiency of a building and known as NABERS the National Australian Built Environment Rating System.
- (iii) Base Building means central services and common areas of a building, as defined under NABERS.

Reason

To ensure the building is designed to meet an appropriate energy efficiency standard.

(46) INSTALLATION OF DUAL-FLUSH TOILETS

All toilets installed within the development must be of water efficient dual-flush or other water-saving capacity with at least a 4-star rating under the Water Efficiency and Labelling Scheme (WELS). The details must be submitted for the approval of the Registered Certifier, prior to a Construction Certificate being issued.

Reason

To ensure the provision of water efficient toilets.

(47) INSTALLATION OF WATER EFFICIENT URINALS

New urinal suites, urinals and urinal flushing control mechanisms must use waterless technology. Where it is submitted that this is not feasible, it must be demonstrated that products have been selected with at least a 4-star rating under the Water Efficiency and Labelling Scheme (WELS). Systems must include "smart controls" to reduce unnecessary flushing. Continuous flushing systems are not approved. Details are to be submitted to and approved by the Registered Certifier, prior to a Construction Certificate being issued.

Reason

To ensure the provision of water efficient urinals.

(48) INSTALLATION OF WATER EFFICIENT TAPS

All taps and shower heads installed must be water efficient with at least a 4-star rating under the Water Efficiency and Labelling Scheme (WELS). The details are to be submitted for the approval of the Principal Certifier, prior to any Occupation Certificate being issued.

Reason

To ensure the provision of water efficient taps.

(49) DESIGN FOR ENVIRONMENTAL PERFORMANCE

- (a) Prior to the issue of any Construction Certificate, the Registered Certifier must be satisfied that those matters listed in the following sections of the approved Design for Environmental Performance report prepared by Alex Kobler dated August 4 2023 (Council Ref: 2023/472983) are incorporated into the relevant construction plans and accompanying documentation:
 - (ii) Section 4 – Energy Efficiency and Greenhouse Gas Abatement
 - (iii) Section 5 – Passive Design for Thermal Performance – Building Envelope Design
 - (iv) Section 6 – On site Renewable Energy Generation and Storage
 - (v) Section 7 – Design for Resilience to Climate Change

- (vi) Section 8 – Designing for mains potable water savings and water efficiency
- (vii) Section 9 – Storm water quality
- (b) Changes to any commitments as listed in the approved Design for Environmental Performance report must be submitted to and approved by Council's Area Planning Manager/Coordinator prior to the issue of any relevant Construction Certificate.

Reason

To ensure the environmental performance of the development.

(50) PUBLIC DOMAIN DAMAGE BOND

- (a) A Public Domain Damage Deposit calculated on the basis of 411 square metres of concrete site frontage must be lodged with Council in accordance with the City of Sydney's adopted Schedule of Fees and Charges. The bond must be provided as security for repairing any damage to the public domain in the vicinity of the site.
- (b) The City's Public Domain Unit must be contacted to determine the bond amount prior to lodgement. The Bond must be lodged with the City prior to an approval for demolition being granted or any Construction Certificate being issued, whichever is earlier.
- (c) The bond in this condition will be released in full when the Public Domain Works Security Bond is lodged with the City.

Reason

To allow for the appropriate management and rectification of damage to the public domain.

(51) PROTECTION OF STONE KERBS

- (a) The existing stone kerbs on the Cleveland, Elizabeth and Perry Street frontages of the site are to be retained and properly protected during demolition, excavation and construction works.
- (b) To avoid damage to stone kerbs during excavation and construction works for the development, temporary removal and storage of the stone kerbs may be approved by Council. Removed, serviceable stone kerbs (i.e. those that are in good condition as agreed by Council officers) must be re-installed in accordance with the City of Sydney's standard details and specifications after the construction works have been completed. A temporary concrete kerb will need to be constructed to retain the footpath until the stone kerbs can be reinstalled.
- (c) Note the following:
 - (i) all costs associated with the works are to be borne by the developer.

- (ii) Damaged kerbs are to be replaced to match existing to Council's satisfaction or as otherwise advised by Council officers.
- (iii) Where new vehicle crossings or temporary crossings are to be constructed to access the property, the affected kerb stones should be salvaged and reused wherever possible.
- (iv) All new driveway laybacks and kerbs are to be constructed with stone kerbs to match existing stones or as specified by City officers.
- (v) Council approval is required before kerbs are removed.
- (vi) Council approval is required prior to the cutting of existing stone kerbs for stormwater kerb outlets.
- (vii) Stone kerbs and gutters may be bonded in accordance with the City of Sydney's adopted Schedule of Fees and Charges. If so, this will be included with the Public Domain Damage Bond.

Reason

To ensure the protection of stone kerbs.

(52) SURVEY INFRASTRUCTURE – IDENTIFICATION AND RECOVERY

Under Section 24 of the Surveying and Spatial Information Act 2002, it is an offence to remove, damage, destroy, displace, obliterate or deface any survey mark unless authorised to do so by the Surveyor-General. Accordingly, the applicant must, where possible, ensure the preservation of existing survey infrastructure undisturbed and in its original state or else provide evidence of the Surveyor-General's authorisation to remove or replace marks.

Prior to the issue of any Construction Certificate, documentary evidence must be prepared by a Registered Surveyor and submitted to and approved by Council's Area Planning Manager / Coordinator. This evidence must include either:

- (a) A copy of any Surveyor-General's Approval for Survey Mark Removal granted by NSW Spatial Services for the subject site, including all documentation submitted as part of that application (for example the survey mark audit schedule, strategy plan and strategy report); or
- (b) A letter, signed by a current NSW Registered Land Surveyor and including his or her Board of Surveying and Spatial Information (BOSSI) identification number, stating that all investigations required under Surveyor-General's Direction No.11 have been made for the subject site and that no survey infrastructure will be affected by the proposal.

Council's Principal Surveyor may request further information and/or add conditions to any Surveyor-General's Approval at their discretion.

Reason

To ensure the preservation of existing survey infrastructure.

(53) PUBLIC DOMAIN CONCEPT PLAN

A public domain concept plan, showing all the site frontages and extending a minimum of 5m past the boundary and to the road centreline, must be prepared in accordance with the City's *Public Domain Manual* and *Sydney Streets Code*. It must be submitted to and approved by the City's Public Domain Unit prior to the issue of any Construction Certificate for the development other than for demolition or excavation.

Note: A detailed Public Domain Plan will be required prior to construction (refer to Public Domain Plan Detailed Documentation for Construction condition).

Reason

To ensure public domain works comply with Council's requirements.

(54) PUBLIC DOMAIN LEVELS AND GRADIENTS - MAJOR

Prior to the issue of any Construction Certificate, a Public Domain Levels and Gradients submission for the building and site frontages must be submitted to and approved by the City's Public Domain Unit. The submission must be prepared in accordance with the City's *Public Domain Manual* and submitted with a completed Application for *Public Domain Levels and Gradients*. Information on how to complete the submission can be downloaded from the City's website at <https://www.cityofsydney.nsw.gov.au/development/public-domain-works/da-associated-works>.

Any requirements to comply with Disability Discrimination Act at the entrance to a building or publicly accessible space must be resolved inside the site boundary.

Note: Public Domain Levels and Gradient plans are to be included with the Public Domain Plan – Detailed Documentation for Construction condition submission.

Reason

To ensure public domain levels and gradients comply with Council's requirements.

(55) STORMWATER DRAINAGE DESIGN

Prior to issue of any Construction Certificate a detailed stormwater management plan prepared by suitable qualified and experienced professional must be submitted to and approved by the City's Public Domain Unit and must include:

- (a) Council's Sydney Streets Technical Specifications, Part A4 Drainage Design;
- (b) Council's Sydney Streets Technical Specifications, Standard Drawings;
- (c) Council's Sydney Streets Technical Specifications, Part B10: Stormwater Drainage Construction;

- (d) Council's Stormwater Drainage Manual; and
- (e) All relevant Australian Standards.

This information is available for download from the City's website at <https://www.cityofsydney.nsw.gov.au/development/public-domain-works/da-associated-works>.

Note: A Deed of Agreement (Stormwater Deed) for all proposed connections to the City's drainage system, and a Positive Covenant for all OSD systems may be required prior to issue of any Occupation Certificate.

Reason

To ensure stormwater drainage design complies with Council's requirements.

(56) STORMWATER ON-SITE DETENTION

The requirements of Sydney Water with regard to the on-site detention (OSD) of stormwater must be ascertained and complied with. Evidence of the approval must be submitted to Council prior to issue of any Construction Certificate other than demolition.

Where an OSD is not required by Sydney Water one may still be required by the City.

Reason

To ensure the requirements of Sydney Water are complied with.

(57) STORMWATER QUALITY ASSESSMENT

The development must comply with City of Sydney MUSIC-link Report (Project: S22048 - 502-514 Elizabeth Street & 272-276 Cleveland Street, Surry Hills) dated 25/05/2023 approved with this development application.

Prior to issue of any Construction Certificate a design certification report prepared by a suitably qualified practitioner engineer (NPER) demonstrating compliance with approved music link targets and parameters must be submitted to and approved by the City's Public Domain Unit.

The report must include a response to all stormwater quality improvement devices structural integrity, treatment train and their treatment properties demonstrating compliance with the approved MUSIC link reports.

Reason

To ensure appropriate stormwater quality on the site.

(58) PUBLIC DOMAIN LIGHTING UPGRADE

Prior to issue of any Construction Certificate for excavation, civil construction, drainage or building work (whichever is earlier), a concept Public Domain Lighting Upgrade Plan for pedestrian and street lighting in the public domain must be submitted to and approved by City's Public Domain Unit. The Lighting Plan must be prepared in accordance with the *Sydney Streets Technical Specifications A5 and B8*, *Sydney Lights Design Code* and *Public Domain Manual*. This information is available for download from the City's website at <https://www.cityofsydney.nsw.gov.au/development/public-domain-works/da-associated-works>.

The lighting upgrade plan must cover all adjacent street frontages, being Cleveland Street, Elizabeth Street, Goodlet Street, and Perry Street and shall be designed to include the following requirements:

Signalised intersection

Submit RMS approved intersection traffic designs for council review prior to approval can be given to lighting designs. Use suitable 9.6m COS Smartpole in the design.

Electrical/Lighting

General

1. Lighting designs must consist of two parts, i.e. Illumination design and Electrical supply reticulation design. Electrical Reticulation Design cannot be approved until Illumination Designs have been approved.
2. Provide site-specific structural footing designs certified by a practicing structural engineer for council review and approval prior to footing construction.
3. Provide suitable temporary lighting prior to removal of existing public lighting until the public lights are operational.
4. Supply and Install a metered 3-phase MSB as per COS requirements.
5. Establish an access easement for ongoing maintenance and upgrade of wall mounted council lighting, if applicable.
6. Any façade lighting and signage lighting requires a separate DA application.

Cleveland St and Elizabeth St

7. Lighting Category V3 on the roadway and Category PP1 on the footways
8. Remove Ausgrid underground supplied lights: SY06334 and SY06335 (designer to confirm asset ID on site)
9. Supply and install COS Smartpole 9.6m complete with GE R250 Eco Gen2 160w LED + 3.0m outreach arm. Provide standard banner arm and high level GPO.
10. Provide under awning lighting complying with requirements of Sydney DCP 2012.

Goodlet St

11. Lighting Category PR1 on the roadway & PP1 footways
12. Consider upgrading Ausgrid luminaire or supply and installing supplementary COS 4.5m Post top to achieve compliant light levels or under awning lighting complying with requirements of Sydney DCP 2012.

Perry St

13. Lighting Category PR2 on the roadway.
14. Replace existing Ausgrid light along the development site (i.e. SY05357 - designer to confirm asset ID on site) with a new Ausgrid or COS steel standard pole and luminaire or COS standard wall mounted lighting or COS 4.5m Post top to achieve compliant light levels.
15. Solution should provide consideration for lighting at intersection of Goodlet Laneway.

Advice on site specific lighting requirements must be obtained from City's Public Domain Unit before proceeding with the preparation of any final lighting design proposals.

Reason

To ensure pedestrian and street lighting in the public domain complies with Council's requirements.

(59) FOOTPATH AWNINGS

Footpath Awnings which are proposed to be constructed above the public domain (including a public footway) must have separate approval(s) obtainable through the lodgement of an application under Section 68 of the Local Government Act 1993 and/or Section 138/139 of the Roads Act 1993 prior to any Construction Certificate for the building.

Documentation must be submitted to the City's Construction and Building Certification Services Unit with the application demonstrating that the awning height complies with Development Control Plan 2012. Plans are to include dimensions confirming the awning width and setback from the kerb. Awning gutters are to be concealed from the public domain and plans are to confirm downpipes are located within or recessed into the ground floor frontage of the building.

(60) DILAPIDATION REPORT - PUBLIC DOMAIN

Prior to an approval for demolition and preparatory works being granted or the issue of any Construction Certificate, whichever is earlier, a photographic recording of the public domain site frontages is to be prepared as described in the Public Domain Manual and submitted for approval by Council's Public Domain Unit. The City's *Public Domain Manual* is available for download from the City's website at <https://www.cityofsydney.nsw.gov.au/>

The submission is to include written confirmation, issued with the authority of both the applicant and the photographer that the City of Sydney is granted a perpetual non-exclusive license to make use of the copyright in all images supplied, including the right to make copies available to third parties as though they were Council images. The signatures of both the applicant and the photographer must be included.

Reason

To establish and document the condition of the public domain for comparison as building work progresses and is completed.

(61) TEMPORARY DEWATERING DURING CONSTRUCTION

Prior to discharging any water collected during excavation and construction into the City's stormwater drainage system, approval must be sought from the City's Public Domain Unit. A dewatering management plan must be submitted with an *Application for Temporary Dewatering* available to download on the City's website.

Other options for dewatering include disposal to sewer with prior approval from Sydney Water, or off-site disposal by a liquid waste transporter for treatment/disposal to an appropriate waste treatment/processing facility.

Reason

To ensure dewatering is managed appropriately.

(62) WASTE AND RECYCLING MANAGEMENT - COMMERCIAL

- (a) The Waste and Recycling Management Plan accompanying this Development Application has been approved by this consent (Council Ref: 2022/608038-06).
- (b) All requirements of the approved Waste and Recycling Management Plan must be implemented during construction and operation of the development and include:
 - (i) Dedicated space to be provided within the development for the storage and recycling of bulky waste, problem waste, strip out and food waste.
 - (ii) Collection points for waste and recycling must be wholly located within the boundary of the development.
 - (iii) The nominated waste and recycling storage areas must be constructed to meet the relevant conditions required by the City's *Guidelines for Waste Management in New Developments 2018*.
 - (iv) Provision and storage within the boundary of the development of waste and recycling receptacles and any bulky waste at all times.
 - (v) Commercial tenancies must have a commercial waste contract(s) in place prior to commencement of business trading.

- (vi) The path of travel between the bin storage areas/bulky waste storage areas and the designated waste/recycling collection point is to have a minimum 1,200mm wall-to-wall clearance, be slip-proof, of a hard surface, be free of obstructions and at no point have a gradient exceeding 1:14. The use of a lift is permitted, but consideration should be given to the inclusion of a service lift in this instance.

Note: The building manager/strata title manager or body corporate is responsible for ensuring all tenants are kept informed regarding Council's policies, and best practice waste and recycling source separation.

UPON COMPLETION OF THE DEVELOPMENT

- (c) Prior to any Occupation Certificate being issued or the use commencing, whichever is earlier, the Principal Certifier must ensure that waste handling works have been completed in accordance with: the Waste and Recycling Management Plan; other relevant development consent conditions; and Council's *Guidelines for Waste Management in New Developments 2018*.

Reason

To ensure that waste and recycling is appropriately managed.

(63) DILAPIDATION REPORT – MAJOR EXCAVATION/DEMOLITION

- (a) Subject to the receipt of permission of the affected landowner, dilapidation reports, including a photographic survey of 1, 3 and 5 Goodlet Street, Surry Hills, 492-500 Elizabeth Street, Surry Hills, 543-551, 553-555 and 557-565 Elizabeth Street, Surry Hills, and 278-287 Cleveland Street Surry Hills (and any other properties identified by the qualified structural engineer engaged to undertake the report) are to be prepared by an appropriately qualified structural engineer prior to commencement of demolition/excavation works. A copy of the dilapidation report/s together with the accompanying photographs must be given to the above property owners, and a copy lodged with the Registered Certifier and the Council prior to the issue of a Construction Certificate.

UPON COMPLETION OF EXCAVATION/DEMOLITION

- (b) A second Dilapidation Report/s, including a photographic survey must then be submitted at least one month after the completion of demolition/excavation works. A copy of the second dilapidation report/s, together with the accompanying photographs must be given to the above property owners, and a copy lodged with the Principal Certifier and the Council prior to the issue of any Occupation Certificate.

Any damage to buildings, structures, lawns, trees, sheds, gardens and the like must be fully rectified by the applicant or owner, at no cost to the affected property owner.

Note: Prior to the commencement of the building surveys, the applicant/owner must advise (in writing) all property owners of buildings to be surveyed of what the survey will entail and of the process for making a claim regarding property damage. A copy of this information must be submitted to Council.

Reason

To ensure that dilapidation reports are prepared and to identify damage to adjoining/nearby properties resulting from building work on the development site.

(64) TRANSPORT FOR NEW SOUTH WALES CONDITIONS

- (a) All buildings and structures shall be wholly outside the Cleveland Road corridor boundary including the affected area required for a future road proposal.
- (b) Detailed design plans and hydraulic calculations of any changes to the stormwater drainage system along the Cleveland Street frontage are to be submitted to TfNSW for approval, prior to the commencement of any works. Please send all documentation to development.sydney@transport.nsw.gov.au.

A plan checking fee will be payable and a performance bond may be required before TfNSW approval is issued.

- (c) The developer shall be responsible for all public utility adjustment/relocation works, etc. necessitated by the above/approved work and as required by the various public utility authorities and/or their agents. In addition to the above, TfNSW provides the following advisory comments for consideration by Council in the determination of the development application:
 - (i) Details of the development's freight and servicing profile, including the forecast freight and servicing traffic volumes by vehicle size, frequency, time of day and duration of stay.
 - (ii) Details of loading and servicing facilities within the subject site which adequately accommodate the forecast demand of the development so as to not rely on the kerbside restrictions to conduct the development's business
 - (iii) Swept paths of vehicles entering and exiting the loading dock
 - (iv) Management of queuing along Cleveland Street as a result of the proposed loading dock arrangement
 - (v) The details of alternate loading zones to redirect vehicles due to extensive queuing at the access to loading dock
- (d) Prior to the Issue of the construction certificate, the applicant shall prepare a Loading and Servicing Management Plan (LSMP) for the on-site loading dock for the review and TfNSW endorsement. The LSMP needs to specify, but not be limited to, the following:
 - (i) Details of the development's freight and servicing profile, including the forecast freight and servicing traffic volumes by vehicle size, frequency, time of day and duration of stay.
 - (ii) Details of loading and servicing facilities within the subject site which adequately accommodate the forecast demand of the development so as to not rely on the kerbside restrictions to conduct the development's business
 - (iii) Swept paths of vehicles entering and exiting the loading dock
 - (iv) Management of queuing along Cleveland Street as a result of the proposed loading dock arrangement
 - (v) The details of alternate loading zones to redirect vehicles due to extensive queuing at the access to loading dock

- (vi) Management of incidents at the access to the loading dock
 - (vii) Loading dock management details including measures to minimise freight and service vehicle movements during peak periods
 - (viii) Management of conflicts between cars accessing the car park and vehicle movements to/from the loading dock; and
 - (ix) Management of conflicts between vehicles accessing the loading dock and pedestrian movements along Cleveland Street.
- (e) Prior to the issue of any construction certificate or any preparatory, demolition or excavation works, whichever is the earlier, the applicant shall:
- (i) Prepare a CPTMP needs to specify matters including, but not limited to, the following:
 - a. A description of the development; o Location of any proposed work zone(s)
 - b. Details of crane arrangements including location of any crane(s)
 - c. Haulage routes
 - d. Proposed construction hours
 - e. Predicted number of construction vehicle movements and detail of vehicle types, noting that vehicle movements are to be minimised during peak periods
 - f. Details of specific measures to ensure the arrival of construction vehicles to the site do not cause additional queuing within the CBD
 - g. Details of the monitoring regime for maintaining the simultaneous operation of buses and construction vehicles on roads surrounding the site
 - h. Pedestrian and traffic management measures
 - i. Construction program and construction methodology
 - j. A detailed plan of any proposed hoarding and/or scaffolding
 - k. Measures to avoid construction worker vehicle movements within the CBD
 - l. Consultation strategy for liaison with surrounding stakeholders, including other developments under construction

- m. Existing CPTMPs for developments within or around the development site should be referenced in the CPTMP to ensure that coordination of work activities are managed to minimise impacts on the surrounding road network.
 - n. Proposed mitigation measures. Should any impacts be identified, the duration of the impacts and measures proposed to mitigate any associated general traffic, public transport, pedestrian and cyclist impacts should be clearly identified and included in the CPTMP.
- (ii) Submit a copy of the final plan to sco@transport.nsw.gov.au for TfNSW endorsement.
 - (iii) Provide the builder's direct contact number to small businesses adjoining or impacted by the construction work and the Transport Management Centre and TfNSW (via sco@transport.nsw.gov.au) to resolve issues relating to traffic, public transport, freight, servicing and pedestrian access during construction in real time. The applicant is responsible for ensuring the builder's direct contact number is current during any stage of construction.

BEFORE BUILDING WORK COMMENCES

(65) AUSGRID CONDITION - AUSGRID UNDERGROUND CABLES ARE IN THE VICINITY OF THE DEVELOPMENT

Special care should be taken to ensure that driveways and any other construction activities do not interfere with existing underground cables located in the footpath or adjacent roadways.

It is recommended that the developer locate and record the depth of all known underground services prior to any excavation in the area. Information regarding the position of cables along footpaths and roadways can be obtained by contacting Dial Before You Dig (DBYD).

In addition to DBYD the proponent should refer to the following documents to support safety in design and construction:

SafeWork Australia – Excavation Code of Practice.

Ausgrid's Network Standard NS156 which outlines the minimum requirements for working around Ausgrid's underground cables.

The following points should also be taken into consideration.

Ausgrid cannot guarantee the depth of cables due to possible changes in ground levels from previous activities after the cables were installed.

Should ground anchors be required in the vicinity of Ausgrid underground cables, the anchors must not be installed within 300mm of any cable, and the anchors must not pass over the top of any cable.

(66) AUSGRID CONDITION - AUSGRID OVERHEAD POWERLINES ARE IN THE VICINITY OF THE DEVELOPMENT

The developer should refer to SafeWork NSW Document – Work Near Overhead Powerlines: Code of Practice. This document outlines the minimum separation requirements between electrical mains (overhead wires) and structures within the development site throughout the construction process. It is a statutory requirement that these distances be maintained throughout the construction phase.

Consideration should be given to the positioning and operating of cranes, scaffolding, and sufficient clearances from all types of vehicles that are expected be entering and leaving the site.

The "as constructed" minimum clearances to the mains must also be maintained. These distances are outlined in the Ausgrid Network Standard, NS220 Overhead Design Manual. This document can be sourced from Ausgrid's website at www.ausgrid.com.au.

It is the responsibility of the developer to verify and maintain minimum clearances onsite. In the event where minimum safe clearances are not able to be met due to the design of the development, the Ausgrid mains may need to be relocated in this instance. Any Ausgrid asset relocation works will be at the developer's cost.

Additional information can be found in the Ausgrid Quick Reference Guide for Safety Clearances "Working Near Ausgrid Assets - Clearances". This document can be found by visiting the following Ausgrid website: www.ausgrid.com.au/Your-safety/Working-Safe/Clearance-enquiries

(67) RODENT TREATMENT PROGRAMME – PRE-DEMOLITION AND/OR EXCAVATION

- (a) Prior to the commencement of any demolition and/or excavation works, a programme of baiting and monitoring of rodent activity is to be put in place at the site.
- (b) A licensed Pest Control Operative must carry out all pest control work and prepare a report, confirming that there is no evidence of any rodent activity at the site prior to the commencement of any works on site. The report must be submitted to and be approved/endorsed by Council's Area Coordinator Planning Assessments/Area Planning Manager.

Reason

To ensure that the potential impact of rodents during the demolition, excavation and construction phase is appropriately managed.

(68) SYDNEY WATER CERTIFICATE (TAP-IN)

- (a) The approved plans must be submitted to Sydney Water's "Tap-in" online service to determine whether the development will affect Sydney Water's sewer and water mains, stormwater drains and/or easements, and if further requirements need to be met. Sydney Water's "Tap-in" online service is available at www.sydneywater.com.au, (see Plumbing, Building & Development and then Sydney Water "Tap-in").
- (b) The Consent Authority or a Principal Certifier must ensure that Sydney Water has appropriately stamped the plans before the commencement of work.

Reason

To ensure the development satisfies Sydney Waters requirements.

(69) DISPOSAL OF SURPLUS SALVAGED MATERIALS

Salvaged traditional building materials surplus to the requirements of this project including stone, bricks, structural timber, staircases and joinery are to be sold to an established dealer in second-hand heritage building materials. Documentation of the salvage methodology must be submitted for the approval of Council prior to the commencement of demolition.

Reason

To ensure the salvaging and reuse of traditional building materials.

(70) HAZARDOUS MATERIALS SURVEY REQUIRED

A Hazardous Materials Survey Report must be prepared by a certified Occupational Hygienist (*Australia Institute of Occupational Hygienists*) and submitted to the satisfaction of Council's Area Coordinator Planning Assessments / Area Planning Manager prior to any demolition / refurbishment work commencing at the site. The report must identify and record the type, location and extent of any hazardous materials on the site and make recommendations as to their safe management and/or removal to ensure the site is made safe for demolition, construction and future use/occupation.

Reason

To ensure that hazardous materials on the site are identified and appropriately managed.

(71) TREE PROTECTION ZONE

- (a) Before the commencement of works, Tree Protection Zone/s (TPZ) must be established around all trees to be retained not less than the distance indicated in the TPZ schedule below.
- (b) Tree protection must be installed and maintained in accordance with the Australian Standard 4970 Protection of Trees on Development Sites and with the following schedule:

TPZ Schedule

Tree No.	Species Name	Location	Radius (m) From Trunk
1	Melaleuca quinquenervia (Paperbark)	Goodlet Street	6
2			10
3			4

- (e) The following works must be excluded from within any TPZs:
 - (i) Excavation except for the demolition of the concrete slab and localised siting of piers;
 - (ii) Soil cut or fill including trenching;
 - (iii) Soil cultivation, disturbance or compaction;
 - (iv) Stockpiling, storage or mixing of materials;
 - (v) The parking, storing, washing and repairing of tools, equipment and machinery;

- (vi) The disposal of liquids and refuelling;
 - (vii) The disposal of building materials;
 - (viii) The siting of offices or sheds;
 - (ix) Any action leading to the impact on tree health or structure.
- (f) Any trenching works for services / hydraulics / drainage etc must not be undertaken within any TPZ. Alternative installation methods for services, such as directional boring/drilling, or redirection of services must be employed.
- (g) All work undertaken within or above the TPZ must be:
- (i) Carried out in accordance with a work methodology statement prepared by an Arborist (minimum AQF Level 5) and written approval is obtained from Council's Tree Management Officer before its implementation; and
 - (ii) Supervised by a Project Arborist (minimum AQF Level 5).

Reason

To ensure the protection and ongoing health of trees.

(72) STREET TREE PRUNING AND REMOVAL

- (a) The consent from Council's Tree Management Officer must be obtained prior to the undertaking of any street tree pruning works including tree roots greater than 30mm diameter. Only minor pruning works will be approved by Council.
- (b) Any pruning that has been approved by Council, must be carried out by a qualified Arborist (AQF3), and must be in accordance with AS4373 Australian Standards 'Pruning of Amenity Trees'.

Reason

To ensure that approval is obtained for any pruning works to, or removal of, street trees and that such works are carried out in an appropriate manner.

(73) PUBLIC DOMAIN WORK – CONSTRUCTION APPROVAL UNDER SECTION 138 ROADS ACT 1993

Prior to the construction of any public domain works, approval under Section 138 / 139 of the Roads Act 1993 must be issued by the City's Public Domain Unit.

Reason

To ensure relevant approvals for public domain work are obtained.

DURING BUILDING WORK

(74) COMPLIANCE WITH NATIONAL CONSTRUCTION CODE

All proposed work must comply with the *National Construction Code* (previously known as *Building Code of Australia*).

Reason

(Prescribed condition - EP&A Regulation 2021 clause 69(1)).

(75) COVERING OF LOADS

All vehicles involved in the excavation and/or demolition process and departing the property with demolition materials, spoil or loose matter must have their loads fully covered before entering the public roadway.

Reason

To ensure loads are managed appropriately and do not impact local amenity.

(76) EROSION AND SEDIMENT CONTROL

The Soil and Water Management Plan (SWMP) or Erosion and Sediment Control Plan (ESCP) which has been approved by the Principal Certifier must be implemented in full during the construction period.

During the construction period:-

- (a) erosion and sediment controls must be regularly inspected, repaired and maintained in working order sufficient for a 10 year Average Recurrence Interval (ARI) rainfall event;
- (b) erosion and sediment control signage available from Council must be completed and attached to the most prominent structure visible at all times when entering the site for the duration of construction; and
- (c) building operations and stockpiles must not be located on the public footway or any other locations which could lead to the discharge of materials into the stormwater system.

Reason

To ensure no substance other than rainwater enters the stormwater system and waterways.

(77) VEHICLE CLEANSING

Prior to the commencement of work, suitable measures are to be implemented to ensure that sediment and other materials are not tracked onto the roadway by vehicles leaving the site. It is an offence to allow, permit or cause materials to pollute or be placed in a position from which they may pollute waters.

Reason

To ensure sediment is not tracked onto the roadway.

(78) SYDNEY WATER CERTIFICATE

A Section 73 Compliance Certificate under the Sydney Water Act 1994 must be obtained from Sydney Water Corporation.

Application must be made through an authorised Water Servicing Coordinator. Please refer to the Building Developing and Plumbing section on the web site www.sydneywater.com.au then refer to "Water Servicing Coordinator" under "Developing Your Land" or telephone 13 20 92 for assistance.

Following application a "Notice of Requirements" will advise of water and sewer infrastructure to be built and charges to be paid. Please make early contact with the Coordinator, since building of water/sewer infrastructure can be time consuming and may impact on other services and building, driveway or landscape design.

The Section 73 Certificate must be submitted to Council or the Principal Certifier prior to any Occupation Certificate or subdivision/strata certificate being issued.

Reason

To ensure the requirements of Sydney Water are met.

(79) COMPLIANCE WITH DEMOLITION, EXCAVATION & CONSTRUCTION NOISE AND VIBRATION MANAGEMENT PLAN

- (a) All works conducted on site which form part of this development must be carried out in accordance with the submitted Demolition, Excavation and Construction Management required by Condition 32.
- (b) Where all such control measures have been implemented and the resultant noise and/ or vibration levels at any sensitive receiver still exceed the council's applicable criteria stated in the Construction Hours/Noise Code 1992 and are giving rise to sustained complaints then the contractor must provide regular, appropriate and sustained periods of respite in consultation with Council's Health and Building unit. Approval to vary the authorised noise and vibration levels must be received in writing by the proponent from Council prior to activities being undertaken that exceed sanctioned emission levels. Such periods must be set and agreed to by Council's Health and Building Unit.

Reason

To ensure all parties are aware of the supporting documentation that applies to the development.

(80) PROTECTION OF PUBLIC FEATURES IN CONSERVATION AREAS

The proposed work must take measures to protect existing street furniture and features on the public land including street and laneway stone kerbs and gutters. If they need to be interrupted during process of construction, they must be properly recorded and reinstated to the original condition.

Reason

To ensure the protection of existing street furniture, stone kerbs and gutters and the like.

(81) ARCHAEOLOGICAL DISCOVERY DURING EXCAVATION

- (a) Should any relics be unexpectedly discovered on the site during excavation, all excavation or disturbance to the area is to stop immediately and the Heritage Council of NSW should be informed in accordance with section 146 of the Heritage Act 1977.
- (b) Should any Aboriginal objects be unexpectedly discovered then all excavation or disturbance of the area is to stop immediately and NSW Government Office of Environment and Heritage is to be informed in accordance with Section 89A of the *National Parks and Wildlife Act 1974*.
- (c) Should any archaeological remains or Aboriginal objects be discovered, a copy of recording of the finds and the final archaeological summary report is to be submitted to Council prior to the issue of any Occupational Certificate.
- (d) If the discovery is on Council's land, Council must be informed.

Reason

To ensure that the archaeology of the site is appropriately managed and protected.

(82) ASBESTOS REMOVAL WORKS

- (a) All works removing asbestos containing materials must be carried out by a suitably licensed asbestos removalist duly licensed with Safework NSW, holding either a Friable (Class A) or a Non-Friable (Class B) Asbestos Removal Licence which ever applies.

A copy of the relevant licence must be made available to any authorised Council officer on request within 24 hours.

- (b) Five days prior to the commencement of licensed asbestos removal, Safework NSW must be formally notified of the works. All adjoining properties and those opposite the development must be notified in writing of the dates and times when asbestos removal is to be conducted. The notification must identify the licensed asbestos removal contractor and include a contact person for the site together with telephone number and email address.

- (c) All work must be carried out in accordance with the *Work Health and Safety Regulation 2017* and the NSW Government and SafeWork NSW document entitled *How to manage and control asbestos in the work place: Code of Practice (Safework NSW) December 2011* and the *City of Sydney Managing Asbestos Policy dated 21 October 2013 and associated guidelines*.
- (d) The asbestos removalist must use signs and barricades to clearly indicate the area where the asbestos removal work is being performed. Signs must be placed in positions so that people are aware of where the asbestos removal work area is and should remain in place until removal is completed and clearance to reoccupy has been granted. Responsibilities for the security and safety of the asbestos removal site and removal must be specified in the asbestos removal control plan (where required). This includes inaccessible areas that are likely to contain asbestos.
- (e) Warning signs must be placed so they inform all people nearby that asbestos removal work is taking place in the area. Signs must be placed at all of the main entry points to the asbestos removal work area where asbestos is present. These signs must be weatherproof, constructed of light-weight material and adequately secured so they remain in prominent locations. The signs must be in accordance with AS 1319 - 1994 *Safety Signs for the Occupational Environment* for size, illumination, location and maintenance.
- (f) Asbestos waste must only be transported and disposed of at an EPA licensed waste facility.
- (g) No asbestos products are to be reused on the site (i.e. packing pieces, spacers, formwork or fill etc).
- (h) No asbestos laden skips or bins are to be left in any public place without the written approval of Council.
- (i) A site notice board must be located at the main entrance to the site in a prominent position and must have minimum dimensions of 841mm x 594mm (A1) with any text on the notice to be a minimum of 30 point type size.

The site notice board must include the following:

- (i) contact person for the site;
- (ii) telephone and facsimile numbers and email address; and
- (iii) site activities and time frames.

Reason

To ensure that the handling and removal of asbestos from the site is appropriately managed.

(83) LAND REMEDIATION

The site is to be remediated and validated in accordance with the recommendations set out within the Remedial Action Plan, prepared by EI Australia dated 12 May 2023 reference E25326.E12_Rev1 and in particular Section 6.

Any new information which comes to light during remediation, demolition or construction works which has the potential to alter previous conclusions about site contamination must be immediately notified to the Council and the Principal Certifier.

Reason

To ensure that the site is appropriately remediated.

(84) NOTIFICATION – NEW CONTAMINATION EVIDENCE

Council's Area Planning Manager and the Principal Certifier must be notified of any new information which comes to light during remediation, demolition or construction works which has the potential to alter previous conclusions about site contamination.

Reason

To ensure that the site is appropriately remediated.

(85) IMPORTED FILL MATERIALS

All fill imported onto the site must be validated to ensure the imported fill is suitable for the proposed land use from a contamination perspective. Fill imported on to the site shall also be compatible with the existing soil characteristic for site drainage purposes.

The City may require details of appropriate validation of imported fill material to be submitted with any application for future development of the site. Hence all fill imported onto the site should be validated by either one or both of the following methods during remediation works:

- (a) Imported fill must be accompanied by documentation from the supplier which certifies that the material is not contaminated based upon analyses of the material for the known past history of the site where the material is obtained; and/or
- (b) Sampling and analysis of the fill material shall be conducted in accordance with NSW EPA (1995) Sampling Design Guidelines.

Reason

To ensure that imported fill is not contaminated.

(86) CLASSIFICATION OF WASTE

Prior to the exportation of waste (including fill or soil) from the site, the waste materials must be classified in accordance with the provisions of the Protection of the *Environment Operations Act 1997* and the *NSW DECC Waste Classification Guidelines, Part1: Classifying Waste (July 2009)*. The classification of the material is essential to determine where the waste may be legally taken. The *Protection of the Environment Operations Act 1997* provides for the commission of an offence for both the waste owner and the transporters if the waste is taken to a place that cannot lawfully be used as a waste facility for the particular class of waste. For the transport and disposal of industrial, hazardous or Group A liquid waste advice should be sought from the EPA.

Reason

To ensure that waste from site is classified and disposed of appropriately.

(87) DISCHARGE OF CONTAMINATED GROUNDWATER

Contaminated groundwater must not be discharged into the City's stormwater drainage system.

Options for the disposal of groundwater include disposal to sewer with prior approval from Sydney Water or off-site disposal by a liquid waste transporter for treatment/disposal to an appropriate waste treatment/processing facility.

Reason

To ensure that the discharge of ground water is appropriately managed.

(88) STOCKPILES

- (a) No stockpiles of soil or other materials must be placed on footpaths or nature strips unless prior approval has been obtained from the City's Construction Regulation Team.
- (b) All stockpiles of soil or other materials must be placed away from drainage lines, gutters or stormwater pits or inlets.
- (c) All stockpiles of soil or other materials likely to generate dust or odours must be covered.
- (d) All stockpiles of contaminated soil must be stored in a secure area and be covered if remaining more than 24 hours.

Reason

To ensure that stockpiles of soil or other materials are appropriately managed.

(89) ENVIRONMENTAL MANAGEMENT PLAN

Where the ongoing land use suitability and release of the final asbestos clearance certificate is dependent upon the implementation of an ongoing Environmental Management Plan (EMP) in relation to any residual asbestos soil contamination remaining onsite such as in any containment cell, this remediation proposal and the EMP must first be approved by the Council's Area Planning Manager before this work is undertaken and prior to the issue of the final asbestos clearance certificate.

The owner of the land is required to comply with the ongoing obligations of any EMP which form part of the final asbestos clearance certificate.

A covenant must be registered on the title of the land binding the owners and future owners to be responsible for ongoing maintenance and any future rehabilitation works required in terms of the encapsulated/remaining contaminated materials, including the discharge or prevention of discharge from any contaminants or for any works subsequently required by the NSW Environment Protection Authority

A copy of the revised certificate of land title recording the covenant must be submitted to Council's Area Planning Manager and the Principal Certifier prior to the issue of any Occupation Certificate.

Reason

To ensure that contamination is appropriately managed.

(90) TREE PROTECTION DURING CONSTRUCTION

All trees that will be affected by the development within the property and on any adjoining land, must be protected in accordance with the Australian Standard 4970 Protection of Trees on Development Sites and as follows:

- (a) Stockpiling, storage or mixing of materials, washing of equipment, vehicle parking, disposal of liquids, machinery repairs and refuelling, disposal of building materials such as cement slurry, siting of offices or sheds and the lighting of fires, must not occur within 5.5 metres of the trunk of any tree to be retained (including trees within adjoining properties).
- (b) Excavation (except for demolishing of concrete slab and localised siting of piers) must not occur within 5.5 metres of the trunk of trees (including trees within adjoining properties). If excavation is proposed within this zone, Council's Tree Management Officer must be contacted immediately and the excavation must be carried out in accordance with Council's direction.
- (c) Excavations for the footings where they are within 5.5 metres of any tree (including trees in adjoining properties) must be undertaken using non-destructive methods (such as by hand) to ensure no tree roots greater than 40mm diameter are damaged, pruned or removed.

- (d) Footings must be relocated / realigned if any tree root greater than 40mm in diameter is encountered during excavations. A minimum of 150mm clearance must be provided between the tree root and footing.
- (e) Tree trunk and major branch protection must be undertaken prior to the commencement of any works. The protection must be installed and certified by a qualified Arborist (minimum AQF 3) and must include:
 - (i) Tree trunk/s and/or major branches must be protected by wrapped thick carpet underlay or similar padding material to limit damage;
 - (ii) Timber planks (50mm x 100mm must be placed around tree trunk/s. The timber planks must be spaced at 100mm intervals, and must be fixed against the trunk with tie wire, or strapping. The hessian and timber planks must not be fixed to the tree in any instance, or in any fashion;
 - (iii) Tree trunk and major branch protection is to remain in place for the duration of construction and development works, and must be removed at the completion of the project.
- (f) The consent from Council's Tree Management Officer must be obtained prior to the undertaking of any tree pruning works, including tree roots greater than 40mm in diameter. Only minor pruning works will be approved by Council.

Reason

To ensure the protection and ongoing health of trees.

(91) TREE ROOT PROTECTION (STRUCTURAL ROOT ZONE)

Structural Root Zone (SRZ) Schedule:

Tree No	Botanical/common name	Tree location	SRZ (m) from trunk
1	<i>Melaleuca quinquenervia</i> (Broad Leaf Paperbark)	Goodlet Street (Street Tree)	2.5
2			3
3			2.5

- (a) Any excavations within the SRZ must be undertaken using non-destructive methods (such as by hand or with an Airspade) to ensure no tree roots greater than 40mm diameter are damaged, pruned or removed.

- (b) Footings must be relocated / realigned if any tree root greater than 40mm in diameter is encountered during excavations. A minimum of 150mm clearance must be provided between the tree root and footing.
- (c) All excavations located within the TPZ must be supervised by a qualified Consultant Arborist, who holds the Diploma in Horticulture (Arboriculture), Level 5 under the Australian Qualification Framework.
- (d) All root pruning must be undertaken by a qualified Arborist with a minimum AQF level 3.

Reason

To ensure the protection and ongoing health of trees.

(92) STREET TREE PROTECTION

All street trees located directly outside the site must be retained and protected in accordance with the Australian Standard 4970 Protection of Trees on Development Sites. All street trees must be protected during the construction works as follows:

- (a) Tree trunk and major limb protection must be undertaken prior to the commencement of any works (including demolition). The protection must be installed and certified by a qualified Arborist (AQR Level 3) and must include:
 - (i) An adequate clearance, minimum 250mm, must be provided between the structure and tree branches, and trucks at all times.
 - (ii) Tree trunk/s and/or major branches must be protected by wrapped thick underlay carpet or similar padding material to limit damage, and
 - (iii) Timber planks (50mm x 100mm or similar) must be placed around tree trunk/s. The timber planks must be spaced at 100mm intervals and must be fixed against the trunk with tie wire, or strapping. The thick underlay carpet or similar padding material and timber planks must not be fixed to the tree in any instance, or in any fashion.
 - (iv) Tree trunk and major branch protection is to remain in place for the duration of construction and development works and must be removed at the completion of the project.
- (b) All hoarding support columns are to be placed a minimum of 300mm from the edge of the existing tree pits/setts, so that no sinking or damage occurs to the existing tree pits. Supporting columns must not be placed on any tree roots that are exposed.

- (c) Young street trees must be protected by installing three (3) wooden stakes around the edge of the tree pits or a minimum of 1 metre from the base of the trunk. Hessian must be wrapped around the stakes. If existing stakes or a metal tree guard are already in place, these suffice as tree protection.
- (d) Materials or goods, including site sheds, must not be stored or placed:
 - (i) around or under the tree canopy; or
 - (ii) within two (2) metres of tree trunks or branches of any street trees.
- (e) Any excavation within any area known to or suspected of having tree roots greater than 30mm diameter must be undertaken by hand.
- (f) Any trenching works for services, hydraulics, drainage etc. must not be undertaken within any TPZ. Alternate installation methods for services such as directional boring/drilling or redirection of services must be employed where roots greater than 30mm diameter are encountered during installation of any services.
- (g) Existing sections of kerbs adjacent to any street tree must not be removed without approval from the Council's Tree Management Officer.
- (h) Any damage sustained to street tree/s as a result of the erection of any construction activities (including demolition) must be immediately reported to the Council's Tree Management Officer on 9265 9333. Any damage to street trees as a result of any construction activities may result in prosecution under the Local Government Act 1993 and the Environmental Planning and Assessment Act 1979.

Reason

To ensure the protection and ongoing health of the street trees.

(93) TREE ROOT PROTECTION

- (a) Excavations for the footings must be undertaken using non-destructive methods (such as an Airspade) to ensure no tree roots greater than 40mm diameter are damaged, pruned or removed.
- (b) Footings must be relocated / realigned if any tree root greater than 40mm in diameter is encounter during excavations. A minimum of 150mm clearance must be provided between the tree root and footing.
- (c) Excavations for any pier and beam footings located within the Tree Protection Zone (TPZ), must be supervised by a qualified Consultant Arborist, who holds the Diploma in Horticulture (Arboriculture), Level 5 under the Australian Qualification Framework.
- (d) The consent from Council must be obtained prior to the undertaking of any root pruning greater than 40mm in diameter.
- (e) All root pruning must be undertaken by a qualified Arborist with a minimum AQF level 3.

Reason

To ensure the protection and ongoing health of trees on the site.

(94) TREE ROOT INVESTIGATION

Prior to determining the final location of the underground car park and the design of the footing along the boundary:

- (a) Exploratory root investigation must be undertaken by a qualified Arborist (minimum AQF Level 5) along the north alignment. This shall consist of carefully removing the asphalt and hand digging a trench along the boundary to expose tree roots to a minimum depth of 800mm below the existing grade. An assessment of tree root size, number and condition must be provided (including photos) in a report and submitted to Council's Area Planning Manager for approval prior to installation of the driveway and crossover.
- (b) In the event any large structural roots (greater than 40mm diameter) are identified as a result of the exploratory root investigation, the underground carpark is likely to require five metres setback from the boundary to ensure the street tree is not compromised as a result of the works.
- (c) In the event any large structural roots (greater than 40mm diameter) are identified as a result of the exploratory root investigation, the design of the northern footing must be constructed without the use of a continuous strip footing. The construction method shall include pier and beam footing or other root sensitive methods, to ensure tree roots greater than 40mm in diameter are not damaged, pruned or removed during construction of the wall.
- (d) Any root pruning approved by Council must be undertaken by a qualified Arborist with a minimum AQF level 3.

Reason

To ensure the protection and ongoing health of the street trees.

(95) PUBLIC DOMAIN WORKS SECURITY BOND

A Public Domain Works Security Bond will be required for the public domain works and for repairing damage that may be caused to the public domain in the vicinity of the site, in accordance with the City of Sydney's adopted fees and charges and the Public Domain Manual.

The City's Public Domain Unit must be contacted to determine the bond amount prior to lodgement. The bond must be lodged with the City prior to an approval being issued for the approval of the Public Domain Plan.

The bond will be retained in full until all public domain works, including rectification of damage to the public domain, are completed to City's standards and approval and the required works-as-executed documentation are approved. On satisfying the above requirements, and the issue of the Public Domain Works Letter of Completion Operational Acceptance by the City, 90% of the bond will be released. The remaining 10% will be retained for the duration of the specified Defects Liability Period.

Reason

To ensure public domain works are completed and any damage to the public domain is rectified.

(96) DRAINAGE AND SERVICE PIT LIDS

All existing or proposed drainage and service pit lids throughout the public domain must be to City of Sydney specifications and heel/bicycle safe, slip resistant, infill with material to match surrounding surface, finished flush with the adjacent pavement to avoid trip hazards and be clear of obstructions for easy opening and cleaning. Infill pit lids are to be detailed where specified by Council's Public Domain Officer. Private pits are not permitted within the public domain. All details of pit lids must be shown on the public domain plan and must be approved by the City's Public Domain Unit prior to the issue of an approval for public domain works.

Reason

To ensure drainage and service pit lids within the public domain are appropriately designed and installed.

(97) PUBLIC DOMAIN PLAN DETAILED DOCUMENTATION FOR CONSTRUCTION

A detailed public domain plan and all relevant documentation must be submitted to and approved by City's Public Domain Unit prior to the construction of any public domain works. This Plan must document all works required to ensure that the public domain upgrade work complies with the City's specifications and requirements, as outlined in documents such as City of Sydney's *Public Domain Manual*, *Sydney Streets Code*, *Sydney Street Tree Masterplan*, *Sydney Lights: Public Domain Design Code* and *Sydney Streets Technical Specification*. The documentation must be *checked, accurate, and comply with specified requirements*. Plans must be based on an accurate survey, to scale and fully coordinated across all disciplines and submissions. The supplied documentation must be for Construction issue and will be approved under Section 138 of the Roads Act.

The Public Domain Manual and all other relevant documents are available for download from Council's website at <https://www.cityofsydney.nsw.gov.au/development/public-domain-works/da-associated-works>.

The Public Domain Plan documentation must be submitted with an Application for Public Domain Plan Assessment and include the approved Public Domain Levels and Gradients documentation. If the proposed detailed design of the public domain requires changes to any previously approved levels, details must be submitted for approval with the public domain plan and additional fees may apply.

Reason

To ensure the public domain complies with Council's requirements.

(98) HOLD POINTS

Prior to an approval being issued for the construction of public domain and / or planning agreement works, including civil, drainage and subsurface works, a set of hold points will be provided by the City's Public Domain Unit in accordance with the City's Public Domain Manual and Sydney Streets Technical Specification. The list of hold point inspections will be included in the Public Domain works approval letter.

These hold point inspections must be adhered to during construction works. Prior to the issue of any Occupation Certificate, confirmation from the City's Public Domain Unit, that hold point inspections have been completed and works have been accepted by the City must be provided to the Principal Certifier.

Reason

To ensure hold points are adhered to during construction works.

(99) STORMWATER DRAINAGE CONNECTION

For approval of a connection into the City of Sydney's drainage system an "*Application for Approval of Stormwater Drainage Connections*" must be submitted to the City, together with an application fee in accordance with the City of Sydney's adopted Schedule of Fees and Charges. This must be approved prior to approval being issued for the construction of public domain work.

Reason

To ensure approval of connection into the Council's drainage system is sought.

(100) PUBLIC DOMAIN LIGHTING RETICULATION

Prior to the issue of any relevant approval for the construction of public domain works, a detailed Public Domain Lighting Reticulation Plan for pedestrian and street lighting in the public domain must be submitted to and approved by the City's Public Domain Unit in accordance with the City's *Sydney Lights Design Code*, *Sydney Streets Code*, *Sydney Streets Technical Specification* and *Public Domain Manual*.

The Public Domain Manual and all other relevant documents are available for download from Council's website at

<https://www.cityofsydney.nsw.gov.au/development/public-domain-works/da-associated-works>.

If applicable, this public domain lighting documentation must include pole footing locations and structural details, location and details of underground electrical reticulation including connections and conduits, pit cabling and certifications as described in the City's *Public Domain Manual*. The public domain lighting is to be superimposed on the public domain plan to show any conflicts between lighting and the proposed landscape design.

Reason

To ensure the public domain lighting documentation complies with Council requirements.

(101) HOURS OF WORK AND NOISE – OUTSIDE CBD

The hours of construction and work on the development must be as follows:

- (a) All work, including building/demolition and excavation work, and activities in the vicinity of the site generating noise associated with preparation for the commencement of work (eg. loading and unloading of goods, transferring of tools etc) in connection with the proposed development must only be carried out between the hours of 7.30am and 5.30pm on Mondays to Fridays, inclusive, and 7.30am and 3.30pm on Saturdays, with safety inspections being permitted at 7.00am on work days, and no work must be carried out on Sundays or public holidays.
- (b) All work, including demolition, excavation and building work must comply with the City of Sydney Code of Practice for Construction Hours/Noise 1992 and Australian Standard 2436 - 2010 Guide to Noise Control on Construction, Maintenance and Demolition Sites.
- (c) Notwithstanding the above, the use of a crane for special operations, including the delivery of materials, hoisting of plant and equipment and erection and dismantling of on-site tower cranes which warrant the on-street use of mobile cranes outside of above hours can occur, subject to a separate application being submitted to and approved by Council under Section 68 of the Local Government Act 1993 and Sections 138/139 of the Roads Act 1993.

Note: Works may be undertaken outside of hours, where it is required to avoid the loss of life, damage to property, to prevent environmental harm and/or to avoid structural damage to the building. Written approval must be given by the Construction Regulation Team, prior to works proceeding.

The *City of Sydney Code of Practice for Construction Hours/Noise 1992* allows extended working hours subject to the approval of an application in accordance with the Code and under Section 4.55 of the *Environmental Planning and Assessment Act 1979*.

Reason

To protect the amenity of the surrounding area.

(102) NOTIFICATION OF EXCAVATION WORKS OR USE OF HIGH NOISE EMISSION APPLIANCES/PLANT

The immediately adjoining neighbours must be given a minimum of 48 hours notice that excavation, shoring or underpinning works or use of high noise emission appliances / plant are about to commence.

Reason

To protect the amenity of the surrounding area.

(103) LOADING AND UNLOADING DURING CONSTRUCTION

The following requirements apply:

- (a) All loading and unloading associated with construction activity must be accommodated on site, where possible.
- (b) If, it is not feasible for loading and unloading to take place on site, a Works Zone on the street may be considered by Council.
- (c) A Works Zone may be required if loading and unloading is not possible on site. If a Works Zone is warranted an application must be made to Council at least 8 weeks prior to commencement of work on the site. An approval for a Works Zone may be given for a specific period and certain hours of the days to meet the particular need for the site for such facilities at various stages of construction. The approval will be reviewed periodically for any adjustment necessitated by the progress of the construction activities.
- (d) Where hoisting activity over the public place is proposed to be undertaken including hoisting from a Works Zone, a separate application under Section 68 of the Local Government Act 1993 and Sections 138/139 of the Roads Act 1993 must be submitted to and approved by Council.

Reason

To protect the amenity of the public domain.

(104) NO OBSTRUCTION OF PUBLIC WAY

Unless otherwise approved by Council, the public way must not be obstructed by any materials, vehicles, waste receptacles, skip-bins or the like. Non-compliance with this requirement may result in the issue of a notice by Council to stop all work on the site.

Reason

To protect the amenity of the public domain.

(105) USE OF MOBILE CRANES

The following requirements apply:

- (a) Mobile cranes operating from the road must not be used as a method of demolishing or constructing a building.
- (b) For special operations including the delivery of materials, hoisting of plant and equipment and erection and dismantling of on-site tower cranes which warrant the on-street use of mobile cranes, permits must be obtained from Council for the use of a mobile crane. The permits must be obtained 48 hours beforehand for partial road closures which, in the opinion of Council will create minimal traffic disruptions and 4 weeks beforehand in the case of full road closures and partial road closures which, in the opinion of Council, will create significant traffic disruptions.
- (c) The use of a crane for special operations, including the delivery of materials, hoisting of plant and equipment and erection and dismantling of on-site tower cranes which warrant the on-street use of mobile cranes outside of approved hours of construction can occur, subject to a separate application being submitted to and approved by Council under Section 68 of the Local Government Act 1993 and Sections 138/139 of the Roads Act 1993.

Reason

To ensure mobile cranes are used appropriately.

(106) SURVEY

All footings, walls and floor slabs adjacent to a boundary must be set out by a registered surveyor. On commencement of brickwork or wall construction a survey and report, prepared by a Registered Surveyor, must be submitted to the Principal Certifier indicating the position of external walls in relation to the boundaries of the allotment. Any encroachments by the subject building over adjoining boundaries or roads must be removed prior to continuation of building construction work.

Reason

To ensure the development does not encroach onto neighbouring properties.

BEFORE ISSUE OF AN OCCUPATION CERTIFICATE

(107) PHYSICAL MODELS

- (a) Prior to the issue of any Occupation Certificate an accurate 1:500 scale model of the development as constructed must be submitted to and approved by Council's Area Coordinator Planning Assessments/Area Planning Manager for the City Model in Town Hall House.

Note:

- (i) The models must be constructed in accordance with the Model Specifications available online at <http://www.cityofsydney.nsw.gov.au/development/application-guide/application-process/model-requirements> Council's modellers must be consulted prior to construction of the model.
- (ii) The models are to comply with all of the conditions of the Development Consent.
- (iii) The models must be amended to reflect any further modifications to the approval (under Section 4.55 of the *Environmental Planning and Assessment Act*) that affect the external appearance of the building.

Reason

To ensure the provision of an appropriate physical model of the development.

(108) SUBMISSION OF ELECTRONIC CAD MODELS PRIOR TO OCCUPATION CERTIFICATE

- (a) Prior to any Occupation Certificate being issued, an accurate 1:1 electronic CAD model of the completed development must be submitted to and approved by Council's Area Coordinator Planning Assessments/Area Planning Manager for the electronic Visualisation City Model.
- (b) The data required to be submitted within the surveyed location must include and identify:
 - (i) building design above and below ground in accordance with the development consent;
 - (ii) all underground services and utilities, underground structures and basements, known archaeological structures and artefacts;
 - (iii) a current two points on the site boundary clearly marked to show their Northing and Easting MGA (Map Grid of Australia) coordinates, which must be based on Established Marks registered in the Department of Lands and Property Information's SCIMS Database with a Horizontal Position Equal to or better than Class C.

The data is to be submitted as a DGN or DWG file on a Compact Disc. All modelling is to be referenced to the Map Grid of Australia (MGA) spatially located in the Initial Data Extraction file.

- (c) The electronic model must be constructed in accordance with the City's 3D CAD electronic model specification. The specification is available online at <http://www.cityofsydney.nsw.gov.au/development/application-guide/application-process/model-requirements> Council's Modelling staff should be consulted prior to creation of the model. The data is to comply with all of the conditions of the Development Consent.

Reason

To ensure the provision of an appropriate electronic model of the development.

(109) RESTRICTION OF END OF JOURNEY FACILITIES

Prior to any Occupation Certificate being issued or the use commencing, whichever is earlier, a documentary restrictive covenant to the effect that 327 sqm of the building has been approved as end of journey facilities is to be registered on the Title of the development site pursuant to section 88E of the *Conveyancing Act 1919*. The covenant is to be created appurtenant to Council and at no cost to Council.

Reason

To ensure the bonus floor space approved as part of the consent continuously used for the approved purpose.

(110) RESTRICTION ON USE OF CAR SPACES - COMMERCIAL WITH NO STRATA SUBDIVISION

The following conditions apply to car parking:

- (a) The on-site car parking spaces, exclusive of service car spaces, are not to be used other than by an occupant or tenant of the subject building.
- (b) Prior to any Occupation Certificate being issued or the use commencing, whichever is earlier, a documentary restrictive covenant, is to be registered on the Title of the development site pursuant to section 88E of the *Conveyancing Act 1919*, to the effect of (a) above. The covenant is to be created appurtenant to Council, at no cost to and to the satisfaction of Council.
- (c) Any future strata subdivision of the site is to include a restriction on User pursuant to section 39 of the *Strata Titles (Freehold Development) Act, 1973* as amended, so burdening all utility car parking allotments in the Strata Plan and/or an appropriate restrictive covenant pursuant to section 88B of the *Conveyancing Act 1919* burdening all car parking part - lots in the Strata Scheme.

Reason

To ensure the on-site car parking spaces, exclusive of service car spaces are not to be used other than by an occupant or tenant of the building.

(111) WASTE AND RECYCLING COLLECTION CONTRACT

Prior to any Occupation Certificate being issued, the building owner must ensure that there is a contract with a licensed contractor for the removal of **all waste**. Waste is to be stored and collected from within the curtilage of the site at all times.

Reason

To ensure that waste and recycling is appropriately managed.

(112) COMPLIANCE WITH HAZARDOUS MATERIALS SURVEY REPORT

All of the recommendations for management and/or removal of hazardous materials on the site, as outlined in the Hazardous Materials Survey Report (prepared in accordance with Condition 71) must be complied with.

Prior to the issue of any Occupation Certificate, certification must be submitted to the Principal Certifier from a certified Occupational Hygienist (*Australia Institute of Occupational Hygienists*) confirming that all hazardous materials identified have been contained, managed or removed in accordance with the recommendations given in the approved Hazardous Materials Survey Report and that the site is safe for future occupation in accordance with the approved use.

Reason

To ensure that hazardous materials on the site are appropriately managed.

(113) PUBLIC DOMAIN WORKS COMPLETION

The Public Domain works are to be constructed in accordance with the Public Domain Works Approval letter, stamped plans for Public Domain Levels and Gradients, Stormwater, Public Domain Lighting, the City's *Public Domain Manual*, *Stormwater Drainage Manual*, *Sydney Lights Design Code* and *Sydney Streets Technical Specification*.

The public domain work must be inspected and a Public Domain Work Letter of Completion Operational Acceptance must be issued by Council's Public Domain Officer prior to the issue of any Occupation Certificate or before the commencement of use, whichever is earlier.

Reason

To ensure the public domain works are completed in accordance with the approved documents and Council's requirements.

(114) PUBLIC DOMAIN COMPLETION – WORK AS EXECUTED DOCUMENTATION

Prior to a Public Domain Works Letter of Completion Operational Acceptance being issued for public domain works, works-as-executed (As-Built) plans and documentation, must be submitted to and accepted by the City of Sydney for all public domain works, including where required Stormwater, Public Domain Lighting and road construction. These works must be certified by a suitably qualified, independent professional. Details of the documentation required for approval will be advised by the City's Public Domain Unit.

Reason

To ensure Council receives works-as-executed documentation for public domain works.

(115) STORMWATER COMPLETION DEED OF AGREEMENT AND POSITIVE COVENANT

Prior to the issue of any Occupation Certificate:

- (a) The Owner is required to enter into a Deed of Agreement (Stormwater Deed) with the City of Sydney and obtain registration of Title of a Positive Covenant for all proposed connections to the City's underground drainage system. The deed and positive covenant will contain terms reasonably required by the City and will be drafted by the City's Legal Services Unit at the cost of the applicant, in accordance with the City's Fees and Charges.
- (b) A Positive Covenant must be registered on the property title for all drainage systems involving On-Site Detention (OSD) to ensure maintenance of the approved OSD system regardless of the method of connection. The positive covenant will contain terms reasonably required by the City and will be drafted by the City's solicitor at the cost of the applicant, in accordance with the City's Fees and Charges.

Reason

To protect underground drainage system.

(116) SURVEY INFRASTRUCTURE – RESTORATION

- (a) Prior to any Occupation Certificate being issued for the development, documentary evidence of restoration must be prepared by a Registered Surveyor and submitted to and approved by Council's Area Planning Manager / Coordinator. This evidence must include:
 - (i) Certification that all requirements requested under the Surveyor-General's Approval for Survey Mark Removal or by the City's Principal Surveyor under condition "Survey Infrastructure – Identification and Recovery" have been complied with;
 - (ii) Certification that all requirements requested under any Surveyor-General's Approval for Deferment of Survey Marks from condition "Survey Infrastructure – Pre Subdivision Certificate works" have been complied with and;
 - (iii) Time-stamped photographic records of all new survey infrastructure relating to the site clearly showing the mark itself and sufficient context to aid in identifying the mark on site.

Reason

To ensure all requirements for survey mark removal are complied with.

(117) SURVEY CERTIFICATE AT COMPLETION

A Survey Certificate prepared by a Registered Surveyor must be submitted to the Principal Certifier at the completion of the building work certifying the location of the building in relation to the boundaries of the allotment.

Reason

To ensure the development does not encroach onto neighbouring properties.

(118) LOADING AND SERVICING MANAGEMENT PLAN

A Loading and Servicing Management Plan must be submitted to and approved by Council prior to the Occupation Certificate for the site/use being granted.

The proposed loading dock must not be reserved for any other single tenancy and must be available to all users within the site. A management plan, loading dock manager, loading schedule or similar must be prepared so all users are aware of their entitlements. The Loading and Servicing Management Plan must include the strategy for the management of all servicing of the site including delivery vehicles, garbage collection, service vehicles and should include information such as arrivals to the site, the anticipated numbers of arrivals per week, time of day of the arrivals, length of stay, vehicle type etc. along with how these will be managed to prevent disruption to public streets. The management of the plan needs to be able to respond to changes in the surrounding road environment and be updated accordingly.

Once approved, this management plan must be provided to all tenants and external users.

(119) CAR LIFT OPERATION AND MANAGEMENT

A Traffic Management Plan and associated Car Lift Management Strategy are to be submitted to the Principal Certifying Authority prior to the Occupation Certificate for the site/use being granted.

The Plan must include, but is not limited to, management of car lift to ensure there is no requirement for any vehicles to wait on public streets to enter the site. This plan must include procedures to be followed in mechanical breakdown and/or system failures. Any induction training that will be required to operate the car lift must be outlined in this plan and the tenants/ delivery and service vehicle drivers must be aware of and comply with these requirements. Once satisfied by the Principal Certifying Authority, this management plan will need to be provided to all tenants and external users of the building.

LAND SUBDIVISION

(120) LOT CONSOLIDATION

All land titles within the site must be consolidated into one lot. A plan of consolidation must be registered with NSW Land Registry Services, prior to any Occupation Certificate being issued.

Reason: To ensure land titles within the site are consolidated.

(121) LAND SUBDIVISION – SEPARATE DA REQUIRED

Any proposal for land subdivision will require a separate application to Council to obtain development consent and the subsequent approval of the plan of subdivision and issue of a Subdivision Certificate under Section 6.15 of the *Environmental Planning and Assessment Act 1979*.

Reason

To ensure separate development consent is sought for land subdivision.

(122) LAND SUBDIVISION – SUBDIVISION CERTIFICATE

A separate application must be made to Council to obtain the approval of the plan of subdivision and issue of a Subdivision Certificate under Section 6.15 of the *Environmental Planning and Assessment Act 1979*.

Reason

To ensure separate development consent is sought for the plan of subdivision and issue of a Subdivision Certificate.

ONGOING USE

(123) ROOFTOP TERRACES HOURS OF OPERATION

The hours of operation for the rooftop terraces are restricted to between 7am and 8pm Monday to Sunday.

Reason

To ensure the premises operates within the approved hours of operation.

(124) NO SPEAKERS OR MUSIC OUTSIDE

Speakers and/or noise amplification equipment must not be installed and music must not be played in any of the outdoor areas associated with the premises including the public domain. Speakers located within the premises must not be placed so as to direct the playing of music towards the outdoor areas associated with the premises.

Reason

To safeguard the amenity of the surrounding neighbourhood.

(125) NOISE FROM GLASS REMOVAL

Glass must not be emptied or transferred from one receptacle to another anywhere in a public place. All glass must be emptied / transferred inside of the building on the premises and removed in containers.

Reason

To safeguard the amenity of the surrounding neighbourhood.

(126) VIBRATION

Operation of the use is not to result in the transmission of any perceptible vibration to an occupiable area within a separate premises.

Reason

To protect the amenity of surrounding properties.

(127) NOISE – COMMERCIAL PLANT / INDUSTRIAL DEVELOPMENT

- (a) Noise from commercial plant and industrial development must not exceed a project amenity/intrusiveness noise level or maximum noise level in accordance with relevant requirements of the NSW EPA [Noise Policy for Industry 2017 \(NPfI\)](#) unless agreed to by the City's Area Planning Manager. Further:
 - (i) Background noise monitoring must be carried out in accordance with the long-term methodology in [Fact Sheet B](#) of the NPfI unless otherwise agreed by the City's Area Planning Manager.

- (ii) Commercial plant is limited to heating, ventilation, air conditioning, refrigeration and energy generation equipment.
- (b) An $L_{Aeq,15 \text{ minute}}$ (noise level) emitted from the development must not exceed the $L_{A90, 15 \text{ minute}}$ (background noise level) by more than 3dB when assessed inside any habitable room of any affected residence or noise sensitive commercial premises at any time. Further:
 - (i) The noise level and the background noise level must both be measured with all external doors and windows of the affected residence closed.
 - (ii) Background noise measurements must not include noise from the development but may include noise from necessary ventilation at the affected premises.
- (c) Corrections in [Fact Sheet C](#) of the NPfI are applicable to relevant noise from the development measured in accordance with this condition, however duration corrections are excluded from commercial noise.

Reason

To protect the acoustic amenity of surrounding properties.

(128) NOISE – INSTALLATION, SETUP, TESTING AND CALIBRATION OF LIMITER/S, PRIOR TO AN OCCUPATION CERTIFICATE

Prior to the issue of an Occupation Certificate, a Suitably Qualified Acoustic Consultant* is to provide a Noise Limiter/s Verification Report to the written satisfaction of the Principal Certifying Authority that the development complies with the requirements set out as follows, and any relevant requirement in the COMPLIANCE WITH THE ACOUSTIC REPORT CONDITION PRIOR TO CONSTRUCTION OR OCCUPATION CERTIFICATES condition:

- (a) All sound amplification equipment in the premises must be controlled by a Root Mean Square (RMS) noise limiter with an attack time constant not exceeding 0.5 seconds, release time constant not less than 1 second and a compression ratio equal of at least 20:1. The limiter shall be set by a suitably qualified acoustic consultant* as per the manufacturer's specification. The consultant must ensure that resultant amplified sound complies with the Council's criteria for entertainment noise.
- (b) All Limiters and all post-limiter equipment including power amplifiers must be tamper proof and only operable by the acoustic consultant, a licensee and business owner who must keep a completed report on the premises.
- (c) This report must certify that limiter/s were installed, tested and calibrated so amplified noise will comply with the NOISE – ENTERTAINMENT Condition. The report will be prepared in accordance with and provide detail on the following requirements:

- (i) An initial calibration of the operation of the limiter with the sound amplification equipment is to be undertaken. This assessment must include setting of the amplification system in addition to a documented overview of the system so that compliance is achieved with the noise criteria as referenced in parts (a) to (c) above.
- (ii) Limiter settings and subsequent equipment must be benchmarked at the time of the above operational assessment. Pink noise and a swept sine wave signal must be fed into the amplification system and the level of the noise increased until the limiter operates continuously to comply with criteria. The L_{Aeq} , L_{A1} , L_{Ceq} and L_{C1} (1/1 octave bands - 31.5 Hz to 8 kHz centre frequencies) levels must be measured at suitable relevant reference location/s in the premises, with the premises empty other than essential staff. Correlating L_{Aeq}/L_{A1} and L_{Ceq}/L_{C1} measurements must be taken at identified nearby noise sensitive receivers during this process.
- (iii) Music must then be played through the sound system(s) with the limiter(s) in continuous operation to verify the limiters work correctly and meet noise criteria at the locations detailed above.
- (iv) The report will address the limiter installed within the premises (including but not limited to its brand, type specifications and location) including the noise control levels the limiter was set to (including a copy of the software configuration file for any digital signal processing device used). Furthermore, all post limiter equipment will be photographed, documented and catalogued in the report including location on a layout drawing.

Note: Suitably Qualified Acoustic Consultant means a consultant who possesses the qualifications to join the Australian Acoustical Society, Institution of Engineers Australia (grade of member) or the Association of Australasian Acoustical Consultants (grade of member firm).

Reason

To protect the acoustic amenity of surrounding properties.

(129) NOISE – AMPLIFIED SOUND AND THE UPKEEP AND OPERATION OF LIMITER/S

Following receipt of the report as per part (b) of the NOISE - INSTALLATION, SETUP, TESTING & CALIBRATION OF LIMITER/S, PRIOR TO AN OCCUPATION CERTIFICATE condition (and receipt of the relevant occupation certificate, the report is to be kept on the premises at all times, signed and dated by the licensee and business owner. From this point forward the licensee and business owner must ensure the following:

- (a) The limiter/s and sound amplification system must be maintained and not tampered with. That unauthorised modifications are not made which are contrary to the report. Repairs and replacements may be made to the system as necessary with any like component but must not be capable of increasing the permitted noise amplification levels outlined in the report.

- (b) That additional amplification equipment must not be brought onsite which if used could cause cumulative entertainment noise (including amplified sound) from the development to exceed controls in this consent. This does not apply to:
 - (i) Equipment that is only used when routed through and controlled by the limiter/s, i.e. the limiters and amplified sound system on the premises are capable of receiving and controlling that equipment, and
 - (ii) Such that use of the equipment must not cause amplified sound which exceeds the cumulative entertainment noise controls in this consent.

Reason

To protect the acoustic amenity of surrounding properties.

(130) ON SITE LOADING AREAS AND OPERATION

All loading and unloading operations associated with servicing the site must be carried out within the confines of the site, at all times and must not obstruct other properties/units or the public way.

At all times the service vehicle docks, car parking spaces and access driveways must be kept clear of goods and must not be used for storage purposes, including garbage storage.

Reason

To maintain the orderly operation of vehicle parking areas and to ensure the public domain is kept free from physical obstructions.

(131) WASTE/RECYCLING COLLECTION - COMMERCIAL

- (a) Waste storage and the collection of waste and recycling must only occur during the designated zone collection times as outlined in the City's Waste Policy – Local Approvals Policy for Managing Waste in Public Places 2017.
- (b) Waste and recycling bins must not be placed on the street for collection. Services must be conducted within the property boundary or as a wheel-out/wheel-back service.
- (c) Unimpeded access must be provided for collection vehicles to set down within 10 metres of waste storage areas during zone collection times on collection days.

Reason

To ensure that waste and recycling is appropriately managed.

(132) MAINTENANCE OF TREES ON SITE

- (a) Tree maintenance must be implemented and complied with immediately following the tree planting, and until the tree reaches the required minimum height limit of 6 metres in height and 4 metres canopy width.
- (b) The newly planted tree on site must be appropriately maintained on an on-going basis.
- (c) Maintenance includes watering, weeding, removal of rubbish from tree bases, pruning (in accordance with AS4373-2007), fertilizing, pest and disease control and any other operations required to maintain a healthy robust tree.
- (d) If the newly planted tree fails to establish or does not reach a height of 6 metres and canopy spread width of 4 metres it must be replaced with a tree of comparable qualities and container size of 200 litres.
- (e) The conditions of this consent will apply to all replacement trees, including the maintenance and reporting which re-starts at each replanting event.

Reason

To ensure the ongoing maintenance of trees planted on the site.

(133) DEFECTS LIABILITY PERIOD – PUBLIC DOMAIN WORKS

All works to the City's public domain, including rectification of identified defects, are subject to a 6-month defects liability period from the date of Completion. The date of Completion will be nominated by Council on the Public Domain Works – Letter of Completion Operational Acceptance.

Reason

To ensure all works to the City's public domain are protected under a liability period.

(134) ENCROACHMENTS – NEIGHBOURING PROPERTIES

No portion of the proposed structure shall encroach onto the adjoining properties.

Reason

To protect neighbouring properties.

(135) ENCROACHMENTS – PUBLIC WAY

No portion of the proposed structure, including gates and doors during opening and closing operations, shall encroach upon Council's footpath area.

Reason

To protect the public way.

(136) ADDITIONAL EASEMENTS

Any other documentary easements or any other encumbrances and indemnities required for joint or reciprocal use of part or all of the proposed lots as a consequence of any future subdivision must be created over appropriate lots in that subdivision, pursuant to Section 88B of the Conveyancing Act 1919 and to Council's satisfaction.

Reason

To ensure the orderly operation of the development.