

Attachment A

Recommended Conditions of Consent
--

GENERAL CONDITIONS

(1) APPROVED DEVELOPMENT

- (a) Development must be in accordance with Development Application No. D/2024/71 dated 8 February 2024 and the following drawings prepared by SJB Architects:

Drawing Number	Drawing Name	Date
DA-0251 Rev 3	Demolition plan – Lower ground	7.12.23
DA-0252 Rev 2	Demolition plan – mezzanine	7.12.23
DA-0253 Rev 3	Demolition plan – Ground floor	7.12.23
DA-0254 Rev 3	Demolition plan – Level 01	7.12.23
DA-0255 Rev 3	Demolition plan – Roof plan	7.12.23
DA-0256 Rev 3	Demolition – Section	7.12.23
DA-0257 Rev 3	Demolition elevation – South	7.12.23
DA-0258 Rev 3	Demolition elevation – North	7.12.23
DA-0101 Rev 4	Site plan	12.06.24
DA-1001 Rev 9	Floor plan – Lower ground	12.06.24
DA-1002 Rev 9	Floor plan – Mezzanine	12.06.24
DA-1003 Rev 10	Floor plan – Ground floor	12.06.24
DA-1005 Rev 10	Floor plan – Level 01	12.06.24
DA-1006 Rev 9	Floor plan – Level 02	12.06.24
DA-1007 Rev 9	Floor plan – Level 3	12.06.24
DA-1008 Rev 10	Floor plan – Level 4	12.06.24

Drawing Number	Drawing Name	Date
DA-1009 Rev 9	Floor plan – Level 5	12.06.24
DA-1010 Rev 10	Floor plan – Level 6	12.06.24
DA-1011 Rev 4	Floor plan – Roof level	12.06.24
DA-1101 Rev 6	Student room types	12.06.24
DA-1501 Rev 9	Elevation - south	12.06.24
DA-1502 Rev 8	Elevation - north	12.06.24
DA-1503 Rev 5	Elevation - east	12.06.24
DA-1504 Rev 5	Elevation - west	12.06.24
DA-1601 Rev 9	Building Section A	12.06.24
DA-1602 Rev 10	Building Section B	12.06.24
DA-1603 Rev 9	Building Section C	12.06.24
DA-1610 Rev 1	Building entry sections	12.06.24
DA-8001 Rev 2	Materials schedule	12.06.24

and as amended by the conditions of this consent.

- (b) In the event of any inconsistency between the approved plans and supplementary documentation, the drawings will prevail.

Reason

To ensure all parties are aware of the approved plans and supporting documentation that applies to the development.

(2) HOUSING AND PRODUCTIVITY CONTRIBUTION

Before the issue of the first Construction Certificate the housing and productivity contribution (HPC) set out in the table below is required to be made.

Housing and productivity contribution	Amount
Housing and productivity contribution (base component)	\$15,173.05
Transport project component	-
Total housing and productivity contribution	\$15,173.05

The HPC must be paid using the NSW planning portal.

At the time of payment, the amount of the HPC is to be adjusted in accordance with the *Environmental Planning and Assessment (Housing and Productivity Contributions) Order 2023* (HPC Order).

The HPC may be made wholly or partly as a non-monetary contribution (apart from any transport project component) if the Minister administering the *Environmental Planning and Assessment Act 1979* agrees.

The HPC is not required to be made to the extent that a planning agreement excludes the application of Subdivision 4 of Division 7.1 of the *Environmental Planning and Assessment Act 1979* to the development, or the HPC Order exempts the development from the contribution.

The amount of the contribution may be reduced under the HPC Order, including if payment is made before 1 July 2025.

Reason

To require contributions towards the provision of regional infrastructure.

(3) SECTION 7.11 CONTRIBUTIONS PAYABLE - CONTRIBUTION TOWARDS PUBLIC AMENITIES – CITY OF SYDNEY DEVELOPMENT CONTRIBUTIONS PLAN 2015 – WEST PRECINCT

Council has identified the development will increase demand for public amenities and facilities. Pursuant to Section 7.11 of the *Environmental Planning and Assessment Act, 1979* (as amended), and the *City of Sydney Development Contributions Plan 2015* the following monetary contributions are required towards the cost of public amenities.

<u>Contribution Category</u>	<u>Amount</u>
Open Space	\$979,471.58
Community Facilities	\$325,294.34
Traffic and Transport	\$1,507.02
Stormwater Drainage	\$0.00
Total	\$1,306,272.93

The City of Sydney will index the above contribution for inflation at the time of payment using the following formula.

$$C_{\text{payment}} = C_{\text{consent}} \times (CPI_{\text{payment}} \div CPI_{\text{consent}})$$

Where:

C_{payment} = Is the contribution at time of payment;

C_{consent} = Is the contribution at the time of consent, as shown above;

CPI_{payment} = Is the Consumer Price Index (All Groups Index) for Sydney published by the Australian Bureau of Statistics that applies at the time of payment; and

CPI_{consent} = Is the Consumer Price Index (All Groups Index) for Sydney at the date the contribution amount above was calculated being – 139.1 for the June 2024 quarter.

The contribution must be paid prior to the issue of any Construction Certificate in relation to this development.

Please contact Council's Planning Administration staff at planningsystemsadmin@cityofsydney.nsw.gov.au to request a letter confirming the indexed contribution amount payable.

Once the letter confirming the indexed contribution is obtained, payment may be made at any of the City's Neighbourhood Service Centres or the One Stop Shop at Town Hall House. Acceptable payment methods are EFTPOS (debit card only), cash (up to 10K only), Credit Card (up to 50K only) or a bank cheque made payable to the City of Sydney. Personal or company cheques will not be accepted.

Reason

To ensure development contributions are paid to address the increased demand for public amenities and services resulting from the approved development.

(4) AFFORDABLE HOUSING CONTRIBUTION – RESIDUAL LAND OR CENTRAL SYDNEY – PAYMENT IN LIEU OF FLOOR SPACE CONTRIBUTION – PRIOR TO CONSTRUCTION CERTIFICATE

(a) In accordance with the City of Sydney Affordable Housing Program and prior to the issue of a Construction Certificate, the applicant must provide evidence that a monetary contribution towards the provision of affordable housing has been paid to the City of Sydney Council.

(b) The contribution is \$1,744,831.81 (indexed at 4 Oct 24). This is calculated by establishing the sum of the equivalent monetary contribution \$11,176.22 multiplied by 1% of the total floor area for non-residential development (1890sqm) and the equivalent monetary contribution \$11,176.22 multiplied by 3% of the total floor area for residential development (4574sqm).

- (c) If the contribution is paid after the indexation period in which the consent is granted, being 1 March 2024 to 28 February 2025 the above contribution will be adjusted according to the Sydney LGA median strata dwelling price ('MDP') using the following formula.
- (d) Contribution payable at Time of Payment = $C \times \text{MDP2} / \text{MDP1}$, where:
 - (i) C is the original total contribution amount payable to the City of Sydney as shown above;
 - (ii) MDP2 is the Median Strata Dwelling Price in Sydney LGA taken from the most recent NSW Government Rent and Sales Report at the time of indexation of the equivalent monetary contribution rate; and
 - (iii) MDP1 is the Median Strata Dwelling Price in Sydney LGA taken from the NSW Government Rent and Sales Report used to establish the current equivalent monetary contribution rate, being 1 March 2024 to 28 February 2025.

Contact Council's Planning Assessment Unit at planningsystemsadmin@cityofsydney.nsw.gov.au for written confirmation of the amount payable, with indexation as necessary, prior to payment.

Reason

To ensure development contributions are paid to contribute to the provision of essential affordable rental housing infrastructure.

(5) BUILDING HEIGHT

- (a) The height of the building must not exceed RL 43.00 (AHD) to the top of the building and RL 38.00 (AHD) to the parapet of the building.
- (b) Prior to an Occupation Certificate being issued, a Registered Surveyor must provide certification that the height of the building accords with (a) above, to the satisfaction of the Principal Certifier.

Reason

To ensure the constructed development complies with the approved height.

(6) FLOOR SPACE RATIO - ALL OTHER AREAS

The following applies to Floor Space Ratio:

- (a) The Floor Space Ratio for the development must not exceed 3.6:1 calculated in accordance with Sydney Local Environmental Plan 2012. For the purposes of the calculation of FSR, the Gross Floor Area of the business component is 317sqm, for the residential component is 4080sqm (areas below ground excluded), and the total Gross Floor Area is 4,441sqm.

- (b) Prior to an Occupation Certificate being issued, a Registered Surveyor must provide certification of the total and component Gross Floor Areas (by use) in the development, utilising the definition under Sydney Local Environmental Plan 2012, applicable at the time of development consent, to the satisfaction of the Principal Certifier.

Reason

To ensure the constructed development complies with the approved floor space ratio.

(7) COMPLIANCE WITH SUBMITTED MATERIALS AND SAMPLES BOARD

The design details of the proposed building facade including all external finishes, colours and glazing must be in accordance with the materials schedule and sample board, and specifications prepared by SJB Ref: 6726 and materials schedule drawing Ref: 8001 Rev 2, dated 12.06.2024.

Reason

To ensure all parties are aware of the approved materials and finishes that apply to the development.

(8) USE - SEPARATE DA REQUIRED

No consent is granted or implied for the fitout or specific use of:

- Ground level retail tenancies.
- Basement mezzanine level commercial tenancy, and retail tenancy.
- Basement level gym and retail tenancy.

A development consent or Complying Development Certificate (as appropriate) is required to be obtained for the fitout and use prior to that fitout or use commencing.

Reason

To require separate consent to be obtained for a use.

(9) RESTRICTION ON SUBDIVISION

In accordance with the provisions of section 70 of the *State Environmental Planning Policy (Housing) 2021* co-living housing cannot be subdivided into separate lots.

Reason

To restrict subdivision of the site containing co-living housing use.

(10) SIGNS - SEPARATE DA REQUIRED

A separate development application for any proposed signs additional to those approved as part of this consent (other than exempt or complying signs) must be submitted to and approved by Council prior to the erection or display of any such signs.

The submitted signage strategy prepared by SJB Architects (Ref: DA-8002 Rev 3, DA-8003 Rev 3) is to be updated with the deletion of signage type C from (2) elevation south (above the awning) prior to endorsement of the strategy.

Reason

To require separate consent to be obtained for any additional signs.

(11) SERVICE VEHICLE SIZE LIMIT

The size of vehicles servicing the property must be a maximum length of 10.6m.

Reason

To maintain the orderly operation of vehicle parking and loading areas.

(12) ASSOCIATED ROADWAY COSTS

All costs associated with the construction of any new road works including kerb and gutter, road pavement, drainage system and footway shall be borne by the developer. The new road works must be designed and constructed in accordance with the City's "Sydney Streets Technical Specification" including amendments and "Sydney Streets Design Code".

Reason

To ensure all roadway works are designed and constructed in accordance with Council requirements.

(13) VEHICLE ACCESS

All vehicles are to enter and depart the site travelling in a forward direction.

Reason

To increase pedestrian safety at the site access.

(14) SWINGING DOORS OVER PUBLIC WAY

Any access doors to enclosures housing building services and facilities, such as hydrant and sprinkler booster assemblies or the like, must not open over the footway/roadway.

Reason

To ensure no element of the development obstructs the use of the public way.

(15) TACTILE GROUND SURFACE INDICATORS AND HANDRAILS

All tactile ground surface indicators, handrails and other elements required to provide access into the building / property must be located entirely within the private property boundary.

Reason

To ensure ground surface indicators, handrails and other elements required to provide access into the building/property are appropriately located.

(16) PAVING MATERIALS

The surface of any material used or proposed to be used for the paving of colonnades, thoroughfares, plazas, arcades and the like which are used by the public must comply with AS/NZS 4586:2004 (including amendments) "Slip resistance classification of new pedestrian surface materials".

Reason

To ensure appropriate and safe paving materials are used.

BUILDING WORK

BEFORE ISSUE OF A CONSTRUCTION CERTIFICATE

(17) EXTERNAL WALLS AND CLADDING FLAMMABILITY

The external walls of the building including attachments must comply with the relevant requirements of the *Building Code of Australia*. Prior to the issue of a Construction Certificate and Occupation Certificate the Registered Certifier and the Principal Certifier must:

- (a) Be satisfied that suitable evidence is provided to demonstrate that the products and systems proposed for use or used in the construction of external walls including finishes and claddings such as synthetic or aluminium composite panels comply with the BCA; and
- (b) Ensure that the documentation relied upon in the approval processes include an appropriate level of detail to demonstrate compliance with the BCA as proposed and as built.

Reason

To ensure the external walls and cladding comply with relevant requirements.

(18) COMPLIANCE WITH THE ACOUSTIC REPORT PRIOR TO CONSTRUCTION AND OR OCCUPATION CERTIFICATES

- (a) All relevant performance parameters (including but not limited to requirements, engineering assumptions and recommendations) in the DA Acoustic Report prepared by SLR Consulting, dated 18 June 2024, Ref: 610.30961.00000-R02-v1.3 must be implemented in the development prior to the commencement of its use.
- (b) Prior to the issue of any relevant Construction Certificate, the final construction drawings and final construction methodology must be assessed and reported to be in accordance with the requirements of the DA Acoustic Report in (a) above, with reference to relevant documentation. This must be done by a Suitably Qualified Acoustic Consultant* (see definition below). This work will be to the satisfaction of the Registered Certifier.
- (c) Prior to the issue of any Occupation Certificate, a Suitably Qualified Acoustic Consultant* is to provide a written Acoustic Verification Report to the satisfaction of the Principal Certifier that the development complies with the requirements set out in the Report and in (a) and (b) above.

Note: Suitably Qualified Acoustic Consultant means a consultant who possesses the qualifications to join the Australian Acoustical Society, Institution of Engineers Australia (grade of member) or the Association of Australasian Acoustical Consultants (grade of member firm).

- (d) All physical aspects of the building's structure installed in order to meet performance parameters in accordance with this condition must be maintained at all times.

Reason

To ensure all parties are aware of the supporting documentation that applies to the development.

(19) DEMOLITION, EXCAVATION AND CONSTRUCTION NOISE AND VIBRATION MANAGEMENT PLAN

A site-specific demolition, excavation and construction noise and vibration management plan must be submitted to the Council for comment and approval prior to issue of any Construction Certificate. The Plan must be prepared by a suitably qualified acoustic consultant who is a person who possesses the qualifications to join the Australian Acoustic Society, Institution of Engineers Australia (grade of member) or the Association of Australasian Acoustic Consultants (grade of member firm). The plan must include but not be limited to the following:-

- (a) identification of noise sensitive receivers near to the site.
- (b) A prediction as to the level of noise impact likely to affect the nearest noise sensitive receivers from the use and proposed number of high noise intrusive appliances intended to be operated onsite. A statement should also be submitted outlining whether or not predicted noise levels will comply with the noise criteria stated within the *City of Sydney Construction Hours /Noise Code of Practice 1992* for the typical construction hours of 07.00am to 7.00pm. Where resultant site noise levels are likely to be in exceedance of this noise criteria then a suitable proposal must be given as to the duration and frequency of respite periods that will be afforded to the occupiers of neighbouring property.
- (c) A representative background noise measurement ($L_{A90, 15 \text{ minute}}$) should be submitted, assessed in the vicinity of any potentially affected receiver locations and measured in accordance with AS 1055:1.2.1997.
- (d) Confirmation of the level of community consultation that has/is and will be undertaken with Building Managers/ occupiers of the main adjoining noise sensitive properties likely to be most affected by site works and the operation of plant/machinery particularly during the demolition and excavation phases.
- (e) Confirmation of noise monitoring methodology that is to be undertaken during the main stages of work at neighbouring noise sensitive properties in order to keep complaints to a minimum and to ensure that noise from site works complies with the noise criteria contained within City's Construction Noise Code.
- (f) What course of action will be undertaken following receipt of a complaint concerning offensive noise.

- (g) Details of any noise mitigation measures that have been outlined by an acoustic consultant or otherwise that will be deployed on site to reduce noise impacts on the occupiers of neighbouring noise sensitive property to a minimum.
- (h) What plant and equipment is to be used on site, the level of sound mitigation measures to be undertaken in each case and the criteria adopted in their selection taking into account the likely noise impacts on the occupiers of neighbouring property and other less intrusive technologies available.

Reason

To ensure an adequate construction noise and vibration management plan is prepared.

(20) PARKING DESIGN

The design, layout, signage, line marking, lighting and physical controls of all off-street parking facilities must comply with the minimum requirements of Australian Standard AS/NZS 2890.1 Parking facilities Part 1: Off-street car parking, AS/NZS 2890.2 Parking facilities Part 2: Off-commercial vehicle facilities and AS/NZS 2890.6 Parking facilities Part 6: Off-street parking for people with disabilities. The details must be submitted to and approved by the Registered Certifier prior to a Construction Certificate being issued.

Reasonblank

To ensure parking facilities are designed in accordance with the Australian Standards.

(21) ALLOCATION OF PARKING

The number of car parking spaces to be provided for the development must comply with the table below. Details confirming the parking numbers must be submitted to the satisfaction of the Registered Certifier prior to the issue of a Construction Certificate.

Car Parking Type	Number
Service vehicle spaces: Medium Rigid Vehicle / Council's 10.6m waste vehicle, loading dock	1

Reason

To ensure the allocation of parking is in accordance with the Council's DCP.

(22) BICYCLE PARKING AND END OF TRIP FACILITIES

- (a) The minimum number of bicycle parking spaces and end of trip facilities to be provided within the site boundary for the development must comply with the table below.

Bicycle Parking Type	Number	Requirements
Residential	120	Spaces must be a class 1 bicycle locker [i]
Residential visitor	14	Spaces must be Class 3 bicycle rails
Non-residential	7	Spaces must be Class 2 bicycle facilities
Non-residential visitor	10	Spaces must be Class 3 bicycle rails
End of Trip Facility Type	Number	
Showers with change area	2	
Personal lockers	12	

All bicycle parking spaces and end of trip facility must be provided on private land. The public domain cannot be used to satisfy this condition.

Notes:

- (i) If a basement storage area on title that is large enough to store a bike and is no smaller than a class 1 bike locker this can be counted as a space.
- (b) The layout, design and security of bicycle facilities must comply with the minimum requirements of Australian Standard AS 2890.3 Parking Facilities Part 3: Bicycle Parking Facilities. The details must be submitted to and approved by the Registered Certifier confirming prior to and form part of the Construction Certificate being issued.

Reason

To ensure the allocation of bicycle parking onsite that is in accordance with Australian Standards and the Council's DCP.

(23) CONSTRUCTION TRAFFIC MANAGEMENT PLAN

- (a) A Construction Traffic Management Plan must be submitted to and approved by Council prior to a Construction Certificate being issued.
- (b) The approved plan must be complied with during any demolition and/or construction work.

Reason

To ensure that the impacts of construction traffic is appropriately managed.

(24) PUBLIC ART

Public art must be installed to the City's satisfaction prior to the issue of any Occupation Certificate.

- (a) A preliminary public art plan is to be submitted and approved by Council's Area Planning Manager prior to the commencement of any works. The plan is to be prepared in accordance with the *Sydney DCP 2012*, the *Public Art Policy*, and the *Interim Guidelines: Public art in private developments*.
- (b) A Detailed Public Art Plan with final details of the proposed public artwork must be submitted to and approved by Council's Area Planning Manager prior to issue of any Construction Certificate for above ground works.
- (c) Public artwork must be installed to the City's satisfaction, inspected and approved and the Final Public Art Report submitted and approved by Council's Area Planning Manager prior to the issue of any Occupation Certificate.

Note: Public Art must be reviewed and endorsed by the City's Public Art Team and/or the Public Art Advisory Panel prior to submission for Council approval. Further information is available online at <http://www.cityofsydney.nsw.gov.au/explore/arts-and-culture/public-art>. Please contact the Public Art Team at publicartreferrals@cityofsydney.nsw.gov.au for further information.

Reason

To ensure public art is installed to the City's satisfaction.

(25) SITE AUDIT STATEMENT

Prior to the issue of a construction certificate associated with the built form of the development (excluding building work directly related to remediation), a Section A Site Audit Statement must be obtained from a NSW Environment Protection Authority accredited Site Auditor and submitted to the Council's Area Planning Manager at email address:-

hbapplications@cityofsydney.nsw.gov.au

The Site Audit Statement must confirm that the site has been remediated in accordance with the approved Remedial Action Plan and clearly state that site is suitable for the proposed use.

- (a) In circumstances where the Site Audit Statement is subject to conditions that require ongoing review by the Auditor or Council, these must be reviewed and must be approved by the Council's Health and Building Unit in writing through the Area Planning Manager before the Site Audit Statement is issued.

- (b) In circumstances where the Site Audit Statement conditions (if applicable) are not consistent with the consent, the development must not proceed until the inconsistency has been resolved to the satisfaction of Council (such as via a S4.55 modification of the consent pursuant to the provisions of the *Environmental Planning & Assessment Act 1979*).
- (c) **No Occupation Certificate is to be issued** by the Principal Certifier unless a Site Audit Statement has been submitted to and approved by Council in accordance with this condition.

Reason

To ensure that the site is appropriately remediated.

(26) LANDSCAPING OF THE SITE

- (a) A detailed landscape design including plans and details drawn to scale, and technical specification, by a registered landscape architect, must be submitted to and approved by Council's Area Coordinator Planning Assessments / Area Planning Manager prior to the issue of a Construction Certificate. These documents must include:
 - (i) Location of existing and proposed planting on the site including existing and proposed trees, planting in natural ground, and planting on structure.
 - (ii) Location and details of existing and proposed structures on the site including, but not limited to, paving, walls, services, furniture, shade structures, lighting and other features.
 - (iii) Details of earthworks and soil depths including finished levels and any mounding. The minimum soil depths for planting on structure must be 1000mm for trees, 450mm for shrubs and 200mm for groundcovers, excluding mulch and drainage layers.
 - (v) Planting details, and location, numbers, type and supply size of plant species, with reference to Australian Standards and preference for drought resistant species that contribute to habitat creation and biodiversity.
 - (vi) Details of drainage, waterproofing and watering systems.
 - (vii) Landscape maintenance plan. This plan is to be complied with during occupation of the property.
- (b) All landscaping in the approved plan is to be complete prior to any Occupation Certificate being issued.

Reason

To ensure the development is supported by a good quality, buildable landscape scheme that meets the City's controls.

(27) INACCESSIBLE GREEN ROOFS

- (a) A detailed green roof design including plans and details drawn to scale, and technical specification, by a registered landscape architect must be submitted to and approved by Council's Area Coordinator Planning Assessments / Area Planning Manager prior to the issue of a Construction Certificate. These documents must include:
 - (i) Location and details of existing and proposed services, walls, fixings and other structural elements that may interrupt waterproofing, including cross-sectional details of all components.
 - (ii) Details of soil types and depth including any mounding.
 - (iii) Details of drainage and irrigation systems, including overflow provisions and water retention cells in the drainage layer.
 - (iv) Planting details, and location, numbers, type and supply size of plant species, with reference to Australian Standards and preference for drought resistant species that contribute to habitat creation and biodiversity.
 - (v) Green roof maintenance plan. This plan is to be complied with during occupation of the property, and must include any relevant maintenance methodology for safe working at height such as access requirements, location of any anchor points, gates, and transport of materials and green waste.
 - (vi) A plan outlining the intended strategy for decommissioning if planting works fail. This is to ensure green roof maintained is throughout its life.
- (b) Prior to the issue of an Occupation Certificate, structural and waterproofing certifications for the green roof are to be submitted to and approved by the Principal Certifying Authority.
- (c) All landscaping in the approved plan must be complete prior to the issue of an Occupation Certificate.
- (d) Inaccessible green roofs must remain inaccessible for the lifetime of the property.

Reason

To ensure that the inaccessible green roof is designed to accommodate suitable landscaping and to ensure that adequate maintenance procedures are put in place.

(28) PUBLIC DOMAIN TREE PLANTING AND MAINTENANCE

- (a) A Tree Planting Plan must be submitted and approved by the City's Public Domain Unit prior to the issuing of any Construction Certificate. The plan must include and be consistent with the following requirements:

- (i) Tree species shall be consistent with the City's Street Tree Master Plan (refer to relevant precinct plans) or other relevant guidance document. Species substitutes will not be accepted.
- (ii) Tree pits must be located and constructed in accordance with the City's Street Tree Master Plan (Technical Guidelines) or other relevant guidance document.
- (iii) The tree pit design must include structural soils or structural cells to support pavements in accordance with the Street Tree Master Plan (Technical Guidelines).
- (iv) Indicate the chosen tree planting arrangement, being a choice of one of two options, being:

Undertake all tree supply, planting, and maintenance requirements to the required standards and to the satisfaction of the City's Tree Management.

OR

Pay a fee for the City to supply, plant, and maintain each required tree on the applicant's behalf. The fee is consistent with the City's Schedule of Fees and Charges.

- (b) If opting to undertake all tree supply, planting, and maintenance requirements, the following requirements must be met:
 - (i) The trees must be a minimum container size of (insert size) litres at the time of planting.
 - (ii) All new trees must be grown in accordance with the Australian Standard 2303:2015 'Tree stock for landscape use' and meet the requirements of this standard at the time of planting.
 - (iii) Certification from the tree supplier must be submitted to the City's Tree Management Officer and Public Domain Officer, prior to the trees being planted. The certification must confirm the tree(s) have been grown and comply with the requirements of AS2302. Any new trees that do not conform will be rejected by the City.
 - (iv) The trees must be planted by an Arborist or Horticulturist with a minimum AQF Level 3 qualification and be planted before the issuing of the final Occupation Certificate.
 - (v) All new trees must be inspected and approved by the City's Tree Management Officer (or their representative) at the following milestones: before planting with planting pits excavated; after planting; and at the end of the maintenance period.
 - (vi) All trees planted in accordance with the approved Tree Planting Plan must be maintained by an Arborist or Horticulturist with a minimum AQF Level 3 for a minimum period of twelve (12) months, commencing from the date of planting. Maintenance includes, but is not limited to, watering, weeding, removal of rubbish from tree

base, pruning, fertilizing, pest and disease control and any other operations to maintain a healthy robust tree.

- (vii) At the end of the twelve (12) month maintenance period, written acceptance of the tree/s must be obtained from the City before release of the public domain bond.
- (viii) If a tree fails to thrive and successfully establish during the maintenance period, then City will request payment for a replacement tree and establishment period according to the City's Schedule of Fees and Charges.

Reason

To ensure that details of street trees to be planted are approved, the works are carried out in an appropriate manner and the trees are maintained following installation.

(29) DESIGN FOR ENVIRONMENTAL PERFORMANCE

Prior to the issue of any Construction Certificate, the Registered Certifier must be satisfied that those matters listed in the following sections of the approved Design for Environmental Performance report prepared by K Turvey, Dated 7 March 2024, are incorporated into the relevant construction plans and accompanying documentation:

- (i) Section 4 – Energy Efficiency and Greenhouse Gas Emissions Abatement
- (ii) Section 5 – Passive Design for Thermal Performance – Building Envelope Design
- (iii) Section 6 – On site Renewable Energy Generation and Storage
- (iv) Section 7 – Design for Resilience to Climate Change
- (v) Section 8 – Designing for mains potable water savings and water efficiency
- (vi) Section 9 – Storm water quality
- (vii) Section 10 – City Greening
- (viii) Section 11 – Promoting Active Transport and Reducing Transport Emissions
- (ix) Section 12 – Materials, Embodied Carbon and Circularity
- (x) Section 13 – Waste Management and Resource Recovery
- (xi) Section 14 – Third Party Certification and Design, Construction or Technology Innovations

Reason

To ensure the environmental performance of the development.

(30) PUBLIC DOMAIN DAMAGE BOND

- (a) A Public Domain Damage Deposit calculated on the basis of 100 square metres of granite, 50 square metres of asphalt and 25 square metres of concrete site frontage must be lodged with Council in accordance with the City of Sydney's adopted Schedule of Fees and Charges. The bond must be provided as security for repairing any damage to the public domain in the vicinity of the site.
- (b) The City's Public Domain Unit must be contacted to determine the bond amount prior to lodgement. The Bond must be lodged with the City prior to an approval for demolition being granted or any Construction Certificate being issued, whichever is earlier.
- (c) The bond in this condition will be released in full when the Public Domain Works Security Bond is lodged with the City.

Reason

To allow for the appropriate management and rectification of damage to the public domain.

(31) PROTECTION OF STONE KERBS

- (a) The existing stone kerbs on the [Street Name/s] frontage[s] of the site are to be retained and properly protected during demolition, excavation and construction works.
- (b) To avoid damage to stone kerbs during excavation and construction works for the development, temporary removal and storage of the stone kerbs may be approved by Council. Removed, serviceable stone kerbs (i.e. those that are in good condition as agreed by Council officers) must be re-installed in accordance with the City of Sydney's standard details and specifications after the construction works have been completed. A temporary concrete kerb will need to be constructed to retain the footpath until the stone kerbs can be reinstalled.
- (c) Note the following:
 - (i) all costs associated with the works are to be borne by the developer.
 - (ii) Damaged kerbs are to be replaced to match existing to Council's satisfaction or as otherwise advised by Council officers.
 - (iii) Where new vehicle crossings or temporary crossings are to be constructed to access the property, the affected kerb stones should be salvaged and reused wherever possible.
 - (iv) All new driveway laybacks and kerbs are to be constructed with stone kerbs to match existing stones or as specified by City officers.
 - (v) Council approval is required before kerbs are removed.

- (vi) Council approval is required prior to the cutting of existing stone kerbs for stormwater kerb outlets.
- (vii) Stone kerbs and gutters may be bonded in accordance with the City of Sydney's adopted Schedule of Fees and Charges. If so, this will be included with the Public Domain Damage Bond.

Reason

To ensure the protection of stone kerbs.

(32) SURVEY INFRASTRUCTURE – IDENTIFICATION AND RECOVERY

Under Section 24 of the Surveying and Spatial Information Act 2002, it is an offence to remove, damage, destroy, displace, obliterate or deface any survey mark unless authorised to do so by the Surveyor-General. Accordingly, the applicant must, where possible, ensure the preservation of existing survey infrastructure undisturbed and in its original state or else provide evidence of the Surveyor-General's authorisation to remove or replace marks.

Prior to the issue of any Construction Certificate, documentary evidence must be prepared by a Registered Surveyor and submitted to and approved by Council's Area Planning Manager / Coordinator. This evidence must include either:

- (a) A copy of any Surveyor-General's Approval for Survey Mark Removal granted by NSW Spatial Services for the subject site, including all documentation submitted as part of that application (for example the survey mark audit schedule, strategy plan and strategy report); or
- (b) A letter, signed by a current NSW Registered Land Surveyor and including his or her Board of Surveying and Spatial Information (BOSSI) identification number, stating that all investigations required under Surveyor-General's Direction No.11 have been made for the subject site and that no survey infrastructure will be affected by the proposal.

Council's Principal Surveyor may request further information and/or add conditions to any Surveyor-General's Approval at their discretion.

Reason

To ensure the preservation of existing survey infrastructure.

(33) PUBLIC DOMAIN LEVELS AND GRADIENTS - MAJOR

Prior to the issue of any Construction Certificate, a Public Domain Levels and Gradients submission for the building and site frontages must be submitted to and approved by the City's Public Domain Unit. The submission must be prepared in accordance with the City's *Public Domain Manual* and submitted with a completed Application for *Public Domain Levels and Gradients*. Information on how to complete the submission can be downloaded from the City's website at <https://www.cityofsydney.nsw.gov.au/development/public-domain-works/da-associated-works>.

Any requirements to comply with Disability Discrimination Act at the entrance to a building or publicly accessible space must be resolved inside the site boundary.

Note: Public Domain Levels and Gradient plans are to be included with the Public Domain Plan – Detailed Documentation for Construction condition submission.

Reason

To ensure public domain levels and gradients comply with Council's requirements.

(34) STORMWATER DRAINAGE DESIGN

Prior to issue of any Construction Certificate a detailed stormwater management plan prepared by suitable qualified and experienced professional must be submitted to and approved by the City's Public Domain Unit and must include:

- (i) Council's Sydney Streets Technical Specifications, Part A4 Drainage Design;
- (ii) Council's Sydney Streets Technical Specifications, Standard Drawings;
- (iii) Council's Sydney Streets Technical Specifications, Part B10: Stormwater Drainage Construction;
- (iv) Council's Stormwater Drainage Manual; and
- (v) All relevant Australian Standards.

This information is available for download from the City's website at <https://www.cityofsydney.nsw.gov.au/development/public-domain-works/da-associated-works>.

Note: A Deed of Agreement (Stormwater Deed) for all proposed connections to the City's drainage system, and a Positive Covenant for all OSD systems may be required prior to issue of any Occupation Certificate.

Reason

To ensure stormwater drainage design complies with Council's requirements.

(35) STORMWATER ON-SITE DETENTION

The requirements of Sydney Water with regard to the on-site detention (OSD) of stormwater must be ascertained and complied with. Evidence of the approval must be submitted to Council prior to issue of any Construction Certificate other than demolition.

Where an OSD is not required by Sydney Water one may still be required by the City.

Reason

To ensure the requirements of Sydney Water are complied with.

(36) STORMWATER QUALITY ASSESSMENT

The development must comply with MUSIC-Link report 263-279 Broadway dated 3 May 2024 approved with this development application.

Prior to issue of any Construction Certificate a design certification report prepared by a suitably qualified practitioner engineer (NPER) demonstrating compliance with approved music link targets and parameters must be submitted to and approved by the City's Public Domain Unit.

The report must include a response to all stormwater quality improvement devices structural integrity, treatment train and their treatment properties demonstrating compliance with the approved MUSIC link reports.

Reason

To ensure appropriate stormwater quality on the site.

(37) FLOOD PLANNING LEVELS

The development must be constructed to comply with the recommended flood planning levels indicated in Table 2 of the report titled 'Flood Risk Assessment 263-279 Broadway, Glebe' prepared by Stellen dated 23 August 2024.

Details must be submitted to the Registered Certifier prior to the issue of any Construction Certificate demonstrating that the development will comply with the recommended flood planning levels.

Reason

To ensure the development complies with the recommended flood planning levels.

(38) PUBLIC DOMAIN LIGHTING UPGRADE

Prior to issue of any Construction Certificate for excavation, civil construction, drainage or building work (whichever is earlier), a concept Public Domain Lighting Upgrade Plan for pedestrian and street lighting in the public domain must be submitted to and approved by City's Public Domain Unit. The Lighting Plan must be prepared in accordance with the *Sydney Streets Technical Specifications A5 and B8*, *Sydney Lights Design Code* and *Public Domain Manual*. This information is available for download from the City's website at <https://www.cityofsydney.nsw.gov.au/development/public-domain-works/da-associated-works>.

The lighting upgrade plan must cover all adjacent street frontages, being Broadway, Glebe Point Road and Grose Street and shall be designed to include the following requirements.

Broadway (Along development site up to Ausgrid light pole #LE04504):

- Provide lighting design/simulation for existing lighting levels achieved on the roadway and footpath. Design should be based on removal of the Ausgrid pole #LE04503.
- Remove Ausgrid lighting asset #LE04503
- If required supply and install a new COS smartpole. Match existing Smartpoles in the vicinity.

Notes:

- Lighting designs must be certified by a suitably qualified practising lighting engineer and must consist of two parts: illumination design and electrical supply reticulation design. COS can only review electrical reticulation design once receiving final illumination designs.
- Lighting design submission requirements are specified in "Sydney Streets Technical Specifications A5: Street Lighting Design". Notes:
 - Plans should show calculation points as per Australian Standards.
 - Calculation plot scale should not be smaller than 1:250 @ A1
 - Provide a Calculation Summary table showing all relevant light technical parameters and compliance, including Maximum lux levels
 - Highlight all areas of noncompliance
- If applicable, Developers must submit site-specific structural footing designs certified by a practising structural engineer for council review before footing construction.
- If applicable, Provide temporary lighting complying with COS public domain lighting specifications prior to removal of existing public lights – if applicable.
- If applicable, Undertake ASP works required to modify and remove redundant Ausgrid assets and carry out all electrical/civil works to ensure continuity of supply to the remainder of Ausgrid assets on the affected circuits.
- Proposals for Building exterior lighting, signage lighting, terrace lighting and lighting of landscape features are to be assessed under a separate DA.
- If applicable, under awning lighting must comply with the requirements of COS Awnings Policy using LED luminaires.
- All relevant engineering design plans (incl electrical and lighting), design certificates, As-Built plans, WAE plans, and construction certificates must be submitted for COS review.
- All works shall comply with the requirements of all applicable standards and guidelines, including (but not limited to) AS1158, AS4282, and the City of Sydney's A5, B8 and Ausgrid NS119 documents.
- All new COS lights must be connected to COS's nearest metered supply point (subject to suitability assessment by Developer's electrical contractor). Otherwise, if required, supply and install a new COS 3 phase MSB.

Advice on site specific lighting requirements must be obtained from City's Public Domain Unit before proceeding with the preparation of any final lighting design proposals.

Reason

To ensure pedestrian and street lighting in the public domain complies with Council's requirements.

(39) DILAPIDATION REPORT - PUBLIC DOMAIN

Prior to an approval for demolition and preparatory works being granted or the issue of any Construction Certificate, whichever is earlier, a photographic recording of the public domain site frontages is to be prepared as described in the Public Domain Manual and submitted for approval by Council's Public Domain Unit. The City's *Public Domain Manual* is available for download from the City's website at <https://www.cityofsydney.nsw.gov.au/>

The submission is to include written confirmation, issued with the authority of both the applicant and the photographer that the City of Sydney is granted a perpetual non-exclusive license to make use of the copyright in all images supplied, including the right to make copies available to third parties as though they were Council images. The signatures of both the applicant and the photographer must be included.

Reason

To establish and document the condition of the public domain for comparison as building work progresses and is completed.

(40) TEMPORARY DEWATERING DURING CONSTRUCTION

Prior to discharging any water collected during excavation and construction into the City's stormwater drainage system, approval must be sought from the City's Public Domain Unit. A dewatering management plan must be submitted with an *Application for Temporary Dewatering* available to download on the City's website.

Other options for dewatering include disposal to sewer with prior approval from Sydney Water, or off-site disposal by a liquid waste transporter for treatment/disposal to an appropriate waste treatment/processing facility.

Reason

To ensure dewatering is managed appropriately.

(41) WASTE AND RECYCLING MANAGEMENT

The Operational Waste Management Plan dated July 2024 (Trim ref: 2024/402548) accompanying the Development Application has been approved by this consent responsive to architectural plans v9 and dated 12 July 2024. Should the architectural plans be updated, an updated Operational Waste Management Plan is to be submitted to Council's City Cleansing & Resource Recovery Unit and approved by Council's Area Planning Manager prior to the issue of a **Construction Certificate**.

Reason

To document agreed waste management facilities and arrangements and ensure good waste management outcomes.

(42) WASTE INFRASTRUCTURE – RESIDENTIAL

Prior to the issue of **Construction Certificate**, detailed plans, and specifications for the construction of waste management facilities must be submitted for review by Council's City Cleansing & Resource Recovery Unit and approved by Council's Area Planning Manager. The waste management facilities to be provided responsive to Council's controls, policies, and guidelines, including but not limited to:

- (a) Waste and recycling stream(s) storage area(s) to be designed and constructed in accordance with Reference D of *Council's Guidelines for Waste Management in New Developments*. Floors to be waterproofed across all intersections that extend a minimum 1200mm high on the walls.
- (b) Waste chute system to be designed in accordance with Section B and Reference E of the City of Sydney Guidelines for Waste Management in New Developments.
- (c) Integrated on-site waste collection and loading infrastructure to accommodate Councils standard 10.6m waste collection vehicle.

Reason

To allow for the safe and hygienic storage of waste and recycling and support provision of a safe and efficient waste collection service.

BEFORE BUILDING WORK COMMENCES

(43) PUBLIC DOMAIN WORK – CONSTRUCTION APPROVAL UNDER SECTION 138 ROADS ACT 1993

Prior to the construction of any public domain works, approval under Section 138 / 139 of the Roads Act 1993 must be issued by the City's Public Domain Unit.

Reason

To ensure relevant approvals for public domain work are obtained.

DURING BUILDING WORK

(44) COMPLIANCE WITH DEMOLITION, EXCAVATION & CONSTRUCTION NOISE AND VIBRATION MANAGEMENT PLAN

- (a) All works conducted on site which form part of this development must be carried out in accordance with the approved Demolition, Excavation and Construction Management Plan.
- (b) Where all such control measures have been implemented and the resultant noise and/ or vibration levels at any sensitive receiver still exceed the council's applicable criteria stated in the Construction Hours/Noise Code 1992 and are giving rise to sustained complaints then the contractor must provide regular, appropriate and sustained periods of respite in consultation with Council's Health and Building unit. Approval to vary the authorised noise and vibration levels must be received in writing by the proponent from Council prior to activities being undertaken that exceed sanctioned emission levels. (Use where respite periods not specified under the approved DEC NMP)

Such periods must be set and agreed to by Council's Health and Building Unit.

Reason

To ensure all parties are aware of the supporting documentation that applies to the development.

(45) FLASHINGS TO BOUNDARY WALLS

A flashing must be provided to prevent water entering between the proposed and existing external boundary walls of the adjoining properties.

Note: Attachments or connections to party walls may require the consent of the adjoining property owner/s.

Reason

To prevent water entering between the walls of adjoining properties.

(46) PUBLIC DOMAIN WORKS SECURITY BOND

A Public Domain Works Security Bond will be required for the public domain works and for repairing damage that may be caused to the public domain in the vicinity of the site, in accordance with the City of Sydney's adopted fees and charges and the Public Domain Manual.

The City's Public Domain Unit must be contacted to determine the bond amount prior to lodgement. The bond must be lodged with the City prior to an approval being issued for the approval of the Public Domain Plan.

The bond will be retained in full until all public domain works, including rectification of damage to the public domain, are completed to City's standards and approval and the required works-as-executed documentation are approved. On satisfying the above requirements, and the issue of the Public Domain Works Letter of Completion Operational Acceptance by the City, 90% of the bond will be released. The remaining 10% will be retained for the duration of the specified Defects Liability Period.

Reason

To ensure public domain works are completed and any damage to the public domain is rectified.

(47) PUBLIC DOMAIN PLAN DETAILED DOCUMENTATION FOR CONSTRUCTION

A detailed public domain plan and all relevant documentation must be submitted to and approved by City's Public Domain Unit prior to the construction of any public domain works. This Plan must document all works required to ensure that the public domain upgrade work complies with the City's specifications and requirements, as outlined in documents such as City of Sydney's *Public Domain Manual*, *Sydney Streets Code*, *Sydney Street Tree Masterplan*, *Sydney Lights: Public Domain Design Code* and *Sydney Streets Technical Specification*. The documentation must be *checked, accurate, and comply with specified requirements*. Plans must be based on an accurate survey, to scale and fully coordinated across all disciplines and submissions. The supplied documentation must be for Construction issue and will be approved under Section 138 of the Roads Act.

The Public Domain Manual and all other relevant documents are available for download from Council's website at <https://www.cityofsydney.nsw.gov.au/development/public-domain-works/detailed-works>.

The Public Domain Plan documentation must be submitted with an Application for Public Domain Plan Assessment and include the approved Public Domain Levels and Gradients documentation. If the proposed detailed design of the public domain requires changes to any previously approved levels, details must be submitted for approval with the public domain plan and additional fees may apply.

Reason

To ensure the public domain complies with Council's requirements.

(48) HOLD POINTS

Prior to an approval being issued for the construction of public domain and / or planning agreement works, including civil, drainage and subsurface works, a set of hold points will be provided by the City's Public Domain Unit in accordance with the City's Public Domain Manual and Sydney Streets Technical Specification. The list of hold point inspections will be included in the Public Domain works approval letter.

These hold point inspections must be adhered to during construction works. Prior to the issue of any Occupation Certificate, confirmation from the City's Public Domain Unit, that hold point inspections have been completed and works have been accepted by the City must be provided to the Principal Certifier.

Reason

To ensure hold points are adhered to during construction works.

(49) STORMWATER DRAINAGE CONNECTION

For approval of a connection into the City of Sydney's drainage system an "*Application for Approval of Stormwater Drainage Connections*" must be submitted to the City, together with an application fee in accordance with the City of Sydney's adopted Schedule of Fees and Charges. This must be approved prior to approval being issued for the construction of public domain work.

Reason

To ensure approval of connection into the Council's drainage system is sought.

(50) PUBLIC DOMAIN LIGHTING RETICULATION

Prior to the issue of any relevant approval for the construction of public domain works, a detailed Public Domain Lighting Reticulation Plan for pedestrian and street lighting in the public domain must be submitted to and approved by the City's Public Domain Unit in accordance with the City's *Sydney Lights Design Code*, *Sydney Streets Code*, *Sydney Streets Technical Specification* and *Public Domain Manual*.

The Public Domain Manual and all other relevant documents are available for download from Council's website at <https://www.cityofsydney.nsw.gov.au/development/public-domain-works/da-associated-works>.

If applicable, this public domain lighting documentation must include pole footing locations and structural details, location and details of underground electrical reticulation including connections and conduits, pit cabling and certifications as described in the City's *Public Domain Manual*. The public domain lighting is to be superimposed on the public domain plan to show any conflicts between lighting and the proposed landscape design.

Reason

To ensure the public domain lighting documentation complies with Council requirements.

(51) HOURS OF WORK AND NOISE – OUTSIDE CBD

The hours of construction and work on the development must be as follows:

- (a) All work, including building/demolition and excavation work, and activities in the vicinity of the site generating noise associated with preparation for the commencement of work (eg. loading and unloading of goods, transferring of tools etc) in connection with the proposed development must only be carried out between the hours of 7.30am and 5.30pm on Mondays to Fridays, inclusive, and 7.30am and 3.30pm on Saturdays, with safety inspections being permitted at 7.00am on work days, and no work must be carried out on Sundays or public holidays.
- (b) All work, including demolition, excavation and building work must comply with the City of Sydney Code of Practice for Construction Hours/Noise 1992 and Australian Standard 2436 - 2010 Guide to Noise Control on Construction, Maintenance and Demolition Sites.
- (c) Notwithstanding the above, the use of a crane for special operations, including the delivery of materials, hoisting of plant and equipment and erection and dismantling of on-site tower cranes which warrant the on-street use of mobile cranes outside of above hours can occur, subject to a separate application being submitted to and approved by Council under Section 68 of the Local Government Act 1993 and Sections 138/139 of the Roads Act 1993.

Note: Works may be undertaken outside of hours, where it is required to avoid the loss of life, damage to property, to prevent environmental harm and/or to avoid structural damage to the building. Written approval must be given by the Construction Regulation Team, prior to works proceeding.

The *City of Sydney Code of Practice for Construction Hours/Noise 1992* allows extended working hours subject to the approval of an application in accordance with the Code and under Section 4.55 of the *Environmental Planning and Assessment Act 1979*.

Reason

To protect the amenity of the surrounding area.

(52) USE OF HIGH NOISE EMISSION APPLIANCES / PLANT

- (a) The operation of high noise emission appliances, plant and/or machinery such as pile – drivers, rock breakers and hydraulic hammers and those which are not listed in Groups B, C, D, E or F of Schedule 1 of the *City of Sydney Code of Practice for Construction Hours/Noise 1992* and Australian Standard 2436-2010 *Guide to Noise Control on Construction, Maintenance and Demolition Sites* is restricted to the hours of (EHO to specify hours)
- (b) All reasonable and feasible steps must be undertaken to ensure that the work, including demolition, excavation and building complies with the *City of Sydney Code of Practice for Construction Hours/Noise 1992* and Australian Standard 2436- 2010 *Guide to Noise Control on Construction, Maintenance and Demolition Sites*.

Reason

To protect the amenity of the surrounding area.

(53) LIGHTING OF SITE OUTSIDE OF STANDARD CONSTRUCTION HOURS

Lighting of the site while any work is undertaken outside of Council's standard hours of construction must ensure that at no time must the intensity, hours of illumination or location of the lighting cause objectionable glare or injury to the amenity of the neighbourhood or Obtrusive Light in accordance with the definition in Australian Standard AS4282-1997 *Control of the obtrusive effects of outdoor lighting*. If in the opinion of Council, injury is likely to be caused, the intensity, hours of illumination and location of the lighting must be varied so that it does not cause injury to nearby residents.

Reason

To protect the amenity of the surrounding area.

(54) NOTIFICATION OF EXCAVATION WORKS OR USE OF HIGH NOISE EMISSION APPLIANCES/PLANT

The immediately adjoining neighbours must be given a minimum of 48 hours notice that excavation, shoring or underpinning works or use of high noise emission appliances / plant are about to commence.

Reason

To protect the amenity of the surrounding area.

(55) LOADING AND UNLOADING DURING CONSTRUCTION

The following requirements apply:

- (a) All loading and unloading associated with construction activity must be accommodated on site, where possible.
- (b) If, it is not feasible for loading and unloading to take place on site, a Works Zone on the street may be considered by Council.
- (c) A Works Zone may be required if loading and unloading is not possible on site. If a Works Zone is warranted an application must be made to Council at least 8 weeks prior to commencement of work on the site. An approval for a Works Zone may be given for a specific period and certain hours of the days to meet the particular need for the site for such facilities at various stages of construction. The approval will be reviewed periodically for any adjustment necessitated by the progress of the construction activities.
- (d) Where hoisting activity over the public place is proposed to be undertaken including hoisting from a Works Zone, a separate application under Section 68 of the Local Government Act 1993 and Sections 138/139 of the Roads Act 1993 must be submitted to and approved by Council.

Reason

To protect the amenity of the public domain.

(56) NO OBSTRUCTION OF PUBLIC WAY

Unless otherwise approved by Council, the public way must not be obstructed by any materials, vehicles, waste receptacles, skip-bins or the like. Non-compliance with this requirement may result in the issue of a notice by Council to stop all work on the site.

Reason

To protect the amenity of the public domain.

(57) SURVEY SETOUT PRIOR TO COMMENCEMENT

- (a) All footings, walls and floor slabs adjacent to a boundary must be set out by a registered surveyor.
- (b) On commencement of brickwork or wall construction a survey and report, prepared by a Registered Surveyor, must be submitted to the Principal Certifier indicating the position of the new components of the external walls in relation to the boundaries of the allotment. Any encroachments by the subject building over adjoining boundaries or roads must be removed prior to continuation of building construction work.

Reason

To ensure the development does not encroach onto neighbouring properties.

(58) SYDNEY WATER CERTIFICATE

A Section 73 Compliance Certificate under the Sydney Water Act 1994 must be obtained from Sydney Water Corporation.

Application must be made through an authorised Water Servicing Coordinator. Please refer to the Building Developing and Plumbing section on the web site www.sydneywater.com.au then refer to "Water Servicing Coordinator" under "Developing Your Land" or telephone 13 20 92 for assistance.

Following application a "Notice of Requirements" will advise of water and sewer infrastructure to be built and charges to be paid. Please make early contact with the Coordinator, since building of water/sewer infrastructure can be time consuming and may impact on other services and building, driveway or landscape design.

The Section 73 Certificate must be submitted to Council or the Principal Certifier prior to any Occupation Certificate or subdivision/strata certificate being issued.

Reason

To ensure the requirements of Sydney Water are met.

BEFORE ISSUE OF AN OCCUPATION CERTIFICATE

(59) PHYSICAL MODELS

- (a) Prior to the issue of any Occupation Certificate an accurate 1:500 scale model of the development as constructed must be submitted to and approved by Council's Area Coordinator Planning Assessments/Area Planning Manager for the City Model in Town Hall House.

Note:

- (i) The models must be constructed in accordance with the Model Specifications available online at <http://www.cityofsydney.nsw.gov.au/development/application-guide/application-process/model-requirements> Council's modellers must be consulted prior to construction of the model.
- (ii) The models are to comply with all of the conditions of the Development Consent.
- (iii) The models must be amended to reflect any further modifications to the approval (under Section 4.55 of the *Environmental Planning and Assessment Act*) that affect the external appearance of the building.

Reason

To ensure the provision of an appropriate physical model of the development.

(60) SUBMISSION OF ELECTRONIC CAD MODELS PRIOR TO OCCUPATION CERTIFICATE

- (a) Prior to any Occupation Certificate being issued, an accurate 1:1 electronic CAD model of the completed development must be submitted to and approved by Council's Area Coordinator Planning Assessments/Area Planning Manager for the electronic Visualisation City Model.
- (b) The data required to be submitted within the surveyed location must include and identify:
- (i) building design above and below ground in accordance with the development consent;
- (ii) all underground services and utilities, underground structures and basements, known archaeological structures and artefacts;
- (iii) a current two points on the site boundary clearly marked to show their Northing and Easting MGA (Map Grid of Australia) coordinates, which must be based on Established Marks registered in the Department of Lands and Property Information's SCIMS Database with a Horizontal Position Equal to or better than Class C.

The data is to be submitted as a DGN or DWG file on a Compact Disc. All modelling is to be referenced to the Map Grid of Australia (MGA) spatially located in the Initial Data Extraction file.

- (c) The electronic model must be constructed in accordance with the City's 3D CAD electronic model specification. The specification is available online at <http://www.cityofsydney.nsw.gov.au/development/application-guide/application-process/model-requirements> Council's Modelling staff should be consulted prior to creation of the model. The data is to comply with all of the conditions of the Development Consent.

Reason

To ensure the provision of an appropriate electronic model of the development.

(61) PLAN OF MANAGEMENT

An updated Plan of Management for the co-living use is to be submitted to and approved by Council's Area Coordinator Planning Assessments / Area Planning Manager prior to the issue of an Occupation Certificate for the site/use:

A copy of the plan is to be kept on site by the site manager.

Reason

To ensure an adequate plan of management is prepared for the approved use.

(62) WASTE AND RECYCLING COLLECTION CONTRACT - COMMERCIAL

Prior to the issue of an **Occupation Certificate** or commencement of the use, whichever is earlier, the building owner/tenant is to enter into a contract with a licensed waste service provider for the removal of all waste and recycling stream(s). A copy of the commercial waste and recycling contract and invoices are to be made available upon request by an authorised Council officer at any time.

Reason

To ensure arrangements are in place to manage commercial waste without reliance on public place or residential waste bins.

(63) WASTE AND RECYCLING MANAGEMENT – RESIDENTIAL

- (a) Prior to the issue of an **Occupation Certificate**, Council's review and written approval of the as-built waste infrastructure, facilities, and vehicle access is required. The City Cleansing & Resource Recovery Unit of Council must be satisfied that:
 - (i) All waste management facilities, storage, and collection infrastructure comply with the stamped plans, approved Operational Waste Management Plan and Council's *Guidelines for Waste Management in New Developments*, the City of Sydney's DCP, and the developments Conditions of Consent.

- (ii) All waste rooms, corridors, doors, and gates to be accessed by Council's collection contractor(s) are to be fitted and accessible via Council's master key system. Specifications of locks, barrels, and supporting infrastructure are to be submitted to Council's City Cleansing & Resource Recovery Unit.
- (b) Site inspections are to be conducted by Council's City Cleansing & Resource Recovery Unit to review the site on-site waste collection, storage and loading bay infrastructure prior to the issue of an **Occupation Certificate**. The inspections are to be conducted a minimum 6-months prior to projects anticipated construction completion. Prior to the inspection an electronic copy of the latest architectural plans are to be submitted.
- (c) An updated Operational Waste Management Plan is to be submitted to Council's City Cleansing & Resource Recovery Unit that aligns with the latest version of architectural plans and waste related updates identified during the site inspections. The plan is to be reviewed by Council's City Cleansing & Resource Recovery Unit and approved by Council's Area Planning Manager prior to the issue of an **Occupation Certificate**.
- (d) The developer is to enter into a formal agreement with the City of Sydney Council for the utilisation of Council's Waste Collection Service. A signed agreement is to be submitted to Council's City Cleansing & Resource Recovery unit prior to the issue of an **Occupation Certificate**.
- (e) The assigned strata manager for the development and direct contact details are to be provided to Council's City Cleansing & Resource Recovery Unit prior to the issue of an **Occupation Certificate**.

Reason

To ensure that facilities and arrangements are in place to enable the provision of a safe and efficient waste collection service responsive to Council's policies and contractual service provisions.

(64) WASTE AND RECYCLING MANAGEMENT - COMMERCIAL

Prior to the issue of an **Occupation Certificate**, the Principal Certifier is to ensure all waste management, collection, loading and supporting infrastructure is provided in accordance with the stamped plans, approved Operational Waste Management Plan and specifications approved at the Construction Certificate.

Reason

To ensure all on-site infrastructure has been provided to support scheduled collections responsive to the Council endorsed OWMP and requirements of the Guidelines for waste management in new developments 2018.

(65) PUBLIC DOMAIN WORKS COMPLETION

The Public Domain works are to be constructed in accordance with the Public Domain Works Approval letter, stamped plans for Public Domain Levels and Gradients, Stormwater, Public Domain Lighting, the City's *Public Domain Manual*, *Stormwater Drainage Manual*, *Sydney Lights Design Code* and *Sydney Streets Technical Specification*.

The public domain work must be inspected and a Public Domain Work Letter of Completion Operational Acceptance must be issued by Council's Public Domain Officer prior to the issue of any Occupation Certificate or before the commencement of use, whichever is earlier.

Reason

To ensure the public domain works are completed in accordance with the approved documents and Council's requirements.

(66) PUBLIC DOMAIN COMPLETION – WORK AS EXECUTED DOCUMENTATION

Prior to a Public Domain Works Letter of Completion Operational Acceptance being issued for public domain works, works-as-executed (As-Built) plans and documentation, must be submitted to and accepted by the City of Sydney for all public domain works, including where required Stormwater, Public Domain Lighting and road construction. These works must be certified by a suitably qualified, independent professional. Details of the documentation required for approval will be advised by the City's Public Domain Unit.

Reason

To ensure Council receives works-as-executed documentation for public domain works.

(67) STORMWATER COMPLETION DEED OF AGREEMENT AND POSITIVE COVENANT

Prior to the issue of any Occupation Certificate:

- (a) The Owner is required to enter into a Deed of Agreement (Stormwater Deed) with the City of Sydney and obtain registration of Title of a Positive Covenant for all proposed connections to the City's underground drainage system. The deed and positive covenant will contain terms reasonably required by the City and will be drafted by the City's Legal Services Unit at the cost of the applicant, in accordance with the City's Fees and Charges.
- (b) A Positive Covenant must be registered on the property title for all drainage systems involving On-Site Detention (OSD) to ensure maintenance of the approved OSD system regardless of the method of connection. The positive covenant will contain terms reasonably required by the City and will be drafted by the City's solicitor at the cost of the applicant, in accordance with the City's Fees and Charges.

Reason

To protect underground drainage system.

(68) SURVEY INFRASTRUCTURE – RESTORATION

- (a) Prior to any Occupation Certificate being issued for the development, documentary evidence of restoration must be prepared by a Registered Surveyor and submitted to and approved by Council's Area Planning Manager / Coordinator. This evidence must include:
- (i) Certification that all requirements requested under the Surveyor-General's Approval for Survey Mark Removal or by the City's Principal Surveyor under condition "Survey Infrastructure – Identification and Recovery" have been complied with;
 - (ii) Certification that all requirements requested under any Surveyor-General's Approval for Deferment of Survey Marks from condition "Survey Infrastructure – Pre Subdivision Certificate works" have been complied with and;
 - (iii) Time-stamped photographic records of all new survey infrastructure relating to the site clearly showing the mark itself and sufficient context to aid in identifying the mark on site.

Reason

To ensure all requirements for survey mark removal are complied with.

(69) CONSTRUCTED FLOOR LEVELS

A certification report prepared by a suitably qualified practitioner engineer (NPER) must be submitted to the Principal Certifier prior to issue of any Occupation certificate stating that the development has been constructed and the required levels achieved in accordance with the recommendations of the report titled Flood Risk Assessment 263279 Broadway, Glebe prepared by Stellen dated 23 August 2024.

Reason

To ensure the development achieves the required floor levels.

(70) FLOOD RISK MANAGEMENT

Prior to the issue of any Occupation Certificate, a certification report prepared by a suitably qualified practitioner engineer (NPER), for flood risk management measures including flood planning level/s demonstrating compliance with the approved construction plans must be submitted to and be approved by the Principal Certifier. A copy of the report must be provided to Council for record keeping purposes.

Reason

To ensure flood risk management measures are complied with.

(71) SURVEY CERTIFICATE PRIOR TO ISSUE OF OCCUPATION CERTIFICATE

A Survey Certificate prepared by a Registered Surveyor must be submitted to the Principal Certifier at the completion of the building work certifying the location of the building in relation to the boundaries of the allotment.

AT COMPLETION – Prior to the issue of any staged or Final Occupation Certificate for the building, a Final Identification Survey prepared and signed by a Surveyor registered under the *Surveying & Spatial Information Act, 2002* must be submitted at the completion of the building work certifying the location of the building and showing offsets in relation to the boundaries of the allotment. Any encroachments of the building including gutters and downpipes over the side boundaries or rear lane must be removed, or alternatively appropriate easements under Section 88B of the *Conveyancing Act, 1919*, with terms to the satisfaction of Council, must be lodged with the office of NSW Land Registry Services, and evidence of lodgement provided to the Principal Certifier prior to the issue of any type of Occupation Certificate. Encroachments upon public roads must, if supported, be approved by Council's Area Planning Manager prior to the issue of any type of Occupation Certificate.

Reason

To ensure the development does not encroach, or that any encroachments are formalised on title.

(72) REGISTRATION OF CONSOLIDATION PLAN

Prior to the issue of any type of Occupation Certificate, a Consolidation Plan must be registered with the office of NSW Land Registry Services

Reason

To ensure the existing lots are consolidated into one title.

OCCUPATION AND ONGOING USE

(73) OCCUPATION CERTIFICATE TO BE SUBMITTED

An Occupation Certificate must be obtained from the Principal Certifier and a copy submitted to Council prior to commencement of occupation or use of the whole or any part of a new building, an altered portion of, or an extension to an existing building.

Reason

To ensure the site is authorised for occupation.

(74) NOISE – STRUCTURE BORNE IMPACT ON SEPARATE RESIDENTIAL PREMISE

(a) Structure borne noise emanating from the premises is not to exceed the following criterion when measured within any separate residential accommodation:

(i) $L_{A1, \text{Slow 15 minute}} \leq L_{A90, \text{15 minute}} \text{ dB(A)}$.

Reason

To protect the acoustic amenity of surrounding properties.

(75) NOISE – STRUCTURE BORNE IMPACT ON SEPARATE COMMERCIAL PREMISE

(a) Structure borne noise emanating from the premises is not to exceed the following criterion when measured within any separate commercial premise:

(i) $L_{A1, \text{Slow 15 minute}} \leq L_{A90, \text{15 minute}} + 3 \text{ dB(A)}$.

Reason

To protect the acoustic amenity of surrounding properties.

(76) VIBRATION

Operation of the use is not to result in the transmission of any perceptible vibration to an occupiable area within a separate premises.

Reason

To protect the amenity of surrounding properties.

(77) NOISE - ENTERTAINMENT

(a) The $L_{Aeq, 15 \text{ minute}}$ noise level from the use must not exceed the background noise level ($L_{A90, 15 \text{ minute}}$) in any octave band (reference frequency 31.5 Hz to 8 kHz inclusive) by more than 5dB between 7.00am and 12.00 midnight when assessed at the boundary of any residential accommodation or tourist and visitor accommodation.

(b) The $L_{Aeq, 15 \text{ minute}}$ noise level from the use must not exceed the background noise level ($L_{A90, 15 \text{ minute}}$) in any octave band (reference frequency 31.5 Hz to 8 kHz inclusive) between 12.00 midnight and 7.00am when assessed at the boundary of any residential accommodation or tourist and visitor accommodation.

(c) Notwithstanding (a) above, the $L_{Aeq, 15 \text{ minute}}$ noise level from the use must not exceed the greater of the following levels between 7am and 12 midnight inside any habitable room of a residential accommodation or tourist and visitor accommodation, or at any time in an affected commercial premises:

- (i) The existing internal $L_{A90, 15 \text{ minute}}$ (from external sources excluding the use) in any octave band (reference frequency 31.5 Hz to 8 kHz inclusive). Or,
 - (ii) If the $L_{Z90, 15 \text{ minute}}$ background level is below the hearing threshold curve (Tf - Table 1 of ISO 226 : 2003) in an above octave band, the lowest audible sound level (L_p) of the Tf curve in that octave band shall become that octave's $L_{Zeq 15 \text{ minute}}$ noise criteria level.
- (d) Notwithstanding (b) above, the $L_{A1 15 \text{ minute}}$ noise level from the use must not exceed the greater of the following sound pressure levels inside any habitable room between 12 midnight and 7am inside any habitable room of an affected residential accommodation or tourist and visitor accommodation:
- (i) The existing internal $L_{A90, 15 \text{ minute}}$ (from external sources excluding the use) minus 10 dB in any octave band (reference frequency 31.5 Hz to 8 kHz inclusive) inside a habitable room of an affected residential accommodation or tourist and visitor accommodation. Or,
 - (ii) If the $L_{Z90, 15 \text{ minute}}$ minus 10 dB level is below the hearing threshold curve (Tf - Table 1 of ISO 226 : 2003) in an above octave band, the lowest audible sound level (L_p) of the Tf curve in that octave band shall become that octave's $L_{Z1 15 \text{ minute}}$ noise criteria level.

Note: L_{eq} , L_{01} , and L_{90} , metrics and 'A' (weightings) are as per the definitions in the standard AS1055-20148. 'Z' means unweighted noise. An internal L_{A90} level must be determined in the absence of noise emitted by the use and be sufficiently representative of the receiver in a low noise level quiet state. External L_{A90} levels for planning must be established as per the long-term methodology in Fact Sheet B of the NPfl unless otherwise agreed by the City's Area Planning Manager.

Reason

To protect the acoustic amenity of surrounding properties.

(78) NOISE – COMMERCIAL PLANT / INDUSTRIAL DEVELOPMENT

- (a) Noise from commercial plant and industrial development must not exceed a project amenity/intrusiveness noise level or maximum noise level in accordance with relevant requirements of the NSW EPA [Noise Policy for Industry 2017 \(NPfl\)](#) unless agreed to by the City's Area Planning Manager. Further:
 - (i) Background noise monitoring must be carried out in accordance with the long-term methodology in [Fact Sheet B](#) of the NPfl unless otherwise agreed by the City's Area Planning Manager.
 - (ii) Commercial plant is limited to heating, ventilation, air conditioning, refrigeration and energy generation equipment.

- (b) An $L_{Aeq,15 \text{ minute}}$ (noise level) emitted from the development must not exceed the $L_{A90, 15 \text{ minute}}$ (background noise level) by more than 3dB when assessed inside any habitable room of any affected residence or noise sensitive commercial premises at any time. Further:
 - (i) The noise level and the background noise level must both be measured with all external doors and windows of the affected residence closed.
 - (ii) Background noise measurements must not include noise from the development but may include noise from necessary ventilation at the affected premises.
- (c) Corrections in [Fact Sheet C](#) of the NPfI are applicable to relevant noise from the development measured in accordance with this condition, however duration corrections are excluded from commercial noise.

Reason

To protect the acoustic amenity of surrounding properties.

(79) HOURS OF OPERATION – OUTDOOR COMMON TERRACE AREAS

The outdoor common areas are to be used only between the hours of 7.00am to 10.00pm daily, and in accordance with the approved plan of management.

Reason

To protect acoustic amenity.

(80) THROUGH-SITE LINK

- (a) The pedestrian through-site link between Glebe Point Road to Grose Street is to be open for access to the public between the hours of 6.00am to 10.00pm Monday to Sunday.

(81) ON SITE LOADING AREAS AND OPERATION

All loading and unloading operations associated with servicing the site must be carried out within the confines of the site, at all times and must not obstruct other properties/units or the public way.

At all times the service vehicle docks, car parking spaces and access driveways must be kept clear of goods and must not be used for storage purposes, including garbage storage.

Reason

To maintain the orderly operation of vehicle parking areas and to ensure the public domain is kept free from physical obstructions.

(82) TRANSPORT ACCESS GUIDE

A Transport Access Guide must be implemented and maintained by the operators of the premises and be made available to staff, clients, customers and visitors at all times.

The following information shall be submitted to and approved by Council's Area Coordinator / Area Planning Manager prior to the issue of an Occupation Certificate for the site/use:

- (a) A Transport Access Guide detailing sustainable transport options to access the site including public transport, cycling and walking or a combination of these modes.
- (b) Communication methods by which the Transport Access Guide will be made available to staff, clients, customers and visitors.

Reason

To ensure that sustainable transport options are considered and communicated effectively.

(83) SIGNS AT EGRESS

The following signs must be provided and maintained within the site at the point(s) of vehicle egress:

- (a) Compelling drivers to stop before proceeding onto the public way
- (b) Compelling drivers to "Give Way to Pedestrians" before crossing the footway; or compelling drivers to "Give Way to Pedestrians and Bicycles" before crossing a footway on an existing or identified shared path route.

Reason

To ensure the safety of surrounding pedestrians and cyclists.

(84) LOADING DOCK MANAGEMENT PLAN

A Loading Dock Management Plan is to be prepared for distribution to relevant tenants outlining how the loading dock will be managed and used by all relevant tenants. The Plan must include, but is not limited to, management of deliveries to ensure vehicles are not waiting on public streets to enter the site.

The Plan is to include that unimpeded access will be provided for residential collection vehicles to set down within 10 metres of waste storage areas between 6am and 6pm on collection day(s).

The plan is to be prepared and submitted to and approved by Council's Area Coordinator / Area Planning Manager prior to issue of an Occupation Certificate.

Once approved, this management plan is to be provided to all relevant tenants and external users of the loading area.

Reason

To ensure that the loading dock is appropriately managed.

(85) ONGOING WASTE MANAGEMENT – RESIDENTIAL

- (a) The ongoing use of development must be in accordance with the approved Operational Waste Management Plan, Council's *Guidelines for Waste Management in New Developments*, the City of Sydney's DCP, and the developments Conditions of Consent.
- (b) All general waste and recycling stream(s) materials emanating from the premises must be stored in the designated waste storage area(s) integrated within the built form and must not be stored outside the premises (including any public place) at any time.
- (c) The property manager is responsible for lodging requests for damaged/broken bins, managing the rotation of bins, ensuring the full allocation of relevant bins are available for scheduled collections, management of odour and the routine cleaning and maintenance of all waste storage areas.
- (d) Contracts (or agreements) with cleaners, building managers and tenants must clearly outline the waste management and collection arrangements, identifying clear roles and responsibilities outlined within the approved Operational Waste Management Plan.
- (e) The property manager is responsible for the installation and maintenance of all education signage for the respective waste stream(s) as requested by the City of Sydney Council responsive to the approved Operational Waste Management plan.
- (f) Commercial waste and recycling stream(s) and supporting infrastructure to be stored in a separate lockable, enclosed, and walled area free from the residential waste and recycling stream(s) rooms. The residential rooms to have relevant locks to inhibit commercial tenants access to Councils residential waste streams.

Reason

To support the safe and efficient scheduled Council waste collection service and ensure the impacts of waste management on the public domain and public health are minimised.

(86) SCHEDULED COLLECTIONS - RESIDENTIAL

- (a) Scheduled collections and waste management arrangements of Council's residential waste stream(s) is to be conducted in accordance with the stamped plans, approved Operational Waste Management Plan, the developments Conditions of Consent and the City's Local Approvals Policy Managing Waste in Public Spaces.
- (b) Council's Domestic Waste Charge is applied to all residential rate accommodation properties in accordance with section 496 of the *Local Government Act 1993*. Residential accommodation is defined in accordance with the *Sydney Local Environmental Plan 2012* dictionary.

- (c) Unobstructed access to be provided for Councils standard waste collection vehicles to access the waste and recycling storage area(s), loadings bays and supporting infrastructure between the hours 6am and 6pm on collection day(s) to support the provision of a safe and efficient waste collection service to the site.

Reason

To support the safe and efficient scheduled residential waste collection service and minimise the impacts on public amenity and safety.

(87) DEFECTS LIABILITY PERIOD – PUBLIC DOMAIN WORKS

All works to the City's public domain, including rectification of identified defects, are subject to a 6 month defects liability period from the date of Completion. The date of Completion will be nominated by Council on the Public Domain Works – Letter of Completion Operational Acceptance.

Reason

To ensure all works to the City's public domain are protected under a liability period.

(88) ENCROACHMENTS – PUBLIC WAY

No portion of the proposed structure, including gates and doors during opening and closing operations, shall encroach upon Council's footpath area.

Reason

To protect the public way.

DEMOLITION WORK

BEFORE DEMOLITION WORK COMMENCES

(89) DILAPIDATION REPORT – MAJOR EXCAVATION/DEMOLITION

- (a) Subject to the receipt of permission of the affected landowner, dilapidation report/s, including a photographic survey of adjoining properties (and any other properties identified by the qualified structural engineer engaged to undertake the report) are to be prepared by an appropriately qualified structural engineer prior to commencement of demolition/excavation works. A copy of the dilapidation report/s together with the accompanying photographs must be given to the above property owners, and a copy lodged with the Registered Certifier and the Council prior to the issue of a Construction Certificate.

UPON COMPLETION OF EXCAVATION/DEMOLITION

- (b) A second Dilapidation Report/s, including a photographic survey must then be submitted at least one month after the completion of demolition/excavation works. A copy of the second dilapidation report/s, together with the accompanying photographs must be given to the above property owners, and a copy lodged with the Principal Certifier and the Council prior to the issue of any Occupation Certificate.

Any damage to buildings, structures, lawns, trees, sheds, gardens and the like must be fully rectified by the applicant or owner, at no cost to the affected property owner.

Note: Prior to the commencement of the building surveys, the applicant/owner must advise (in writing) all property owners of buildings to be surveyed of what the survey will entail and of the process for making a claim regarding property damage. A copy of this information must be submitted to Council.

Reason

To ensure that dilapidation reports are prepared and to identify damage to adjoining/nearby properties resulting from building work on the development site.

(90) DISPOSAL OF SURPLUS SALVAGED MATERIALS

Salvaged traditional building materials surplus to the requirements of this project including brickwork, joinery such as the remnant sections of timber flooring with herringbone bracing and the open string timber stair, metal framed windows and expressed timber trusses in 263 Broadway are to be sold to an established dealer in second-hand heritage building materials. Documentation of the salvage methodology must be submitted for the approval of Council's Area Coordinator / Area Planning Manager prior to the commencement of demolition.

Reason

To ensure the salvaging and reuse of traditional building materials.

(91) HERITAGE INDUCTION

A Heritage Induction is to be prepared by a suitably qualified archaeologist prior to works starting. All personnel on site are to undergo a heritage induction at the time of their onsite induction prior to commencing on site so that they are aware of the potential archaeological resources on site and know what to do in the event that unexpected historic relics are exposed.

Reason

To ensure that all workers are aware of the potential archaeological resources on site and that an Unexpected Finds Procedure is followed in the event that unexpected historic relics are exposed.

(92) EROSION AND SEDIMENT CONTROL - BETWEEN 250 AND 2,500SQM

The Erosion and Sediment Control Plan accompanying this Development Application has not been approved by this consent.

Prior to the commencement of demolition/excavation/construction work, an Erosion and Sediment Control Plan (ESCP) must be submitted to and be approved by the Principal Certifier. The ESCP must:

- (a) Conform to the specifications and standards contained in *Managing Urban Stormwater: Soils and Construction* (Landcom, 2004); the *Guidelines for Erosion and Sediment Control on Building Sites* (City of Sydney, 2004); and the *NSW Protection of the Environment Operations Act 1997*.
- (b) Include a drawing(s) that clearly shows:
 - (i) location of site boundaries and adjoining roads
 - (ii) approximate grades and indications of direction(s) of fall
 - (iii) approximate location of trees and other vegetation, showing items for removal or retention
 - (iv) location of site access, proposed roads and other impervious areas
 - (v) existing and proposed drainage patterns with stormwater discharge points
 - (vi) north point and scale
- (c) Specify how soil conservation measures will be conducted on site including:
 - (i) timing of works
 - (ii) locations of lands where a protective ground cover will, as far as is practicable, be maintained

- (iii) access protection measures
- (iv) nature and extent of earthworks, including the amount of any cut and fill
- (v) where applicable, the diversion of runoff from upslope lands around the disturbed areas
- (vi) location of all soil and other material stockpiles including topsoil storage, protection and reuse methodology
- (vii) procedures by which stormwater is to be collected and treated prior to discharge including details of any proposed pollution control device(s)
- (viii) frequency and nature of any maintenance program
- (ix) other site-specific soil or water conservation structures.

Reason

To ensure that appropriate erosion and sediment control measures are put in place during construction to protect the environment.

(93) HAZARDOUS MATERIALS SURVEY REQUIRED

A Hazardous Materials Survey Report must be prepared by a certified Occupational Hygienist (*Australia Institute of Occupational Hygienists*) and submitted to the satisfaction of Council's Area Coordinator Planning Assessments / Area Planning Manager prior to any demolition / refurbishment work commencing at the site. The report must identify and record the type, location and extent of any hazardous materials on the site and make recommendations as to their safe management and/or removal to ensure the site is made safe for demolition, construction and future use/occupation.

Reason

To ensure that hazardous materials on the site are identified and appropriately managed.

(94) INSTALLATION OF ARTWORK AND IMAGES ON SCAFFOLDING (DEMOLITION / CONSTRUCTION WRAPS)

- (a) Where scaffolding is to be installed to undertake the proposed development an approved artwork / historic image installation must be provided on the scaffolding system to screen the development from the public place, minimise adverse visual impacts on the locality and add visual and public art in the streetscape.
- (b) The artwork installation must be printed, installed and maintained in accordance with Council's *Guidelines for Hoardings and Scaffolding*. Details of the proposed installation must be submitted to and approved by Council prior to the issue of a construction certificate or work commencing.

Note: The scaffolding system on which a required artwork wrap is to be installed must be designed to safely and adequately accommodate and support the wrap mesh material on which the artwork is printed/displayed. This includes designing the scaffold to address potential increased wind loads that may be encountered in the locality.

Reason

To minimise adverse visual impacts on the locality.

(95) DEMOLITION, EXCAVATION AND CONSTRUCTION NOISE AND VIBRATION MANAGEMENT PLAN

A site-specific demolition, excavation and construction noise and vibration management plan must be submitted to the Council for comment and approval prior to any demolition works commencing. The Plan must be prepared by a suitably qualified acoustic consultant who is a person who possesses the qualifications to join the Australian Acoustic Society, Institution of Engineers Australia (grade of member) or the Association of Australasian Acoustic Consultants (grade of member firm). The plan must include but not be limited to the following:-

- (a) identification of noise sensitive receivers near to the site.
- (b) A prediction as to the level of noise impact likely to affect the nearest noise sensitive receivers from the use and proposed number of high noise intrusive appliances intended to be operated onsite. A statement should also be submitted outlining whether or not predicted noise levels will comply with the noise criteria stated within the *City of Sydney Construction Hours /Noise Code of Practice 1992* for the typical construction hours of 07.00am to 7.00pm. Where resultant site noise levels are likely to be in exceedance of this noise criteria then a suitable proposal must be given as to the duration and frequency of respite periods that will be afforded to the occupiers of neighbouring property.
- (c) A representative background noise measurement ($L_{A90, 15 \text{ minute}}$) should be submitted, assessed in the vicinity of any potentially affected receiver locations and measured in accordance with AS 1055:1.2.1997.
- (d) Confirmation of the level of community consultation that has/is and will be undertaken with Building Managers/ occupiers of the main adjoining noise sensitive properties likely to be most affected by site works and the operation of plant/machinery particularly during the demolition and excavation phases.
- (e) Confirmation of noise monitoring methodology that is to be undertaken during the main stages of work at neighbouring noise sensitive properties in order to keep complaints to a minimum and to ensure that noise from site works complies with the noise criteria contained within City's Construction Noise Code.
- (f) What course of action will be undertaken following receipt of a complaint concerning offensive noise.

- (g) Details of any noise mitigation measures that have been outlined by an acoustic consultant or otherwise that will be deployed on site to reduce noise impacts on the occupiers of neighbouring noise sensitive property to a minimum.
- (h) What plant and equipment is to be used on site, the level of sound mitigation measures to be undertaken in each case and the criteria adopted in their selection taking into account the likely noise impacts on the occupiers of neighbouring property and other less intrusive technologies available.

Reason

To ensure an adequate construction noise and vibration management plan is prepared.

DURING DEMOLITION WORK

(96) COMPLIANCE WITH DEMOLITION, EXCAVATION & CONSTRUCTION NOISE AND VIBRATION MANAGEMENT PLAN

- (a) All works conducted on site which form part of this development must be carried out in accordance with the approved Demolition, Excavation and Construction Management Plan.
- (b) Where all such control measures have been implemented and the resultant noise and/ or vibration levels at any sensitive receiver still exceed the council's applicable criteria stated in the Construction Hours/Noise Code 1992 and are giving rise to sustained complaints then the contractor must provide regular, appropriate and sustained periods of respite in consultation with Council's Health and Building unit. Approval to vary the authorised noise and vibration levels must be received in writing by the proponent from Council prior to activities being undertaken that exceed sanctioned emission levels. (Use where respite periods not specified under the approved DEC NMP)

Such periods must be set and agreed to by Council's Health and Building Unit.

Reason

To ensure all parties are aware of the supporting documentation that applies to the development.

(97) UNEXPECTED FINDS PROCEDURE

- (a) Should any unexpected historic (non-Aboriginal) heritage finds be uncovered during the project works, the Unexpected Finds Procedure, prepared by AMBS Ecology & Heritage for Sovereign Construction Pty Ltd, dated December 2023 is to be followed. If an unexpected find is made, all works to the area must stop immediately, and the applicant's archaeologist contacted to make an initial assessment of the find. If a relic is found the Heritage Council of NSW should be informed in accordance with section 146 of the Heritage Act 1977. The Archaeologist is to provide written clearance before any works in the affected area can recommence.
- (b) Should any Aboriginal objects be unexpectedly discovered then all excavation or disturbance of the area is to stop immediately and NSW Government Office of Environment and Heritage is to be informed in accordance with Section 89A of the *National Parks and Wildlife Act 1974*.
- (c) Should any archaeological remains or Aboriginal objects be discovered, a copy of recording of the finds and the final archaeological summary report is to be submitted to Council prior to the issue of any Occupational Certificate.
- (d) If the discovery is on Council's land, Council must be informed.

Reason

To ensure that the archaeology of the site is appropriately managed and protected.

(98) ASBESTOS REMOVAL WORKS

- (a) All works removing asbestos containing materials must be carried out by a suitably licensed asbestos removalist duly licensed with Safework NSW, holding either a Friable (Class A) or a Non-Friable (Class B) Asbestos Removal Licence which ever applies.

A copy of the relevant licence must be made available to any authorised Council officer on request within 24 hours.

- (b) Five days prior to the commencement of licensed asbestos removal, Safework NSW must be formally notified of the works. All adjoining properties and those opposite the development must be notified in writing of the dates and times when asbestos removal is to be conducted. The notification must identify the licensed asbestos removal contractor and include a contact person for the site together with telephone number and email address.
- (c) All work must be carried out in accordance with the *Work Health and Safety Regulation 2017* and the NSW Government and SafeWork NSW document entitled *How to manage and control asbestos in the work place: Code of Practice (Safework NSW) December 2011* and the *City of Sydney Managing Asbestos Policy dated 21 October 2013 and associated guidelines*.
- (d) The asbestos removalist must use signs and barricades to clearly indicate the area where the asbestos removal work is being performed. Signs must be placed in positions so that people are aware of where the asbestos removal work area is and should remain in place until removal is completed and clearance to reoccupy has been granted. Responsibilities for the security and safety of the asbestos removal site and removal must be specified in the asbestos removal control plan (where required). This includes inaccessible areas that are likely to contain asbestos.
- (e) Warning signs must be placed so they inform all people nearby that asbestos removal work is taking place in the area. Signs must be placed at all of the main entry points to the asbestos removal work area where asbestos is present. These signs must be weatherproof, constructed of light-weight material and adequately secured so they remain in prominent locations. The signs must be in accordance with AS 1319 - 1994 *Safety Signs for the Occupational Environment* for size, illumination, location and maintenance.
- (f) Asbestos waste must only be transported and disposed of at an EPA licensed waste facility.
- (g) No asbestos products are to be reused on the site (i.e. packing pieces, spacers, formwork or fill etc).

- (h) No asbestos laden skips or bins are to be left in any public place without the written approval of Council.
- (i) A site notice board must be located at the main entrance to the site in a prominent position and must have minimum dimensions of 841mm x 594mm (A1) with any text on the notice to be a minimum of 30 point type size.

The site notice board must include the following:

- (i) contact person for the site;
- (ii) telephone and facsimile numbers and email address; and
- (iii) site activities and time frames.

Reason

To ensure that the handling and removal of asbestos from the site is appropriately managed.

(99) LAND CONTAMINATION – DETAILED ENVIRONMENTAL SITE INVESTIGATION / REMEDIATION ACTION PLAN

- (a) Prior to the demolition of the ground floor slab to the Grose Street level, a Detailed Environmental Site Contamination Investigation (DESI) must be undertaken. The investigation and reporting must be undertaken by a suitably qualified and experienced environmental consultant in accordance with relevant guidelines including, but not limited to, the EPA 'Guidelines for Consultants Reporting on Contaminated Sites 2014' (updated 2020) and 'Sampling Design Guidelines 2022'.
- (b) The DESI must be reviewed by a NSW EPA Site Auditor and a Section B Audit Statement, or a letter of Interim Advice must be provided that the DESI is appropriate for the purposes of assessing the site. The DESI report must consider and provide an indication of any remedial action required to ensure that the site will be suitable for the proposed development.
- (c) Following the completion of the Detailed Site Contamination Investigation, and where the DESI states that the site requires remediation to make it suitable for the proposed land use subject to this consent, a Remedial Action Plan (RAP) must be prepared by a suitably qualified and experienced environmental consultant, in accordance with the relevant 'Guidelines for Consultants Reporting on Contaminated Sites 2014'.
- (d) The RAP must set the remediation objectives and determine the most appropriate remedial strategy to ensure that the site will be suitable for the development.
- (e) The RAP must be submitted to the NSW EPA accredited site auditor for review and a Section B Audit Statement or a Letter of Interim Advice must be provided certifying that the RAP is practical and the site will be suitable after remediation for the proposed use.

- (f) The RAP must be submitted to the satisfaction of Council.
- (g) The site must be remediated in accordance with the RAP reviewed and approved by Council's Area Planning Manager and appointed NSW EPA Site Auditor.
- (h) All remediation work carried out shall be conducted in accordance with the guidelines in force from time to time under the *Contaminated Land Management Act 1997*.
- (i) Any new information which comes to light during remediation, demolition or construction works which has the potential to alter previous conclusions about site contamination must be immediately notified to the Council's Area Planning Manager, the Site Auditor and the Principal Certifier.
- (j) Any variations to the approved Remediation Action Plan must be approved in writing by the Site Auditor and Council's Area Coordinator Planning Assessments / Area Planning Manager prior to the commencement of such work.

(100) DECOMMISSIONING OF UNDERGROUND PETROLEUM STORAGE TANKS

Any removal of underground petroleum storage tanks must be undertaken in accordance with Safework NSW requirements which includes writing to the Chief Inspector of Dangerous Goods and complying with any conditions imposed and all relevant NSW Environmental Protection Authority/Office of the Environment and Heritage Guidelines and Australian Standards including following;

NSW EPA Technical Note: *Decommissioning, Abandonment and Removal of UPSS* (January 2010),

NSW EPA Technical Note: *Investigation of Service Station Sites* (April 2014),

AS 1940 –2004: Storage and handling of flammable and combustible liquids,

AS 4976 – 2008: The removal and disposal of underground petroleum storage tanks.

A site contamination assessment must be conducted in accordance with the *Guidelines for Consultants Reporting on Contaminated Sites* (NSW Office of the Environment and Heritage 2011) and the *Sampling Design Guidelines* (NSW Environmental Protection Authority September 1995) to determine whether petroleum has contaminated soil and groundwater in the vicinity of the storage system and whether remediation is required to ensure the land remains suitable for the continued approved land use.

Subsequent remediation of the site must be undertaken in accordance with the *Managing Land Contamination – Planning Guidelines* (Department of Urban Affairs and Planning 1998) and the *State Environmental Planning Policy (Resilience and Hazards 2021)* including notification to Council's Area Planning Manager at the start and completion of land remediation.

The removal or in-situ decommissioning of the underground petroleum storage system and any subsequent contamination assessment, preparation of a remediation strategy and final decommissioning reporting must be carried out by a duly qualified person, who has competencies and experience in relation to this area of work that are recognised as appropriate by the relevant industry and the NSW Environmental Protection Authority.

Reason

To ensure the removal of underground petroleum storage tanks is appropriately managed.

(101) NOTIFICATION – NEW CONTAMINATION EVIDENCE

Council's Area Planning Manager and the Principal Certifier must be notified of any new information which comes to light during remediation, demolition or construction works which has the potential to alter previous conclusions about site contamination.

Reason

To ensure that the site is appropriately remediated.

(102) IMPORTED FILL MATERIALS

All fill imported onto the site must be validated to ensure the imported fill is suitable for the proposed land use from a contamination perspective. Fill imported on to the site shall also be compatible with the existing soil characteristic for site drainage purposes.

The City may require details of appropriate validation of imported fill material to be submitted with any application for future development of the site. Hence all fill imported onto the site should be validated by either one or both of the following methods during remediation works:

- (a) Imported fill must be accompanied by documentation from the supplier which certifies that the material is not contaminated based upon analyses of the material for the known past history of the site where the material is obtained; and/or
- (b) Sampling and analysis of the fill material shall be conducted in accordance with NSW EPA (2022) Sampling Design Guidelines.

Reason

To ensure that imported fill is not contaminated.

(103) CLASSIFICATION OF WASTE

Prior to the exportation of waste (including fill or soil) from the site, the waste materials must be classified in accordance with the provisions of the Protection of the *Environment Operations Act 1997* and the *NSW EPA Waste Classification Guidelines, Part1: Classifying Waste (November 2014)*. The classification of the material is essential to determine where the waste may be legally taken. The *Protection of the Environment Operations Act 1997* provides for the commission of an offence for both the waste owner and the transporters if the waste is taken to a place that cannot lawfully be used as a waste facility for a particular class of waste. For the transport and disposal of industrial, hazardous or Group A liquid waste advice should be sought from the EPA.

Reason

To ensure that waste from site is classified and disposed of appropriately.

(104) DISCHARGE OF CONTAMINATED GROUNDWATER

Contaminated groundwater must not be discharged into the City's stormwater drainage system.

Options for the disposal of groundwater include disposal to sewer with prior approval from Sydney Water or off-site disposal by a liquid waste transporter for treatment/disposal to an appropriate waste treatment/processing facility.

Reason

To ensure that the discharge of ground water is appropriately managed.

(105) STOCKPILES

- (a) No stockpiles of soil or other materials must be placed on footpaths or nature strips unless prior approval has been obtained from the City's Construction Regulation Team.
- (b) All stockpiles of soil or other materials must be placed away from drainage lines, gutters or stormwater pits or inlets.
- (c) All stockpiles of soil or other materials likely to generate dust or odours must be covered.
- (d) All stockpiles of contaminated soil must be stored in a secure area and be covered if remaining more than 24 hours.

Reason

To ensure that stockpiles of soil or other materials are appropriately managed.

(106) HOURS OF WORK AND NOISE – OUTSIDE CBD

The hours of construction and work on the development must be as follows:

- (a) All work, including building/demolition and excavation work, and activities in the vicinity of the site generating noise associated with preparation for the commencement of work (eg. loading and unloading of goods, transferring of tools etc) in connection with the proposed development must only be carried out between the hours of 7.30am and 5.30pm on Mondays to Fridays, inclusive, and 7.30am and 3.30pm on Saturdays, with safety inspections being permitted at 7.00am on work days, and no work must be carried out on Sundays or public holidays.
- (b) All work, including demolition, excavation and building work must comply with the City of Sydney Code of Practice for Construction Hours/Noise 1992 and Australian Standard 2436 - 2010 Guide to Noise Control on Construction, Maintenance and Demolition Sites.
- (c) Notwithstanding the above, the use of a crane for special operations, including the delivery of materials, hoisting of plant and equipment and erection and dismantling of on-site tower cranes which warrant the on-street use of mobile cranes outside of above hours can occur, subject to a separate application being submitted to and approved by Council under Section 68 of the Local Government Act 1993 and Sections 138/139 of the Roads Act 1993.

Note: Works may be undertaken outside of hours, where it is required to avoid the loss of life, damage to property, to prevent environmental harm and/or to avoid structural damage to the building. Written approval must be given by the Construction Regulation Team, prior to works proceeding.

The *City of Sydney Code of Practice for Construction Hours/Noise 1992* allows extended working hours subject to the approval of an application in accordance with the Code and under Section 4.55 of the *Environmental Planning and Assessment Act 1979*.

Reason

To protect the amenity of the surrounding area.

(107) USE OF HIGH NOISE EMISSION APPLIANCES / PLANT

- (a) The operation of high noise emission appliances, plant and/or machinery such as pile – drivers, rock breakers and hydraulic hammers and those which are not listed in Groups B, C, D, E or F of Schedule 1 of the *City of Sydney Code of Practice for Construction Hours/Noise 1992* and Australian Standard 2436-2010 *Guide to Noise Control on Construction, Maintenance and Demolition Sites* is restricted to the hours of (EHO to specify hours)
- (b) All reasonable and feasible steps must be undertaken to ensure that the work, including demolition, excavation and building complies with the *City of Sydney Code of Practice for Construction Hours/Noise 1992* and Australian Standard 2436- 2010 *Guide to Noise Control on Construction, Maintenance and Demolition Sites*.

Reason

To protect the amenity of the surrounding area.

(108) LIGHTING OF SITE OUTSIDE OF STANDARD CONSTRUCTION HOURS

Lighting of the site while any work is undertaken outside of Council's standard hours of construction must ensure that at no time must the intensity, hours of illumination or location of the lighting cause objectionable glare or injury to the amenity of the neighbourhood or Obtrusive Light in accordance with the definition in Australian Standard AS4282-1997 *Control of the obtrusive effects of outdoor lighting*. If in the opinion of Council, injury is likely to be caused, the intensity, hours of illumination and location of the lighting must be varied so that it does not cause injury to nearby residents.

Reason

To protect the amenity of the surrounding area.

(109) NOTIFICATION OF EXCAVATION WORKS OR USE OF HIGH NOISE EMISSION APPLIANCES/PLANT

The immediately adjoining neighbours must be given a minimum of 48 hours notice that excavation, shoring or underpinning works or use of high noise emission appliances / plant are about to commence.

Reason

To protect the amenity of the surrounding area.

(110) LOADING AND UNLOADING DURING CONSTRUCTION

The following requirements apply:

- (a) All loading and unloading associated with construction activity must be accommodated on site, where possible.
- (b) If, it is not feasible for loading and unloading to take place on site, a Works Zone on the street may be considered by Council.
- (c) A Works Zone may be required if loading and unloading is not possible on site. If a Works Zone is warranted an application must be made to Council at least 8 weeks prior to commencement of work on the site. An approval for a Works Zone may be given for a specific period and certain hours of the days to meet the particular need for the site for such facilities at various stages of construction. The approval will be reviewed periodically for any adjustment necessitated by the progress of the construction activities.
- (d) Where hoisting activity over the public place is proposed to be undertaken including hoisting from a Works Zone, a separate application under Section 68 of the Local Government Act 1993 and Sections 138/139 of the Roads Act 1993 must be submitted to and approved by Council.

Reason

To protect the amenity of the public domain.

(111) NO OBSTRUCTION OF PUBLIC WAY

Unless otherwise approved by Council, the public way must not be obstructed by any materials, vehicles, waste receptacles, skip-bins or the like. Non-compliance with this requirement may result in the issue of a notice by Council to stop all work on the site.

Reason

To protect the amenity of the public domain.

ON COMPLETION OF DEMOLITION WORK

(112) SITE AUDIT STATEMENT – ENVIRONMENTAL MANAGEMENT PLAN

Where the ongoing land use suitability and release of the Final (Section A) Site Audit Statement is dependent upon the implementation of an Environmental Management Plan (EMP) in relation to any residual contamination remaining onsite, the EMP must be approved by the Site Auditor and Council's Area Planning Manager prior to the issue of the final Site Audit Statement.

The owner of the land is required to comply with the ongoing obligations of any EMP which form part of the final Site Audit Statement for the site.

A covenant must be registered on the title of the land binding the owners and future owners to be responsible for ongoing maintenance and any future rehabilitation works required in terms of the encapsulated/remaining contaminated materials, including the discharge or prevention of discharge from any contaminants or for any works subsequently required by the NSW Environment Protection Authority

A copy of the revised certificate of land title recording the covenant must be submitted to Council's Area Planning Manager and the Principal Certifier prior to the issue of any Occupation Certificate.

Reason

To ensure that contamination is appropriately managed.